

Table 1. Frequency Table for Straight Rubber Duck antenna with 2.2 dBi gain

Action	Lower/Upper Frequency (MHz)	Bandwidth (MHz)	Power at input of transmit antenna port (W)	ERP (W)	Mean or Peak	Frequency Tolerance	Station Class
Add	2431.875-2438.125	6.25	2.075	2.1	Mean	1 kHz	Mobile
Add	2431.75-2438.25	6.5	2.075	2.1	Mean	1 kHz	Mobile
Add	2431.09-2438.91	7.82	2.075	2.1	Mean	1 kHz	Mobile
Add	2430.9375-2439.0625	8.125	2.075	2.1	Mean	1 kHz	Mobile
Add	2430.12-2439.88	9.76	2.075	2.1	Mean	1 kHz	Mobile
Add	2429.9-2440.1	10.2	2.075	2.1	Mean	1 kHz	Mobile
Add	2428.75-2441.25	12.5	2.075	2.1	Mean	1 kHz	Mobile
Add	2428.5-2441.5	13.0	2.075	2.1	Mean	1 kHz	Mobile
Add	2437.185-2442.815	15.63	2.075	2.1	Mean	1 kHz	Mobile
Add	2426.875-2443.125	16.25	2.075	2.1	Mean	1 kHz	Mobile
Add	2425.235-2444.765	19.53	2.075	2.1	Mean	1 kHz	Mobile
Add	2424.84-2445.16	20.32	2.075	2.1	Mean	1 kHz	Mobile
Add	2423.28-2446.72	23.44	2.075	2.1	Mean	1 kHz	Mobile
Add	2422.81-2447.19	24.38	2.075	2.1	Mean	1 kHz	Mobile
Add	2422.5-2447.5	25	2.075	2.1	Mean	1 kHz	Mobile
Add	2422.0-2448.0	26	2.075	2.1	Mean	1 kHz	Mobile
Add	2419.375-2450.625	31.25	2.075	2.1	Mean	1 kHz	Mobile
Add	2418.75-2451.25	32.5	2.075	2.1	Mean	1 kHz	Mobile
Add	2415.45-2454.55	39.1	2.075	2.1	Mean	1 kHz	Mobile
Add	2414.685-2455.315	40.63	2.075	2.1	Mean	1 kHz	Mobile
Add	2420-2460	40.0	2.075	2.1	Mean	1 kHz	Mobile