

0994-EX-CN-2026

Antenna Description

All transmission operations will occur strictly under authorized ground-based conditions. No airborne transmissions will occur on any of the requested frequencies.

During testing, aircraft will fly northeast of Greenville, TX (approximate reference position: 33°04'13"N, 96°03'24"W) along headings between 350° and 140°, at altitudes up to 30,000 feet within controlled FAA-coordinated airspace. Ground-based transmit antennas will track the aircraft using IFF or ADS-B data. To avoid unintentional transmission toward the Dallas/Fort Worth area, antenna movement is electronically limited to the 350°–140° sector. Operators also have a manual override capability if aircraft navigation data becomes unreliable. For example, if the aircraft is 270 degrees from Greenville, the antennas will not follow the aircraft due to the stops. The antennas do however track the aircraft using elevation. The flight level of the aircraft is fed into software driving the antennas. Please refer to Figure 1 for the typical flight path (in red) within the MANO box (in orange) and the system's degrees (in blue).

The transmit antenna is mounted on a pedestal located behind the control facility, with a maximum height of 7.7 meters above ground level including the structure. The antenna site is approximately 1.5 km from the nearest landing area of the active runway at Majors Airport. Reference images, including an example antenna and a Google Earth view showing the pedestal location relative to the runway, are provided below.

Table of Equipment configuration:

Band (MHz)	Tx Part #	Ant Gain	Ant Vertical BW	Ant Horizontal BW
108.375-399.875	100W1000B	7 dBi	65 degrees	105 degrees
1275.0 – 2900.0	60S1G6	16 dBi	17.0 degrees	19.0 degrees



Figure 1 Typical Flight Path and System Tracking Limits within Mano Box

