

H U R R Y - U P[®] TELESCOPING MAST

Will-Burt's portable 25-ft
Hurry-Up Telescoping Mast can
be extended to full height in
one minute or less, and is ideal
for deployment of light weight
antennas and instruments. The
mast consists of six graduated
aluminum tubes which nest one
inside another.

Payload Capacity	Extended Height	Nested Height	Approx. Mast Weight	No. of Sections	Tube Diameter Range	Collar Type
20 lb (9.1 kg)	25' (7.6 m)	5' 10" (1.8 m)	29 lb (13 kg)	6	3.5-1.5" (89-38 mm)	Friction Locking

Free-standing unit, so guylines are not needed.

Rigid azimuth locking for quick direction adjustment.

Low friction synthetic bearings for smooth operation and long life.

Anodized finish for corrosion resistance.

Quick lock/release collars to extend mast manually by pushing up sections and fixing them in position.

Mounting is a "drive on" plate with reinforced vertical holding tube.

Standard Equipment

- "Drive On" stand
- Antenna extension stub
- Installation & operation manual
- Shipping crate

Optional Equipment

- External support brackets for permanent vehicle mountings



Dimensions and specifications provided in catalog or on willburt.com are for reference only and are not intended for vehicle design purposes. Specifications subject to change without notice.