

RF Exposure Report

Report No.: SA170712E09A

FCC ID: 2AAAS-NM01

Test Model: NM01

Received Date: July 12, 2017

Test Date: Aug. 31, 2017

Issued Date: Sep. 07, 2017

Applicant: Vivint, Inc.

Address: 4931 North 300 West Provo, Utah 84604 United States

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch
Hsin Chu Laboratory

Lab Address: E-2, No.1, Li Hsin 1st Road, Hsinchu Science Park, Hsinchu City 300,
Taiwan R.O.C.

This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by any government agencies.

Table of Contents

| | |
|---|----------|
| Release Control Record | 3 |
| 1 Certificate of Conformity | 4 |
| 2 RF Exposure | 5 |
| 2.1 Limits for Maximum Permissible Exposure (MPE) | 5 |
| 2.2 MPE Calculation Formula | 5 |
| 2.3 Classification | 5 |
| 2.4 Antenna Gain | 5 |
| 2.5 Calculation Result of Maximum Conducted Power | 6 |

Report Issue History Record

| Attachment No. | Issue Date | Description |
|----------------|---------------|-------------------|
| SA170712E09 | Aug. 15, 2017 | Original release. |
| SA170712E09A | Sep. 07, 2017 | Changed Diplexer. |

Release Control Record

| Issue No. | Description | Date Issued |
|--------------|-------------------|---------------|
| SA170712E09A | Original release. | Sep. 07, 2017 |

1 Certificate of Conformity

Product: Vivint 2.4GHz/5GHz WiFi Module

Brand: Vivint

Test Model: NM01

Sample Status: ENGINEERING SAMPLE

Applicant: Vivint, Inc.

Test Date: Aug. 31, 2017

Standards: FCC Part 2 (Section 2.1091)

KDB 447498 D01 General RF Exposure Guidance v06

IEEE C95.1-1992

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

Prepared by :

Cindy Hsin

Date:

Sep. 07, 2017

Cindy Hsin / Specialist

Approved by :

May Chen

Date:

Sep. 07, 2017

May Chen / Manager

2 RF Exposure

2.1 Limits for Maximum Permissible Exposure (MPE)

| Frequency Range (MHz) | Electric Field Strength (V/m) | Magnetic Field Strength (A/m) | Power Density (mW/cm ²) | Average Time (minutes) |
|---|-------------------------------|-------------------------------|-------------------------------------|------------------------|
| Limits For General Population / Uncontrolled Exposure | | | | |
| 0.3-1.34 | 614 | 1.63 | (100)* | 30 |
| 1.34-30 | 824/f | 2.19/f | (180/f ²)* | 30 |
| 30-300 | 27.5 | 0.073 | 0.2 | 30 |
| 300-1500 | ... | ... | f/1500 | 30 |
| 1500-100,000 | ... | ... | 1.0 | 30 |

f = Frequency in MHz ; *Plane-wave equivalent power density

2.2 MPE Calculation Formula

$$Pd = (Pout * G) / (4 * \pi * r^2)$$

where

Pd = power density in mW/cm²

Pout = output power to antenna in mW

G = gain of antenna in linear scale

Pi = 3.1416

R = distance between observation point and center of the radiator in cm

2.3 Classification

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user.
 So, this device is classified as **Mobile Device**.

2.4 Antenna Gain

The antennas provided to the EUT, please refer to the following table:

| No. | PCB Chain No | Brand | Model | Antenna Gain(dBi) | Frequency range | Antenna Type | Connector type | Cable Length (mm) | Cable Loss (dB) | excluding cable loss Antenna Gain(dBi) |
|-----|--------------|-------|--------------|-------------------|-----------------|--------------|----------------|-------------------|-----------------|--|
| 1 | Chain 0 | NA | TE 2108517-1 | 2.5 | 2.4~2.4835GHz | PIFA | I-pex | 60 | 0.5 | 3 |
| | | | | 2 | 5.15~5.85GHz | | | | 1 | |
| 2 | Chain 1 | NA | TE 2108517-1 | 2 | 2.4~2.4835GHz | PIFA | I-pex | 230 | 1 | 3 |
| | | | | 1.5 | 5.15~5.85GHz | | | | 1.5 | |

2.5 Calculation Result of Maximum Conducted Power

| Frequency Band (MHz) | Max Power (mW) | Antenna Gain (dBi) | Distance (cm) | Power Density (mW/cm ²) | Limit (mW/cm ²) |
|----------------------|----------------|--------------------|---------------|-------------------------------------|-----------------------------|
| 2412-2462 | 499.746 | 5.26 | 20 | 0.33379 | 1 |
| 5180-5240 | 89.413 | 4.76 | 20 | 0.05323 | 1 |
| 5260-5320 | 92.483 | 4.76 | 20 | 0.05505 | 1 |
| 5500-5700 | 68.637 | 4.76 | 20 | 0.04086 | 1 |
| 5745-5825 | 72.062 | 4.76 | 20 | 0.04290 | 1 |

NOTE:

2.4GHz: Directional gain = $10 \log[(10^{G1/20} + 10^{G2/20})^2 / 2] = 5.26\text{dBi}$

5 GHz : Directional gain = $10 \log[(10^{G1/20} + 10^{G2/20})^2 / 2] = 4.76\text{dBi}$

Conclusion:

The formula of calculated the MPE is:

$CPD1 / LPD1 + CPD2 / LPD2 + \dots\text{etc.} < 1$

CPD = Calculation power density

LPD = Limit of power density

$WLAN\ 2.4GHz + WLAN\ 5GHz = 0.33379 / 1 + 0.05505 / 1 = 0.38884$

Therefore the maximum calculations of above situations are less than the "1" limit.

--- END ---