

## INTERTEK TESTING SERVICES

---

### RF Exposure

The equipment under test (EUT) is a Wednesday Animated Thing operating at 2.4G Band. The EUT can be powered by DC 4.5V (3 x 1.5V LR44 batteries). For more detail information pls. refer to the user manual.

Antenna Type: Integral antenna.

Antenna Gain: 0dBi.

The normal radiated output power (e.i.r.p) is: -7.0dBm (tolerance: +/- 3dB).

The normal conducted output power is -7.0dBm (tolerance: +/- 3dB).

Modulation Type: GFSK.

According to the KDB 447498 V06:

The Maximum peak radiated emission for the EUT is 88.7dB $\mu$ V/m at 3m in the frequency 2420MHz

The EIRP = [(FS\*D) ^2 / 30] mW = -6.53dBm  
which is within the production variation.

The Minimum peak radiated emission for the EUT is 86.6.dB $\mu$ V/m at 3m in the frequency 2445MHz

The EIRP = [(FS\*D) ^2 / 30] mW = -8.63dBm  
which is within the production variation.

The maximum conducted output power specified is -4dBm= 0.398mW

The source- based time-averaging conducted output power  
=0.398mW

The SAR Exclusion Threshold Level:

= 3.0 \* (min. test separation distance, mm) / sqrt(freq. in GHz)

= 3.0 \* 5 / sqrt (2.460) mW

= 9.54 mW

Since the source-based time-averaging conducted output power is well below the SAR low threshold level, so the EUT is considered to comply with SAR requirement without testing.