

1F., Block A of Tongsheng Technology Building, Huahui Road, Dalang Street, Longhua District, Shenzhen, China

Report Template Version: V03

Report Template Revision Date: Mar.1st, 2017

Telephone: +86-755-26648640 Fax: +86-755-26648637

Website: <u>www.cqa-cert.com</u>

RF Exposure Evaluation Report

Report No.: CQASZ20180600096E-02

Applicant: ATake Digital Technology (Shenzhen) Co., Ltd.

Address of Applicant: 15th Building, Changxing Industry Zone, Changzhen Village, Gongming,

Guangming New District, Shenzhen, Guangdong, China 518132

Manufacturer: ATake Digital Technology (Shenzhen) Co., Ltd.

Address of Manufacturer: 15th Building, Changxing Industry Zone, Changzhen Village, Gongming,

Guangming New District, Shenzhen, Guangdong, China 518132

Factory: ATake Digital Technology (Shenzhen) Co., Ltd.

Address of Factory: 15th Building, Changxing Industry Zone, Changzhen Village, Gongming,

Guangming New District, Shenzhen, Guangdong, China 518132

Equipment Under Test (EUT):

Product: Colorful Pulsing Light Waterproof Floating 2.0 Stereo Speaker

Model No.: ASP-809
Brand Name: N/A

FCC ID: 2ADZIASP-809
Standards: 47 CFR Part 1.1307

47 CFR Part 2.1093

KDB447498D01 General RF Exposure Guidance v06

Date of Test: 2018-06-25 to 2018-07-05

Date of Issue: 2018-07-05
Test Result: PASS*

Tested By:

(Martin Lee)

Reviewed By: Wen Zhou

Owen Zhou)

Approved By:



The test report is effective only with both signature and specialized stamp, The result(s) shown in this report refer only to the sample(s) tested. Without written approval of CQA, this report can't be reproduced except in full.

^{*} In the configuration tested, the EUT complied with the standards specified above.



Report No.: CQASZ20180600096E-02

1 Version

Revision History Of Report

Report No.	Version	Description	Issue Date
CQASZ20180600096E-02	Rev.01	Initial report	2018-07-05





Report No.: CQASZ20180600096E-02

2 Contents

		Page
1	VERSION	2
2	2 CONTENTS	3
3	B GENERAL INFORMATION	4
	3.1 CLIENT INFORMATION	1
	3.2 GENERAL DESCRIPTION OF EUT.	4
4	SAR EVALUATION	5
	4.1 RF EXPOSURE COMPLIANCE REQUIREMENT	5
	4.1.1 Standard Requirement	5
	4.1 RF Exposure Compliance Requirement	5
	4.1.3 EUT RF Exposure	5



Report No.: CQASZ20180600096E-02

3 General Information

3.1 Client Information

Applicant:	ATake Digital Technology (Shenzhen) Co., Ltd. 15th Building, Changxing Industry Zone, Changzhen Village, Gongming, Guangming New District, Shenzhen, Guangdong, China 518132	
Address of Applicant:		
Manufacturer:	ATake Digital Technology (Shenzhen) Co., Ltd.	
Address of Manufacturer:	15th Building, Changxing Industry Zone, Changzhen Village, Gongming, Guangming New District, Shenzhen, Guangdong, China 518132	
Factory:	ATake Digital Technology (Shenzhen) Co., Ltd.	
Address of Factory:	15th Building, Changxing Industry Zone, Changzhen Village, Gongming, Guangming New District, Shenzhen, Guangdong, China 518132	

3.2 General Description of EUT

Product Name:	Colorful Pulsing Light Waterproof Floating 2.0 Stereo Speaker
Model No.:	ASP-809
Trade Mark:	N/A
Hardware Version:	V1.0
Software Version:	V1.0
Operation Frequency:	2402MHz~2480MHz
Bluetooth Version:	V4.2
Modulation Technique:	Frequency Hopping Spread Spectrum(FHSS)
Modulation Type:	GFSK, π/4DQPSK, 8DPSK
Number of Channel:	79
Hopping Channel Type:	Adaptive Frequency Hopping systems
Sample Type:	portable production
Test Software of EUT:	AppoTech RE Control Kit V4.2.18 (manufacturer declare)
Antenna Type:	PCB antenna
Antenna Gain:	1.3dBi
Power Supply:	lithium battery:DC3.7V, 1200mAh, Charge by DC5.0V



Report No.: CQASZ20180600096E-02

4 SAR Evaluation

4.1 RF Exposure Compliance Requirement

4.1.1 Standard Requirement

According to KDB447498D01 General RF Exposure Guidance v06

4.3.1. Standalone SAR test exclusion considerations

Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Exclusion Threshold condition, listed below, is satisfied.

4.1.2 Limits

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)] $\cdot [\sqrt{f(GHz)}] \le 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where

f(GHz) is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation 17

The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is \leq 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion

4.1.3 EUT RF Exposure



Report No.: CQASZ20180600096E-02

For BT:

Measurement Data

GFSK mode		
Test channel	Peak Output Power (dBm)	
Lowest	-0.390	
Middle	-1.070	
Highest	-1.460	
π/4DQPSK mode		
Test channel	Peak Output Power (dBm)	
Lowest	-1.740	
Middle	-2.320	
Highest	-2.560	
8DPSK mode		
Test channel	Peak Output Power (dBm)	
Lowest	-1.430	
Middle	-1.880	
Highest	-1.940	

The Max Conducted Peak Output Power is -0.390dBm in lowest channel(2.402GHz);

The best case gain of the antenna is 1.3dBi.

EIRP = -0.39dBm + 1.3dBi = 0.94dBm

0.94dBm logarithmic terms convert to numeric result is nearly 1.24mW

According to the formula. calculate the EIRP test result:

[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)] \cdot [$\sqrt{f(GHz)}$]

General RF Exposure = $(1.24 \text{mW} / 5 \text{ mm}) \times \sqrt{2.402 \text{GHz}} = 0.384 \text{ }\bigcirc$

SAR requirement:

S = 3.0

②;

(1) < (2).

So the SAR report is not required.

Remark: The Max Conducted Peak Output Power data refer to report Report No.: CQASZ20180600096E-01