

Annex 1: Measurement diagrams to
TEST REPORT
No.: 16-1-0188601T01a

According to:

FCC Regulations

Part 15.205
Part 15.209
Part 15.407

for

Intel Corporation

VLMTX58G Video Link Module TX 5.8GHz

+

WALSIN PCB ANTENNA RFPCA201018IM5B301 (2 pcs)

FCC-ID: 2AJ2A-VLMTX58G


Laboratory Accreditation and Listings			
 DAkkS Deutsche Akkreditierungsstelle D-PL-12047-01-01	 FEDERAL COMMUNICATIONS COMMISSION FCC USA MRA US-EU 0003	 Industry Canada Reg. No.: 3462D-2 Reg. No.: 3462D-3	 Voluntary Controls for Electromagnetic Emissions Reg. No.: R-2666 C-2914, T-1967, G-301
 WiFi ALLIANCE AUTHORIZED RF LABORATORY	 ctia Authorized™ Test Lab Lab Code: 20011130-00		
accredited according to DIN EN ISO/IEC 17025			
CETECOM GmbH Laboratory Radio Communications & Electromagnetic Compatibility Im Teelbruch 116 • 45219 Essen • Germany Registered in Essen, Germany, Reg. No.: HRB Essen 8984 Tel.: + 49 (0) 20 54 / 95 19-954 • Fax: + 49 (0) 20 54 / 95 19-964 E-mail: info@cetecom.com • Internet: www.cetecom.com			

TABLE OF CONTENTS:


1. CONDUCTED RF-MEASUREMENTS - ANTENNA PORT (MIMO).....	3
1.1. Duty-Cycle Measurements	3
1.2. Power Spectral Density.....	5
1.2.1. Channel 5190 MHz	5
1.2.2. Channel 5230 MHz	7
1.2.3. Channel 5270 MHz	9
1.2.4. Channel 5310 MHz	11
1.2.5. Channel 5510 MHz	13
1.2.6. Channel 5550 MHz	15
1.2.7. Channel 5590 MHz	17
1.2.8. Channel 5670 MHz	19
1.2.9. Channel 5755 MHz	21
1.2.10. Channel 5795 MHz	23
1.3. 26dBc Bandwidth and 99% Occupied Bandwidth.....	25
1.3.1. U-NII-1 Band	25
1.3.2. U-NII-2A Band	30
1.3.3. U-NII-2C Band.....	35
1.3.4. U-NII-3 Band	39
2. RADIATED FIELD STRENGTH MEASUREMENTS	43
2.1. Radiated Field Strength Emissions – 9 kHz to 30 MHz	43
2.2. Radiated Field Strength Emissions – 30 MHz to 1 GHz	52
2.3. Radiated Field Strength Emissions – 1 GHz to 7 GHz	62
2.4. Radiated Field Strength Emissions – 7 GHz to 18 GHz	71
2.5. Radiated Field Strength Emissions – 18 GHz to 40 GHz	80
3. RADIATED BAND-EDGE MEASUREMENTS	89
3.1. Channel 5190 MHz (U-NII-1:left band edge).....	89
3.2. Channel 5230 MHz (U-NII-1:right band edge)	90
3.3. Channel 5310 MHz (U-NII-2A: right band edge)	91
3.4. Channel 5510 MHz (U-NII-2C: left band edge).....	92
3.5. Channel 5670 MHz (U-NII-2C: right band edge).....	93
3.6. Channel 5755 MHz (U-NII-3: left band edge).....	94
3.7. Channel 5795 MHz (U-NII-3: right band edge)	95

1. Conducted RF-Measurements - Antenna Port (MIMO)


1.1. Duty-Cycle Measurements




Plot 1: U-NII-1 Band-B.W. 40 MHz-Ch 5190 MHz



Plot 2: U-NII-2A Band-B.W. 40MHz-Ch 5310 MHz




Plot 3: U-NII-2C Band-B.W. 40 MHz-Ch 5510 MHz




Plot 4: U-NII-3Band-B.W. 40 MHz- Ch 5795 MHz

1.2. Power Spectral Density


1.2.1. Channel 5190 MHz



Plot 5: U-NII-1 Band-B.W. 40 MHz-Ch 5190 MHz- Port 0




Plot 6: U-NII-1 Band-B.W. 40 MHz-Ch 5190 MHz- Port 1




Plot 7: U-NII-1 Band-B.W. 40 MHz-Ch 5190 MHz- Sum [Port 0+ Port 1] (MIMO)

MAX-Value: at 5190.94 MHz	1.96023933	dBm
	1.57044935	mW


1.2.2. Channel 5230 MHz



Plot 8: U-NII-1 Band-B.W. 40 MHz-Ch 5230 MHz, Port 0




Plot 9: U-NII-1 Band-B.W. 40 MHz-Ch 5230 MHz, Port 1




Plot 10: U-NII-1 Band-B.W. 40 MHz-Ch 5230 MHz- Sum [Port 0+ Port 1] (MIMO)

MAX-Value at 5231.08 MHz	1.33251207	dBm
	1.35909936	mW


1.2.3. Channel 5270 MHz



Plot 11: U-NII-2A Band-B.W. 40 MHz-Ch 5270 MHz, Port 0




Plot 12: U-NII-2A Band-B.W. 40 MHz-Ch 5270 MHz, Port 1




Plot 13: U-NII-2A Band-B.W. 40 MHz-Ch 5270 MHz- Sum [Port 0+ Port 1] (MIMO)

MAX-Value at 5271.08 MHz	0.6876269	dBm
	1.17155502	mW


1.2.4. Channel 5310 MHz



Plot 14: U-NII-2A Band-B.W. 40 MHz-Ch 5310 MHz, Port 0




Plot 15: U-NII-2A Band-B.W. 40 MHz-Ch 5310 MHz, Port 1




Plot 16: U-NII-2A Band-B.W. 40 MHz-Ch 5310 MHz- Sum [Port 0+ Port 1] (MIMO)

MAX-Value at 5311.14 MHz	2.11925939	dBm
	1.62901821	mW


1.2.5. Channel 5510 MHz



Plot 17: U-NII-2C Band-B.W. 40 MHz-Ch 5510 MHz, Port 0



Plot 18: U-NII-2C Band-B.W. 40 MHz-Ch 5510 MHz, Port 1




Plot 19: U-NII-2C Band-B.W. 40 MHz-Ch 5510 MHz- Sum [Port 0+ Port 1] (MIMO)


MAX-Value at 5514.24 MHz	1.01614001	dBm
	1.26361275	mW

1.2.6. Channel 5550 MHz


MAX-Value: 0.91 dBm | (values in dBm)



Plot 20: U-NII-2C Band-B.W. 40 MHz-Ch 5550 MHz, Port 0




Plot 21: U-NII-2C Band-B.W. 40 MHz-Ch 5550 MHz, Port 1




Plot 22: U-NII-2C Band-B.W. 40 MHz-Ch 5550 MHz- Sum [Port 0+ Port 1] (MIMO)

MAX-Value at 5563.73 MHz	2.38568089	dBm
	1.73208057	mW


1.2.7. Channel 5590 MHz



Plot 23: U-NII-2C Band-B.W. 40 MHz-Ch 5590 MHz, Port 0




Plot 24: U-NII-2C Band-B.W. 40 MHz-Ch 5590 MHz, Port 1




Plot 25: U-NII-2C Band-B.W. 40 MHz-Ch 5590 MHz- Sum [Port 0+ Port 1] (MIMO)

MAX-Value at 5590.88 MHz	1.64838058	dBm
	1.46163205	mW


1.2.8. Channel 5670 MHz



Plot 26: U-NII-2C Band-B.W. 40 MHz-Ch 5670 MHz, Port 0




Plot 27: U-NII-2C Band-B.W. 40 MHz-Ch 5670 MHz, Port 1




Plot 28: U-NII-2C Band-B.W. 40 MHz-Ch 5670 MHz- Sum [Port 0+ Port 1] (MIMO)

MAX-Value at 5665.49 MHz	1.12472216	dBm
	1.29560381	mW


1.2.9. Channel 5755 MHz



Plot 29: U-NII-3 Band-B.W. 40 MHz-Ch 5755 MHz, Port 0




Plot 30: U-NII-3 Band-B.W. 40 MHz-Ch 5755 MHz, Port 1




Plot 31: U-NII-3 Band-B.W. 40 MHz-Ch 5755 MHz- Sum [Port 0+ Port 1] (MIMO)

MAX-Value at 5751.15 MHz	0.27788912	dBm
	1.06607783	mW


1.2.10. Channel 5795 MHz



Plot 32: U-NII-3 Band-B.W. 40 MHz-Ch 5795 MHz, Port 0



Plot 33: U-NII-3 Band-B.W. 40 MHz-Ch 5795 MHz, Port 1




Plot 34: U-NII-3 Band-B.W. 40 MHz-Ch 5795 MHz- Sum [Port 0+ Port 1] (MIMO)

MAX-Value at 5794.36 MHz	-1.58659346	dBm
	0.69396993	mW

1.3. 26dBc Bandwidth and 99% Occupied Bandwidth


1.3.1. U-NII-1 Band

1.3.1.1. 26dBc B.W.-Channel 5190 MHz- Port 0




Plot 35: 26dBc B.W-U-NII-1 Band-B.W. 40 MHz-Ch 5190 MHz- Port 0

1.3.1.2. 99% OBW-Channel 5190 MHz- Port 0




Plot 36: 99% OBW-U-NII-1 Band-B.W. 40 MHz-Ch 5190 MHz- Port 0

1.3.1.3. 26dBc B.W.-Channel 5190 MHz- Port 1




Plot 37: 26dBc B.W-U-NII-1 Band-B.W. 40 MHz-Ch 5190 MHz- Port 1

1.3.1.4. 99% OBW-Channel 5190 MHz- Port 1




Plot 38: 99% OBW-U-NII-1 Band-B.W. 40 MHz-Ch 5190 MHz- Port 1

1.3.1.5. 26dBc B.W.-Channel 5230 MHz- Port 0




Plot 39: 26dBc B.W-U-NII-1 Band-B.W. 40 MHz-Ch 5230 MHz- Port 0




Plot 40: 26dBc B.W-U-NII-1 Band-B.W. 40 MHz-Ch 5230 MHz- Port 0-Frequency Counter Mode


1.3.1.6. 99% OBW-Channel 5230 MHz- Port 0



Plot 41: 99% OBW-U-NII-1 Band-B.W. 40 MHz-Ch 5230 MHz- Port 0


1.3.1.7. 26dBc B.W.-Channel 5230 MHz- Port 1

**Plot 42: 26dBc B.W-U-NII-1 Band-B.W. 40 MHz-Ch 5230 MHz- Port 1**



Plot 43: 26dBc B.W-U-NII-1 Band-B.W. 40 MHz-Ch 5230 MHz- Port 1-Frequency Counter Mode


1.3.1.8. 99% OBW-Channel 5230 MHz- Port 1




Plot 44: 99% OBW-U-NII-1 Band-B.W. 40 MHz-Ch 5230 MHz- Port 1

1.3.2. U-NII-2A Band

1.3.2.1. 26dBc B.W.-Channel 5270 MHz- Port 0




Plot 45: 26dBc B.W-U-NII-2A Band-B.W. 40 MHz-Ch 5270 MHz- Port 0



Plot 46: 26dBc B.W-U-NII-2A Band-B.W. 40 MHz-Ch 5270 MHz- Port 0 Frequency Counter Mode


[26dBc point falls within 5150-5250MHz -> no requirement for DFS or spurious emission in the UN-II-1 band (99% OBW falls in 5250-5350 MHz band)]

1.3.2.2. 99% OBW-Channel 5270 MHz- Port 0




Plot 47: 99% OBW-U-NII-2A Band-B.W. 40 MHz-Ch 5270 MHz- Port 0

1.3.2.3. 26dBc B.W.-Channel 5270 MHz- Port 1




Plot 48: 26dBc B.W-U-NII-2A Band-B.W. 40 MHz-Ch 5270 MHz- Port 1

1.3.2.4. 99% OBW-Channel 5270 MHz- Port 1




Plot 49: 99% OBW-U-NII-2A Band-B.W. 40 MHz-Ch 5270 MHz- Port 1

1.3.2.5. 26dBc B.W.-Channel 5310 MHz- Port 0




Plot 50: 26dBc B.W-U-NII-2A Band-B.W. 40 MHz-Ch 5310 MHz- Port 0

1.3.2.6. 99% OBW-Channel 5310 MHz- Port 0




Plot 51: 99% OBW-U-NII-2A Band-B.W. 40 MHz-Ch 5310 MHz- Port 0

1.3.2.7. 26dBc B.W.-Channel 5310 MHz- Port 1



Plot 52: 26dBc B.W-U-NII-2A Band-B.W. 40 MHz-Ch 5310 MHz- Port 1


1.3.2.8. 99% OBW-Channel 5310 MHz- Port 1



Plot 53: 99% OBW-U-NII-2A Band-B.W. 40 MHz-Ch 5310 MHz- Port 1


1.3.3. U-NII-2C Band

1.3.3.1. 26dBc B.W.-Channel 5510 MHz- Port 0




Plot 54: 26dBc B.W-U-NII-2C Band-B.W. 40 MHz-Ch 5510 MHz- Port 0

1.3.3.2. 99% OBW-Channel 5510 MHz- Port 0




Plot 55: 99% OBW-U-NII-2C Band-B.W. 40 MHz-Ch 5510 MHz- Port 0

1.3.3.3. 26dBc B.W.-Channel 5510 MHz- Port 1




Plot 56: 26dBc B.W-U-NII-2C Band-B.W. 40 MHz-Ch 5510 MHz- Port 0

1.3.3.4. 99% OBW-Channel 5510 MHz- Port 1




Plot 57: 99% OBW-U-NII-2C Band-B.W. 40 MHz-Ch 5510 MHz- Port 1

1.3.3.5. 26dBc B.W.-Channel 5670 MHz- Port 0


**Plot 58: 26dBc B.W-U-NII-2C Band-B.W. 40 MHz-Ch 5670 MHz- Port 0**

1.3.3.6. 99% OBW-Channel 5670 MHz- Port 0




Plot 59: 99% OBW-U-NII-2C Band-B.W. 40 MHz-Ch 5670 MHz- Port 0

1.3.3.7. 26dBc B.W.-Channel 5670 MHz- Port 1



Plot 60: 26dBc B.W-U-NII-2C Band-B.W. 40 MHz-Ch 5670 MHz- Port 1


1.3.3.8. 99% OBW-Channel 5670 MHz- Port 1



Plot 61: 99% OBW-U-NII-2C Band-B.W. 40 MHz-Ch 5670 MHz- Port 1


1.3.4. U-NII-3 Band

1.3.4.1. 26dBc B.W.-Channel 5755 MHz- Port 0




Plot 62: 26dBc B.W-U-NII-3 Band-B.W. 40 MHz-Ch 5755 MHz- Port 0

1.3.4.2. 99% OBW-Channel 5755 MHz- Port 0


**Plot 63: 99% OBW-U-NII-3 Band-B.W. 40 MHz-Ch 5755 MHz- Port 0**

1.3.4.3. 26dBc B.W.-Channel 5755 MHz- Port 1




Plot 64: 26dBc B.W-U-NII-3 Band-B.W. 40 MHz-Ch 5755 MHz- Port 1

1.3.4.4. 99% OBW-Channel 5755 MHz- Port 1




Plot 65: 99% OBW-U-NII-3 Band-B.W. 40 MHz-Ch 5755 MHz- Port 1

1.3.4.5. 26dBc B.W.-Channel 5795 MHz- Port 0




Plot 66: 26dBc B.W-U-NII-3 Band-B.W. 40 MHz-Ch 5795 MHz- Port 0

1.3.4.6. 99% OBW-Channel 5795 MHz- Port 0




Plot 67: 99% OBW-U-NII-3 Band-B.W. 40 MHz-Ch 5795 MHz- Port 0

1.3.4.7. 26dBc B.W.-Channel 5795 MHz- Port 1



Plot 68: 26dBc B.W-U-NII-3 Band-B.W. 40 MHz-Ch 5795 MHz- Port 1

1.3.4.8. 99% OBW-Channel 5795 MHz- Port 1



Plot 69: 99% OBW-U-NII-3 Band-B.W. 40 MHz-Ch 5795 MHz- Port 1

2. Radiated Field Strength Measurements

2.1. Radiated Field Strength Emissions – 9 kHz to 30 MHz

2.01_ TX-Sp.VLMTX58G+WALSIN-BW40MHz-5190 MHz-+10dBm


Common Information

Test description:	Magnetic Field Strength Measurement related to 30/300 m distance
Test site and distance:	Ref.-Nr. 441 Semi Anechoic Room (SAR) with 3 m measurement distance
Version of Testsoftware:	EMC32 V9.25.0
Distance correction:	used accord. table, pls. see test report
Technical Data:	Please see page 2 for detailed data of measurement setup
Rec. antenna (pre-scan):	height 1.00 m, parallel and 90° to EUT polarisation
Used filter:	bypass
Test specification:	FCC 15.205 § 15.209; RSS-Gen: Issue 4
Operator:	RIs
Operating conditions:	U-NII-1 BW 40 MHz 5190 MHz Fixed Channel
Power during tests:	5V DC

EUT Information

Manufacturer:	Intel
Module details:	VLMTX58G
Module Type:	Video Link Module TX 5.8 GHz (Video RF Transmitter)
Module MAC version:	4.10.37.8
Module APP version:	3.13.20.0
Module Serial number:	1ABOPTX10PTXD1006160905
Antenna Details:	WALSIN PCB ANTENNA - RFPCA201018IM5B301
Antenna Type:	DIPOLE
Antenna HW version:	N/A
Antenna Gain:	5.47 dBi
Antenna Serial number:	N/A
Test Configuration:	2 X WALSIN Antenna connected to VLMTX58G Modules (J1 & J2) connector using micro-UFL connector cable 10 cm in length
Connected Interfaces:	Both of these Antennas were separated by at least 20 cm
Test Mode Settings:	Using AppCom-Version 4.0.4.26 Software
Power Supply:	5 V DC (using Laboratory DC Supply)

Full Spectrum



2.02_ TX-Sp.VLMTX58G+WALSIN-BW40MHz-5230 MHz-+10dBm


Common Information

Test description:	Magnetic Field Strength Measurement related to 30/300 m distance
Test site and distance:	Ref.-Nr. 441 Semi Anechoic Room (SAR) with 3 m measurement distance
Version of Testsoftware:	EMC32 V9.25.0
Distance correction:	used accord. table, pls. see test report
Technical Data:	Please see page 2 for detailed data of measurement setup
Rec. antenna (pre-scan):	height 1.00 m, parallel and 90° to EUT polarisation
Used filter:	bypass
Test specification:	FCC 15.205 § 15.209; RSS-Gen: Issue 4
Operator:	RLs
Operating conditions:	U-NII-1 BW 40 MHz 5230 MHz Fixed Channel
Power during tests:	5V DC

EUT Information

Manufacturer:	Intel
Module details:	VLMTX58G
Module Type:	Video Link Module TX 5.8 GHz (Video RF Transmitter)
Module MAC version:	4.10.37.8
Module APP version:	3.13.20.0
Module Serial number:	1ABOPTX10PTXD1006160905
Antenna Details:	WALSIN PCB ANTENNA - RFPCA201018IM5B301
Antenna Type:	DIPOLE
Antenna HW version:	N/A
Antenna Gain:	5.47 dBi
Antenna Serial number:	N/A
Test Configuration:	2 X WALSIN Antenna connected to VLMTX58G Modules (J1 & J2) connector using micro-UFL connector cable 10 cm in length
Connected Interfaces:	Both of these Antennas were separated by at least 20 cm
Test Mode Settings:	Using AppCom-Version 4.0.4.26 Software
Power Supply:	5 V DC (using Laboratory DC Supply)

Full Spectrum



2.03_TX-Sp.VLMTX58G+WALSIN-BW40MHz-5270 MHz-+10dBm


Common Information

Test description:	Magnetic Field Strength Measurement related to 30/300 m distance
Test site and distance:	Ref.-Nr. 441 Semi Anechoic Room (SAR) with 3 m measurement distance
Version of Testsoftware:	EMC32 V9.25.0
Distance correction:	used accord. table, pls. see test report
Technical Data:	Please see page 2 for detailed data of measurement setup
Rec. antenna (pre-scan):	height 1.00 m, parallel and 90° to EUT polarisation
Used filter:	bypass
Test specification:	FCC 15.205 § 15.209; RSS-Gen: Issue 4
Operator:	RLs
Operating conditions:	U-NII-1 BW 40 MHz 5270 MHz Fixed Channel
Power during tests:	5V DC

EUT Information

Manufacturer:	Intel
Module details:	VLMTX58G
Module Type:	Video Link Module TX 5.8 GHz (Video RF Transmitter)
Module MAC version:	4.10.37.8
Module APP version:	3.13.20.0
Module Serial number:	1ABOPTX10PTXD1006160905
Antenna Details:	WALSIN PCB ANTENNA - RFPCA201018IM5B301
Antenna Type:	DIPOLE
Antenna HW version:	N/A
Antenna Gain:	5.47 dBi
Antenna Serial number:	N/A
Test Configuration:	2 X WALSIN Antenna connected to VLMTX58G Modules (J1 & J2) connector using micro-UFL connector cable 10 cm in length
Connected Interfaces:	Both of these Antennas were separated by at least 20 cm
Test Mode Settings:	Using AppCom-Version 4.0.4.26 Software
Power Supply:	5 V DC (using Laboratory DC Supply)

Full Spectrum



2.04_TX-Sp.VLMTX58G+WALSIN-BW40MHz-5310 MHz-+10dBm


Common Information

Test description:	Magnetic Field Strength Measurement related to 30/300 m distance
Test site and distance:	Ref.-Nr. 441 Semi Anechoic Room (SAR) with 3 m measurement distance
Version of Testsoftware:	EMC32 V9.25.0
Distance correction:	used accord. table, pls. see test report
Technical Data:	Please see page 2 for detailed data of measurement setup
Rec. antenna (pre-scan):	height 1.00 m, parallel and 90° to EUT polarisation
Used filter:	bypass
Test specification:	FCC 15.205 § 15.209; RSS-Gen: Issue 4
Operator:	Klv
Operating conditions:	U-NII-2A BW 40 MHz 5310 MHz Fixed Channel
Power during tests:	5V DC

EUT Information

Manufacturer:	Intel
Module details:	VLMTX58G
Module Type:	Video Link Module TX 5.8 GHz (Video RF Transmitter)
Module MAC version:	4.10.37.8
Module APP version:	3.13.20.0
Module Serial number:	1ABOPTX10PTXD1006160905
Antenna Details:	WALSIN PCB ANTENNA - RFPCA201018IM5B301
Antenna Type:	DIPOLE
Antenna HW version:	N/A
Antenna Gain:	5.47 dBi
Antenna Serial number:	N/A
Test Configuration:	2 X WALSIN Antenna connected to VLMTX58G Modules (J1 & J2) connector using micro-UFL connector cable 10 cm in length
Connected Interfaces:	Both of these Antennas were separated by at least 20 cm
Test Mode Settings:	Using AppCom-Version 4.0.4.26 Software
Power Supply:	5 V DC (using Laboratory DC Supply)

Full Spectrum



2.05_TX-Sp.VLMTX58G+WALSIN-BW40MHz-5510 MHz-+10dBm


Common Information

Test description:	Magnetic Field Strength Measurement related to 30/300 m distance
Test site and distance:	Ref.-Nr. 441 Semi Anechoic Room (SAR) with 3 m measurement distance
Version of Testsoftware:	EMC32 V9.25.0
Distance correction:	used accord. table, pls. see test report
Technical Data:	Please see page 2 for detailed data of measurement setup
Rec. antenna (pre-scan):	height 1.00 m, parallel and 90° to EUT polarisation
Used filter:	bypass
Test specification:	FCC 15.205 § 15.209; RSS-Gen: Issue 4
Operator:	Klv
Operating conditions:	U-NII-2C BW 40 MHz 5510 MHz Fixed Chanel
Power during tests:	5V DC

EUT Information

Manufacturer:	Intel
Module details:	VLMTX58G
Module Type:	Video Link Module TX 5.8 GHz (Video RF Transmitter)
Module MAC version:	4.10.37.8
Module APP version:	3.13.20.0
Module Serial number:	1ABOPTX10PTXD1006160905
Antenna Details:	WALSIN PCB ANTENNA - RFPCA201018IM5B301
Antenna Type:	DIPOLE
Antenna HW version:	N/A
Antenna Gain:	5.47 dBi
Antenna Serial number:	N/A
Test Configuration:	2 X WALSIN Antenna connected to VLMTX58G Modules (J1 & J2) connector using micro-UFL connector cable 10 cm in length
Connected Interfaces:	Both of these Antennas were separated by at least 20 cm
Test Mode Settings:	Using AppCom-Version 4.0.4.26 Software
Power Supply:	5 V DC (using Laboratory DC Supply)

Full Spectrum



2.06_TX-Sp.VLMTX58G+WALSIN-BW40MHz-5590 MHz-+10dBm


Common Information

Test description:	Magnetic Field Strength Measurement related to 30/300 m distance
Test site and distance:	Ref.-Nr. 441 Semi Anechoic Room (SAR) with 3 m measurement distance
Version of Testsoftware:	EMC32 V9.25.0
Distance correction:	used accord. table, pls. see test report
Technical Data:	Please see page 2 for detailed data of measurement setup
Rec. antenna (pre-scan):	height 1.00 m, parallel and 90° to EUT polarisation
Used filter:	bypass
Test specification:	FCC 15.205 § 15.209; RSS-Gen: Issue 4
Operator:	Klv
Operating conditions:	U-NII-2C BW 40 MHz 5590 MHz Fixed Chanel
Power during tests:	5V DC

EUT EUT Information

Manufacturer:	Intel
Module details:	VLMTX58G
Module Type:	Video Link Module TX 5.8 GHz (Video RF Transmitter)
Module MAC version:	4.10.37.8
Module APP version:	3.13.20.0
Module Serial number:	1ABOPTX10PTXD1006160905
Antenna Details:	WALSIN PCB ANTENNA - RFPCA201018IM5B301
Antenna Type:	DIPOLE
Antenna HW version:	N/A
Antenna Gain:	5.47 dBi
Antenna Serial number:	N/A
Test Configuration:	2 X WALSIN Antenna connected to VLMTX58G Modules (J1 & J2) connector using micro-UFL connector cable 10 cm in length
Connected Interfaces:	Both of these Antennas were separated by at least 20 cm
Test Mode Settings:	Using AppCom-Version 4.0.4.26 Software
Power Supply:	5 V DC (using Laboratory DC Supply)

Full Spectrum



2.07_TX-Sp.VLMTX58G+WALSIN-BW40MHz-5670 MHz-+10dBm


Common Information

Test description:	Magnetic Field Strength Measurement related to 30/300 m distance
Test site and distance:	Ref.-Nr. 441 Semi Anechoic Room (SAR) with 3 m measurement distance
Version of Testsoftware:	EMC32 V9.25.0
Distance correction:	used accord. table, pls. see test report
Technical Data:	Please see page 2 for detailed data of measurement setup
Rec. antenna (pre-scan):	height 1.00 m, parallel and 90° to EUT polarisation
Used filter:	bypass
Test specification:	FCC 15.205 § 15.209; RSS-Gen: Issue 4
Operator:	Klv
Operating conditions:	U-NII-2C BW 40 MHz 5670 MHz Fixed Chanel
Power during tests:	5V DC

EUT EUT Information

Manufacturer:	Intel
Module details:	VLMTX58G
Module Type:	Video Link Module TX 5.8 GHz (Video RF Transmitter)
Module MAC version:	4.10.37.8
Module APP version:	3.13.20.0
Module Serial number:	1ABOPTX10PTXD1006160905
Antenna Details:	WALSIN PCB ANTENNA - RFPCA201018IM5B301
Antenna Type:	DIPOLE
Antenna HW version:	N/A
Antenna Gain:	5.47 dBi
Antenna Serial number:	N/A
Test Configuration:	2 X WALSIN Antenna connected to VLMTX58G Modules (J1 & J2) connector using micro-UFL connector cable 10 cm in length
Connected Interfaces:	Both of these Antennas were separated by at least 20 cm
Test Mode Settings:	Using AppCom-Version 4.0.4.26 Software
Power Supply:	5 V DC (using Laboratory DC Supply)

Full Spectrum



2.08_TX-Sp.VLMTX58G+WALSIN-BW40MHz-5755 MHz-+10dBm


Common Information

Test description:	Magnetic Field Strength Measurement related to 30/300 m distance
Test site and distance:	Ref.-Nr. 441 Semi Anechoic Room (SAR) with 3 m measurement distance
Version of Testsoftware:	EMC32 V9.25.0
Distance correction:	used accord. table, pls. see test report
Technical Data:	Please see page 2 for detailed data of measurement setup
Rec. antenna (pre-scan):	height 1.00 m, parallel and 90° to EUT polarisation
Used filter:	bypass
Test specification:	FCC 15.205 § 15.209; RSS-Gen: Issue 4
Operator:	Klv
Operating conditions:	U-NII-3 BW 40 MHz 5755 MHz Fixed Channel
Power during tests:	5V DC

EUT Information

Manufacturer:	Intel
Module details:	VLMTX58G
Module Type:	Video Link Module TX 5.8 GHz (Video RF Transmitter)
Module MAC version:	4.10.37.8
Module APP version:	3.13.20.0
Module Serial number:	1ABOPTX10PTXD1006160905
Antenna Details:	WALSIN PCB ANTENNA - RFPCA201018IM5B301
Antenna Type:	DIPOLE
Antenna HW version:	N/A
Antenna Gain:	5.47 dBi
Antenna Serial number:	N/A
Test Configuration:	2 X WALSIN Antenna connected to VLMTX58G Modules (J1 & J2) connector using micro-UFL connector cable 10 cm in length
Connected Interfaces:	Both of these Antennas were separated by at least 20 cm
Test Mode Settings:	Using AppCom-Version 4.0.4.26 Software
Power Supply:	5 V DC (using Laboratory DC Supply)

Full Spectrum



2.09_TX-Sp.VLMTX58G+WALSIN-BW40MHz-5795 MHz-+10dBm


Common Information

Test description:	Magnetic Field Strength Measurement related to 30/300 m distance
Test site and distance:	Ref.-Nr. 441 Semi Anechoic Room (SAR) with 3 m measurement distance
Version of Testsoftware:	EMC32 V9.25.0
Distance correction:	used accord. table, pls. see test report
Technical Data:	Please see page 2 for detailed data of measurement setup
Rec. antenna (pre-scan):	height 1.00 m, parallel and 90° to EUT polarisation
Used filter:	bypass
Test specification:	FCC 15.205 § 15.209; RSS-Gen: Issue 4
Operator:	Klv
Operating conditions:	U-NII-3 BW 40 MHz 5795 MHz Fixed Channel
Power during tests:	5V DC

EUT Information

Manufacturer:	Intel
Module details:	VLMTX58G
Module Type:	Video Link Module TX 5.8 GHz (Video RF Transmitter)
Module MAC version:	4.10.37.8
Module APP version:	3.13.20.0
Module Serial number:	1ABOPTX10PTXD1006160905
Antenna Details:	WALSIN PCB ANTENNA - RFPCA201018IM5B301
Antenna Type:	DIPOLE
Antenna HW version:	N/A
Antenna Gain:	5.47 dBi
Antenna Serial number:	N/A
Test Configuration:	2 X WALSIN Antenna connected to VLMTX58G Modules (J1 & J2) connector using micro-UFL connector cable 10 cm in length
Connected Interfaces:	Both of these Antennas were separated by at least 20 cm
Test Mode Settings:	Using AppCom-Version 4.0.4.26 Software
Power Supply:	5 V DC (using Laboratory DC Supply)

Full Spectrum



2.2. Radiated Field Strength Emissions – 30 MHz to 1 GHz

3.01_ TX-Sp.VLMTX58G+WALSIN-BW40MHz-5190 MHz-+10dBm


Common Information

Test description: 14.02.2017 Page 1 of 2
 Test site and distance: Electric Field Strength Measurement
 Version of Testsoftware: Ref.-Nr. 441 Semi Anechoic Room (SAR) with 3 m measurement distance
 Distance correction: EMC32 V9.25.0
 Used filter: not used
 Technical Data: not used
 Test specification.: please see page 2 for detailed data of measurement setup
 Operator: FCC 15.209; RSS-Gen: Issue 4
 Operating conditions: YSa
 TX, continuous
 U-NII-1 | BW 40 MHz | 5190 MHz | Fixed Channel

EUT Information

Manufacturer: Intel
 Module details: VLMTX58G
 Module Type: Video Link Module TX 5.8 GHz (Video RF Transmitter)
 Module MAC version: 4.10.37.8
 Module APP version: 3.13.20.0
 Module Serial number: 1ABOPTX10PTXD1006160905
 Antenna Details: WALSIN PCB ANTENNA - RFPCA201018IM5B301
 Antenna Type: DIPOLE
 Antenna HW version: N/A
 Antenna Gain: 5.47 dBi
 Antenna Serial number: N/A
 Test Configuration: 2 X WALSIN Antenna connected to VLMTX58G Modules (J1 & J2) connector using micro-UFL connector cable 10 cm in length
 Connected Interfaces: Both of these Antennas were separated by at least 20 cm
 Test Mode Settings: Using AppCom-Version 4.0.4.26 Software
 Power Supply: 5 V DC (using Laboratory DC Supply)

Full Spectrum



Final_Result

Frequency (MHz)	QuasiPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Elevation (deg)	Corr (dB)
862.764000	30.24	46.00	15.76	1000.0	120.000	145.0	H	314.0	90.0	25.8
923.996000	31.46	46.00	14.54	1000.0	120.000	105.0	H	204.0	90.0	27.1

3.02_ TX-Sp.VLMTX58G+WALSIN-BW40MHz-5230 MHz-+10dBm


Common Information

Test description: Electric Field Strength Measurement
 Test site and distance: Ref.-Nr. 441 Semi Anechoic Room (SAR) with 3 m measurement distance
 Version of Testsoftware: EMC32 V9.25.0
 Distance correction: not used
 Used filter: not used
 Technical Data: please see page 2 for detailed data of measurement setup
 Test specification.: FCC 15.209; RSS-Gen: Issue 4
 Operator: YSa
 Operating conditions: U-NII-1 | BW 40 MHz | 5230 MHz | Fixed Channel

EUT Information

Manufacturer: Intel
 Module details: VLMTX58G
 Module Type: Video Link Module TX 5.8 GHz (Video RF Transmitter)
 Module MAC version: 4.10.37.8
 Module APP version: 3.13.20.0
 Module Serial number: 1ABOPTX10PTXD1006160905
 Antenna Details: WALSIN PCB ANTENNA - RFPCA201018IM5B301
 Antenna Type: DIPOLE
 Antenna HW version: N/A
 Antenna Gain: 5.47 dBi
 Antenna Serial number: N/A
 Test Configuration: 2 X WALSIN Antenna connected to VLMTX58G Modules (J1 & J2) connector using micro-UFL connector cable 10 cm in length
 Connected Interfaces: Both of these Antennas were separated by at least 20 cm
 Test Mode Settings: Using AppCom-Version 4.0.4.26 Software
 Power Supply: 5 V DC (using Laboratory DC Supply)

Full Spectrum



Final Result

Frequency (MHz)	QuasiPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Elevation (deg)	Corr (dB)
843.148000	29.91	46.00	16.09	1000.0	120.000	360.0	V	298.0	0.0	26.0
939.772000	31.54	46.00	14.46	1000.0	120.000	335.0	H	34.0	90.0	27.1
954.236000	31.57	46.00	14.43	1000.0	120.000	179.0	H	179.0	0.0	27.3

3.03_TX-Sp.VLMTX58G+WALSIN-BW40MHz-5270 MHz-+10dBm


Common Information

Test description: 14.02.2017 Page 1 of 2
 Test site and distance: Electric Field Strength Measurement
 Version of Testsoftware: Ref.-Nr. 441 Semi Anechoic Room (SAR) with 3 m measurement distance
 Distance correction: EMC32 V9.25.0
 Used filter: not used
 Technical Data: please see page 2 for detailed data of measurement setup
 Test specification.: FCC 15.209; RSS-Gen: Issue 4
 Operator: YSa
 Operating conditions: U-NII-2A | BW 40 MHz | 5270 MHz | Fixed Chanel

EUT Information

Manufacturer: Intel
 Module details: VLMTX58G
 Module Type: Video Link Module TX 5.8 GHz (Video RF Transmitter)
 Module MAC version: 4.10.37.8
 Module APP version: 3.13.20.0
 Module Serial number: 1ABOPTX10PTXD1006160905
 Antenna Details: WALSIN PCB ANTENNA - RFPCA201018IM5B301
 Antenna Type: DIPOLE
 Antenna HW version: N/A
 Antenna Gain: 5.47 dBi
 Antenna Serial number: N/A
 Test Configuration: 2 X WALSIN Antenna connected to VLMTX58G Modules (J1 & J2) connector using micro-UFL connector cable 10 cm in length
 Connected Interfaces: Both of these Antennas were separated by at least 20 cm
 Test Mode Settings: Using AppCom-Version 4.0.4.26 Software
 Power Supply: 5 V DC (using Laboratory DC Supply)

Full Spectrum



Final_Result

Frequency (MHz)	QuasiPeak (dBµV/m)	Limit (dBµV/m)	Margi n (dB)	Meas. Time (ms)	Bandwidth (kHz)	Heigh t (cm)	Pol	Azimuth (deg)	Elevation (deg)	Corr . (dB)
871.308000	30.66	46.00	15.34	1000.0	120.000	345.0	H	17.0	0.0	26.2
951.284000	31.57	46.00	14.43	1000.0	120.000	245.0	V	260.0	90.0	27.2

3.04_TX-Sp.VLMTX58G+WALSIN-BW40MHz-5310 MHz-+10dBm


Common Information

Test description: 15.02.2017 Page 1 of 2
 Test site and distance: Electric Field Strength Measurement
 Version of Testsoftware: Ref.-Nr. 441 Semi Anechoic Room (SAR) with 3 m measurement distance
 Distance correction: EMC32 V9.25.0
 Used filter: not used
 Technical Data: please see page 2 for detailed data of measurement setup
 Test specification.: FCC 15.209; RSS-Gen: Issue 4
 Operator: Kiv
 Operating conditions: U-NII-2A | BW 40 MHz | 5310 MHz | Fixed Chanel

EUT Information

Manufacturer: Intel
 Module details: VLMTX58G
 Module Type: Video Link Module TX 5.8 GHz (Video RF Transmitter)
 Module MAC version: 4.10.37.8
 Module APP version: 3.13.20.0
 Module Serial number: 1ABOPTX10PTXD1006160905
 Antenna Details: WALSIN PCB ANTENNA - RFPCA201018IM5B301
 Antenna Type: DIPOLE
 Antenna HW version: N/A
 Antenna Gain: 5.47 dBi
 Antenna Serial number: N/A
 Test Configuration: 2 X WALSIN Antenna connected to VLMTX58G Modules (J1 & J2) connector using micro-UFL connector cable 10 cm in length
 Connected Interfaces: Both of these Antennas were separated by at least 20 cm
 Test Mode Settings: Using AppCom-Version 4.0.4.26 Software
 Power Supply: 5 V DC (using Laboratory DC Supply)

Full Spectrum



Final Result

Frequency (MHz)	QuasiPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Elevation (deg)	Corr (dB)
912.816000	31.52	46.00	14.48	1000.0	120.000	355.0	V	61.0	90.0	27.2
918.204000	30.85	46.00	15.15	1000.0	120.000	271.0	V	269.0	90.0	26.6
920.820000	31.59	46.00	14.41	1000.0	120.000	208.0	V	160.0	90.0	27.1
921.940000	31.94	46.00	14.06	1000.0	120.000	113.0	H	270.0	90.0	27.1
926.476000	31.66	46.00	14.34	1000.0	120.000	109.0	H	89.0	90.0	27.0
941.308000	31.24	46.00	14.76	1000.0	120.000	189.0	H	114.0	0.0	26.8

3.05_ TX-Sp.VLMTX58G+WALSIN-BW40MHz-5510 MHz-+10dBm


Common Information

Test description:	15.02.2017 Page 1 of 2
Test site and distance:	Electric Field Strength Measurement
Version of Testsoftware:	Ref.-Nr. 441 Semi Anechoic Room (SAR) with 3 m measurement distance
Distance correction:	EMC32 V9.25.0
Used filter:	not used
Technical Data:	not used
Test specification.:	please see page 2 for detailed data of measurement setup
Operator:	FCC 15.209; RSS-Gen: Issue 4
Operating conditions:	Klv
	U-NII-2C BW 40 MHz 5510 MHz Fixed Channel

EUT Information

Manufacturer:	Intel
Module details:	VLMTX58G
Module Type:	Video Link Module TX 5.8 GHz (Video RF Transmitter)
Module MAC version:	4.10.37.8
Module APP version:	3.13.20.0
Module Serial number:	1ABOPTX10PTXD1006160905
Antenna Details:	WALSIN PCB ANTENNA - RFPCA201018IM5B301
Antenna Type:	DIPOLE
Antenna HW version:	N/A
Antenna Gain:	5.47 dBi
Antenna Serial number:	N/A
Test Configuration:	2 X WALSIN Antenna connected to VLMTX58G Modules (J1 & J2) connector using micro-UFL connector cable 10 cm in length
Connected Interfaces:	Both of these Antennas were separated by at least 20 cm
Test Mode Settings:	Using AppCom-Version 4.0.4.26 Software
Power Supply:	5 V DC (using Laboratory DC Supply)

Full Spectrum



Final_Result

Frequency (MHz)	QuasiPeak (dBμV/m)	Limit (dBμV/m)	Margi n (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Elevation (deg)	Corr . (dB)
890.424000	30.70	46.00	15.30	1000.0	120.000	174.0	H	172.0	0.0	26.6
891.880000	30.88	46.00	15.12	1000.0	120.000	308.0	H	67.0	0.0	26.6
896.164000	31.05	46.00	14.95	1000.0	120.000	286.0	H	167.0	0.0	26.8
898.568000	30.81	46.00	15.19	1000.0	120.000	235.0	H	197.0	90.0	26.7
910.780000	31.50	46.00	14.50	1000.0	120.000	183.0	H	63.0	0.0	27.4
912.424000	31.35	46.00	14.65	1000.0	120.000	157.0	V	153.0	0.0	27.2
936.404000	31.40	46.00	14.60	1000.0	120.000	325.0	V	44.0	90.0	27.0
937.220000	31.41	46.00	14.59	1000.0	120.000	288.0	V	31.0	90.0	27.0
943.364000	31.28	46.00	14.72	1000.0	120.000	355.0	V	196.0	0.0	26.9
944.248000	31.39	46.00	14.61	1000.0	120.000	202.0	H	294.0	0.0	27.0

3.06_TX-Sp.VLMTX58G+WALSIN-BW40MHz-5590 MHz-+10dBm


Common Information

15.02.2017 Page 1 of 2
 Test description: Electric Field Strength Measurement
 Test site and distance: Ref.-Nr. 441 Semi Anechoic Room (SAR) with 3 m measurement distance
 Version of Testsoftware: EMC32 V9.25.0
 Distance correction: not used
 Used filter: not used
 Technical Data: please see page 2 for detailed data of measurement setup
 Test specification.: FCC 15.209; RSS-Gen: Issue 4
 Operator: Kiv
 Operating conditions: U-NII-2C | BW 40 MHz | 5590 MHz | Fixed Chanel

EUT Information

Manufacturer: Intel
 Module details: VLMTX58G
 Module Type: Video Link Module TX 5.8 GHz (Video RF Transmitter)
 Module MAC version: 4.10.37.8
 Module APP version: 3.13.20.0
 Module Serial number: 1ABOPTX10PTXD1006160905
 Antenna Details: WALSIN PCB ANTENNA - RFPCA201018IM5B301
 Antenna Type: DIPOLE
 Antenna HW version: N/A
 Antenna Gain: 5.47 dBi
 Antenna Serial number: N/A
 Test Configuration: 2 X WALSIN Antenna connected to VLMTX58G Modules (J1 & J2) connector using micro-UFL connector cable 10 cm in length
 Connected Interfaces: Both of these Antennas were separated by at least 20 cm
 Test Mode Settings: Using AppCom-Version 4.0.4.26 Software
 Power Supply: 5 V DC (using Laboratory DC Supply)

Full Spectrum



Final Result

Frequency (MHz)	QuasiPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Elevation (deg)	Corr (dB)
843.032000	30.00	46.00	16.00	1000.0	120.000	248.0	H	286.0	0.0	26.0
910.028000	31.57	46.00	14.43	1000.0	120.000	163.0	H	304.0	90.0	27.5
913.536000	31.33	46.00	14.67	1000.0	120.000	327.0	V	16.0	90.0	27.1

3.07_TX-Sp.VLMTX58G+WALSIN-BW40MHz-5670 MHz-+10dBm


Common Information

Test description:	Electric Field Strength Measurement
Test site and distance:	Ref.-Nr. 441 Semi Anechoic Room (SAR) with 3 m measurement distance
Version of Testsoftware:	EMC32 V9.25.0
Distance correction:	not used
Used filter:	not used
Technical Data:	please see page 2 for detailed data of measurement setup
Test specification.:	FCC 15.209; RSS-Gen: Issue 4
Operator:	RIs
Operating conditions:	U-NII-2C BW 40 MHz 5670 MHz Fixed Chanel

EUT Information

Manufacturer:	Intel
Module details:	VLMTX58G
Module Type:	Video Link Module TX 5.8 GHz (Video RF Transmitter)
Module MAC version:	4.10.37.8
Module APP version:	3.13.20.0
Module Serial number:	1ABOPTX10PTXD1006160905
Antenna Details:	WALSIN PCB ANTENNA - RFPCA201018IM5B301
Antenna Type:	DIPOLE
Antenna HW version:	N/A
Antenna Gain:	5.47 dBi
Antenna Serial number:	N/A
Test Configuration:	2 X WALSIN Antenna connected to VLMTX58G Modules (J1 & J2) connector using micro-UFL connector cable 10 cm in length Both of these Antennas were separated by at least 20 cm
Connected Interfaces:	Using AppCom-Version 4.0.4.26 Software
Test Mode Settings:	5 V DC (using Laboratory DC Supply)
Power Supply:	

Full Spectrum



Final Result

Frequency (MHz)	QuasiPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Elevation (deg)	Corr (dB)
285.232000	34.68	46.00	11.32	1000.0	120.000	105.0	H	201.0	90.0	14.6
890.712000	30.81	46.00	15.19	1000.0	120.000	158.0	V	30.0	90.0	26.6

3.08_TX-Sp.VLMTX58G+WALSIN-BW40MHz-5755 MHz-+10dBm


Common Information

Test description:	Electric Field Strength Measurement
Test site and distance:	Ref.-Nr. 441 Semi Anechoic Room (SAR) with 3 m measurement distance
Version of Testsoftware:	EMC32 V9.25.0
Distance correction:	not used
Used filter:	not used
Technical Data:	please see page 2 for detailed data of measurement setup
Test specification.:	FCC 15.209; RSS-Gen: Issue 4
Operator:	RIs
Operating conditions:	U-NII-3 BW 40 MHz 5755 MHz Fixed Channel

EUT Information

Manufacturer:	Intel
Module details:	VLMTX58G
Module Type:	Video Link Module TX 5.8 GHz (Video RF Transmitter)
Module MAC version:	4.10.37.8
Module APP version:	3.13.20.0
Module Serial number:	1ABOPTX10PTXD1006160905
Antenna Details:	WALSIN PCB ANTENNA - RFPCA201018IM5B301
Antenna Type:	DIPOLE
Antenna HW version:	N/A
Antenna Gain:	5.47 dBi
Antenna Serial number:	N/A
Test Configuration:	2 X WALSIN Antenna connected to VLMTX58G Modules (J1 & J2) connector using micro-UFL connector cable 10 cm in length Both of these Antennas were separated by at least 20 cm
Connected Interfaces:	Using AppCom-Version 4.0.4.26 Software
Test Mode Settings:	5 V DC (using Laboratory DC Supply)
Power Supply:	

Full Spectrum



3.09_TX-Sp.VLMTX58G+WALSIN-BW40MHz-5795 MHz-+10dBm


Common Information

Test description:	Electric Field Strength Measurement
Test site and distance:	Ref.-Nr. 441 Semi Anechoic Room (SAR) with 3 m measurement distance
Version of Testsoftware:	EMC32 V9.25.0
Distance correction:	not used
Used filter:	not used
Technical Data:	please see page 2 for detailed data of measurement setup
Test specification.:	FCC 15.209; RSS-Gen: Issue 4
Operator:	RIs
Operating conditions:	U-NII-3 BW 40 MHz 5795 MHz Fixed Channel

EUT Information

Manufacturer:	Intel
Module details:	VLMTX58G
Module Type:	Video Link Module TX 5.8 GHz (Video RF Transmitter)
Module MAC version:	4.10.37.8
Module APP version:	3.13.20.0
Module Serial number:	1ABOPTX10PTXD1006160905
Antenna Details:	WALSIN PCB ANTENNA - RFPCA201018IM5B301
Antenna Type:	DIPOLE
Antenna HW version:	N/A
Antenna Gain:	5.47 dBi
Antenna Serial number:	N/A
Test Configuration:	2 X WALSIN Antenna connected to VLMTX58G Modules (J1 & J2) connector using micro-UFL connector cable 10 cm in length Both of these Antennas were separated by at least 20 cm
Connected Interfaces:	Using AppCom-Version 4.0.4.26 Software
Test Mode Settings:	5 V DC (using Laboratory DC Supply)
Power Supply:	

Full Spectrum



2.3. Radiated Field Strength Emissions – 1 GHz to 7 GHz

4.01_ TX-Sp.VLMTX58G+WALSIN-BW40MHz-5190 MHz-+10dBm


Common Information

Test Description:	Radiated field strength emission in 3m distance
Test Site:	CETECOM GmbH Essen
Test Standard:	FCC 15.407&15.209 Intentional Radiator
Antenna polarisation:	horizontal/vertical
Operation mode:	TX, continuous VLMTX58G+ 2X WALSIN ANTENNAS U-NII-1 BW 40 MHz 5190 MHz Fixed Chanel
Operator Name:	APh

EUT Information

Manufacturer:	Intel
Module details:	VLMTX58G
Module Type:	Video Link Module TX 5.8 GHz (Video RF Transmitter)
Module MAC version:	4.10.37.8
Module APP version:	3.13.20.0
Module Serial number:	1ABOPTX10PTXD1006160905
Antenna Details:	WALSIN PCB ANTENNA - RFPCA201018IM5B301
Antenna Type:	DIPOLE
Antenna HW version:	N/A
Antenna Gain:	5.47 dBi
Antenna Serial number:	N/A
Test Configuration:	2 X WALSIN Antenna connected to VLMTX58G Modules (J1 & J2) connector using micro-UFL connector cable 10 cm in length Both of these Antennas were separated by at least 20 cm
Connected Interfaces:	Using AppCom-Version 4.0.4.26 Software
Test Mode Settings:	5 V DC (using Laboratory DC Supply)

Full Spectrum



4.02_ TX-Sp.VLMTX58G+WALSIN-BW40MHz-5230 MHz-+10dBm


Common Information

Test Description:	Radiated field strength emission in 3m distance
Test Site:	CETECOM GmbH Essen
Test Standard:	FCC 15.407&15.209 Intentional Radiator
Antenna polarisation:	horizontal/vertical
Operation mode:	TX, continuous VLMTX58G+ 2X WALSIN ANTENNAS
	U-NII-1 BW 40 MHz 5230 MHz Fixed Channel
Operator Name:	AFr

EUT Information

Manufacturer:	Intel
Module details:	VLMTX58G
Module Type:	Video Link Module TX 5.8 GHz (Video RF Transmitter)
Module MAC version:	4.10.37.8
Module APP version:	3.13.20.0
Module Serial number:	1ABOPTX10PTXD1006160905
Antenna Details:	WALSIN PCB ANTENNA - RFPCA201018IM5B301
Antenna Type:	DIPOLE
Antenna HW version:	N/A
Antenna Gain:	5.47 dBi
Antenna Serial number:	N/A
Test Configuration:	2 X WALSIN Antenna connected to VLMTX58G Modules (J1 & J2) connector using micro-UFL connector cable 10 cm in length
Connected Interfaces:	Both of these Antennas were separated by at least 20 cm
Test Mode Settings:	Using AppCom-Version 4.0.4.26 Software
Power Supply:	5 V DC (using Laboratory DC Supply)

Full Spectrum



4.03_TX-Sp.VLMTX58G+WALSIN-BW40MHz-5270 MHz-+10dBm


Common Information

Test Description:	Radiated field strength emission in 3m distance
Test Site:	CETECOM GmbH Essen
Test Standard:	FCC 15.407&15.209 Intentional Radiator
Antenna polarisation:	horizontal/vertical
Operation mode:	TX, continuous VLMTX58G+ 2X WALSIN ANTENNAS
	U-NII-2A BW 40 MHz 5270 MHz Fixed Chanel
Operator Name:	AFr

EUT Information

Manufacturer:	Intel
Module details:	VLMTX58G
Module Type:	Video Link Module TX 5.8 GHz (Video RF Transmitter)
Module MAC version:	4.10.37.8
Module APP version:	3.13.20.0
Module Serial number:	1ABOPTX10PTXD1006160905
Antenna Details:	WALSIN PCB ANTENNA - RFPCA201018IM5B301
Antenna Type:	DIPOLE
Antenna HW version:	N/A
Antenna Gain:	5.47 dBi
Antenna Serial number:	N/A
Test Configuration:	2 X WALSIN Antenna connected to VLMTX58G Modules (J1 & J2) connector using micro-UFL connector cable 10 cm in length
Connected Interfaces:	Both of these Antennas were separated by at least 20 cm
Test Mode Settings:	Using AppCom-Version 4.0.4.26 Software
Power Supply:	5 V DC (using Laboratory DC Supply)

Full Spectrum



4.04_TX-Sp.VLMTX58G+WALSIN-BW40MHz-5310 MHz-+10dBm


Common Information

Test Description:	Radiated field strength emission in 3m distance
Test Site:	CETECOM GmbH Essen
Test Standard:	FCC 15.407&15.209 Intentional Radiator
Antenna polarisation:	horizontal/vertical
Operation mode:	TX, continuous VLMTX58G+ 2X WALSIN ANTENNAS
	U-NII-2A BW 40 MHz 5310 MHz Fixed Channel
Operator Name:	AFr

EUT Information

Manufacturer:	Intel
Module details:	VLMTX58G
Module Type:	Video Link Module TX 5.8 GHz (Video RF Transmitter)
Module MAC version:	4.10.37.8
Module APP version:	3.13.20.0
Module Serial number:	1ABOPTX10PTXD1006160905
Antenna Details:	WALSIN PCB ANTENNA - RFPCA201018IM5B301
Antenna Type:	DIPOLE
Antenna HW version:	N/A
Antenna Gain:	5.47 dBi
Antenna Serial number:	N/A
Test Configuration:	2 X WALSIN Antenna connected to VLMTX58G Modules (J1 & J2) connector using micro-UFL connector cable 10 cm in length
Connected Interfaces:	Both of these Antennas were separated by at least 20 cm
Test Mode Settings:	Using AppCom-Version 4.0.4.26 Software
Power Supply:	5 V DC (using Laboratory DC Supply)

Full Spectrum



4.05_TX-Sp.VLMTX58G+WALSIN-BW40MHz-5510 MHz-+10dBm


Common Information

Test Description:	Radiated field strength emission in 3m distance
Test Site:	CETECOM GmbH Essen
Test Standard:	FCC 15.407&15.209 Intentional Radiator
Antenna polarisation:	horizontal/vertical
Operation mode:	TX, continuous VLMTX58G+ 2X WALSIN ANTENNAS
	U-NII-2C BW 40 MHz 5510 MHz Fixed Chanel (Modulated)
Operator Name:	AFr

EUT Information

Manufacturer:	Intel
Module details:	VLMTX58G
Module Type:	Video Link Module TX 5.8 GHz (Video RF Transmitter)
Module MAC version:	4.10.37.8
Module APP version:	3.13.20.0
Module Serial number:	1ABOPTX10PTXD1006160905
Antenna Details:	WALSIN PCB ANTENNA - RFPCA201018IM5B301
Antenna Type:	DIPOLE
Antenna HW version:	N/A
Antenna Gain:	5.47 dBi
Antenna Serial number:	N/A
Test Configuration:	2 X WALSIN Antenna connected to VLMTX58G Modules (J1 & J2) connector using micro-UFL connector cable 10 cm in length
Connected Interfaces:	Both of these Antennas were separated by at least 20 cm
Test Mode Settings:	Using AppCom-Version 4.0.4.26 Software
Power Supply:	5 V DC (using Laboratory DC Supply)

Full Spectrum



4.06_TX-Sp.VLMTX58G+WALSIN-BW40MHz-5590 MHz-+10dBm


Common Information

Test Description:	Radiated field strength emission in 3m distance
Test Site:	CETECOM GmbH Essen
Test Standard:	FCC 15.407&15.209 Intentional Radiator
Antenna polarisation:	horizontal/vertical
Operation mode:	TX, continuous VLMTX58G+ 2X WALSIN ANTENNAS U-NII-2C BW 40 MHz 5590 MHz Fixed Channel (Modulated)
Operator Name:	APh

EUT Information

Manufacturer:	Intel
Module details:	VLMTX58G
Module Type:	Video Link Module TX 5.8 GHz (Video RF Transmitter)
Module MAC version:	4.10.37.8
Module APP version:	3.13.20.0
Module Serial number:	1ABOPTX10PTXD1006160905
Antenna Details:	WALSIN PCB ANTENNA - RFPCA201018IM5B301
Antenna Type:	DIPOLE
Antenna HW version:	N/A
Antenna Gain:	5.47 dBi
Antenna Serial number:	N/A
Test Configuration:	2 X WALSIN Antenna connected to VLMTX58G Modules (J1 & J2) connector using micro-UFL connector cable 10 cm in length
Connected Interfaces:	Both of these Antennas were separated by at least 20 cm
Test Mode Settings:	Using AppCom-Version 4.0.4.26 Software
Power Supply:	5 V DC (using Laboratory DC Supply)

Full Spectrum



4.07_TX-Sp.VLMTX58G+WALSIN-BW40MHz-5670 MHz-+10dBm


Common Information

Test Description:	Radiated field strength emission in 3m distance
Test Site:	CETECOM GmbH Essen
Test Standard:	FCC 15.407&15.209 Intentional Radiator
Antenna polarisation:	horizontal/vertical
Operation mode:	TX, continuous VLMTX58G+ 2X WALSIN ANTENNAS
	U-NII-2C BW 40 MHz 5670 MHz Fixed Channel (Modulated)
Operator Name:	KIv

EUT Information

Manufacturer:	Intel
Module details:	VLMTX58G
Module Type:	Video Link Module TX 5.8 GHz (Video RF Transmitter)
Module MAC version:	4.10.37.8
Module APP version:	3.13.20.0
Module Serial number:	1ABOPTX10PTXD1006160905
Antenna Details:	WALSIN PCB ANTENNA - RFPCA201018IM5B301
Antenna Type:	DIPOLE
Antenna HW version:	N/A
Antenna Gain:	5.47 dBi
Antenna Serial number:	N/A
Test Configuration:	2 X WALSIN Antenna connected to VLMTX58G Modules (J1 & J2) connector using micro-UFL connector cable 10 cm in length
Connected Interfaces:	Both of these Antennas were separated by at least 20 cm
Test Mode Settings:	Using AppCom-Version 4.0.4.26 Software
Power Supply:	5 V DC (using Laboratory DC Supply)

Full Spectrum



4.08_TX-Sp.VLMTX58G+WALSIN-BW40MHz-5755 MHz-+10dBm


Common Information

Test Description:	Radiated field strength emission in 3m distance
Test Site:	CETECOM GmbH Essen
Test Standard:	FCC 15.407&15.209 Intentional Radiator
Antenna polarisation:	horizontal/vertical
Operation mode:	TX, continuous VLMTX58G+ 2X WALSIN ANTENNAS U-NII-3 BW 40 MHz 5755 MHz Fixed Channel (Modulated)
Operator Name:	KIv

EUT Information

Manufacturer:	Intel
Module details:	VLMTX58G
Module Type:	Video Link Module TX 5.8 GHz (Video RF Transmitter)
Module MAC version:	4.10.37.8
Module APP version:	3.13.20.0
Module Serial number:	1ABOPTX10PTXD1006160905
Antenna Details:	WALSIN PCB ANTENNA - RFPCA201018IM5B301
Antenna Type:	DIPOLE
Antenna HW version:	N/A
Antenna Gain:	5.47 dBi
Antenna Serial number:	N/A
Test Configuration:	2 X WALSIN Antenna connected to VLMTX58G Modules (J1 & J2) connector using micro-UFL connector cable 10 cm in length
Connected Interfaces:	Both of these Antennas were separated by at least 20 cm
Test Mode Settings:	Using AppCom-Version 4.0.4.26 Software
Power Supply:	5 V DC (using Laboratory DC Supply)

Full Spectrum



4.09_TX-Sp.VLMTX58G+WALSIN-BW40MHz-5795 MHz-+10dBm


Common Information

Test Description:	Radiated field strength emission in 3m distance
Test Site:	CETECOM GmbH Essen
Test Standard:	FCC 15.407&15.209 Intentional Radiator
Antenna polarisation:	horizontal/vertical
Operation mode:	TX, continuous VLMTX58G+ 2X WALSIN ANTENNAS U-NII-3 BW 40 MHz 5795 MHz Fixed Channel (Modulated)
Operator Name:	KIv

EUT Information

Manufacturer:	Intel
Module details:	VLMTX58G
Module Type:	Video Link Module TX 5.8 GHz (Video RF Transmitter)
Module MAC version:	4.10.37.8
Module APP version:	3.13.20.0
Module Serial number:	1ABOPTX10PTXD1006160905
Antenna Details:	WALSIN PCB ANTENNA - RFPCA201018IM5B301
Antenna Type:	DIPOLE
Antenna HW version:	N/A
Antenna Gain:	5.47 dBi
Antenna Serial number:	N/A
Test Configuration:	2 X WALSIN Antenna connected to VLMTX58G Modules (J1 & J2) connector using micro-UFL connector cable 10 cm in length Both of these Antennas were separated by at least 20 cm
Connected Interfaces:	Both of these Antennas were separated by at least 20 cm
Test Mode Settings:	Using AppCom-Version 4.0.4.26 Software
Power Supply:	5 V DC (using Laboratory DC Supply)

Full Spectrum



2.4. Radiated Field Strength Emissions – 7 GHz to 18 GHz

4.01a_ TX-Sp.VLMTX58G+WALSIN-BW40MHz-5190 MHz-+10dBm


Common Information

Test Description: Radiated field strength emission in 3m distance
Test Site: CETECOM GmbH Essen
Test Standard: FCC 15.407&15.209 Intentional Radiator
Antenna polarisation: horizontal/vertical
Operation mode: TX, continuous
U-NII-1 | BW 40 MHz | 5190 MHz | Fixed Channel
Operator Name: APh

EUT Information

Manufacturer: Intel
Module details: VLMTX58G
Module Type: Video Link Module TX 5.8 GHz (Video RF Transmitter)
Module MAC version: 4.10.37.8
Module APP version: 3.13.20.0
Module Serial number: 1ABOPTX10PTXD1006160905
Antenna Details: WALSIN PCB ANTENNA - RFPCA201018IM5B301
Antenna Type: DIPOLE
Antenna HW version: N/A
Antenna Gain: 5.47 dBi
Antenna Serial number: N/A
Test Configuration: 2 X WALSIN Antenna connected to VLMTX58G Modules (J1 & J2) connector using micro-UFL connector cable 10 cm in length
Connected Interfaces: Both of these Antennas were separated by at least 20 cm
Test Mode Settings: Using AppCom-Version 4.0.4.26 Software
Power Supply: 5 V DC (using Laboratory DC Supply)

Full Spectrum



Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	RMS (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Elevation (deg)	Corr. (dB)
10380.000000	55.50	---	68.00	12.50	155.0	V	310.0	90.0	9.6
10380.000000	---	53.92	150.00	96.08	155.0	V	310.0	90.0	9.6
15569.600000	56.12	---	74.00	17.88	155.0	V	160.0	90.0	19.9

4.02a_ TX-Sp.VLMTX58G+WALSIN-BW40MHz-5230 MHz-+10dBm


Common Information

Test Description: Radiated field strength emission in 3m distance
Test Site: CETECOM GmbH Essen
Test Standard: FCC 15.407&15.209 Intentional Radiator
Antenna polarisation: horizontal/vertical
Operation mode: TX, continuous
U-NII-1 | BW 40 MHz | 5230 MHz | Fixed Channel
RIs
Operator Name:

EUT EUT Information

Manufacturer: Intel
Module details: VLMTX58G
Module Type: Video Link Module TX 5.8 GHz (Video RF Transmitter)
Module MAC version: 4.10.37.8
Module APP version: 3.13.20.0
Module Serial number: 1ABOPTX10PTXD1006160905
Antenna Details: WALSIN PCB ANTENNA - RFPCA201018IM5B301
Antenna Type: DIPOLE
Antenna HW version: N/A
Antenna Gain: 5.47 dBi
Antenna Serial number: N/A
Test Configuration: 2 X WALSIN Antenna connected to VLMTX58G Modules (J1 & J2) connector using micro-UFL connector cable 10 cm in length
Connected Interfaces: Both of these Antennas were separated by at least 20 cm
Test Mode Settings: Using AppCom-Version 4.0.4.26 Software
Power Supply: 5 V DC (using Laboratory DC Supply)

Full Spectrum



Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	RMS (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Elevation (deg)	Corr. (dB)
10460.000000	54.76	---	68.00	13.24	155.0	V	310.0	90.0	9.1
10460.000000	---	52.82	150.00	97.18	155.0	V	310.0	90.0	9.1
15690.800000	56.18	---	74.00	17.82	155.0	V	170.0	0.0	20.1

4.03a_ TX-Sp.VLMTX58G+WALSIN-BW40MHz-5270 MHz-+10dBm


Common Information

Test Description: Radiated field strength emission in 3m distance
 Test Site: CETECOM GmbH Essen
 Test Standard: FCC 15.407&15.209 Intentional Radiator
 Antenna polarisation: horizontal/vertical
 Operation mode: TX, continuous
 U-NII-2A | BW 40 MHz | 5270 MHz | Fixed Channel
 Operator Name: RIs

EUT Information

Manufacturer: Intel
 Module details: VLMTX58G
 Module Type: Video Link Module TX 5.8 GHz (Video RF Transmitter)
 Module MAC version: 4.10.37.8
 Module APP version: 3.13.20.0
 Module Serial number: 1ABOPTX10PTXD1006160905
 Antenna Details: WALSIN PCB ANTENNA - RFPCA201018IM5B301
 Antenna Type: DIPOLE
 Antenna HW version: N/A
 Antenna Gain: 5.47 dBi
 Antenna Serial number: N/A
 Test Configuration: 2 X WALSIN Antenna connected to VLMTX58G Modules (J1 & J2) connector using micro-UFL connector cable 10 cm in length
 Connected Interfaces: Both of these Antennas were separated by at least 20 cm
 Test Mode Settings: Using AppCom-Version 4.0.4.26 Software
 Power Supply: 5 V DC (using Laboratory DC Supply)

Full Spectrum



Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	RMS (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Elevation (deg)	Corr. (dB)
10540.000000	54.68	---	68.00	13.32	155.0	V	0.0	0.0	9.1
10540.000000	---	52.45	150.00	97.55	155.0	V	0.0	0.0	9.1

4.04a_ TX-Sp.VLMTX58G+WALSIN-BW40MHz-5310 MHz-+10dBm


Common Information

Test Description: Radiated field strength emission in 3m distance
 Test Site: CETECOM GmbH Essen
 Test Standard: FCC 15.407&15.209 Intentional Radiator
 Antenna polarisation: horizontal/vertical
 Operation mode: TX, continuous
 U-NII-2A | BW 40 MHz | 5310 MHz | Fixed Channel
 RIs
 Operator Name:

EUT Information

Manufacturer: Intel
 Module details: VLMTX58G
 Module Type: Video Link Module TX 5.8 GHz (Video RF Transmitter)
 Module MAC version: 4.10.37.8
 Module APP version: 3.13.20.0
 Module Serial number: 1ABOPTX10PTXD1006160905
 Antenna Details: WALSIN PCB ANTENNA - RFPCA201018IM5B301
 Antenna Type: DIPOLE
 Antenna HW version: N/A
 Antenna Gain: 5.47 dBi
 Antenna Serial number: N/A
 Test Configuration: 2 X WALSIN Antenna connected to VLMTX58G Modules (J1 & J2) connector using micro-UFL connector cable 10 cm in length
 Connected Interfaces: Both of these Antennas were separated by at least 20 cm
 Test Mode Settings: Using AppCom-Version 4.0.4.26 Software
 Power Supply: 5 V DC (using Laboratory DC Supply)

Full Spectrum



Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	RMS (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Elevation (deg)	Corr. (dB)
10620.000000	54.59	---	74.00	19.41	155.0	H	290.0	0.0	9.8
10620.000000	---	52.07	54.00	1.93	155.0	H	290.0	0.0	9.8

4.05a_ TX-Sp.VLMTX58G+WALSIN-BW40MHz-5510 MHz-+10dBm


Common Information

Test Description: Radiated field strength emission in 3m distance
 Test Site: CETECOM GmbH Essen
 Test Standard: FCC 15.407&15.209 Intentional Radiator
 Antenna polarisation: horizontal/vertical
 Operation mode: TX, continuous
 U-NII-2C | BW 40 MHz | 5510 MHz | Fixed Channel
 Operator Name: Klv

EUT Information

Manufacturer: Intel
 Module details: VLMTX58G
 Module Type: Video Link Module TX 5.8 GHz (Video RF Transmitter)
 Module MAC version: 4.10.37.8
 Module APP version: 3.13.20.0
 Module Serial number: 1ABOPTX10PTXD1006160905
 Antenna Details: WALSIN PCB ANTENNA - RFPCA201018IM5B301
 Antenna Type: DIPOLE
 Antenna HW version: N/A
 Antenna Gain: 5.47 dBi
 Antenna Serial number: N/A
 Test Configuration: 2 X WALSIN Antenna connected to VLMTX58G Modules (J1 & J2) connector using micro-UFL connector cable 10 cm in length
 Connected Interfaces: Both of these Antennas were separated by at least 20 cm
 Test Mode Settings: Using AppCom-Version 4.0.4.26 Software
 Power Supply: 5 V DC (using Laboratory DC Supply)

Full Spectrum



Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	RMS (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Elevation (deg)	Corr. (dB)
11020.000000	56.14	---	74.00	17.86	155.0	H	290.0	0.0	12.0
11020.000000	---	53.92	54.00	0.08	155.0	H	290.0	0.0	12.0

4.06a_ TX-Sp.VLMTX58G+WALSIN-BW40MHz-5590 MHz-+10dBm


Common Information

Test Description: Radiated field strength emission in 3m distance
 Test Site: CETECOM GmbH Essen
 Test Standard: FCC 15.407&15.209 Intentional Radiator
 Antenna polarisation: horizontal/vertical
 Operation mode: TX, continuous
 U-NII-2C | BW 40 MHz | 5590 MHz | Fixed Channel
 Operator Name: Klv

EUT Information

Manufacturer: Intel
 Module details: VLMTX58G
 Module Type: Video Link Module TX 5.8 GHz (Video RF Transmitter)
 Module MAC version: 4.10.37.8
 Module APP version: 3.13.20.0
 Module Serial number: 1ABOPTX10PTXD1006160905
 Antenna Details: WALSIN PCB ANTENNA - RFPCA201018IM5B301
 Antenna Type: DIPOLE
 Antenna HW version: N/A
 Antenna Gain: 5.47 dBi
 Antenna Serial number: N/A
 Test Configuration: 2 X WALSIN Antenna connected to VLMTX58G Modules (J1 & J2) connector using micro-UFL connector cable 10 cm in length
 Connected Interfaces: Both of these Antennas were separated by at least 20 cm
 Test Mode Settings: Using AppCom-Version 4.0.4.26 Software
 Power Supply: 5 V DC (using Laboratory DC Supply)

Full Spectrum



Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	RMS (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Elevation (deg)	Corr. (dB)
11180.000000	53.36	---	74.00	20.64	155.0	H	290.0	0.0	10.4
11180.000000	---	50.75	54.00	3.25	155.0	H	290.0	0.0	10.4

4.07a_ TX-Sp.VLMTX58G+WALSIN-BW40MHz-5670 MHz-+10dBm


Common Information

Test Description: Radiated field strength emission in 3m distance
 Test Site: CETECOM GmbH Essen
 Test Standard: FCC 15.407&15.209 Intentional Radiator
 Antenna polarisation: horizontal/vertical
 Operation mode: TX, continuous
 U-NII-2C | BW 40 MHz | 5670 MHz | Fixed Channel
 Operator Name: Klv

EUT Information

Manufacturer: Intel
 Module details: VLMTX58G
 Module Type: Video Link Module TX 5.8 GHz (Video RF Transmitter)
 Module MAC version: 4.10.37.8
 Module APP version: 3.13.20.0
 Module Serial number: 1ABOPTX10PTXD1006160905
 Antenna Details: WALSIN PCB ANTENNA - RFPCA201018IM5B301
 Antenna Type: DIPOLE
 Antenna HW version: N/A
 Antenna Gain: 5.47 dBi
 Antenna Serial number: N/A
 Test Configuration: 2 X WALSIN Antenna connected to VLMTX58G Modules (J1 & J2) connector using micro-UFL connector cable 10 cm in length
 Connected Interfaces: Both of these Antennas were separated by at least 20 cm
 Test Mode Settings: Using AppCom-Version 4.0.4.26 Software
 Power Supply: 5 V DC (using Laboratory DC Supply)

Full Spectrum



Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	RMS (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Elevation (deg)	Corr. (dB)
11340.000000	53.22	---	74.00	20.78	155.0	H	290.0	0.0	10.3
11340.000000	---	51.16	54.00	2.84	155.0	H	290.0	0.0	10.3

4.08a_ TX-Sp.VLMTX58G+WALSIN-BW40MHz-5755 MHz-+10dBm


Common Information

Test Description: Radiated field strength emission in 3m distance
 Test Site: CETECOM GmbH Essen
 Test Standard: FCC 15.407&15.209 Intentional Radiator
 Antenna polarisation: horizontal/vertical
 Operation mode: TX, continuous
 U-NII-3 | BW 40 MHz | 5755 MHz | Fixed Chanel
 Operator Name: Klv

EUT Information

Manufacturer: Intel
 Module details: VLMTX58G
 Module Type: Video Link Module TX 5.8 GHz (Video RF Transmitter)
 Module MAC version: 4.10.37.8
 Module APP version: 3.13.20.0
 Module Serial number: 1ABOPTX10PTXD1006160905
 Antenna Details: WALSIN PCB ANTENNA - RFPCA201018IM5B301
 Antenna Type: DIPOLE
 Antenna HW version: N/A
 Antenna Gain: 5.47 dBi
 Antenna Serial number: N/A
 Test Configuration: 2 X WALSIN Antenna connected to VLMTX58G Modules (J1 & J2) connector using micro-UFL connector cable 10 cm in length
 Connected Interfaces: Both of these Antennas were separated by at least 20 cm
 Test Mode Settings: Using AppCom-Version 4.0.4.26 Software
 Power Supply: 5 V DC (using Laboratory DC Supply)

Full Spectrum



Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	RMS (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Elevation (deg)	Corr. (dB)
11510.000000	55.96	---	74.00	18.04	155.0	H	290.0	0.0	11.3
11510.000000	---	53.29	54.00	0.71	155.0	H	290.0	0.0	11.3

4.09a_ TX-Sp.VLMTX58G+WALSIN-BW40MHz-5795 MHz-+10dBm_ Retest_15_2_Sweep2


Common Information

Test Description: Radiated field strength emission in 3m distance
Test Site: CETECOM GmbH Essen
Test Standard: FCC 15.407&15.209 Intentional Radiator
Antenna polarisation: horizontal/vertical
Operation mode: U-NII-3 | BW 40 MHz | 5795 MHz | Fixed Channel
Operator Name: Lor

EUT Information

Manufacturer: Intel
Module details: VLMTX58G
Module Type: Video Link Module TX 5.8 GHz (Video RF Transmitter)
Module MAC version: 4.10.37.8
Module APP version: 3.13.20.0
Module Serial number: 1ABOPTX10PTXD1006160905
Antenna Details: WALSIN PCB ANTENNA - RFPCA201018IM5B301
Antenna Type: DIPOLE
Antenna HW version: N/A
Antenna Gain: 5.47 dBi
Antenna Serial number: N/A
Test Configuration: 2 X WALSIN Antenna connected to VLMTX58G Modules (J1 & J2) connector using micro-UFL connector cable 10 cm in length
Both of these Antennas were separated by at least 20 cm
Connected Interfaces: Using AppCom-Version 4.0.4.26 Software
Test Mode Settings: 5 V DC (using Laboratory DC Supply)
Power Supply:

Full Spectrum



Final_Result

Frequency (MHz)	MaxPeak (dBµV/m)	RMS (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)
11589.800000	---	48.00	54.00	6.00	100.0	1000.000	155.0	H	105.0
11589.800000	50.76	---	74.00	23.24	100.0	1000.000	155.0	H	106.0

(continuation of the "Final_Result" table from column 15 ...)

Frequency (MHz)	Elevation (deg)	Corr. (dB)	Comment
11589.800000	90.0	5.9	20:43:42 - 15.02.2017
11589.800000	90.0	5.9	20:42:43 - 15.02.2017


2.5. Radiated Field Strength Emissions – 18 GHz to 40 GHz

4.01b_ TX-Sp.VLMTX58G+WALSIN-BW40MHz-5190 MHz-+10dBm

Common Information

Test Description:	Radiated field strength emission in 1m distance
Test Site:	CETECOM GmbH Essen
Test Standard:	FCC 15.247, 15.205&15.209 Intentional Radiator
Antenna polarisation:	horizontal/vertical
Distance correction factor	3 to 1m: -10.5 dB applying to measurement results
SW-Version:	EMC32 V8.53.0
Operation mode:	U-NII-1 BW 40 MHz 5190 MHz Fixed Channel
Operator Name:	KIv

FCC_Sweep_15.407_18_40GHz_Pre




4.02b_ TX-Sp.VLMTX58G+WALSIN-BW40MHz-5230 MHz-+10dBm

Common Information

Test Description:	Radiated field strength emission in 1m distance
Test Site:	CETECOM GmbH Essen
Test Standard:	FCC 15.247, 15.205&15.209 Intentional Radiator
Antenna polarisation:	horizontal/vertical
Distance correction factor	3 to 1m: -10.5 dB applying to measurement results
SW-Version:	EMC32 V8.53.0
Operation mode:	U-NII-1 BW 40 MHz 5230 MHz Fixed Channel
Operator Name:	KIv

FCC_Sweep_15.407_18_40GHz_Pre




4.03b_ TX-Sp.VLMTX58G+WALSIN-BW40MHz-5270 MHz-+10dBm

Common Information

Test Description:	Radiated field strength emission in 1m distance
Test Site:	CETECOM GmbH Essen
Test Standard:	FCC 15.247, 15.205&15.209 Intentional Radiator
Antenna polarisation:	horizontal/vertical
Distance correction factor	3 to 1m: -10.5 dB applying to measurement results
SW-Version:	EMC32 V8.53.0
Operation mode:	U-NII-2A BW 40 MHz 5270 MHz Fixed Channel
Operator Name:	KIv
Comment:	Channel no. low/middle/high

FCC_Sweep_15.407_18_40GHz_Pre




4.04b_ TX-Sp.VLMTX58G+WALSIN-BW40MHz-5310 MHz-+10dBm

Common Information

Test Description:	Radiated field strength emission in 1m distance
Test Site:	CETECOM GmbH Essen
Test Standard:	FCC 15.247, 15.205&15.209 Intentional Radiator
Antenna polarisation:	horizontal/vertical
Distance correction factor	3 to 1m: -10.5 dB applying to measurement results
SW-Version:	EMC32 V8.53.0
Operation mode:	U-NII-2A BW 40 MHz 5310 MHz Fixed Channel
Operator Name:	KIv

FCC_Sweep_15.407_18_40GHz_Pre




4.05b_ TX-Sp.VLMTX58G+WALSIN-BW40MHz-5510 MHz-+10dBm

Common Information

Test Description:	Radiated field strength emission in 1m distance
Test Site:	CETECOM GmbH Essen
Test Standard:	FCC 15.247, 15.205&15.209 Intentional Radiator
Antenna polarisation:	horizontal/vertical
Distance correction factor	3 to 1m: -10.5 dB applying to measurement results
SW-Version:	EMC32 V8.53.0
Operation mode:	U-NII-2C BW 40 MHz 5510 MHz Fixed Channel
Operator Name:	KIv

FCC_Sweep_15.407_18_40GHz_Pre




4.06b_ TX-Sp.VLMTX58G+WALSIN-BW40MHz-5590 MHz-+10dBm

Common Information

Test Description:	Radiated field strength emission in 1m distance
Test Site:	CETECOM GmbH Essen
Test Standard:	FCC 15.247, 15.205&15.209 Intentional Radiator
Antenna polarisation:	horizontal/vertical
Distance correction factor	3 to 1m: -10.5 dB applying to measurement results
SW-Version:	EMC32 V8.53.0
Operation mode:	U-NII-2C BW 40 MHz 5590 MHz Fixed Channel
Operator Name:	KIv

FCC_Sweep_15.407_18_40GHz_Pre




4.07b_ TX-Sp.VLMTX58G+WALSIN-BW40MHz-5670 MHz-+10dBm

Common Information

Test Description:	Radiated field strength emission in 1m distance
Test Site:	CETECOM GmbH Essen
Test Standard:	FCC 15.247, 15.205&15.209 Intentional Radiator
Antenna polarisation:	horizontal/vertical
Distance correction factor	3 to 1m: -10.5 dB applying to measurement results
SW-Version:	EMC32 V8.53.0
Operation mode:	U-NII-2C BW 40 MHz 5670 MHz Fixed Channel
Operator Name:	KIv

FCC_Sweep_15.407_18_40GHz_Pre




4.08b_ TX-Sp.VLMTX58G+WALSIN-BW40MHz-5755 MHz-+10dBm

Common Information

Test Description:	Radiated field strength emission in 1m distance
Test Site:	CETECOM GmbH Essen
Test Standard:	FCC 15.247, 15.205&15.209 Intentional Radiator
Antenna polarisation:	horizontal/vertical
Distance correction factor	3 to 1m: -10.5 dB applying to measurement results
SW-Version:	EMC32 V8.53.0
Operation mode:	U-NII-3 BW 40 MHz 5755 MHz Fixed Chanel
Operator Name:	KIv

FCC_Sweep_15.407_18_40GHz_Pre




4.09b_ TX-Sp.VLMTX58G+WALSIN-BW40MHz-5795 MHz-+10dBm

Common Information

Test Description:	Radiated field strength emission in 1m distance
Test Site:	CETECOM GmbH Essen
Test Standard:	FCC 15.247, 15.205&15.209 Intentional Radiator
Antenna polarisation:	horizontal/vertical
Distance correction factor	3 to 1m: -10.5 dB applying to measurement results
SW-Version:	EMC32 V8.53.0
Operation mode:	U-NII-3 BW 40 MHz 5795 MHz Fixed Channel
Operator Name:	KIv

FCC_Sweep_15.407_18_40GHz_Pre



3.2. Channel 5230 MHz (U-NII-1:right band edge)

9.02_BE- VLMTX58G+WALSIN-BW40MHz-5230 MHz-+10dBm


Common Information

Test Description:	Radiated field strength emission in 3m distance
Test Site:	CETECOM GmbH Essen
Test Standard:	FCC 15.407&15.209 Intentional Radiator
Antenna polarisation:	horizontal/vertical
Operation mode:	TX, continuous VLMTX58G+ 2X WALSIN ANTENNAS U-NII-1 BW 40 MHz 5230 MHz Fixed Channel (Modulated)
Operator Name:	KIv

EUT Information

Manufacturer:	Intel
Module details:	VLMTX58G
Module Type:	Video Link Module TX 5.8 GHz (Video RF Transmitter)
Module MAC version:	4.10.37.8
Module APP version:	3.13.20.0
Module Serial number:	1ABOPTX10PTXD1006160905
Antenna Details:	WALSIN PCB ANTENNA - RFPCA201018IM5B301
Antenna Type:	DIPOLE
Antenna HW version:	N/A
Antenna Gain:	5.47 dBi
Antenna Serial number:	N/A
Test Configuration:	2 X WALSIN Antenna connected to VLMTX58G Modules (J1 & J2) connector using micro-UFL connector cable 10 cm in length Both of these Antennas were separated by at least 20 cm
Connected Interfaces:	Using AppCom-Version 4.0.4.26 Software
Test Mode Settings:	5 V DC (using Laboratory DC Supply)
Power Supply:	

Full Spectrum



3.3. Channel 5310 MHz (U-NII-2A: right band edge)

9.04_BE- VLMTX58G+WALSIN-BW40MHz-5310 MHz-+10dBm


Common Information

Test Description:	Radiated field strength emission in 3m distance
Test Site:	CETECOM GmbH Essen
Test Standard:	FCC 15.407&15.209 Intentional Radiator
Antenna polarisation:	horizontal/vertical
Operation mode:	TX, continuous VLMTX58G+ 2X WALSIN ANTENNAS
	U-NII-2A BW 40 MHz 5310 MHz Fixed Channel (Modulated)
Operator Name:	Klv

EUT Information

Manufacturer:	Intel
Module details:	VLMTX58G
Module Type:	Video Link Module TX 5.8 GHz (Video RF Transmitter)
Module MAC version:	4.10.37.8
Module APP version:	3.13.20.0
Module Serial number:	1ABOPTX10PTXD1006160905
Antenna Details:	WALSIN PCB ANTENNA - RFPCA201018IM5B301
Antenna Type:	DIPOLE
Antenna HW version:	N/A
Antenna Gain:	5.47 dBi
Antenna Serial number:	N/A
Test Configuration:	2 X WALSIN Antenna connected to VLMTX58G Modules (J1 & J2) connector using micro-UFL connector cable 10 cm in length
Connected Interfaces:	Both of these Antennas were separated by at least 20 cm
Test Mode Settings:	Using AppCom-Version 4.0.4.26 Software
Power Supply:	5 V DC (using Laboratory DC Supply)

Full Spectrum



3.4. Channel 5510 MHz (U-NII-2C: left band edge)

9.05_BE- VLMTX58G+WALSIN-BW40MHz-5510 MHz-+10dBm


Common Information

Test Description:	Radiated field strength emission in 3m distance
Test Site:	CETECOM GmbH Essen
Test Standard:	FCC 15.407&15.209 Intentional Radiator
Antenna polarisation:	horizontal/vertical
Operation mode:	TX, continuous VLMTX58G+ 2X WALSIN ANTENNAS
	U-NII-2C BW 40 MHz 5510 MHz Fixed Channel (Modulated)
Operator Name:	Klv

EUT Information

Manufacturer:	Intel
Module details:	VLMTX58G
Module Type:	Video Link Module TX 5.8 GHz (Video RF Transmitter)
Module MAC version:	4.10.37.8
Module APP version:	3.13.20.0
Module Serial number:	1ABOPTX10PTXD1006160905
Antenna Details:	WALSIN PCB ANTENNA - RFPCA201018IM5B301
Antenna Type:	DIPOLE
Antenna HW version:	N/A
Antenna Gain:	5.47 dBi
Antenna Serial number:	N/A
Test Configuration:	2 X WALSIN Antenna connected to VLMTX58G Modules (J1 & J2) connector using micro-UFL connector cable 10 cm in length
Connected Interfaces:	Both of these Antennas were separated by at least 20 cm
Test Mode Settings:	Using AppCom-Version 4.0.4.26 Software
Power Supply:	5 V DC (using Laboratory DC Supply)

Full Spectrum



3.5. Channel 5670 MHz (U-NII-2C: right band edge)

9.07_BE- VLMTX58G+WALSIN-BW40MHz-5670 MHz-+10dBm


Common Information

Test Description:	Radiated field strength emission in 3m distance
Test Site:	CETECOM GmbH Essen
Test Standard:	FCC 15.407&15.209 Intentional Radiator
Antenna polarisation:	horizontal/vertical
Operation mode:	TX, continuous VLMTX58G+ 2X WALSIN ANTENNAS
	U-NII-2C BW 40 MHz 5670 MHz Fixed Channel (Modulated)
Operator Name:	Klv

EUT Information

Manufacturer:	Intel
Module details:	VLMTX58G
Module Type:	Video Link Module TX 5.8 GHz (Video RF Transmitter)
Module MAC version:	4.10.37.8
Module APP version:	3.13.20.0
Module Serial number:	1ABOPTX10PTXD1006160905
Antenna Details:	WALSIN PCB ANTENNA - RFPCA201018IM5B301
Antenna Type:	DIPOLE
Antenna HW version:	N/A
Antenna Gain:	5.47 dBi
Antenna Serial number:	N/A
Test Configuration:	2 X WALSIN Antenna connected to VLMTX58G Modules (J1 & J2) connector using micro-UFL connector cable 10 cm in length
Connected Interfaces:	Both of these Antennas were separated by at least 20 cm
Test Mode Settings:	Using AppCom-Version 4.0.4.26 Software
Power Supply:	5 V DC (using Laboratory DC Supply)

Full Spectrum



3.6. Channel 5755 MHz (U-NII-3: left band edge)

9.08_BE- VLMTX58G+WALSIN-BW40MHz-5755 MHz-+10dBm


Common Information

Test Description:	Radiated field strength emission in 3m distance
Test Site:	CETECOM GmbH Essen
Test Standard:	FCC 15.407&15.209 Intentional Radiator
Antenna polarisation:	horizontal/vertical
Operation mode:	TX, continuous VLMTX58G+ 2X WALSIN ANTENNAS
Operator Name:	U-NII-3 BW 40 MHz 5755 MHz Fixed Channel (Modulated) APh

EUT Information

Manufacturer:	Intel
Module details:	VLMTX58G
Module Type:	Video Link Module TX 5.8 GHz (Video RF Transmitter)
Module MAC version:	4.10.37.8
Module APP version:	3.13.20.0
Module Serial number:	1ABOPTX10PTXD1006160905
Antenna Details:	WALSIN PCB ANTENNA - RFPCA201018IM5B301
Antenna Type:	DIPOLE
Antenna HW version:	N/A
Antenna Gain:	5.47 dBi
Antenna Serial number:	N/A
Test Configuration:	2 X WALSIN Antenna connected to VLMTX58G Modules (J1 & J2) connector using micro-UFL connector cable 10 cm in length
Connected Interfaces:	Both of these Antennas were separated by at least 20 cm
Test Mode Settings:	Using AppCom-Version 4.0.4.26 Software
Power Supply:	5 V DC (using Laboratory DC Supply)

Full Spectrum



3.7. Channel 5795 MHz (U-NII-3: right band edge)

9.09_BE- VLMTX58G+WALSIN-BW40MHz-5795 MHz-+10dBm

Common Information

Test Description:	Radiated field strength emission in 3m distance
Test Site:	CETECOM GmbH Essen
Test Standard:	FCC 15.407&15.209 Intentional Radiator
Antenna polarisation:	horizontal/vertical
Operation mode:	TX, continuous VLMTX58G+ 2X WALSIN ANTENNAS
	U-NII-3 BW 40 MHz 5795 MHz Fixed Channel (Modulated)
Operator Name:	Aph

EUT Information

Manufacturer:	Intel
Module details:	VLMTX58G
Module Type:	Video Link Module TX 5.8 GHz (Video RF Transmitter)
Module MAC version:	4.10.37.8
Module APP version:	3.13.20.0
Module Serial number:	1ABOPTX10PTXD1006160905
Antenna Details:	WALSIN PCB ANTENNA - RFPCA201018IM5B301
Antenna Type:	DIPOLE
Antenna HW version:	N/A
Antenna Gain:	5.47 dBi
Antenna Serial number:	N/A
Test Configuration:	2 X WALSIN Antenna connected to VLMTX58G Modules (J1 & J2) connector using micro-UFL connector cable 10 cm in length
Connected Interfaces:	Both of these Antennas were separated by at least 20 cm
Test Mode Settings:	Using AppCom-Version 4.0.4.26 Software
Power Supply:	5 V DC (using Laboratory DC Supply)

Full Spectrum

