

Page : 1 of 10

Issued date : Aug. 27, 2019

FCC ID : 2ASXC-TMO-NBT-01

## **Maximum Permissible Exposure Report**

**Product** : Pet tracker

**Model Name** : TMUS-SUP-1

FCC ID : 2ASXC-TMO-NBT-01

**Test Regulation** : 47 CFR FCC Part 2.1091

**Received Date** : May 3, 2019

**Issued Date** : Aug. 27, 2019

**Applicant** : T-mobile Usa, Inc.

12920 Se 38th Street, Bellevue, Washington, United

States, 98006

**Issued By** : Underwriters Laboratories Taiwan Co., Ltd.

Building B and Building E, No. 372-7, Sec. 4, Zhongxing

Rd., Zhudong Township, Hsinchu County, Taiwan





The results reported herein have been performed in accordance with the laboratory's terms of accreditation. This report shall not be reproduced except in full without the written approval of the Laboratory. The results in this report are responsible of the test sample(s) provided by the client only and are not to be used to indicate applicability to other similar products.

Telephone :+886-2-7737-3000 Facsimile (FAX) :+886-3-583-7948

Doc No: 17-EM-F0864 / 2.0



Page : 2 of 10

Issued date : Aug. 27, 2019

FCC ID : 2ASXC-TMO-NBT-01

# **REVISION HISTORY**

Original Test Report No.: 4789004574-US-R4-V0

Rev.	Test report No. 4789004574-US-R4-V0	Date	Page revised	Contents
Original	4789004574-US-R4-V0	Aug. 27, 2019	-	Initial issue
<u> </u>				
-				



Page : 3 of 10

Issued date : Aug. 27, 2019

FCC ID : 2ASXC-TMO-NBT-01

## **Table Of Contents**

1. A	ttestation of Test Results	4
2. To	est Methodology	5
3. Fa	acilities and Accreditation	5
4. E	quipment Under Test	6
4.1.	Description of EUT	6
4.2.	Description Of Available Antennas	8
5. R	equirement	9
6. R	adio Frequency Radiation Exposure Evaluation	



Page : 4 of 10

Issued date : Aug. 27, 2019

FCC ID : 2ASXC-TMO-NBT-01

#### 1. Attestation of Test Results

**APPLICANT:** T-mobile Usa, Inc.

12920 Se 38th Street, Bellevue, Washington, United States,

98006

**MANUFACTURER** CyberTAN Technology Inc.

No. 99, Park Avenue III Science-based Industrial Park

Hsinchu Taiwan 308

**EUT DESCRIPTION:** Pet tracker

**BRAND:** T-mobile

MODEL: TMUS-SUP-1

**SAMPLE STAGE:** Engineering sample

#### APPLICABLE STANDARDS

**STANDARD** 

**Test Results** 

47 CFR FCC PART 2.1091

**PASS** 

Underwriters Laboratories Taiwan Co., Ltd. tested the above equipment in accordance with the requirements set forth in the above standards. All indications of Pass/Fail in this report are opinions expressed by Underwriters Laboratories Taiwan Co., Ltd. based on interpretations and/or observations of test results. Measurement Uncertainties were not taken into account and are published for informational purposes only. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

**Note:** The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. This document may not be altered or revised in any way unless done so by Underwriters Laboratories Taiwan Co., Ltd. and all revisions are duly noted in the revisions section. Any alteration of this document not carried out by Underwriters Laboratories Taiwan Co., Ltd. will constitute fraud and shall nullify the document. This report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, any agency of the Federal Government, or any agency of any government.

Prepared By:

Approved and Authorized By:

Evelyn Lee

Date: Aug. 27, 2019

Stanley Wu D

Date: Aug. 27, 2019

Project Handler Senior Project Engineer

Underwriters Laboratories Taiwan Co., Ltd.

Building B and Building E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan

Telephone :+886-2-7737-3000 Facsimile (FAX) :+886-3-583-7948

Doc No: 17-EM-F0864 / 2.0



Page : 5 of 10

Issued date : Aug. 27, 2019

FCC ID : 2ASXC-TMO-NBT-01

## 2. Test Methodology

The tests documented in this report were performed in accordance with KDB 447498 D01 General RF Exposure Guidance v06.

## 3. Facilities and Accreditation

Test Location Underwriters Laboratories Taiwan Co., Ltd.		
Address	Building B and Building E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan	
Accreditation Certificate	Underwriters Laboratories Taiwan Co., Ltd. is accredited by TAF, Laboratory Code 3398. The full scope of accreditation can be viewed at <a href="http://accreditation.taftw.org.tw/taf/public/basic/viewApplyItems.action?unitNo=3398">http://accreditation.taftw.org.tw/taf/public/basic/viewApplyItems.action?unitNo=3398</a>	



Page : 6 of 10

Issued date : Aug. 27, 2019

FCC ID : 2ASXC-TMO-NBT-01

## 4. Equipment Under Test

## 4.1. Description of EUT

Product Name	Pet tracker			
Brand Name	T-Mobile			
Model Name	TMUS-SUP-	TMUS-SUP-1		
On anoting Engage	BLE	2402MHz ~ 2480MHz		
Operating Frequency	WLAN	2.4GHz: 2412MHz ~ 2462MHz		
	BLE	GFSK		
Modulation	WLAN	CCK, DQPSK, DBPSK for DSSS		
	WLAN	64QAM, 16QAM, QPSK, BPSK for OFDM		
Number of Channel	BLE	40		
Number of Channel	WLAN	802.11b, 802.11g, 802.11n (HT20): 11		
Normal Valtaga	5Vdc (adapter or host equipment)			
Normal Voltage	3.7Vdc for battery			
Hardware Version	V01			
Software Version	0.31.10.14			

#### Note:

1. The EUT incorporates a SISO function. Physically, the EUT provides one completed transmitter and one receiver.

<b>Modulation Mode</b>	Tx,Rx Function
802.11b	1TX,1RX
802.11g	1TX,1RX
802.11n (HT20)	1TX,1RX



Page : 7 of 10

Issued date : Aug. 27, 2019

FCC ID : 2ASXC-TMO-NBT-01

2. The EUT contains following accessory devices Product Brand Model Description USB Cable

Product	Brand	Model	Description
Adapter	CyberTAN	AN05A-050E-H	I/P: 100-240Vac, 50-60Hz, 0.2A O/P: 5.0 Vdc, 1.0A
Battery	CyberTAN	GWB001-A1	3.7 Vdc, 450 mAh
Charging Dock	CyberTAN	N/A	N/A
Collar mount	CyberTAN	N/A	N/A
USB Cable	N/A	N/A	1 meter shielded cable without core
Bands	CyberTAN	N/A	N/A

The above EUT information is declared by manufacturer and for more detailed features description, please refer the manufacturer's or user's manual.



Page : 8 of 10

Issued date : Aug. 27, 2019

FCC ID : 2ASXC-TMO-NBT-01

## 4.2. Description Of Available Antennas

Antenna	<b>Brand Name</b>	Model Name	Antenna Type	Antenna Gain(dBi)
BLE	N/A	NB-IOT tracker	Internal	-2.3

Antenna	<b>Brand Name</b>	Model Name	Antenna Type	Antenna Gain(dBi)
WLAN 2.4GHz	N/A	NB-IOT tracker	Internal	-2.3

Note: The above antenna information was provided from customer and for more detailed features description, please refer the manufacturer's specification or user's manual.

Telephone :+886-2-7737-3000

Facsimile (FAX): +886-3-583-7948 Doc No: 17-EM-F0864 / 2.0



Page : 9 of 10

Issued date : Aug. 27, 2019

FCC ID : 2ASXC-TMO-NBT-01

### 5. Requirement

Limits for General Population/Uncontrolled Exposure

Limits for General Population/Uncontrolled Exposure								
Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm <sup>2</sup> )	Averaging Time  E 2,  H 2 or S (minutes)				
0.3-1.34	614	1.63	*100	30				
1.34-30	824/f	2.19/f	*180/f <sup>2</sup>	30				
30-300	27.5	0.073	0.2	30				
300-1500			f/1500	30				
1500-100,000			1.0	30				

Note 1: f = frequency in MHz, \* means Plane-wave equivalent power density

Note 2: General population/uncontrolled exposures apply in situations in which the general public may be exposed, or in which persons that are exposed as a consequence of their employment may not be fully aware of the potential for exposure or cannot exercise control over their exposure.

Power Density (S) is calculated by the following formula:

 $S=(P*G)/4\pi R^2$ 

where:  $S = power density (in appropriate units, e.g. <math>mW/cm^2$ )

P = power input to the antenna (in appropriate units, e.g., mW)

G = power gain of the antenna in the direction of interest relative to an isotropic radiator <math>R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)



Page : 10 of 10 Issued date : Aug. 27, 2019

FCC ID : 2ASXC-TMO-NBT-01

### 6. Radio Frequency Radiation Exposure Evaluation

#### **BLE**

BLE							
Max. Average power   Antenna Gain   Max. EIRP   Max. EIRP   Power density @ 20 cm   Limit							
(dBm)	(dBi)	(dBm)	(mW)	(mW/cm <sup>2</sup> )	(mW/cm <sup>2</sup> )		
1.65	-2.30	-0.65	0.861	0.000	1		

#### WLAN 2.4GHz

WLAN 2.4GHz							
Max. Average power   Antenna Gain   Max. EIRP   Max. EIRP   Power density @ 20 cm   Limit							
(dBm)	(dBi)	(dBm)	(mW)	(mW/cm <sup>2</sup> )	(mW/cm <sup>2</sup> )		
14	-2.30	11.70	14.791	0.003	1		

#### Note:

- 1. Max. EIRP (dBm) = Max. Average power (dBm) + Antenna Gain (dBi)
- 2. Max. EIRP (mW) =  $10^{(\text{Max. EIRP (dBm)}/10)}$
- 3. Power density (mW/cm<sup>2</sup>) = Max. EIRP (mW) / [  $4 \times \pi \times (\text{calculated distance})^2$  ], the calculated distance is 20 cm.
- 4. WiFi has more data transmission. When the tracker is removed and placed on the charging stand, the MPE is calculated at a distance of 20cm.

#### **Conclusion:**

According to 47 CFR §2.1091, the RF exposure analysis concludes that the RF Exposure is FCC compliant.