

Remote control parameters		Operation temperature	-5 ℃ -40 ℃
Dimension	146*43*16		
working voltage	AAA-3V	Standby current	2uA
Operating Frequency	2.4M Hz	Transmitting distance	>30M

(12)

Kind reminder:

When the transmitter cannot remotely control the receiver, please check whether the switch battery contacts are normal, whether the positive and negative poles are placed correctly, and whether the battery level is sufficient (if the signal light is dim; please replace the battery, both batteries must be of the same brand).

- 2. When the transmitter cannot remotely control the receiver, please check if there are remote control products of the same frequency in the nearby area, and check if their transmitter buttons are pressed, because transmitting remote control products of the same frequency at the same time can cause interference, affecting the effect of receiving incorrect commands. If the remote control function is ruled out, it will return to normal.
- 3. Please do not place this product within the reach of children when using it
- 4. This product has a fan power-off memory function, which automatically turns on the direction of the previous fan next time.
- 5. Code learning operation: Within 1 minute of powering on, hold down "1H" and the light will flash, indicating successful code matching.
- 6. When the remote control cannot be effectively controlled: Please check the battery. If it is not used for a long time, please remove the battery.

FCC Warnning:

This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to part 15 of the FCC Rules. These limits are designed to provide reasonable protection againstharmful interference in a residential installation. This equipment generates, uses and can radiateradio frequency energy and, if not installed and used in accordance with the instructions, maycause harmful interference to radio communications. However, there is no guarantee thatinterference will not occur in a particular installation. If this equipment does cause harmfulinterference to radio or television reception, which can be determined by turning the equipmentoff and on, the user is encouraged to try to correct the interference by one or more of thefollowing measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

Caution: Any changes or modifications to this device not explicitly approved by manufacturer could void your authority to operate this equipment.

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions:

(1)This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

This equipment complies with FCC radiation exposure limits set forth for an uncontrolled environment. This equipment should be installed and operated with minimum distance 0cm between the radiator and your body.