



Antenna Kitting Information

Component	Type specification	Gain/Loss					Manufacturer
		LTE-707	LTE-781	800MH	1900MHz	1700MHz\2100MHz	
Outside Cable	SRLMR400-75NN 75Feet	4.2dB	4.2dB	4.4dB	6.1dB	5.8dB\6.5dB	Suirongcable
Outside Cable	RG6FF 75Feet	3.6dB	3.8dB	4.2dB	6.3dB	5.5dB\7dB	Suirongcable
Outside Cable	LMR240 75Feet	4.88dB	5.25dB	5.63dB	8.25dB	8.25\8.63 dB	Suirongcable
Outside Cable	RG6FF 60Feet	2.9dB	3.0dB	3.3dB	5dB	4.4dB\5.6dB	Suirongcable
Outside Antenna	ANT050701	7dBi	7dBi	7dBi	10dBi	10dBi\10dBi	Shenzhen Dachi Communicatio ns Co., Ltd.
Outside Antenna	ANT010901	9dBi	9dBi	9dBi	9dBi	9dBi	Shenzhen Dachi Communicatio ns Co., Ltd.
Outside Antenna	ANT010701	9dBi	9dBi	9dBi	9dBi	9dBi	Shenzhen Dachi Communicatio ns Co., Ltd.
Inside Antenna	ST-215-BZ-01	3dBi	3dBi	3dBi	3dBi	3dBi	Shenzhen Dachi Communicatio ns Co., Ltd.
Inside Antenna	ST-215-BZ-01-B	3dBi	3dBi	3dBi	3dBi	3dBi	Shenzhen Dachi Communicatio ns Co., Ltd.
Lightning Protector	ACC010101	0.1 dB	0.1 dB	0.1 dB	0.18dB	0.16dB\0.2dB	Shenzhen Dachi Communicatio ns Co., Ltd.
All equivalent antennas and cables are suitable for use with the SolidRF booster.							

Default combination:

SR55652001A + ANT050701 + RG6FF 75Feet + ST-215-BZ-01*4 pcs

SR55652001B + ANT050701 + RG6FF 75Feet + ST-215-BZ-01-B*4 pcs