

			IIAT	INFORMATION
-11		PROID	11621	INFORNATION
	I AIID	11100	-	

Type of Equipment	Wireless Indoor Camera			
Applicant Name	Panasonic Corporation of North America			
Address	Two Riverfront Plaza, 9th Floor Newark, NJ 07102-5490			
Contact	Ben Botros			
Telephone	+1-(201) 348-7760			
Email	ben.botros@us.panasonic.com			
Brand Name	Panasonic			
Model Number	KX-HNC810			
Hardware Version				
Software Version				
FCC ID	ACJ96NKX-HNC810			
IC ID	IC:216A-KXHNC810			

1. Basic Information					
FCC 15 Part	■ 15.247	□ 15.249	■ Other		
Please specify if other: 15.407					
Type of Equipment	☐ FHSS	⊠ DTS	☐ Other		
Please specify if other:	•				
Classification of EUT	⊠ Portable	☐ Mobile	☐ Fixed		
Lowest Operating Frequency	2412MHz				
Highest Operating Frequency	2462MHz	2462MHz			
Nominal Output Power	30mW				
Maximum Duty Cycle (in actual use)	60%				
Operating Mode (list all)	IEEE802.11b/g/n (HT20)				
Modulation Type (list all)	Digital (DSSS, OFDM)				
Nominal 99% Bandwidth	18MHz				
Maximum Number of channels	11				
Channel Separation	5MHz				
Number of Antennas	1				
Antenna Diversity Supported	□ Yes	⊠ No			
Smart Antenna System	☐ Yes	⊠ No			
Reduced output power on any channels	☐ Yes	⊠ No	⊠ No		
If YES, please specify:	•	•			



2. FHSS Equipment (fill in if FHSS Equipment, FCC 15.247)						
Adaptive Frequency Hopping	□ Yes		⊠ No			
If YES, please specify minimum number of	If YES, please specify minimum number of hopping channels :					
3. DTS Equipment (fill in if DTS Equip		247)				
Nominal 6 dB Bandwidth	18MHz					
5 Di cata cata Farris manat (fill in if Diverse)						
BT 2.0 EDR ?	4. Bluetooth Equipment (fill in if Bluetooth Equipment)					
BT 3.0 HS ?	□ Yes		□ No			
	□ Yes					
BT Low Energy	□ Yes		□ No			
5. 2.4GHz WLAN Equipment (fill in if 2.40	Hz WLAN Equipn	nent)				
Supported Operating Modes	⊠ 802.11b	⊠ 802.11g	⊠ 802.	11n	□ 802.11ac	
Supported Channel Bandwidths	□ 40 MHz	□ 40 MHz		<u> </u>		
Number of Antennas						
Antenna Diversity Supported	☐ Yes	□ Yes		⊠ No		
Smart Antenna System	□ Yes		⊠ No			
If Smart Antenna System supported, please specify number of streams						
If number of channels differ in any of the o	perating modes, p	lease specify:				
6. 5GHz WLAN Equipment (fill in if 5GHz	WLAN Equipment	t)				
Supported Operating Modes	⊠ 802.11a ⊠ 802.11n		□ 802.11ac			
Supported Frequency Bands	⊠ 5150 – 5250 MHz		⊠ 5250 – 5350 MHz			
	⊠ 5470 – 5725 MHz		⊠ 5725 – 5825 MHz			
Device type	☐ Master		⊠ Slave			
DFS	☐ Yes (Master or Slave with DFS capability)		⊠ No (Slave without DFS capability)		ut DFS capability)	
Supported Channel Bandwidths	□ 40 MHz	□ 80 MHz		□ 160	MHz	
Number of Antennas	1					
Antenna Diversity Supported	☐ Yes	⊠ No				
Smart Antenna System	☐ Yes		⊠ No			
If Smart Antenna System supported, please specify number of streams						
If Output Power is reduced on any channels in one of the Frequency Bands, please specify:						
If we was a sharp all differs in any of the analytics modes where we will be						
If number of channels differ in any of the operating modes, please specify:						



6. Power Supply and Connections						
Type of Power Supply	⊠ Mains	☐ Battery	☐ Other			
Please specify if other than Mains						
Nominal Voltage	120V AC					
Please specify all connections on the EUT:						
ADDITIONAL REMARKS:						
DECLARED BY:						
		Bal	Ber L.			
February 12, 2019 Ben Boti	ros	0 1				



About this document

This document specifies the information that is needed to select the correct testcases and test procedures for testing to FCC Part 15C. The form must be completed by the applicant and submitted to Nemko before testing is started.

Preparation of Equipment for Testing

Note (a): Number of samples for testing

In general, the following samples are needed for FCC 15C testing:

RF Conducted Tests:

One sample with a 50 ohm antenna connector (preferably SMA Female). Only one antenna connector is normally needed even if the equipment has more than one antenna, however EUTs with Smart Antenna Systems must have antenna connectors on all antennas.

Radiated Tests:

One sample with integral antennas. This sample will be used to measure Radiated Emissions, Antenna Gain, Part 15B and Power-Line Conducted tests.

If it is not possible to mount antenna connector(s) on the EUT all tests will be performed radiated or with a test jig. In this case the applicant shall always supply a value for the antenna gain.

Note (b): Power supply

Means of connecting the equipment to an external power supply shall be supplied by the applicant together with the equipment to be tested.

Battery operated equipment shall be supplied with the necessary batteries and chargers. All tests on battery operated equipment will be performed with new or fully charged batteries.

Note (c): Test Modes

Most RF tests are performed with the EUT in force transmit mode. Software and necessary programming tools must be submitted to Nemko together with the test samples before start of testing.

All tests will normally be performed on 3 channels and with all supported modulation types.

Frequency hopping equipment will be tested both with hopping active and without hopping.

Equipment with digital modulations other than Frequency hopping should transmit with as high duty cycle as possible.