

 MOTOROLA SOLUTIONS	  MS ISO/IEC 17025 TESTING SAMM No.0826 CERTIFICATE 2518.05
DECLARATION OF COMPLIANCE SAR ASSESSMENT Part 2 of 2	
Motorola Solutions Inc. EME Test Laboratory Motorola Solutions Malaysia Sdn Bhd (Innoplex) Plot 2A, Medan Bayan Lepas, Mukim 12 SWD 11900 Bayan Lepas Penang, Malaysia.	Date of Report: 18/10/2019 Report Revision: A
Responsible Engineer: Lee Kin Kting (EME Engineer) Report Author: Lee Kin Kting (EME Engineer) Date/s Tested: 10/13/2019-10/15/2019 Manufacturer: Motorola Solutions Inc. DUT Description: Handheld Portable – Tanapa T460 FRS Consumer Radio 462 -467 MHz Dark Blue Test TX mode(s): CW (PTT) Max. Power output: 2.00W (462.5500 – 462.7250 MHz), 0.60W (467.5625 – 467.7125 MHz) Nominal Power: 1.80W (462.5500 – 462.7250 MHz), 0.50W (467.5625 – 467.7125 MHz) Tx Frequency Bands: 462.5500 – 462.7250 MHz, 467.5625 - 467.7125 MHz Signaling type: FM Model(s) Tested: T460 (PMUE4641B) Model(s) Certified: T460 (PMUE4641B), T402 (PMUE5059B), T465 (PMUE4642B) Serial Number(s): 1654QP0030 & 1654QP0034 Classification: General Population/Uncontrolled Environment FCC ID: AZ489FT4957 FCC Test Firm Registration Number: 823256 The test results clearly demonstrate compliance with FCC General Population / Uncontrolled RF Exposure limits of 1.6 W/kg averaged over 1 gram per the requirements of FCC 47 CFR § 2.109	
Based on the information and the testing results provided herein, the undersigned certifies that when used as stated in the operating instructions supplied, said product complies with the national and international reference standards and guidelines listed in section 4.0 of this report (no deviation from standard methods). This report shall not be reproduced without written approval from an officially designated representative of the Motorola Solutions Inc EME Laboratory. I attest to the accuracy of the data and assume full responsibility for the completeness of these measurements. This reporting format is consistent with the suggested guidelines of the TIA TSB-150 December 2004. The results and statements contained in this report pertain only to the device(s) evaluated.	
 Tiong Nguk Ing Deputy Technical Manager (Approved Signatory) Approval Date: 11/6/2019	

Appendix E

System Verification Check Scans

Motorola Solutions, Inc. EME Laboratory

Date/Time: 10/13/2019 9:34:06 AM

Robot#: DASY5-PG-4 | Run#: AN-SYSP-450H-191013-01
Dipole Model#: D450V3
Phantom#: ELI4 1103
Tissue Temp: 21.8 (C)
Serial#: 1053
Test Freq: 450.0000 (MHz)
Start Power: 250 (mW)
Rotation (1D): 0.076 dB
Adjusted SAR (1W): 4.16 mW/g (1g)

Comments:

Duty Cycle: 1:1, Medium parameters used: $f = 450$ MHz; $\sigma = 0.88$ S/m; $\epsilon_r = 41.8$; $\rho = 1000$ kg/m³
Probe: EX3DV4 - SN7485, Calibrated: 1/23/2019, Frequency: 450 MHz, ConvF(11.95, 11.95, 11.95) @ 450 MHz
Electronics: DAE4 Sn688, Calibrated: 1/10/2019

Below 2 GHz-Rev.2/System Performance Check/Dipole Area Scan 2 (41x211x1):Interpolated grid: $dx=1.500$ mm, $dy=1.500$ mm

Reference Value = 39.80 V/m; Power Drift = -0.06 dB

Fast SAR: SAR(1 g) = 1.09 W/kg; SAR(10 g) = 0.758 W/kg (SAR corrected for target medium)

Maximum value of SAR (interpolated) = 1.34 W/kg

Below 2 GHz-Rev.2/System Performance Check/0-Degree Cube (5x5x7)/Cube 0:Measurement grid: $dx=7.5$ mm, $dy=7.5$ mm, $dz=5$ mm

Reference Value = 39.80 V/m; Power Drift = -0.06 dB



Peak SAR (extrapolated) = 1.59 W/kg

SAR(1 g) = 1.04 W/kg; SAR(10 g) = 0.701 W/kg (SAR corrected for target medium)

Maximum value of SAR (measured) = 1.34 W/kg

Below 2 GHz-Rev.2/System Performance Check/Z-Axis Retraction (1x1x17): Measurementgrid: $dx=20$ mm, $dy=20$ mm, $dz=10$ mm

Maximum value of SAR (measured) = 1.34 W/kg



Motorola Solutions, Inc. EME Laboratory

Date/Time: 10/14/2019 2:37:01 PM

Robot#: DASY5-PG-4 | Run#: AN-SYSP-450H-191014-12
 Dipole Model#: D450V3
 Phantom#: ELI4 1103
 Tissue Temp: 22.0 (C)
 Serial#: 1053
 Test Freq: 450.0000 (MHz)
 Start Power: 250 (mW)
 Rotation (1D): 0.071 dB
 Adjusted SAR (1W): 4.40 mW/g (1g)

Comments:

Duty Cycle: 1:1, Medium parameters used: $f = 450$ MHz; $\sigma = 0.89$ S/m; $\epsilon_r = 42.8$; $\rho = 1000$ kg/m³
 Probe: EX3DV4 - SN7485, Calibrated: 1/23/2019, Frequency: 450 MHz, ConvF(11.95, 11.95, 11.95) @ 450 MHz
 Electronics: DAE4 Sn688, Calibrated: 1/10/2019

Below 2 GHz-Rev.2/System Performance Check/Dipole Area Scan 2 (41x211x1):

Interpolated grid: dx=1.500 mm, dy=1.500 mm

Reference Value = 40.44 V/m; Power Drift = 0.00 dB

Fast SAR: SAR(1 g) = 1.14 W/kg; SAR(10 g) = 0.799 W/kg (SAR corrected for target medium)

Maximum value of SAR (interpolated) = 1.41 W/kg

Below 2 GHz-Rev.2/System Performance Check/0-Degree Cube (5x5x7)/Cube 0:

Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 40.44 V/m; Power Drift = 0.00 dB

Peak SAR (extrapolated) = 1.68 W/kg



SAR(1 g) = 1.1 W/kg; SAR(10 g) = 0.750 W/kg (SAR corrected for target medium)

Maximum value of SAR (measured) = 1.42 W/kg

Below 2 GHz-Rev.2/System Performance Check/Z-Axis Retraction (1x1x17): Measurement

grid: dx=20mm, dy=20mm, dz=10mm

Maximum value of SAR (measured) = 1.42 W/kg



Appendix F

DUT Scans

Assessments at the Body - Table 18

Motorola Solutions, Inc. EME Laboratory

Date/Time: 10/13/2019 12:35:50 PM

Robot#: DASY5-PG-4 | Run#: AN-AB-191013-04
 Model#: T460 (PMUE4641B)
 Phantom#: ELI4 1103
 Tissue Temp: 21.9 (C)
 Serial#: 1654QP0030
 Antenna: Fixed antenna
 Test Freq: 462.6500 MHz
 Battery: 1532
 Carry Acc: PMLN7220A
 Audio Acc: NTN8867A
 Start Power: 1.44 (W)

Comments:

Duty Cycle: 1:1, Medium parameters used: $f = 463$ MHz; $\sigma = 0.89$ S/m; $\epsilon_r = 41.5$; $\rho = 1000$ kg/m³
 Probe: EX3DV4 - SN7485, Calibrated: 1/23/2019, Frequency: 462.65 MHz, ConvF(11.95, 11.95, 11.95) @ 462.65 MHz
 Electronics: DAE4 Sn688, Calibrated: 1/10/2019

Below 2 GHz-Rev.2/Ab Scan/1-Area Scan (81x161x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Reference Value = 50.32 V/m; Power Drift = -0.45 dB

Fast SAR: SAR(1 g) = 2.04 W/kg; SAR(10 g) = 1.46 W/kg (SAR corrected for target medium)

Maximum value of SAR (interpolated) = 2.44 W/kg

Below 2 GHz-Rev.2/Ab Scan/3-Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 50.32 V/m; Power Drift = -0.55 dB


Peak SAR (extrapolated) = 2.66 W/kg

SAR(1 g) = 1.93 W/kg; SAR(10 g) = 1.38 W/kg (SAR corrected for target medium)

Maximum value of SAR (measured) = 2.32 W/kg

Below 2 GHz-Rev.2/Ab Scan/4-Z-Axis Scan (1x1x17): Measurement grid: dx=20mm, dy=20mm, dz=10mm

Maximum value of SAR (measured) = 2.30 W/kg



Assessments at the Body - Table 19

Motorola Solutions, Inc. EME Laboratory

Date/Time: 10/13/2019 2:00:01 PM

Robot#: DASY5-PG-4 | Run#: AN-AB-191013-07
Model#: T460 (PMUE4641B)
Phantom#: ELI4 1103
Tissue Temp: 21.8 (C)
Serial#: 1654QP0030
Antenna: Fixed antenna
Test Freq: 462.6500 MHz
Battery: 1532
Carry Acc: PMLN7240A
Audio Acc: NTN8867A
Start Power: 1.44 (W)

Comments:

Duty Cycle: 1:1, Medium parameters used: $f = 463$ MHz; $\sigma = 0.89$ S/m; $\epsilon_r = 41.5$; $\rho = 1000$ kg/m³
Probe: EX3DV4 - SN7485, Calibrated: 1/23/2019, Frequency: 462.65 MHz, ConvF(11.95, 11.95, 11.95) @ 462.65 MHz
Electronics: DAE4 Sn688, Calibrated: 1/10/2019

Below 2 GHz-Rev.2/Ab Scan/1-Area Scan (81x161x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Reference Value = 49.24 V/m; Power Drift = -0.46 dB

Fast SAR: SAR(1 g) = 1.9 W/kg; SAR(10 g) = 1.37 W/kg (SAR corrected for target medium)

Maximum value of SAR (interpolated) = 2.26 W/kg

Below 2 GHz-Rev.2/Ab Scan/3-Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 49.24 V/m; Power Drift = -0.92 dB


Peak SAR (extrapolated) = 2.28 W/kg

SAR(1 g) = 1.67 W/kg; SAR(10 g) = 1.21 W/kg (SAR corrected for target medium)

Maximum value of SAR (measured) = 2.00 W/kg

Below 2 GHz-Rev.2/Ab Scan/4-Z-Axis Scan (1x1x17): Measurement grid: dx=20mm, dy=20mm, dz=10mm

Maximum value of SAR (measured) = 1.97 W/kg



Assessments at the Body - Table 20

Motorola Solutions, Inc. EME Laboratory

Date/Time: 10/13/2019 4:23:45 PM

Robot#: DASY5-PG-4 | Run#: AN-AB-191013-10
 Model#: T460 (PMUE4641B)
 Phantom#: ELI4 1103
 Tissue Temp: 22.0 (C)
 Serial#: 1654QP0030
 Antenna: Fixed antenna
 Test Freq: 462.6500 MHz
 Battery: 1532
 Carry Acc: PMLN7706A
 Audio Acc: NTN8867A
 Start Power: 1.44 (W)

Comments:

Duty Cycle: 1:1, Medium parameters used: $f = 463$ MHz; $\sigma = 0.89$ S/m; $\epsilon_r = 41.5$; $\rho = 1000$ kg/m³
 Probe: EX3DV4 - SN7485, Calibrated: 1/23/2019, Frequency: 462.65 MHz, ConvF(11.95, 11.95, 11.95) @ 462.65 MHz
 Electronics: DAE4 Sn688, Calibrated: 1/10/2019

Below 2 GHz-Rev.2/Ab Scan/1-Area Scan (81x161x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Reference Value = 50.70 V/m; Power Drift = -0.53 dB

Fast SAR: SAR(1 g) = 1.86 W/kg; SAR(10 g) = 1.35 W/kg (SAR corrected for target medium)

Maximum value of SAR (interpolated) = 2.22 W/kg

Below 2 GHz-Rev.2/Ab Scan/3-Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 50.70 V/m; Power Drift = -0.68 dB


Peak SAR (extrapolated) = 2.40 W/kg

SAR(1 g) = 1.76 W/kg; SAR(10 g) = 1.29 W/kg (SAR corrected for target medium)

Maximum value of SAR (measured) = 2.11 W/kg

Below 2 GHz-Rev.2/Ab Scan/4-Z-Axis Scan (1x1x17): Measurement grid: dx=20mm, dy=20mm, dz=10mm

Maximum value of SAR (measured) = 2.08 W/kg



Assessments at the Body - Table 21

Motorola Solutions, Inc. EME Laboratory

Date/Time: 10/13/2019 10:08:38 PM

Robot#: DASY5-PG-4 | Run#: CK-AB-191013-15
Model#: T460 (PMUE4641B)
Phantom#: ELI4 1103
Tissue Temp: 22.2 (C)
Serial#: 1654QP0030
Antenna: Fixed antenna
Test Freq: 462.6500 MHz
Battery: 1532
Carry Acc: PMLN7220A
Audio Acc: NTN9396B
Start Power: 1.44 (W)

Comments:

Duty Cycle: 1:1, Medium parameters used: $f = 463$ MHz; $\sigma = 0.89$ S/m; $\epsilon_r = 41.5$; $\rho = 1000$ kg/m³
Probe: EX3DV4 - SN7485, Calibrated: 1/23/2019, Frequency: 462.65 MHz, ConvF(11.95, 11.95, 11.95) @ 462.65 MHz
Electronics: DAE4 Sn688, Calibrated: 1/10/2019

Below 2 GHz-Rev.2/Ab Scan/1-Area Scan (81x161x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Reference Value = 48.03 V/m; Power Drift = -0.39 dB

Fast SAR: SAR(1 g) = 2.06 W/kg; SAR(10 g) = 1.48 W/kg (SAR corrected for target medium)

Maximum value of SAR (interpolated) = 2.46 W/kg

Below 2 GHz-Rev.2/Ab Scan/3-Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 48.03 V/m; Power Drift = -0.55 dB


Peak SAR (extrapolated) = 2.68 W/kg

SAR(1 g) = 1.94 W/kg; SAR(10 g) = 1.39 W/kg (SAR corrected for target medium)

Maximum value of SAR (measured) = 2.34 W/kg

Below 2 GHz-Rev.2/Ab Scan/4-Z-Axis Scan (1x1x17): Measurement grid: dx=20mm, dy=20mm, dz=10mm

Maximum value of SAR (measured) = 2.29 W/kg



Assessments at the Face - Table 23

Motorola Solutions, Inc. EME Laboratory

Date/Time: 10/15/2019 1:30:38 AM

Robot#: DASY5-PG-4 | Run#: CK-FACE-191015-03#
Model#: T460 (PMUE4641B)
Phantom#: ELI4 1103
Tissue Temp: 22.0 (C)
Serial#: 1654QP0034
Antenna: Fixed antenna
Test Freq: 462.6500 MHz
Battery: 1532
Carry Acc: @ front
Audio Acc: N/A
Start Power: 1.44 (W)

Comments:

Duty Cycle: 1:1, Medium parameters used: $f = 463$ MHz; $\sigma = 0.9$ S/m; $\epsilon_r = 42.5$; $\rho = 1000$ kg/m³
Probe: EX3DV4 - SN7485, Calibrated: 1/23/2019, Frequency: 462.65 MHz, ConvF(11.95, 11.95, 11.95) @ 462.65 MHz
Electronics: DAE4 Sn688, Calibrated: 1/10/2019

Below 2 GHz-Rev.2/Face Scan/1-Area Scan (81x161x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Reference Value = 41.87 V/m; Power Drift = -0.55 dB

Fast SAR: SAR(1 g) = 1.49 W/kg; SAR(10 g) = 1.09 W/kg (SAR corrected for target medium)

Maximum value of SAR (interpolated) = 1.77 W/kg

Below 2 GHz-Rev.2/Face Scan/3-Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 41.87 V/m; Power Drift = -0.62 dB


Peak SAR (extrapolated) = 1.86 W/kg

SAR(1 g) = 1.41 W/kg; SAR(10 g) = 1.05 W/kg (SAR corrected for target medium)

Maximum value of SAR (measured) = 1.65 W/kg

Below 2 GHz-Rev.2/Face Scan/4-Z-Axis Scan (1x1x17): Measurement grid: dx=20mm, dy=20mm, dz=10mm

Maximum value of SAR (measured) = 1.64 W/kg



Assessments at the Body - Table 25

Motorola Solutions, Inc. EME Laboratory

Date/Time: 10/14/2019 2:38:06 AM

Robot#: DASY5-PG-4 | Run#: CK-AB-191014-04#
 Model#: T460 (PMUE4641B)
 Phantom#: ELI4 1103
 Tissue Temp: 22.1 (C)
 Serial#: 1654QP0030
 Antenna: Fixed antenna
 Test Freq: 467.6375 MHz
 Battery: 1532
 Carry Acc: PMLN7220A
 Audio Acc: NTN8867A
 Start Power: 0.405 (W)

Comments:

Duty Cycle: 1:1, Medium parameters used: $f = 468$ MHz; $\sigma = 0.9$ S/m; $\epsilon_r = 41.4$; $\rho = 1000$ kg/m³
 Probe: EX3DV4 - SN7485, Calibrated: 1/23/2019, Frequency: 467.637 MHz, ConvF(11.95, 11.95, 11.95) @ 467.637 MHz
 Electronics: DAE4 Sn688, Calibrated: 1/10/2019

Below 2 GHz-Rev.2/Ab Scan/1-Area Scan (81x161x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Reference Value = 39.66 V/m; Power Drift = -0.38 dB

Fast SAR: SAR(1 g) = 1.44 W/kg; SAR(10 g) = 1.03 W/kg (SAR corrected for target medium)

Maximum value of SAR (interpolated) = 1.73 W/kg

Below 2 GHz-Rev.2/Ab Scan/3-Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 39.66 V/m; Power Drift = -0.47 dB


Peak SAR (extrapolated) = 1.90 W/kg

SAR(1 g) = 1.37 W/kg; SAR(10 g) = 0.980 W/kg (SAR corrected for target medium)

Maximum value of SAR (measured) = 1.65 W/kg

Below 2 GHz-Rev.2/Ab Scan/4-Z-Axis Scan (1x1x17): Measurement grid: dx=20mm, dy=20mm, dz=10mm

Maximum value of SAR (measured) = 1.63 W/kg



Assessments at the Body - Table 26

Motorola Solutions, Inc. EME Laboratory

Date/Time: 10/14/2019 5:08:44 AM

Robot#: DASY5-PG-4 | Run#: CK-AB-191014-07#
Model#: T460 (PMUE4641B)
Phantom#: ELI4 1103
Tissue Temp: 22.1 (C)
Serial#: 1654QP0030
Antenna: Fixed antenna
Test Freq: 467.6375 MHz
Battery: 1532
Carry Acc: PMLN7240A
Audio Acc: NTN8867A
Start Power: 0.405 (W)

Comments:

Duty Cycle: 1:1, Medium parameters used: $f = 468$ MHz; $\sigma = 0.9$ S/m; $\epsilon_r = 41.4$; $\rho = 1000$ kg/m³
Probe: EX3DV4 - SN7485, Calibrated: 1/23/2019, Frequency: 467.637 MHz, ConvF(11.95, 11.95, 11.95) @ 467.637 MHz
Electronics: DAE4 Sn688, Calibrated: 1/10/2019

Below 2 GHz-Rev.2/Ab Scan/1-Area Scan (81x161x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Reference Value = 38.47 V/m; Power Drift = -0.37 dB

Fast SAR: SAR(1 g) = 1.27 W/kg; SAR(10 g) = 0.914 W/kg (SAR corrected for target medium)

Maximum value of SAR (interpolated) = 1.52 W/kg

Below 2 GHz-Rev.2/Ab Scan/3-Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 38.47 V/m; Power Drift = -0.47 dB


Peak SAR (extrapolated) = 1.66 W/kg

SAR(1 g) = 1.21 W/kg; SAR(10 g) = 0.879 W/kg (SAR corrected for target medium)

Maximum value of SAR (measured) = 1.45 W/kg

Below 2 GHz-Rev.2/Ab Scan/4-Z-Axis Scan (1x1x17): Measurement grid: dx=20mm, dy=20mm, dz=10mm

Maximum value of SAR (measured) = 1.44 W/kg



Assessments at the Body - Table 27

Motorola Solutions, Inc. EME Laboratory

Date/Time: 10/14/2019 8:23:23 AM

Robot#: DASY5-PG-4 | Run#: AN-AB-191014-10#
 Model#: T460 (PMUE4641B)
 Phantom#: ELI4 1103
 Tissue Temp: 21.8 (C)
 Serial#: 1654QP0030
 Antenna: Fixed antenna
 Test Freq: 467.6375 MHz
 Battery: 1532
 Carry Acc: PMLN7706A
 Audio Acc: NTN8867A
 Start Power: 0.405 (W)

Comments:

Duty Cycle: 1:1, Medium parameters used: $f = 468 \text{ MHz}$; $\sigma = 0.9 \text{ S/m}$; $\epsilon_r = 41.4$; $\rho = 1000 \text{ kg/m}^3$

Probe: EX3DV4 - SN7485, Calibrated: 1/23/2019, Frequency: 467.637 MHz, ConvF(11.95, 11.95, 11.95) @ 467.637 MHz

Electronics: DAE4 Sn688, Calibrated: 1/10/2019

Below 2 GHz-Rev.2/Ab Scan/1-Area Scan (81x161x1): Interpolated grid: $dx=1.500 \text{ mm}$, $dy=1.500 \text{ mm}$

Reference Value = 42.01 V/m; Power Drift = -0.43 dB

Fast SAR: SAR(1 g) = 1.36 W/kg; SAR(10 g) = 0.979 W/kg (SAR corrected for target medium)

Maximum value of SAR (interpolated) = 1.62 W/kg

Below 2 GHz-Rev.2/Ab Scan/3-Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=7.5 \text{ mm}$, $dy=7.5 \text{ mm}$, $dz=5 \text{ mm}$

Reference Value = 42.01 V/m; Power Drift = -0.54 dB


Peak SAR (extrapolated) = 1.77 W/kg

SAR(1 g) = 1.29 W/kg; SAR(10 g) = 0.940 W/kg (SAR corrected for target medium)

Maximum value of SAR (measured) = 1.55 W/kg

Below 2 GHz-Rev.2/Ab Scan/4-Z-Axis Scan (1x1x17): Measurement grid: $dx=20 \text{ mm}$, $dy=20 \text{ mm}$, $dz=10 \text{ mm}$

Maximum value of SAR (measured) = 1.53 W/kg



Assessments at the Body - Table 28

Motorola Solutions, Inc. EME Laboratory

Date/Time: 10/14/2019 8:47:51 AM

Robot#: DASY5-PG-4 | Run#: AN-AB-191014-11#
 Model#: T460 (PMUE4641B)
 Phantom#: ELI4 1103
 Tissue Temp: 21.8 (C)
 Serial#: 1654QP0030
 Antenna: Fixed antenna
 Test Freq: 467.6375 MHz
 Battery: 1532
 Carry Acc: PMLN7220A
 Audio Acc: GU6443A
 Start Power: 0.405 (W)

Comments:

Duty Cycle: 1:1, Medium parameters used: $f = 468$ MHz; $\sigma = 0.9$ S/m; $\epsilon_r = 41.4$; $\rho = 1000$ kg/m³
 Probe: EX3DV4 - SN7485, Calibrated: 1/23/2019, Frequency: 467.637 MHz, ConvF(11.95, 11.95, 11.95) @ 467.637 MHz
 Electronics: DAE4 Sn688, Calibrated: 1/10/2019

Below 2 GHz-Rev.2/Ab Scan/1-Area Scan (81x161x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Reference Value = 41.80 V/m; Power Drift = -0.40 dB

Fast SAR: SAR(1 g) = 1.48 W/kg; SAR(10 g) = 1.06 W/kg (SAR corrected for target medium)

Maximum value of SAR (interpolated) = 1.76 W/kg

Below 2 GHz-Rev.2/Ab Scan/3-Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 41.80 V/m; Power Drift = -0.50 dB


Peak SAR (extrapolated) = 1.95 W/kg

SAR(1 g) = 1.41 W/kg; SAR(10 g) = 1.01 W/kg (SAR corrected for target medium)

Maximum value of SAR (measured) = 1.69 W/kg

Below 2 GHz-Rev.2/Ab Scan/4-Z-Axis Scan (1x1x17): Measurement grid: dx=20mm, dy=20mm, dz=10mm

Maximum value of SAR (measured) = 1.68 W/kg



Assessments at the Face - Table 30

Motorola Solutions, Inc. EME Laboratory

Date/Time: 10/15/2019 12:09:50 AM

Robot#: DASY5-PG-4 | Run#: CK-FACE-191015-01#
 Model#: T460 (PMUE4641B)
 Phantom#: ELI4 1103
 Tissue Temp: 22.0 (C)
 Serial#: 1654QP0030
 Antenna: Fixed antenna
 Test Freq: 467.6375 MHz
 Battery: 1532
 Carry Acc: @ front
 Audio Acc: N/A
 Start Power: 0.405 (W)

Comments:

Duty Cycle: 1:1, Medium parameters used: $f = 468$ MHz; $\sigma = 0.91$ S/m; $\epsilon_r = 42.4$; $\rho = 1000$ kg/m³
 Probe: EX3DV4 - SN7485, Calibrated: 1/23/2019, Frequency: 467.637 MHz, ConvF(11.95, 11.95, 11.95) @ 467.637 MHz
 Electronics: DAE4 Sn688, Calibrated: 1/10/2019

Below 2 GHz-Rev.2/Face Scan/1-Area Scan (81x161x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Reference Value = 35.69 V/m; Power Drift = -0.41 dB

Fast SAR: SAR(1 g) = 1.1 W/kg; SAR(10 g) = 0.800 W/kg (SAR corrected for target medium)

Maximum value of SAR (interpolated) = 1.30 W/kg

Below 2 GHz-Rev.2/Face Scan/3-Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 35.69 V/m; Power Drift = -0.51 dB


Peak SAR (extrapolated) = 1.41 W/kg

SAR(1 g) = 1.06 W/kg; SAR(10 g) = 0.786 W/kg (SAR corrected for target medium)

Maximum value of SAR (measured) = 1.25 W/kg

Below 2 GHz-Rev.2/Face Scan/4-Z-Axis Scan (1x1x17): Measurement grid: dx=20mm, dy=20mm, dz=10mm

Maximum value of SAR (measured) = 1.22 W/kg



APPENDIX G

Shortened Scan of Highest SAR configuration

Shortened Scan Table 31

Motorola Solutions, Inc. EME Laboratory
Date/Time: 10/15/2019 4:12:23 AM

Robot#: DASY5-PG-4 | Run#: CK-AB-191015-06#
Model#: T460 (PMUE4641B)
Phantom#: ELI4 1103
Tissue Temp: 22.0 (C)
Serial#: 1654QP0030
Antenna: Fixed antenna
Test Freq: 462.6500 MHz
Battery: 1532
Carry Acc: PMLN7220A
Audio Acc: NTN9396B
Start Power: 1.44 (W)

Comments: Shorten Scan


Duty Cycle: 1:1, Medium parameters used: $f = 463$ MHz; $\sigma = 0.9$ S/m; $\epsilon_r = 42.5$; $\rho = 1000$ kg/m³
Probe: EX3DV4 - SN7485, Calibrated: 1/23/2019, Frequency: 462.65 MHz, ConvF(11.95, 11.95, 11.95) @ 462.65 MHz
Electronics: DAE4 Sn688, Calibrated: 1/10/2019

Below 2 GHz-Rev.2/Ab Scan/1-Area Scan (81x161x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Reference Value = 46.79 V/m; Power Drift = -0.41 dB
Fast SAR: SAR(1 g) = 1.81 W/kg; SAR(10 g) = 1.3 W/kg (SAR corrected for target medium)
Maximum value of SAR (interpolated) = 2.16 W/kg

Below 2 GHz-Rev.2/Ab Scan/2-Volume 2D Scan (41x41x1): Interpolated grid: dx=0.7500 mm, dy=0.7500 mm, dz=1.000 mm
Reference Value = 46.79 V/m; Power Drift = -0.48 dB
Fast SAR: SAR(1 g) = 1.77 W/kg; SAR(10 g) = 1.29 W/kg (SAR corrected for target medium)
Maximum value of SAR (interpolated) = 2.08 W/kg

Below 2 GHz-Rev.2/Ab Scan/4-Z-Axis Scan (1x1x17): Measurement grid: dx=20mm, dy=20mm, dz=10mm
Maximum value of SAR (measured) = 2.05 W/kg

Below 2 GHz-Rev.2/Ab Scan/3-Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm
Reference Value = 49.13 V/m; Power Drift = -0.27 dB
Peak SAR (extrapolated) = 2.57 W/kg
SAR(1 g) = 1.86 W/kg; SAR(10 g) = 1.34 W/kg (SAR corrected for target medium)
Maximum value of SAR (measured) = 2.24 W/kg



Shortened scan reflects highest SAR producing configuration and is compared to the full scan.

Scan Description	Referenced Table	Test Time (min.)	SAR 1g (W/kg)
Shorten scan (zoom)	31	7	1.31
Full scan (area & zoom)	21	20	1.45

APPENDIX H DUT Test Position Photos

Photos available in Exhibit 7B

APPENDIX I
DUT, Body worn and audio accessories Photos

Photos available in Exhibit 7B