





Band Edge Conducted Spurious Emission



Band 14, 5MHz QPSK, Low CH 23305			
RB = 1	Offset = 0	RB = X (100%)	Offset = 0





Band 14, 5MHz QPSK, High CH 23355			
RB = 1	Offset = X-1	RB = X (100%)	Offset = 0










## 1.11. Conducted Spurious Emission

### 1.11.1. Test Setup



- 1) The DUT transmitter output port was connected to communication simulator with above setup.
- 2) Path loss for the measurement included.
- 3) Set DUT to transmit maximum power through communication simulator.
- 4) Spectrum Analyzer setting, RBW = 1 MHz, VBW = 3\*RBW.
- 5) The spurious emission of lowest, middle and highest channels with the highest RF powers were measured.
- 6) Record the maximum trace plot into the test report.

### 1.11.2. Test Limit

(e) For operations in the 758-768 MHz and the 788-798 MHz bands, the power of any emission outside the licensee's frequency band(s) of operation shall be attenuated below the transmitter power (P) within the licensed band(s) of operation, measured in watts, in accordance with the following:

(1) On all frequencies between 769-775 MHz and 799-805 MHz, by a factor not less than  $76 + 10 \log (P)$  dB in a 6.25 kHz band segment, for base and fixed stations.

(2) On all frequencies between 769-775 MHz and 799-805 MHz, by a factor not less than  $65 + 10 \log (P)$  dB in a 6.25 kHz band segment, for mobile and portable stations.

(3) On any frequency between 775-788 MHz, above 805 MHz, and below 758 MHz, by at least  $43 + 10 \log (P)$  dB.



(4) Compliance with the provisions of paragraphs (e)(1) and (2) of this section is based on the use of measurement instrumentation such that the reading taken with any resolution bandwidth setting should be adjusted to indicate spectral energy in a 6.25 kHz segment.


(5) Compliance with the provisions of paragraph (e)(3) of this section is based on the use of measurement instrumentation employing a resolution bandwidth of 100 kHz or greater. However, in the 100 kHz bands immediately outside and adjacent to the frequency block, a resolution bandwidth of 30 kHz may be employed.




1.11.3. Conducted Spurious Emission - LTE Band 14 (788-798MHz)



5MHz








10MHz



## 1.12. Radiated Spurious Emission

### 1.12.1. Test Setup



- 1) The spectrum setting for scanning Radiated Emission below 1 GHz is RBW = 100 kHz, VBW = 300 kHz and above 1 GHz is RBW = 1MHz, VBW = 3MHz. Detector mode is positive peak.
- 2) In the semi-anechoic chamber, setup as illustrated above the EUT placed on the Turn Table at 0.8m height for below 1GHz measurement and at 1.5m height for above 1GHz measurement, rotated the table around 360 degrees to search the maximum radiation power and receiver antenna shall be rotated vertical and horizontal polarization and moved height from 1m to 4m to find the maximum polar radiated power. The “Read Value” is the spectrum reading the maximum power value.
- 3) The substitution antenna is substituted for EUT at the same position and signals generator (S.G) export the CW signal to the substitution antenna via a TX cable. The receiver antenna shall be rotated vertical and horizontal polarization and moved height from 1m to 4m to find the maximum radiation power. Record the power level of maximum radiation power from spectrum. So, the measured substitution value = Ref level of S.G + TX cables loss – Substituted Antenna Gain.
- 4) Final Radiated Spurious Emission = “Read Value” + Measured substitution value.

### **1.12.2. Test Limit**

(e) For operations in the 758-768 MHz and the 788-798 MHz bands, the power of any emission outside the licensee's frequency band(s) of operation shall be attenuated below the transmitter power (P) within the licensed band(s) of operation, measured in watts, in accordance with the following:

(1) On all frequencies between 769-775 MHz and 799-805 MHz, by a factor not less than  $76 + 10 \log (P)$  dB in a 6.25 kHz band segment, for base and fixed stations.

(2) On all frequencies between 769-775 MHz and 799-805 MHz, by a factor not less than  $65 + 10 \log (P)$  dB in a 6.25 kHz band segment, for mobile and portable stations.

(3) On any frequency between 775-788 MHz, above 805 MHz, and below 758 MHz, by at least  $43 + 10 \log (P)$  dB.


(4) Compliance with the provisions of paragraphs (e)(1) and (2) of this section is based on the use of measurement instrumentation such that the reading taken with any resolution bandwidth setting should be adjusted to indicate spectral energy in a 6.25 kHz segment.

(5) Compliance with the provisions of paragraph (e)(3) of this section is based on the use of measurement instrumentation employing a resolution bandwidth of 100 kHz or greater. However, in the 100 kHz bands immediately outside and adjacent to the frequency block, a resolution bandwidth of 30 kHz may be employed.

### 1.12.3. Radiated Spurious Emission – LTE Band 14 (788-798MHz)

**SAC Transmitter Radiated Emission:**  
Model Number: AAH90ZDU9RH1AN S/N: 734TWP0308 SR:18058-EMC-00054  
Battery Part No: PMNN4804A Accy Part No: AN000348A01  
Test Mode: TX LTE (Band 14) X-Plane  
790.500000 MHz (Low) Bandwidth 5MHz 0.252 Watt(s) /Max Power

Frequency (MHz)	Limit	Horizontal Measured Emission Equiv Pwr Into Ideal Dipole (dBm)	Vertical Measured Emission Equiv Pwr Into ideal Dipole (dBm)
1581.0000	-13.0000	-59.2369 **	-59.5825 **
2371.5000	-13.0000	-54.9835 **	-55.6703 **
3162.0000	-13.0000	-51.6220 **	-51.9755 **
3952.5000	-13.0000	-50.0214 **	-51.0358 **
4743.0000	-13.0000	-50.1759 **	-50.7438 **
5533.5000	-13.0000	-47.4451 **	-48.4147 **
6324.0000	-13.0000	-46.6151 **	-46.7356 **
7114.5000	-13.0000	-43.8224 **	-42.7745 **
7905.0000	-13.0000	-43.7239 **	-42.9511 **



The data presented here was taken using the substitution method as found in the ANSI C63.26-2015 document.  
Motorola Penang EMC Lab - Test Performed by: Qawiman&Nazrin Thu, 10 Sep, 2020

Remarks: \*\* Indicates the spurious emission could not be detected due to noise limitations or ambient.


\*Pursuant to CFR 47 Part 2.1057 ( c ), emissions attenuated more than 20 dB below the permissible limit are not reported  
Temp(Deg): 23.9 Hum(%RH): 68.7

System MU: 4.03 dB

Remarks: Passed Results Marginal Results Failed Results

**SAC Transmitter Radiated Emission:**  
**Model Number: AAH90ZDU9RH1AN** **S/N: 734TWP0308** **SR:18058-EMC-00054**  
**Battery Part No: PMNN4804A** **Accy Part No: AN000348A01**  
**Test Mode: TX LTE (Band 14) X-Plane**  
**793.000000 MHz (Mid)** **Bandwidth 5MHz** **0.252 Watt(s) /Max Power**

Frequency (MHz)	Limit	Horizontal Measured Emission Equiv Pwr Into Ideal Dipole (dBm)	Vertical Measured Emission Equiv Pwr Into ideal Dipole (dBm)
1586.0000	-13.0000	-61.3751 **	-59.9374 **
2385.0600	-13.0000	-35.8500 *	-31.6300
3172.0000	-13.0000	-51.9091 **	-52.2434 **
3965.0000	-13.0000	-52.1060 **	-50.6458 **
4758.0000	-13.0000	-49.4892 **	-49.4187 **
5551.0000	-13.0000	-46.4818 **	-47.6205 **
6344.0000	-13.0000	-46.7009 **	-45.9138 **
7137.0000	-13.0000	-43.0419 **	-42.9251 **
7930.0000	-13.0000	-42.3963 **	-42.6887 **



The data presented here was taken using the substitution method as found in the ANSI C63.26-2015 document.  
 Motorola Penang EMC Lab - Test Performed by: Qawiman&Nazrin Thu, 10 Sep, 2020

Remarks: \*\* Indicates the spurious emission could not be detected due to noise limitations or ambient.

\*Pursuant to CFR 47 Part 2.1057 ( c ), emissions attenuated more than 20 dB below the permissible limit are not reported  
 Temp(Deg): 23.9 Hum(%RH): 68.7

System MU: 4.03 dB


Remarks: 

Passed Results	Marginal Results	Failed Results
----------------	------------------	----------------



**Model Number: AAH90ZDU9RH1AN** **SAC Transmitter Radiated Emission:** **S/N: 734TWP0308** **SR:18058-EMC-00054**  
**Battery Part No: PMNN4804A** **Accy Part No: AN000348A01**  
**Test Mode: TX LTE (Band 14) X-Plane**  
**795.500000 MHz (High)** **Bandwidth 5MHz** **0.252 Watt(s) /Max Power**

Frequency (MHz)	Limit	Horizontal Measured Emission Equiv Pwr Into Ideal Dipole (dBm)	Vertical Measured Emission Equiv Pwr Into ideal Dipole (dBm)
1591.0000	-13.0000	-60.0517 **	-59.0232 **
2386.8100	-13.0000	-49.0300 *	-39.5600 *
3182.0000	-13.0000	-52.7644 **	-52.6836 **
3977.5000	-13.0000	-51.1981 **	-51.0050 **
4773.0000	-13.0000	-50.0866 **	-50.0704 **
5568.5000	-13.0000	-48.2222 **	-47.8865 **
6364.0000	-13.0000	-45.2794 **	-45.8816 **
7159.5000	-13.0000	-42.2987 **	-43.1257 **
7955.0000	-13.0000	-43.4457 **	-42.4940 **



The data presented here was taken using the substitution method as found in the ANSI C63.26-2015 document.  
Motorola Penang EMC Lab - Test Performed by: Qawiman&Nazrin Thu, 10 Sep, 2020

Remarks: \*\* Indicates the spurious emission could not be detected due to noise limitations or ambient.

\*Pursuant to CFR 47 Part 2.1057 ( c ), emissions attenuated more than 20 dB below the permissible limit are not reported  
Temp(Deg): 23.9 Hum(%RH): 68.7


System MU: 4.03 dB

Remarks:

Passed Results	Marginal Results	Failed Results
----------------	------------------	----------------

Model Number: AAH90ZDU9RH1AN  
 Battery Part No: PMNN4804A  
 SAC Transmitter Radiated Emission:  
 S/N: 734TWP0308  
 Accy Part No: AN000348A01  
 Test Mode: TX LTE (Band 14) Y-Plane  
 Bandwidth 5MHz  
 0.252 Watt(s) /Max Power  
 SR:18058-EMC-00054

Frequency (MHz)	Limit	Horizontal Measured Emission Equiv Pwr Into Ideal Dipole (dBm)	Vertical Measured Emission Equiv Pwr Into ideal Dipole (dBm)
1581.0000	-13.0000	-59.7775 **	-59.5602 **
2371.5000	-13.0000	-54.9615 **	-56.2762 **
3162.0000	-13.0000	-52.9773 **	-53.4257 **
3952.5000	-13.0000	-50.8839 **	-50.8214 **
4743.0000	-13.0000	-49.9721 **	-50.5887 **
5533.5000	-13.0000	-48.9483 **	-48.3408 **
6324.0000	-13.0000	-46.7741 **	-45.3197 **
7114.5000	-13.0000	-44.0668 **	-43.3009 **
7905.0000	-13.0000	-43.2163 **	-43.8104 **



The data presented here was taken using the substitution method as found in the ANSI C63.26-2015 document.  
 Motorola Penang EMC Lab - Test Performed by: Qawiman&Nazrin  
 Thu, 10 Sep, 2020

Remarks: \*\* Indicates the spurious emission could not be detected due to noise limitations or ambient.


\*Pursuant to CFR 47 Part 2.1057 ( c ), emissions attenuated more than 20 dB below the permissible limit are not reported  
 Temp(Deg): 23.9 Hum(%RH): 68.7

System MU: 4.03 dB

Remarks: Passed Results Marginal Results Failed Results

**Model Number: AAH90ZDU9RH1AN** **SAC Transmitter Radiated Emission:** **S/N: 734TWP0308** **SR:18058-EMC-00054**  
**Battery Part No: PMNN4804A** **Accy Part No: AN000348A01**  
**Test Mode: TX LTE (Band 14) Y-Plane**  
**793.000000 MHz (Mid)** **Bandwidth 5MHz** **0.252 Watt(s) /Max Power**

Frequency (MHz)	Limit	Horizontal Measured Emission Equiv Pwr Into Ideal Dipole (dBm)	Vertical Measured Emission Equiv Pwr Into ideal Dipole (dBm)
1586.0000	-13.0000	-60.9134 **	-59.4791 **
2379.0000	-13.0000	-56.0889 **	-56.4026 **
3172.0000	-13.0000	-53.4086 **	-53.2511 **
3965.0000	-13.0000	-50.7755 **	-50.0830 **
4758.0000	-13.0000	-50.2230 **	-50.3693 **
5551.0000	-13.0000	-49.4151 **	-49.4627 **
6344.0000	-13.0000	-47.1857 **	-46.6062 **
7137.0000	-13.0000	-43.9281 **	-42.9552 **
7930.0000	-13.0000	-42.0968 **	-42.7724 **



The data presented here was taken using the substitution method as found in the ANSI C63.26-2015 document.  
Motorola Penang EMC Lab - Test Performed by: Qawiman&Nazrin Thu, 10 Sep, 2020

Remarks: \*\* Indicates the spurious emission could not be detected due to noise limitations or ambient.

\*Pursuant to CFR 47 Part 2.1057 ( c ), emissions attenuated more than 20 dB below the permissible limit are not reported  
Temp(Deg): 23.9 Hum(%RH): 68.7


System MU: 4.03 dB

Remarks: 

Passed Results	Marginal Results	Failed Results
----------------	------------------	----------------

**Model Number: AAH90ZDU9RH1AN** **SAC Transmitter Radiated Emission:** **S/N: 734TWP0308** **SR:18058-EMC-00054**  
**Battery Part No: PMNN4804A** **Accy Part No: AN000348A01**  
**Test Mode: TX LTE (Band 14) Y-Plane**  
**795.500000 MHz (High)** **Bandwidth 5MHz** **0.252 Watt(s) /Max Power**

Frequency (MHz)	Limit	Horizontal Measured Emission Equiv Pwr Into Ideal Dipole (dBm)	Vertical Measured Emission Equiv Pwr Into ideal Dipole (dBm)
1591.0000	-13.0000	-60.4241 **	-60.5949 **
2386.8100	-13.0000	-47.8200 *	-39.9700 *
3182.0000	-13.0000	-53.1498 **	-51.7533 **
3977.5000	-13.0000	-50.1480 **	-50.1034 **
4773.0000	-13.0000	-49.6158 **	-49.2865 **
5568.5000	-13.0000	-47.4573 **	-48.5628 **
6364.0000	-13.0000	-47.1132 **	-46.0558 **
7159.5000	-13.0000	-43.1744 **	-43.0255 **
7955.0000	-13.0000	-42.6250 **	-42.9061 **



The data presented here was taken using the substitution method as found in the ANSI C63.26-2015 document.  
 Motorola Penang EMC Lab - Test Performed by: Qawiman&Nazrin Thu, 10 Sep, 2020

Remarks: \*\* Indicates the spurious emission could not be detected due to noise limitations or ambient.


\*Pursuant to CFR 47 Part 2.1057 ( c ), emissions attenuated more than 20 dB below the permissible limit are not reported  
 Temp(Deg): 23.9 Hum(%RH): 68.7

System MU: 4.03 dB

Remarks: Passed Results Marginal Results Failed Results

**SAC Transmitter Radiated Emission:**  
Model Number: AAH90ZDU9RH1AN S/N: 734TWP0308 SR:18058-EMC-00054  
Battery Part No: PMNN4804A Accy Part No: AN000348A01  
Test Mode: TX LTE (Band 14) Z-Plane  
790.500000 MHz (Low) Bandwidth 5MHz 0.252 Watt(s) /Max Power

Frequency (MHz)	Limit	Horizontal Measured Emission Equiv Pwr Into Ideal Dipole (dBm)	Vertical Measured Emission Equiv Pwr Into ideal Dipole (dBm)
1581.0000	-13.0000	-60.6318 **	-59.9259 **
2371.5000	-13.0000	-55.5850 **	-56.7137 **
3162.0000	-13.0000	-53.1559 **	-53.3378 **
3952.5000	-13.0000	-50.4173 **	-51.4490 **
4743.0000	-13.0000	-50.4904 **	-50.9399 **
5533.5000	-13.0000	-47.5301 **	-48.5283 **
6324.0000	-13.0000	-45.3137 **	-46.3044 **
7114.5000	-13.0000	-43.4450 **	-43.3811 **
7905.0000	-13.0000	-42.9853 **	-41.6486 **



The data presented here was taken using the substitution method as found in the ANSI C63.26-2015 document.  
Motorola Penang EMC Lab - Test Performed by: Qawiman&Nazrin Thu, 10 Sep, 2020

Remarks: \*\* Indicates the spurious emission could not be detected due to noise limitations or ambient.

\*Pursuant to CFR 47 Part 2.1057 ( c ), emissions attenuated more than 20 dB below the permissible limit are not reported  
Temp(Deg): 23.9 Hum(%RH): 68.7


System MU: 4.03 dB

Remarks: 

Passed Results	Marginal Results	Failed Results
----------------	------------------	----------------

**Model Number:** AAH90ZDU9RH1AN **SAC Transmitter Radiated Emission:** S/N: 734TWP0308 **SR:18058-EMC-00054**  
**Battery Part No:** PMNN4804A **Accy Part No:** AN000348A01  
**Test Mode:** TX LTE (Band 14) Z-Plane  
**793.000000 MHz (Mid)** **Bandwidth 5MHz** **0.252 Watt(s) /Max Power**

Frequency (MHz)	Limit	Horizontal Measured Emission Equiv Pwr Into Ideal Dipole (dBm)	Vertical Measured Emission Equiv Pwr Into ideal Dipole (dBm)
1590.2500	-13.0000	-52.3600 *	-51.7700 *
2385.4100	-13.0000	-39.4900 *	-43.8500 *
3172.0000	-13.0000	-53.4447 **	-53.5037 **
3965.0000	-13.0000	-52.0831 **	-51.1992 **
4758.0000	-13.0000	-49.3083 **	-49.8709 **
5551.0000	-13.0000	-49.4930 **	-48.2017 **
6344.0000	-13.0000	-46.4876 **	-46.6718 **
7137.0000	-13.0000	-44.0218 **	-41.7423 **
7930.0000	-13.0000	-44.3501 **	-43.2430 **



The data presented here was taken using the substitution method as found in the ANSI C63.26-2015 document.  
Motorola Penang EMC Lab - Test Performed by: Qawiman&Nazrin Thu, 10 Sep, 2020

Remarks: \*\* Indicates the spurious emission could not be detected due to noise limitations or ambient.

\*Pursuant to CFR 47 Part 2.1057 ( c ), emissions attenuated more than 20 dB below the permissible limit are not reported  
Temp(Deg): 23.9 Hum(%RH): 68.7

System MU: 4.03 dB


Remarks: Passed Results Marginal Results Failed Results

Model Number: AAH90ZDU9RH1AN  
 Battery Part No: PMNN4804A  
 795.500000 MHz (High)

SAC Transmitter Radiated Emission:  
 S/N: 734TWP0308  
 Accy Part No: AN000348A01  
 Test Mode: TX LTE (Band 14) Z-Plane  
 Bandwidth 5MHz

SR:18058-EMC-00054  
 0.252 Watt(s) /Max Power

Frequency (MHz)	Limit	Horizontal Measured Emission Equiv Pwr Into Ideal Dipole (dBm)	Vertical Measured Emission Equiv Pwr Into ideal Dipole (dBm)
1591.0000	-13.0000	-58.0410 **	-59.6036 **
2386.8100	-13.0000	-44.2000 *	-47.4700 *
3182.0000	-13.0000	-53.3392 **	-52.0120 **
3977.5000	-13.0000	-50.2604 **	-49.8452 **
4773.0000	-13.0000	-50.3501 **	-49.4248 **
5568.5000	-13.0000	-47.7324 **	-48.6819 **
6364.0000	-13.0000	-45.9279 **	-47.0206 **
7159.5000	-13.0000	-43.3276 **	-43.0758 **
7955.0000	-13.0000	-41.9938 **	-42.3866 **



The data presented here was taken using the substitution method as found in the ANSI C63.26-2015 document.  
 Motorola Penang EMC Lab - Test Performed by: Qawiman&Nazrin  
 Thu, 10 Sep, 2020

Remarks: \*\* Indicates the spurious emission could not be detected due to noise limitations or ambient.


\*Pursuant to CFR 47 Part 2.1057 ( c ), emissions attenuated more than 20 dB below the permissible limit are not reported  
 Temp(Deg): 23.9 Hum(%RH): 68.7

System MU: 4.03 dB

Remarks: Passed Results Marginal Results Failed Results

## 1.13. Effective Radiated Power (ERP)

### 1.13.1. Test Setup



- 1) The spectrum setting for scanning Radiated Emission below 1 GHz is RBW = 100 kHz, VBW = 300 kHz and above 1 GHz is RBW = 1MHz, VBW = 3MHz. Detector mode is RMS.
- 2) In the semi-anechoic chamber, setup as illustrated above the EUT placed on the Turn Table at 0.8m height for below 1GHz measurement and at 1.5m height for above 1GHz measurement, rotated the table around 360 degrees to search the maximum radiation power and receiver antenna shall be rotated vertical and horizontal polarization and moved height from 1m to 4m to find the maximum polar radiated power. The “Read Value” is the spectrum reading the maximum power value.
- 3) The substitution antenna is substituted for EUT at the same position and signals generator (S.G) export the CW signal to the substitution antenna via a TX cable. The receiver antenna shall be rotated vertical and horizontal polarization and moved height from 1m to 4m to find the maximum radiation power. Record the power level of maximum radiation power from spectrum. So, the measured substitution value = Ref level of S.G + TX cables loss – Substituted Antenna Gain.
- 4)  $ERP = \text{“Read Value”} + \text{Measured substitution value.}$

### 1.13.2. Test Limit

The maximum output power of the transmitter for mobile stations is 100 watts (20 dBw). Power is given in terms of effective radiated power (ERP).


### 1.13.3. Effective Radiated Power (ERP) - LTE Band 14 (788-798MHz)

**Not Performed.**



## 1.14. GNSS (EIRP for 1559 - 1610MHz)

### 1.14.1. Test Setup



- 1) The Resolution Bandwidth for Equivalent Isotropically Radiated Power (EIRP) below 1 GHz is 100 kHz with Video Bandwidth = 300 kHz and Resolution Bandwidth for EIRP above 1 GHz is 1 MHz with Video Bandwidth = 3 MHz. Detector Mode is RMS.
- 2) In the semi-anechoic chamber, setup as illustrated above the DUT placed on the 0.8m height of Turn Table, rotated the table 45 degree each interval to search the maximum radiation power and receiver antenna shall be rotated vertical and horizontal polarization and moved height from 1m to 4m to find the maximum polar radiated power for each degree interval. The "Read Value" is the spectrum reading of maximum power value.
- 3) The substitution antenna is substituted for DUT at the same position and signals generator (S.G) export the CW signal to the substitution antenna via a TX cable. The receiver antenna shall be rotated vertical and horizontal polarization and moved height from 1m to 4m to find the maximum radiation power. Record the power level of maximum radiation power from spectrum. So, the Measured substitution value = Ref level of S.G + TX cables loss – Substituted Antenna Gain.
- 4)  $EIRP = \text{"Read Value"} + \text{Measured substitution value} + 2.15$ .

### 1.14.2. Test Limit

FCC: For operations in the 758-775 MHz and 788-805 MHz bands, all emissions including harmonics in the band 1559-1610 MHz shall be limited to  $-70$  dBW/MHz equivalent isotropically radiated power (EIRP) for wideband signals, and  $-80$  dBW EIRP for discrete emissions of less than 700 Hz bandwidth. For the purpose of equipment authorization, a transmitter shall be tested with an antenna that is representative of the type that will be used with the equipment in normal operation.

ISED: The equivalent isotropically radiated power (e.i.r.p.) of all emissions, including harmonics in the band 1559-1610 MHz, shall not exceed  $-70$  dBW/MHz for wideband emissions, and  $-80$  dBW/kHz for discrete emissions of less than 700 Hz bandwidth.

### 1.14.3. GNSS (EIRP for 1599 – 1610MHz) - LTE Band 14 (788-798MHz)

#### EIRP in RNSS band (1.559GHz to 1.610GHz)

S/N: 734TWP0308

Channel Bandwidth: 5 MHz

Accessory: AN000348A01

Tx Power: 0.252 Watts

Modulation: QPSK (LTE B14)

Battery: PMNN4804A

Frequency Channel: 790.5000 MHz (Z-Plane)

Antenna Polarization	2Fc (MHz)	EIRP (dBm)	Limit (dBm)
Horizontal	1581.0000	-68.32	-40
Vertical	1581.0000	-68.06	-40

#### EIRP in RNSS band (1.559GHz to 1.610GHz)

S/N: 734TWP0308

Channel Bandwidth: 5 MHz

Accessory: AN000348A01

Tx Power: 0.252 Watts

Modulation: QPSK (LTE B14)

Battery: PMNN4804A

Frequency Channel: 793.0000 MHz (Z-Plane)

Antenna Polarization	2Fc (MHz)	EIRP (dBm)	Limit (dBm)
Horizontal	1586.0000	-68.23	-40
Vertical	1586.0000	-68.14	-40

**EIRP in RNSS band (1.559GHz to 1.610GHz)**  
**S/N: 734TWP0308**  
**Channel Bandwidth: 5 MHz**  
**Accessory: AN000348A01**

**Tx Power: 0.252 Watts**  
**Modulation: QPSK (LTE B14)**  
**Battery: PMNN4804A**

**Frequency Channel: 784.5000 MHz (Z-Plane)**

Antenna Polarization	2Fc (MHz)	EIRP (dBm)	Limit (dBm)
Horizontal	1569.0000	-68.42	-40
Vertical	1569.0000	-68.25	-40

--End of Test Report--