



# FCC TEST REPORT

**REPORT NO.:** RF960503A01A

**MODEL NO.:** 1123

**RECEIVED:** May 3, 2007

**TESTED:** May 3 ~ 14, 2007

**ISSUED:** May 16, 2007

**APPLICANT:** MICROSOFT CORPORATION

**ADDRESS:** ONE MICROSOFT WAY REDMOND, WA  
98052-6399, U.S.A

**ISSUED BY:** Advance Data Technology Corporation

**LAB LOCATION:** No. 47, 14th Ling, Chia Pau Tsuen, Lin Kou  
Hsiang 244, Taipei Hsien, Taiwan, R.O.C.

This test report consists of 34 pages in total. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The client should not use it to claim product endorsement by CNLA, A2LA or any government agencies. The test results in the report only apply to the tested sample.





## Table of Contents

1.	CERTIFICATION .....	3
2.	SUMMARY OF TEST RESULTS .....	4
2.1	MEASUREMENT UNCERTAINTY .....	4
3.	GENERAL INFORMATION .....	5
3.1	GENERAL DESCRIPTION OF EUT .....	5
3.2	DESCRIPTION OF TEST MODES .....	6
3.2.1	CONFIGURATION OF SYSTEM UNDER TEST .....	6
3.2.2	TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL: .....	7
3.3	GENERAL DESCRIPTION OF APPLIED STANDARDS .....	8
3.4	DESCRIPTION OF SUPPORT UNITS .....	8
4.	TEST TYPES AND RESULTS .....	9
4.1	CONDUCTED EMISSION MEASUREMENT .....	9
4.1.1	LIMITS OF CONDUCTED EMISSION MEASUREMENT .....	9
4.1.2	TEST INSTRUMENTS .....	9
4.1.3	TEST PROCEDURES .....	10
4.1.4	DEVIATION FROM TEST STANDARD .....	10
4.1.5	TEST SETUP .....	10
4.1.6	EUT OPERATING CONDITIONS .....	11
4.1.7	TEST RESULTS .....	12
4.2	RADIATED EMISSION MEASUREMENT .....	18
4.2.1	LIMITS OF RADIATED EMISSION MEASUREMENT .....	18
4.2.2	TEST INSTRUMENTS .....	19
4.2.3	TEST PROCEDURES .....	20
4.2.4	DEVIATION FROM TEST STANDARD .....	20
4.2.5	TEST SETUP .....	21
4.2.6	EUT OPERATING CONDITIONS .....	21
4.2.7	TEST RESULTS .....	22
4.3	FREQUENCY TOLERANCE MEASUREMENT .....	28
4.3.1	LIMITS OF FREQUENCY TOLERANCE MEASUREMENT .....	28
4.3.2	TEST INSTRUMENTS .....	28
4.3.3	TEST PROCEDURE .....	28
4.3.4	DEVIATION FROM TEST STANDARD .....	28
4.3.5	EUT OPERATING CONDITION .....	28
4.3.6	TEST RESULTS .....	29
4.4	BAND EDGES MEASUREMENT .....	30
4.4.1	LIMITS OF BAND EDGES MEASUREMENT .....	30
4.4.2	TEST INSTRUMENTS .....	30
4.4.3	TEST PROCEDURE .....	30
4.4.4	DEVIATION FROM TEST STANDARD .....	30
4.4.5	EUT OPERATING CONDITION .....	30
4.4.6	TEST RESULTS .....	30
5.	INFORMATION ON THE TESTING LABORATORIES .....	33
	APPENDIX-A .....	A-1



## 1. CERTIFICATION

**PRODUCT:** Microsoft® 2.4G Transceiver V2.0  
**BRAND NAME:** Microsoft®  
**MODEL NO.:** 1123  
**APPLICANT:** MICROSOFT CORPORATION  
**TESTED:** May 3 ~ 14, 2007  
**TEST SAMPLE:** ENGINEERING SAMPLE  
**STANDARDS:** FCC Part 15, Subpart C (Section 15.249),  
ANSI C63.4-2003

The above equipment has been tested by **Advance Data Technology Corporation**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

**PREPARED BY** : Annie Chang , **DATE:** May 16, 2007  
( Annie Chang )

**TECHNICAL  
ACCEPTANCE** : Jamison Chan , **DATE:** May 16, 2007  
Responsible for RF ( Jamison Chan )

**APPROVED BY** : Ken Liu , **DATE:** May 16, 2007  
( Ken Liu / Deputy Manager )



## 2. SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC Part 15, Subpart C (Section 15.249)			
STANDARD PARAGRAPH	TEST TYPE	RESULT	REMARK
15.207	Conducted Emission Test	PASS	Minimum passing margin is -14.63dB at 0.180MHz
15.209 15.249 15.249 (d)	Radiated Emission Test Band Edge Measurement Limit: 50dB less than the peak value of fundamental frequency or meet radiated emission limit in section 12.209	PASS	Minimum passing margin is -6.31dB at 2483.500MHz
15.249 (b)(2)	Frequency Tolerance Limit: $\pm 0.001\%$	PASS	Meet the requirement of limit.

### 2.1 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4:

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of  $k=2$ .

Measurement	Uncertainty
Conducted emissions	2.44 dB
Radiated emissions	3.75 dB



### 3. GENERAL INFORMATION

#### 3.1 GENERAL DESCRIPTION OF EUT

<b>EUT</b>	Microsoft® 2.4G Transceiver V2.0
<b>MODEL NO.</b>	1123
<b>FCC ID</b>	C3K1123
<b>POWER SUPPLY</b>	5Vdc from host equipment
<b>MODULATION TYPE</b>	GFSK
<b>TRANSFER RATE</b>	2Mbps
<b>FREQUENCY RANGE</b>	2402MHz ~2479MHz
<b>NUMBER OF CHANNEL</b>	78
<b>ANTENNA TYPE</b>	Strip antenna with -0.64dBi gain
<b>DATA CABLE</b>	N/A
<b>I/O PORTS</b>	USB port
<b>ASSOCIATED DEVICES</b>	N/A

#### NOTE:


1. The EUT is a Microsoft® 2.4G Transceiver V2.0, which includes transmitter & receiver function.
2. The above EUT information was declared by the manufacturer and for more detailed features description, please refer to the manufacturer's specifications or User's Manual.

### 3.2 DESCRIPTION OF TEST MODES

Seventy-eight channels are provided to this EUT:

CHANNEL	FREQ. (MHz)	CHANNEL	FREQ. (MHz)	CHANNEL	FREQ. (MHz)	CHANNEL	FREQ. (MHz)
0	2402	20	2422	40	2442	60	2462
1	2403	21	2423	41	2443	61	2463
2	2404	22	2424	42	2444	62	2464
3	2405	23	2425	43	2445	63	2465
4	2406	24	2426	44	2446	64	2466
5	2407	25	2427	45	2447	65	2467
6	2408	26	2428	46	2448	66	2468
7	2409	27	2429	47	2449	67	2469
8	2410	28	2430	48	2450	68	2470
9	2411	29	2431	49	2451	69	2471
10	2412	30	2431	50	2452	70	2472
11	2413	31	2433	51	2453	71	2473
12	2414	32	2434	52	2454	72	2474
13	2415	33	2435	53	2455	73	2475
14	2416	34	2436	54	2456	74	2476
15	2417	35	2437	55	2457	75	2477
16	2418	36	2438	56	2458	76	2478
17	2419	37	2439	57	2459	77	2479
18	2420	38	2440	58	2460		
19	2421	39	2441	59	2461		

#### 3.2.1 CONFIGURATION OF SYSTEM UNDER TEST





### 3.2.2 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL:

EUT configure mode	Applicable to				Description
	PLC	RE<1G	RE $\geq$ 1G	APCM	
A	✓	✓	✓	✓	Serial No.: EV2-0646-039
B	-	✓	-	-	Serial No.: EV2-0646-091
C	-	✓	-	-	Serial No.: EV2-0646-174

Where PLC: Power Line Conducted Emission

RE $\geq$ 1G: Radiated Emission above 1GHz

RE<1G RE: Radiated Emission below 1GHz

APCM: Antenna Port Conducted Measurement

#### POWER LINE CONDUCTED EMISSION TEST:

Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	AVAILABLE CHANNEL	TESTED CHANNEL	RADIO TECHNOLOGY	MODULATION TYPE
A	0 to 77	0, 38, 77	DSSS	GFSK

#### RADIATED EMISSION TEST (BELOW 1 GHz):

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	AVAILABLE CHANNEL	TESTED CHANNEL	RADIO TECHNOLOGY	MODULATION TYPE
A	0 to 77	77	DSSS	GFSK
B	0 to 77	77	DSSS	GFSK
C	0 to 77	77	DSSS	GFSK

#### RADIATED EMISSION TEST (ABOVE 1 GHz):

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	AVAILABLE CHANNEL	TESTED CHANNEL	RADIO TECHNOLOGY	MODULATION TYPE
A	0 to 77	0, 38, 77	DSSS	GFSK

#### FREQUENCY TOLERANCE:

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	AVAILABLE CHANNEL	TESTED CHANNEL	RADIO TECHNOLOGY	MODULATION TYPE
A	0 to 77	0, 38, 77	DSSS	GFSK



#### **BANDEDGE MEASUREMENT:**

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	AVAILABLE CHANNEL	TESTED CHANNEL	RADIO TECHNOLOGY	MODULATION TYPE
A	0 to 77	0, 77	DSSS	GFSK

### **3.3 GENERAL DESCRIPTION OF APPLIED STANDARDS**

The EUT is a RF product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

**FCC Part 15, Subpart C. (15.249)**

**ANSI C63.4-2003**

All test items have been performed and recorded as per the above standards.

### **3.4 DESCRIPTION OF SUPPORT UNITS**

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

NO.	PRODUCT	BRAND	MODEL NO.	SERIAL NO.	FCC ID
1	NOTEBOOK	DELL	D600	CN-0G5152-486 43-487-0213	FCC DoC Approved
2	PRINTER	EPSON	LQ-300+	DCGY017054	FCC DoC Approved
3	MODEM	ACEEX	1414	980020520	IFAXDM1414

NO.	SIGNAL CABLE DESCRIPTION OF THE ABOVE SUPPORT UNITS
1	N/A
2	1.8m braid shielded wire, terminated with DB25 and Centronics connector via metallic frame, w/o core
3	1.2 m braid shielded wire, terminated with DB25 and DB9 connector via metallic frame, w/o core.

**NOTE:** All power cords of the above support units are non-shielded (1.8m).



## 4. TEST TYPES AND RESULTS

### 4.1 CONDUCTED EMISSION MEASUREMENT

#### 4.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT

FREQUENCY OF EMISSION (MHz)	CONDUCTED LIMIT (dB $\mu$ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56	56 to 46
0.5-5	56	46
5-30	60	50

**NOTE:**

1. The lower limit shall apply at the transition frequencies.
2. All emanations from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

#### 4.1.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED UNTIL
ROHDE & SCHWARZ Test Receiver	ESCS 30	838251/021	Nov. 23, 2007
ROHDE & SCHWARZ Artificial Mains Network (for EUT)	ESH3-Z5	100218	Nov. 21, 2007
LISN With Adapter (for EUT)	AD10	C10Ada-001	Nov. 21, 2007
ROHDE & SCHWARZ Artificial Mains Network (for peripherals)	ESH3-Z5	100219	Nov. 07, 2007
ROHDE & SCHWARZ Artificial Mains Network (for peripherals)	ESH3-Z5	100220	Oct. 26, 2007
Software	ADT_Cond_V7.3.2	NA	NA
Software	ADT_ISN_V7.3.2	NA	NA
RF cable (JYEBAO)	5D-FB	Cable-C10.01	Mar. 01, 2008
SUHNER Terminator (For ROHDE & SCHWARZ LISN)	65BNC-5001	E1-010773	Feb. 11, 2008

**NOTE:**

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The test was performed in ADT Shielded Room No. 10.
3. The VCCI Site Registration No. C-1852.


### 4.1.3 TEST PROCEDURES

- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- c. The frequency range from 150kHz to 30MHz was searched. Emission levels under Limit - 20dB was not recorded.

### 4.1.4 DEVIATION FROM TEST STANDARD

No deviation.

### 4.1.5 TEST SETUP



**Note: 1. Support units were connected to second LISN.**

**2. Both of LISNs (AMN) are 80 cm from EUT and at least 80 cm from other units and other metal planes**

For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.



#### 4.1.6 EUT OPERATING CONDITIONS

- a. Connected the EUT to a notebook placed on a testing table.
- b. The notebook ran a test program (provided by manufacturer) to enable EUT under transmission/receiving condition continuously at specific channel frequency.
- c. The notebook sent "H" messages to its screen.
- d. The notebook sent messages to printer and the printer prints them out
- e. The notebook sent messages to modem.
- f. Repeated c ~ f.

## 4.1.7 TEST RESULTS

### CONDUCTED WORST CASE DATA

TEST MODE	A					
MODULATION TYPE	GFSK			CHANNEL	0	
INPUT POWER (SYSTEM)	120Vac, 60 Hz			6dB BANDWIDTH	9 kHz	
ENVIRONMENTAL CONDITIONS	25deg. C, 70%RH, 1003hPa			PHASE	Line 1	
TESTED BY	Jun Wu					

No	Freq. [MHz]	Corr. Factor	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.
1	0.180	0.20	49.64	-	49.84	-	64.47	54.47	-14.63	-
2	0.240	0.20	42.65	-	42.85	-	62.10	52.10	-19.25	-
3	2.953	0.45	30.02	-	30.47	-	56.00	46.00	-25.53	-
4	3.793	0.49	36.86	-	37.35	-	56.00	46.00	-18.65	-
5	15.121	1.11	36.17	-	37.28	-	60.00	50.00	-22.72	-
6	16.152	1.17	35.85	-	37.02	-	60.00	50.00	-22.98	-

**REMARKS:** 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.


2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.

3. The emission levels of other frequencies were very low against the limit.

4. Margin value = Emission level - Limit value

5. Correction factor = Insertion loss + Cable loss

6. Emission Level = Correction Factor + Reading Value.




TEST MODE	A		
MODULATION TYPE	GFSK	CHANNEL	0
INPUT POWER (SYSTEM)	120Vac, 60 Hz	6dB BANDWIDTH	9 kHz
ENVIRONMENTAL CONDITIONS	25deg. C, 70%RH, 1003hPa	PHASE	Line 2
TESTED BY	Jamison Chan		

No	Freq. Factor	Corr. Factor	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			[MHz]	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.181	0.20	48.44	-	48.64	-	64.43	54.43	-15.79	-
2	0.240	0.20	41.17	-	41.37	-	62.10	52.10	-20.73	-
3	3.621	0.38	36.50	-	36.88	-	56.00	46.00	-19.12	-
4	4.164	0.40	34.38	-	34.78	-	56.00	46.00	-21.22	-
5	14.734	0.78	33.25	-	34.03	-	60.00	50.00	-25.97	-
6	16.539	0.86	30.43	-	31.29	-	60.00	50.00	-28.71	-

**REMARKS:** 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.

2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Correction factor = Insertion loss + Cable loss
6. Emission Level = Correction Factor + Reading Value.




TEST MODE	A		
MODULATION TYPE	GFSK	CHANNEL	38
INPUT POWER (SYSTEM)	120Vac, 60 Hz	6dB BANDWIDTH	9 kHz
ENVIRONMENTAL CONDITIONS	25deg. C, 70%RH, 1003hPa	PHASE	Line 1
TESTED BY	Jun Wu		

No	Freq. Factor	Corr. Factor	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			[MHz]	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.181	0.20	48.19	-	48.39	-	64.43	54.43	-16.04	-
2	0.240	0.20	42.57	-	42.77	-	62.10	52.10	-19.33	-
3	3.191	0.46	32.03	-	32.49	-	56.00	46.00	-23.51	-
4	3.672	0.48	33.96	-	34.44	-	56.00	46.00	-21.56	-
5	14.684	1.07	34.43	-	35.50	-	60.00	50.00	-24.50	-
6	15.465	1.13	35.07	-	36.20	-	60.00	50.00	-23.80	-

**REMARKS:** 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.

2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Correction factor = Insertion loss + Cable loss
6. Emission Level = Correction Factor + Reading Value.




TEST MODE	A					
MODULATION TYPE	GFSK			CHANNEL	38	
INPUT POWER (SYSTEM)	120Vac, 60 Hz			6dB BANDWIDTH	9 kHz	
ENVIRONMENTAL CONDITIONS	25deg. C, 70%RH, 1003hPa			PHASE	Line 2	
TESTED BY	Jamison Chan					

No	Freq. Factor	Corr. [MHz]	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.181	0.20	47.19	-	47.39	-	64.43	54.43	-17.04	-
2	0.240	0.20	41.96	-	42.16	-	62.10	52.10	-19.94	-
3	3.125	0.36	33.08	-	33.44	-	56.00	46.00	-22.56	-
4	3.664	0.38	36.75	-	37.13	-	56.00	46.00	-18.87	-
5	15.266	0.81	37.68	-	38.49	-	60.00	50.00	-21.51	-
6	16.766	0.87	37.40	-	38.27	-	60.00	50.00	-21.73	-

**REMARKS:** 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.

2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Correction factor = Insertion loss + Cable loss
6. Emission Level = Correction Factor + Reading Value.




TEST MODE	A		
MODULATION TYPE	GFSK	CHANNEL	77
INPUT POWER (SYSTEM)	120Vac, 60 Hz	6dB BANDWIDTH	9 kHz
ENVIRONMENTAL CONDITIONS	25deg. C, 70%RH, 1003hPa	PHASE	Line 1
TESTED BY	Jun Wu		

No	Freq. Factor	Reading Value		Emission Level		Limit		Margin	
		[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
		[MHz]	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.181	0.20	48.01	-	48.21	-	64.43	54.43	-16.22
2	0.240	0.20	42.28	-	42.48	-	62.10	52.10	-19.62
3	1.797	0.40	34.70	-	35.10	-	56.00	46.00	-20.90
4	3.961	0.50	37.85	-	38.35	-	56.00	46.00	-17.65
5	14.828	1.09	36.31	-	37.40	-	60.00	50.00	-22.60
6	17.945	1.28	31.23	-	32.51	-	60.00	50.00	-27.49

**REMARKS:** 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.

2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Correction factor = Insertion loss + Cable loss
6. Emission Level = Correction Factor + Reading Value.




TEST MODE	A					
MODULATION TYPE	GFSK			CHANNEL	77	
INPUT POWER (SYSTEM)	120Vac, 60 Hz			6dB BANDWIDTH	9 kHz	
ENVIRONMENTAL CONDITIONS	25deg. C, 70%RH, 1003hPa			PHASE	Line 2	
TESTED BY	Jamison Chan					

No	Freq. Factor	Corr. [MHz]	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.181	0.20	47.03	-	47.23	-	64.43	54.43	-17.20	-
2	0.239	0.20	41.63	-	41.83	-	62.14	52.14	-20.31	-
3	1.680	0.30	34.66	-	34.96	-	56.00	46.00	-21.04	-
4	3.781	0.39	37.88	-	38.27	-	56.00	46.00	-17.73	-
5	15.500	0.82	36.14	-	36.96	-	60.00	50.00	-23.04	-
6	16.695	0.87	31.55	-	32.42	-	60.00	50.00	-27.58	-

**REMARKS:** 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.

2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Correction factor = Insertion loss + Cable loss
6. Emission Level = Correction Factor + Reading Value.





## 4.2 RADIATED EMISSION MEASUREMENT

### 4.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT

Emissions radiated outside of the specified bands, shall be according to the general radiated limits in 15.209 as following:

Frequencies (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

**NOTE:**

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.



#### 4.2.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED UNTIL
HP Preamplifier	8447D	2432A03504	May 21, 2007
HP Preamplifier	8449B	3008A01924	Sep. 05, 2007
HP Preamplifier	8449B	3008A01638	Sep. 17, 2007
ROHDE & SCHWARZ TEST RECEIVER	ESI7	836697/012	Oct. 24, 2007
Schwarzbeck Antenna	VULB 9168	137	Oct. 01, 2007
Schwarzbeck Antenna	VHBA 9123	480	Apr. 18, 2008
EMCO Horn Antenna	3115	6714	Oct. 24, 2007
EMCO Horn Antenna	3115	9312-4192	Apr. 19, 2008
ADT. Turn Table	TT100	0306	NA
ADT. Tower	AT100	0306	NA
Software	ADT_Radiated_V 7.6.15	NA	NA
SUHNER RF cable	SF104-26.5	CABLE-CH6-17m-01	Dec. 11, 2007
ROHDE & SCHWARZ Spectrum Analyzer	FSP 40	100036	Mar. 13, 2008

**NOTE:**

1. The calibration interval of the above test instruments is 12 months. And the calibrations are traceable to NML/ROC and NIST/USA.
2. The horn antenna and HP preamplifier (model: 8449B) are used only for the measurement of emission frequency above 1GHz if tested.
3. The test was performed in ADT Chamber No. 6.
4. The Industry Canada Reference No. IC 3789-6.



#### 4.2.3 TEST PROCEDURES

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi- anechoic. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions would be re-tested one by one using peak, quasi-peak method or average method as specified and then reported in data sheet.


#### NOTE:

1. The resolution bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection at frequency below 1GHz.
2. The resolution bandwidth is 1MHz and video bandwidth of test receiver/spectrum analyzer is 3MHz for Peak detection at frequency above 1GHz. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz for Average detection (AV) at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 10 Hz for Average detection (AV) at frequency above 1GHz.

#### 4.2.4 DEVIATION FROM TEST STANDARD

No deviation

#### 4.2.5 TEST SETUP



For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

#### 4.2.6 EUT OPERATING CONDITIONS

Set the EUT under transmission condition continuously at specific channel frequency.



## 4.2.7 TEST RESULTS

### RADIATED WORST CASE DATA: BELOW 1GHz

TEST MODE	A		
MODULATION TYPE	GFSK	CHANNEL	77
INPUT POWER (SYSTEM)	120Vac, 60 Hz	FREQUENCY RANGE	Below 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH, 1001Pa	DETECTOR FUNCTION	Quasi-Peak
TESTED BY	Jun Wu		

### ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	103.868	29.90 QP	43.50	-13.60	2.00 H	322	17.76	12.14
2	195.230	32.29 QP	43.50	-11.21	1.50 H	109	21.84	10.45
3	500.421	32.62 QP	46.00	-13.38	1.50 H	40	9.76	22.86
4	545.130	32.60 QP	46.00	-13.40	1.50 H	64	7.75	24.85
5	663.707	35.15 QP	46.00	-10.85	1.50 H	22	9.57	25.58
6	733.687	33.16 QP	46.00	-12.84	1.00 H	10	5.87	27.30
7	867.816	37.36 QP	46.00	-8.64	1.00 H	43	8.26	29.10
8	945.571	34.80 QP	46.00	-11.20	1.00 H	145	4.24	30.56

### ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	129.138	33.10 QP	43.50	-10.40	1.50 V	46	20.92	12.18
2	195.230	35.77 QP	43.50	-7.73	1.00 V	142	24.25	11.52
3	599.559	32.66 QP	46.00	-13.34	1.00 V	55	8.34	24.32
4	665.651	36.93 QP	46.00	-9.07	1.00 V	199	11.81	25.12
5	729.800	34.92 QP	46.00	-11.08	1.00 V	187	7.98	26.93
6	867.816	39.40 QP	46.00	-6.60	1.50 V	205	10.56	28.84
7	941.683	32.15 QP	46.00	-13.85	1.00 V	106	1.66	30.49

**REMARKS:**

1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.



<b>TEST MODE</b>	B			
<b>MODULATION TYPE</b>	GFSK		<b>CHANNEL</b>	77
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz		<b>FREQUENCY RANGE</b>	Below 1000MHz
<b>ENVIRONMENTAL CONDITIONS</b>	23deg. C, 70%RH, 1001Pa		<b>DETECTOR FUNCTION</b>	Quasi-Peak
<b>TESTED BY</b>	Jun Wu			

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	193.287	29.83 QP	43.50	-13.67	1.45 H	103	19.25	10.58
2	545.130	33.64 QP	46.00	-12.36	1.39 H	79	8.79	24.85
3	572.345	32.07 QP	46.00	-13.93	1.28 H	97	7.08	24.99
4	667.595	35.26 QP	46.00	-10.74	1.24 H	178	9.65	25.61
5	729.800	33.61 QP	46.00	-12.39	1.19 H	19	6.47	27.14
6	865.872	38.13 QP	46.00	-7.87	1.05 H	100	9.08	29.05
7	931.964	39.29 QP	46.00	-6.71	1.01 H	148	8.93	30.36

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	129.138	31.89 QP	43.50	-11.61	1.00 V	25	19.71	12.18
2	195.230	35.12 QP	43.50	-8.38	1.00 V	10	23.60	11.52
3	667.595	39.03 QP	46.00	-6.97	1.02 V	286	13.88	25.15
4	733.687	33.78 QP	46.00	-12.22	1.26 V	82	6.68	27.10
5	865.872	39.28 QP	46.00	-6.72	1.39 V	199	10.48	28.80
6	941.683	33.13 QP	46.00	-12.87	1.45 V	85	2.64	30.49

**REMARKS:**

1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.



TEST MODE	C			
MODULATION TYPE	GFSK		CHANNEL	77
INPUT POWER (SYSTEM)	120Vac, 60 Hz		FREQUENCY RANGE	Below 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH, 1001Pa		DETECTOR FUNCTION	Quasi-Peak
TESTED BY	Jun Wu			

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	193.287	31.05 QP	43.50	-12.45	1.59 H	280	20.47	10.58
2	665.651	35.12 QP	46.00	-10.88	1.32 H	160	9.53	25.59
3	731.743	35.32 QP	46.00	-10.68	1.30 H	211	8.10	27.22
4	825.050	32.06 QP	46.00	-13.94	1.25 H	283	3.89	28.17
5	865.872	37.27 QP	46.00	-8.73	1.18 H	112	8.22	29.05
6	931.964	39.26 QP	46.00	-6.74	1.02 H	199	8.90	30.36
7	941.683	32.33 QP	46.00	-13.67	1.04 H	166	1.82	30.51

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	123.307	34.52 QP	43.50	-8.98	1.00 V	10	23.11	11.40
2	195.230	35.13 QP	43.50	-8.37	1.00 V	334	23.61	11.52
3	399.339	32.48 QP	46.00	-13.52	1.02 V	16	13.69	18.79
4	663.707	36.57 QP	46.00	-9.43	1.32 V	268	11.48	25.09
5	729.800	35.28 QP	46.00	-10.72	1.39 V	94	8.35	26.93
6	795.892	34.45 QP	46.00	-11.55	1.45 V	304	6.43	28.02
7	865.872	36.83 QP	46.00	-9.17	1.42 V	76	8.03	28.80

**REMARKS:**

1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.


**RADIATED WORST CASE DATA: ABOVE 1GHz**

<b>TEST MODE</b>	A						
<b>MODULATION TYPE</b>	GFSK		<b>CHANNEL</b>		0		
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz		<b>FREQUENCY RANGE</b>		1 ~ 25GHz		
<b>ENVIRONMENTAL CONDITIONS</b>	23deg. C, 70%RH, 1001Pa		<b>DETECTOR FUNCTION</b>		Peak(PK) Average (AV)		
<b>TESTED BY</b>	Jun Wu						

**ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M**

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.000	60.34 PK	74.00	-13.66	1.41 H	282	25.92	34.42
2	2390.000	47.11 AV	54.00	-6.89	1.41 H	282	12.69	34.42
3	*2402.000	93.68 PK	114.00	-20.32	1.41 H	282	59.24	34.44
4	*2402.000	79.87 AV	94.00	-14.13	1.41 H	282	45.43	34.44
5	4804.000	55.84 PK	74.00	-18.16	1.00 H	18	14.44	41.39
6	4804.000	47.00 AV	54.00	-7.00	1.00 H	18	5.60	41.39

**ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M**

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.000	58.30 PK	74.00	-15.70	1.26 V	11	23.88	34.42
2	2390.000	47.10 AV	54.00	-6.90	1.26 V	11	12.68	34.42
3	*2402.000	91.76 PK	114.00	-22.24	1.26 V	11	57.32	34.44
4	*2402.000	77.97 AV	94.00	-16.03	1.26 V	11	43.53	34.44
5	4804.000	50.61 PK	74.00	-23.39	1.25 V	26	9.21	41.39
6	4804.000	42.51 AV	54.00	-11.49	1.25 V	26	1.11	41.39

**REMARKS:**

1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “\*”: Fundamental frequency



<b>TEST MODE</b>	A		
<b>MODULATION TYPE</b>	GFSK	<b>CHANNEL</b>	38
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz	<b>FREQUENCY RANGE</b>	1 ~ 25GHz
<b>ENVIRONMENTAL CONDITIONS</b>	23deg. C, 70%RH, 1001Pa	<b>DETECTOR FUNCTION</b>	Peak(PK) Average (AV)
<b>TESTED BY</b>	Jun Wu		

<b>ANTENNA POLARITY &amp; TEST DISTANCE: HORIZONTAL AT 3 M</b>								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2440.000	93.17 PK	114.00	-20.83	1.42 H	221	58.65	34.52
2	*2440.000	79.71 AV	94.00	-14.29	1.42 H	221	45.19	34.52
3	4880.000	54.83 PK	74.00	-19.17	1.00 H	19	13.24	41.59
4	4880.000	46.92 AV	54.00	-7.08	1.00 H	19	5.33	41.59

<b>ANTENNA POLARITY &amp; TEST DISTANCE: VERTICAL AT 3 M</b>								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2440.000	91.14 PK	114.00	-22.86	1.51 V	14	56.62	34.52
2	*2440.000	77.75 AV	94.00	-16.25	1.51 V	14	43.23	34.52
3	4880.000	50.35 PK	74.00	-23.65	1.19 V	3	8.76	41.59
4	4880.000	40.64 AV	54.00	-13.36	1.19 V	3	-0.95	41.59

**REMARKS:**

1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “\*”: Fundamental frequency



<b>TEST MODE</b>	A		
<b>MODULATION TYPE</b>	GFSK	<b>CHANNEL</b>	77
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz	<b>FREQUENCY RANGE</b>	1 ~ 25GHz
<b>ENVIRONMENTAL CONDITIONS</b>	23deg. C, 70%RH, 1001Pa	<b>DETECTOR FUNCTION</b>	Peak(PK) Average (AV)
<b>TESTED BY</b>	Jun Wu		

#### ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2479.000	92.83 PK	114.00	-21.17	1.38 H	194	58.23	34.60
2	*2479.000	79.54 AV	94.00	-14.46	1.38 H	194	44.94	34.60
3	<b>2483.500</b>	<b>67.69 PK</b>	<b>74.00</b>	<b>-6.31</b>	<b>1.38 H</b>	<b>194</b>	<b>33.08</b>	<b>34.61</b>
4	2483.500	47.44 AV	54.00	-6.56	1.38 H	194	12.83	34.61
5	4958.000	53.29 PK	74.00	-20.71	1.19 H	22	11.49	41.79
6	4958.000	44.18 AV	54.00	-9.82	1.19 H	22	2.38	41.79

#### ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2479.000	90.06 PK	114.00	-23.94	1.43 V	12	55.46	34.60
2	*2479.000	76.90 AV	94.00	-17.10	1.43 V	12	42.30	34.60
3	2483.500	64.72 PK	74.00	-9.28	1.43 V	12	30.11	34.61
4	2483.500	47.47 AV	54.00	-6.53	1.43 V	12	12.86	34.61
5	4958.000	49.17 PK	74.00	-24.83	1.08 V	294	7.37	41.79
6	4958.000	39.02 AV	54.00	-14.98	1.08 V	294	-2.78	41.79

**REMARKS:**

1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “\*”: Fundamental frequency



## 4.3 FREQUENCY TOLERANCE MEASUREMENT

### 4.3.1 LIMITS OF FREQUENCY TOLERANCE MEASUREMENT

Limit :  $\pm 0.001\%$

### 4.3.2 TEST INSTRUMENTS

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
SPECTRUM ANALYZER	FSP 40	100036	Mar. 13, 2008

**NOTE:** The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

### 4.3.3 TEST PROCEDURE

The frequency tolerance of the carrier signal shall be maintained within  $\pm 0.001\%$  of the operating frequency over a temperature variation of –20 degrees to +50 degrees C at normal supply voltage, and for a variation in the primary supply voltage from 85% to 115% of the rated supply voltage at a temperature of 20 degrees C. For battery operated equipment, the equipment tests shall be performed using a new battery.

### 4.3.4 DEVIATION FROM TEST STANDARD

No deviation

### 4.3.5 EUT OPERATING CONDITION

Same as Item 4.2.6



#### 4.3.6 TEST RESULTS

TEST MODE	A			
MODULATION TYPE	GFSK		CHANNEL	0, 38, 77
INPUT POWER (SYSTEM)	120Vac, 60 Hz		ENVIRONMENTAL CONDITIONS	25deg. C, 75%RH, 1001hPa
TESTED BY	Jun Wu			

##### CH 0

TEST CONDITION				Carrier Frequency (MHz)	Frequency Drift (kHz)	Frequency error (%)
T <sub>nom</sub> (°C)	20	V <sub>nom</sub> (V)	120	2401.9865	0	0
T <sub>min</sub> (°C)	-20	V <sub>min</sub> (V)	102	2401.9746	-11.9	-0.0004954
		V <sub>max</sub> (V)	138	2401.9752	-11.3	-0.0004704
T <sub>max</sub> (°C)	50	V <sub>min</sub> (V)	102	2401.9770	-9.5	-0.0003955
		V <sub>max</sub> (V)	138	2401.9768	-9.7	-0.0004038
Limit : ±0.001%						

##### CH 38

TEST CONDITION				Carrier Frequency (MHz)	Frequency Drift (kHz)	Frequency error (%)
T <sub>nom</sub> (°C)	20	V <sub>nom</sub> (V)	120	2439.9862	0	0
T <sub>min</sub> (°C)	-20	V <sub>min</sub> (V)	102	2439.9748	-11.4	-0.0004672
		V <sub>max</sub> (V)	138	2439.9752	-11.0	-0.0004508
T <sub>max</sub> (°C)	50	V <sub>min</sub> (V)	102	2439.9986	12.4	-0.0005082
		V <sub>max</sub> (V)	138	2439.9984	12.2	-0.0005000
Limit : ±0.001%						

##### CH 77

TEST CONDITION				Carrier Frequency (MHz)	Frequency Drift (kHz)	Frequency error (%)
T <sub>nom</sub> (°C)	20	V <sub>nom</sub> (V)	120	2478.9859	0	0
T <sub>min</sub> (°C)	-20	V <sub>min</sub> (V)	102	2478.9844	-1.5	-0.0000605
		V <sub>max</sub> (V)	138	2478.9852	-0.7	-0.0000282
T <sub>max</sub> (°C)	50	V <sub>min</sub> (V)	102	2478.9847	-1.2	-0.0000484
		V <sub>max</sub> (V)	138	2478.9856	-0.3	-0.0000121
Limit : ±0.001%						



## 4.4 BAND EDGES MEASUREMENT

### 4.4.1 LIMITS OF BAND EDGES MEASUREMENT

Below –50dB of the highest emission level of operating band (in 100kHz Resolution Bandwidth).

### 4.4.2 TEST INSTRUMENTS

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
SPECTRUM ANALYZER	FSP 40	100036	Mar. 13, 2008

**NOTE:** The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

### 4.4.3 TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer via a low loss cable. Set both RBW and VBW of spectrum analyzer to 100 kHz and 100 kHz with suitable frequency span including 100 MHz bandwidth from band edge. The band edges was measured and recorded.

The spectrum plots are attached on the following pages.

### 4.4.4 DEVIATION FROM TEST STANDARD



No deviation



### 4.4.5 EUT OPERATING CONDITION

Same as Item 4.2.6

### 4.4.6 TEST RESULTS

The spectrum plots are attached on the following 4 images. D1 line indicates the highest level, and D2 line indicates the 50dB offset below D1. It shows compliance with the requirement in part 15.249(d).







## 5. INFORMATION ON THE TESTING LABORATORIES

We, ADT Corp., were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved by the following approval agencies according to ISO/IEC 17025.

<b>USA</b>	FCC, UL, A2LA
<b>Germany</b>	TUV Rheinland
<b>Japan</b>	VCCI
<b>Norway</b>	NEMKO
<b>Canada</b>	INDUSTRY CANADA , CSA
<b>R.O.C.</b>	CNLA, BSMI, NCC
<b>Netherlands</b>	Telefication
<b>Singapore</b>	PSB, GOST-ASIA(MOU)
<b>Russia</b>	CERTIS(MOU)

Copies of accreditation certificates of our laboratories obtained from approval agencies can be downloaded from our web site:

[www.adt.com.tw/index.5/phtml](http://www.adt.com.tw/index.5/phtml). If you have any comments, please feel free to contact us at the following:

**Linko EMC/RF Lab:**

Tel: 886-2-26052180  
Fax: 886-2-26051924

**Hsin Chu EMC/RF Lab:**

Tel: 886-3-5935343  
Fax: 886-3-5935342

**Hwa Ya EMC/RF/Safety Telecom Lab:**

Tel: 886-3-3183232  
Fax: 886-3-3185050

**Web Site:** [www.adt.com.tw](http://www.adt.com.tw)

The address and road map of all our labs can be found in our web site also



## APPENDIX-A

### MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB

No any modifications are made to the EUT by the lab during the test.