

CERTIFICATION TEST REPORT

Report Number. : 12935947-E7V4

Applicant : Microsoft Corporation
One Microsoft Way
Redmond, WA 98052-6399
USA

Model : 1872

FCC ID : C3K1872

IC ID : 3048A-1872

EUT Description : Portable Computing Device

Test Standard(s) : FCC 47 CFR PART 15 SUBPART E
ISED RSS-247 ISSUE 2
ISED RSS-GEN ISSUE 5

Date Of Issue:
September 16, 2019

Prepared by:
UL Verification Services Inc.
47173 Benicia Street
Fremont, CA 94538 U.S.A.
TEL: (510) 319-4000
FAX: (510) 661-0888



NVLAP Lab code: 200065-0

REPORT REVISION HISTORY

Rev.	Issue Date	Revisions	Revised By
V1	8/29/2019	Initial Issue	--
V2	9/11/2019	Section 5.2: Table Updated Section 5.4 & 8.4: Antenna Gains updated Section 5.6: Statements updated and added Section 8.3: 99% OBW updated Section 8.4: Output Power & PSD updated Section 10: Statement added, Setup photos Removed	Henry Lau
V3	9/13/2019	Section 6: Statement updated Section 8.4.1, 2, 3: Note added	Henry Lau
V4	9/16/2019	Section 8.4.1, 2, 3: Straddle Updated	Henry Lau

TABLE OF CONTENTS

REPORT REVISION HISTORY	2
TABLE OF CONTENTS	3
1. ATTESTATION OF TEST RESULTS	5
2. TEST METHODOLOGY	7
3. FACILITIES AND ACCREDITATION	7
4. CALIBRATION AND UNCERTAINTY	8
4.1. MEASURING INSTRUMENT CALIBRATION	8
4.2. SAMPLE CALCULATION	8
4.3. MEASUREMENT UNCERTAINTY.....	8
5. EQUIPMENT UNDER TEST	9
5.1. EUT DESCRIPTION	9
5.2. MAXIMUM OUTPUT POWER.....	9
5.3. TEST REDUCTIONS CASES	10
5.4. DESCRIPTION OF AVAILABLE ANTENNAS	11
5.5. SOFTWARE AND FIRMWARE.....	11
5.6. WORST-CASE CONFIGURATION AND MODE.....	11
5.7. DESCRIPTION OF TEST SETUP.....	12
6. MEASUREMENT METHOD.....	15
7. TEST AND MEASUREMENT EQUIPMENT	16
8. ANTENNA PORT TEST RESULTS FOR 11ax 5.6 GHz.....	17
8.1. ON TIME AND DUTY CYCLE.....	17
8.2. 26 dB BANDWIDTH.....	26
8.2.1. 802.11ax HE20 MODE IN THE 5.6 GHz BAND	27
8.2.2. 802.11ax HE40 MODE IN THE 5.6 GHz BAND	31
8.2.3. 802.11ax HE80 MODE IN THE 5.6 GHz BAND	36
8.2.4. 802.11ax HE160 MODE IN THE 5.6 GHz BAND	42
8.3. 99% BANDWIDTH.....	49
8.3.1. 802.11ax HE20 MODE IN THE 5.6 GHz BAND	50
8.3.2. 802.11ax HE40 MODE IN THE 5.6 GHz BAND	54
8.3.3. 802.11ax HE80 MODE IN THE 5.6 GHz BAND	59
8.3.4. 802.11ax HE160 MODE IN THE 5.6 GHz BAND	65
8.4. OUTPUT POWER AND PSD.....	72
8.4.1. 802.11ax HE20 MODE IN THE 5.6 GHz BAND (FCC+IC)	75
8.4.2. 802.11ax HE40 MODE IN THE 5.6 GHz BAND (FCC+IC)	88

8.4.3.	802.11ax HE80 MODE IN THE 5.6 GHz BAND (FCC+IC)	104
8.4.4.	802.11ax HE160 MODE IN THE 5.6 GHz BAND (FCC+IC)	121
9.	RADIATED TEST RESULTS FOR 11ax 5.6 GHz.....	136
9.1.	TRANSMITTER ABOVE 1 GHz	138
9.1.1.	TX ABOVE 1 GHz 802.11ax HE20 MODE IN THE 5.6 GHz BAND.....	138
9.1.2.	TX ABOVE 1 GHz 802.11ax HE40 MODE IN THE 5.6 GHz BAND.....	160
9.1.3.	TX ABOVE 1 GHz 802.11ax HE80 MODE IN THE 5.6 GHz BAND.....	180
9.1.4.	TX ABOVE 1 GHz 802.11ax HE160 MODE IN THE 5.6 GHz BAND.....	204
10.	SETUP PHOTOS.....	232

1. ATTESTATION OF TEST RESULTS

COMPANY NAME: Microsoft Corporation
One Microsoft Way
Redmond, WA 98052-6399
USA

EUT DESCRIPTION: Portable Computing Device

MODEL: 1872

SERIAL NUMBER: 006404792757(Conducted)
013880192757(Conducted)
013885392757(Radiated)
014813492757(Radiated)

DATE TESTED: July 16, 2019 – August 20, 2019 and September 9 – 10, 2019


APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
CFR 47 Part 15 Subpart E	Complies
ISED RSS-247 Issue 2	Complies
ISED RSS-GEN Issue 5	Complies

UL Verification Services Inc. tested the above equipment in accordance with the requirements set forth in the above standards. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. It is the manufacturer's responsibility to assure that additional production units of this model are manufactured with identical electrical and mechanical components. All samples tested were in good operating condition throughout the entire test program. Measurement Uncertainties are published for informational purposes only and were not taken into account unless noted otherwise.

This document may not be altered or revised in any way unless done so by UL Verification Services Inc. and all revisions are duly noted in the revisions section. Any alteration of this document not carried out by UL Verification Services Inc. will constitute fraud and shall nullify the document. This report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, any agency of the Federal Government, or any agency of the U.S. government.

Approved & Released For
UL Verification Services Inc. By:



Francisco DeAnda
Operations Leader
Consumer Technology Division
UL Verification Services Inc.

Prepared By:



Glenn Escano
Test Engineer
Consumer Technology Division
UL Verification Services Inc.

Reviewed By:



Henry Lau
Project Engineer
Consumer Technology Division
UL Verification Services Inc.

2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with FCC CFR 47 Part 2, FCC CFR 47 Part 15, FCC 14-30, FCC KDB 662911 D01 v02r01, FCC KDB 905462 D02 v02/D03 v01r02/D06 v02, FCC KDB 789033 D02 v02r01, ANSI C63.10-2013, FCC 06-96, RSS-GEN Issue 5, and RSS-247 Issue 2.

The scope of this report covers the 802.11ax modes in the 5.6 GHz band of Model 1872.

3. FACILITIES AND ACCREDITATION

The test sites and measurement facilities used to collect data are located at 47173 and 47266 Benicia Street, and 47658 Kato Road, Fremont, California, USA. Line conducted emissions are measured only at the 47173 address. The following table identifies which facilities were utilized for radiated emission measurements documented in this report. Specific facilities are also identified in the test results sections.

47173 Benicia Street	47266 Benicia Street	47658 Kato Rd
<input type="checkbox"/> Chamber A	<input type="checkbox"/> Chamber D	<input checked="" type="checkbox"/> Chamber I
<input type="checkbox"/> Chamber B	<input type="checkbox"/> Chamber E	<input type="checkbox"/> Chamber J
<input type="checkbox"/> Chamber C	<input type="checkbox"/> Chamber F	<input checked="" type="checkbox"/> Chamber K
	<input type="checkbox"/> Chamber G	<input checked="" type="checkbox"/> Chamber L
	<input type="checkbox"/> Chamber H	<input type="checkbox"/> Chamber M

The above test sites and facilities are covered under FCC Test Firm Registration # 208313. Chambers above are covered under Industry Canada company address and respective code 2324A.

UL Verification Services Inc. is accredited by NVLAP, Laboratory Code 200065-0

4. CALIBRATION AND UNCERTAINTY

4.1. MEASURING INSTRUMENT CALIBRATION

The measuring equipment utilized to perform the tests documented in this report has been calibrated in accordance with the manufacturer's recommendations, and is traceable to recognized national standards.

4.2. SAMPLE CALCULATION

RADIATED EMISSIONS

Where relevant, the following sample calculation is provided:

Field Strength (dBuV/m) = Measured Voltage (dBuV) + Antenna Factor (dB/m) + Cable Loss (dB) – Preamp Gain (dB)
 $36.5 \text{ dBuV} + 18.7 \text{ dB/m} + 0.6 \text{ dB} - 26.9 \text{ dB} = 28.9 \text{ dBuV/m}$

MAINS CONDUCTED EMISSIONS

Where relevant, the following sample calculation is provided:

Final Voltage (dBuV) = Measured Voltage (dBuV) + Cable Loss (dB) + Limiter Factor (dB) + LISN Insertion Loss.
 $36.5 \text{ dBuV} + 0 \text{ dB} + 10.1 \text{ dB} + 0 \text{ dB} = 46.6 \text{ dBuV}$

4.3. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

PARAMETER	UNCERTAINTY
Worst Case Conducted Disturbance, 9KHz to 0.15 MHz	3.84 dB
Worst Case Conducted Disturbance, 0.15 to 30 MHz	3.65 dB
Worst Case Radiated Disturbance, 9KHz to 30 MHz	2.52 dB
Worst Case Radiated Disturbance, 30 to 1000 MHz	4.88 dB
Worst Case Radiated Disturbance, 1000 to 18000 MHz	4.24 dB
Worst Case Radiated Disturbance, 18000 to 26000 MHz	4.37 dB
Worst Case Radiated Disturbance, 26000 to 40000 MHz	5.17 dB

Uncertainty figures are valid to a confidence level of 95%.

5. EQUIPMENT UNDER TEST

5.1. EUT DESCRIPTION

The EUT is a Portable Computing Device.

5.2. MAXIMUM OUTPUT POWER

The transmitter has a maximum conducted output power as follows:

5.6GHz BAND 802.11 ax MODE

Frequency Range (MHz)	Mode	Output Power (dBm)	Output Power (mW)
5.6 GHz band, 2TX			
5500-5720	802.11ax HE20 SU	21.47	140.28
5500-5720	802.11ax HE20 OFDMA, 242-Tones	21.51	141.58
5510-5710	802.11ax HE40 SU	21.33	135.83
5510-5710	802.11ax HE40 OFDMA, 484-Tones	21.62	145.21
5530-5690	802.11ax HE80 SU	21.33	135.83
5530-5690	802.11ax HE80 OFDMA, 996-Tones	21.43	139.00
5570	802.11ax HE160 SU	11.41	13.84
5570	802.11ax HE160 OFDMA, 106-Tones	19.95	98.86

5.3. TEST REDUCTIONS CASES

26dB Bandwidth:

- All tones were tested for each bandwidth.
- For HE20, HE40, & HE80, each Low, Mid, High RU allocation is tested to the respective Low, Mid and High channel.
- For HE160, Low, Mid & High RU allocations were tested.

99% Bandwidth:

- All tones were tested for each bandwidth.
- For HE20, HE40, & HE80, each Low, Mid, High RU allocation is tested to the respective Low, Mid and High channel.
- For HE160, Low, Mid & High RU allocation were tested.

Output Power and Power Spectral Density

- All tones were tested for each bandwidth.
- For HE20, HE40, & HE80, every RU allocation per channel is the same power thus each Low, Mid, High RU allocation is tested to the respective Low, Mid and High channel.
- For HE160, Low, Mid & High RU allocation were tested.

Radiated Band Edge:

- All tones and bandwidths were tested.
- The RU allocations closest to the band edge was tested to cover all other RU's.

Radiated Spurious Emissions:

- 26T and 242T at HE20 was investigated. It was determined that 26T at the highest power setting to be worst case thus 26T will be representative of all RU's at all tones at HE20, HE40, HE80, and HE160.

5.4. DESCRIPTION OF AVAILABLE ANTENNAS

The radio utilizes two dual band PIFA antennas, with a maximum gain of:

Frequency Band (GHz)	Chain 0	Chain 1
	Antenna Gain (dBi)	Antenna Gain (dBi)
5180-5240	6	3
5260-5320	7.8	3.5
5500-5700	8	4
5745-5825	8.3	4.6

5.5. SOFTWARE AND FIRMWARE

The operating system installed on the EUT is MTEOS 1.652.0.

The Wifi Driver installed on the EUT is version 99.0.43.8.

The test utility software used during testing was version 11.1916.0-09531

5.6. WORST-CASE CONFIGURATION AND MODE

WORST-CASE CONFIGURATION AND MODE FOR FINAL TEST

Please refer to UL Report number: 12935947-E4 for worst case Radiated emissions below 30 MHz, 1GHz, above 18GHz, power line conducted emissions data and simultaneous TX data.

Band edge and radiated emissions between 1GHz and 18GHz were performed with the EUT set to transmit at the highest power on low, middle and high channels.

For all modes, tests were performed with the EUT set at the 2Tx MIMO mode with power setting equal to SISO modes as the worst case scenario thus MIMO is representative of SISO.

The EUT has one intended orientations, X; therefore, all final radiated testing was performed with the EUT in X orientation.

Worst-case data rates as provided by the client were:

802.11ax HE20mode: MCS0
802.11ax HE40mode: MCS0
802.11ax HE80mode: MCS0
802.11ax HE160mode: MCS0

EUT does not employ CDD for HT, VHT and HE rates. CDD is supported for legacy modes only.

5.7. DESCRIPTION OF TEST SETUP

SUPPORT EQUIPMENT

Support Equipment List				
Description	Manufacturer	Model	Serial Number	FCC ID
AC DC Adapter	Microsoft	1706	0C130J02T8396	DoC
USB Mouse	Microsoft	1113	X821908-002	DoC
USB Type C to Audio Jack	SONY	A1-0231	N/A	DoC
Earphone	SONY	AG1100	N/A	DoC
Earphone	SONY	AG1100	N/A	DoC

I/O CABLES (CONDUCTED TEST)


I/O Cable List						
Cable No	Port	# of identical ports	Connector Type	Cable Type	Cable Length (m)	Remarks
1	AC	1	AC	Un-Shielded	0.2	to AC/DC Adaptor
2	DC	1	DC	Shielded	1	to Laptop, to EUT
3	Antenna	1	SMA	Un-Shielded	0.2	to Analyzer

I/O CABLES (RADIATED AND CONDUCTED EMISSIONS)

I/O Cable List						
Cable No	Port	# of identical ports	Connector Type	Cable Type	Cable Length (m)	Remarks
1	AC	1	Type C	Un-shielded	0.2	to AC/DC Adapter
2	DC	1	DC	Shielded	1	to EUT
3	USB	1	Type A	Shielded	1.5	EUT TO Mouse
4	USB	1	Type C	Shielded	0.1	EUT to earphone AUX
5	earphone	1	3.5mm	Un-shielded	1	EUT to earphone

TEST SETUP

CONDUCTED TEST SETUP DIAGRAM



TEST SETUP

For conducted tests, the test software exercises the radio.

6. MEASUREMENT METHOD

On Time and Duty Cycle: KDB 789033 D02 v02r01, Section B.

6 dB Emission BW: KDB 789033 D02 v02r01, Section C.2

26 dB Emission BW: KDB 789033 D02 v02r01, Section C.1

99% Occupied BW: KDB 789033 D02 v02r01, Section D.

Conducted Output Power: KDB 789033 D02 v02r01, Section E.3.b (Method PM-G)

Power Spectral Density: KDB 789033 D02 v02r01, Section F

Unwanted emissions in restricted bands: KDB 789033 D02 v02r01, Sections G.3, G.4, G.5, and G.6.

Unwanted emissions in non-restricted bands: KDB 789033 D02 v02r01, Sections G.3, G.4, and G.5.

7. TEST AND MEASUREMENT EQUIPMENT

The following test and measurement equipment was utilized for the tests documented in this report:

TEST EQUIPMENT LIST					
Description	Manufacturer	Model	ID Num	Cal Due	Last Cal
Antenna, Passive Loop 30Hz to 1MHz	ELETRO METRICS	EM-6871	PRE0179465	05/31/2020	05/31/2019
Antenna, Passive Loop 100kHz to 30MHz	ELETRO METRICS	EM-6872	PRE0179467	05/31/2020	05/31/2019
Amplifier, 9KHz to 1GHz, 32dB	Sonoma Instrument	310	PRE0186650	12/13/2019	12/13/2018
Hybrid Antenna, 30MHz to 3GHz	Sunol Sciences Corp	JB3	PRE0184971	11/13/2019	11/13/2018
Amplifier, 9kHz to 1GHz, 32 dB	Sonoma Instrument	310	PRE0180175	06/29/2020	06/29/2019
Antenna, Horn 1-18GHz	ETS-Lindgren	3117	T120	07/10/2020	07/10/2019
Amplifier, 1 to18GHz	MITEQ	AFS42-00101800-25-S-42	T1568	06/18/2020	06/18/2019
Antenna, Horn 1-18GHz	ETS-Lindgren	3117	T862	06/05/2020	06/05/2019
Amplifier, 1 to18GHz	MITEQ	AFS42-00101800-25-S-42	PRE018078	08/01/2019	08/01/2018
Antenna, Horn 18 to 26.5GHz	ARA	MWH-1826/B	PRE0182188	08/29/2019	08/29/2018
Rf Amplifier, 18-26.5GHz, 60dB gain	Ampical	AMP18G26.5-60	PRE0181238	05/01/2020	05/01/2019
Antenna, Horn 26 to 40GHz	ARA	MWH-2640	T90	09/11/2019	09/11/2018
Pre-Amp, 26-40GHz	Ampical	AMP26G40-60	PRE0181238	05/01/2020	05/01/2019
Power Meter, P-series single channel	Agilent (Keysight) Technologies	N1911A	T1265	01/29/2020	01/29/2019
Power Sensor, P-series, 50MHz to 18GHz, Wideband	Agilent (Keysight) Technologies	N1921A	T1227	02/05/2020	02/05/2019
EMI Test Receiver	Rohde & Schwarz	ESW44	PRE0179367	05/16/2020	05/16/2019
EMI Test Receiver	Rohde & Schwarz	ESW44	PRE0179372	02/16/2020	02/16/2019
EMI Test Receiver	Rohde & Schwarz	ESW44	PRE0179367	05/16/2020	05/16/2019
Spectrum Analyzer, PXA, 3Hz to 44GHz	Agilent (Keysight) Technologies	N9030A	T917	01/24/2020	01/24/2019
Spectrum Analyzer, PXA, 3Hz to 44GHz	Agilent (Keysight) Technologies	N9030A	T908	01/23/2020	01/23/2019
AC Line Conducted					
EMI Receiver	Rohde & Schwarz	ESR	T1436	02/14/2020	02/14/2019
LISN for Conducted Emissions CISPR-16	FCC INC.	FCC LISN 50/250	T1310	01/24/2020	01/24/2019
Test Software List					
Radiated Software	UL	UL EMC	Ver 9.5, June 22, 2018 & Jan 11, 2019		
Antenna Port Software	UL	UL RF	Ver 9.7, May 7, 2019		
AC Line Conducted Software	UL	UL EMC	Ver 9.5, May 26, 2015		

NOTES:

- Equipment listed above that calibrated during the testing period was set for test after the calibration.
- Equipment listed above that has a calibration due date during the testing period, the testing is completed before equipment expiration date.

8. ANTENNA PORT TEST RESULTS FOR 11ax 5.6 GHz

8.1. ON TIME AND DUTY CYCLE

LIMITS

None; for reporting purposes only.

PROCEDURE

KDB 558074 D01 Zero-Span Spectrum Analyzer Method.

ON TIME AND DUTY CYCLE RESULTS

802.11ax HE20

Mode	ON Time B (msec)	Period (msec)	Duty Cycle x (linear)	Duty Cycle (%)	Duty Cycle Correction Factor (dB)	1/B Minimum VBW (kHz)
802.11ax HE20 OFDMA, SU	3.963	4.008	0.989	98.88%	0.00	0.010
802.11ax HE20 OFDMA, RU size 242T	3.973	4.018	0.989	98.88%	0.00	0.010
802.11ax HE20 OFDMA, RU size 106T	3.983	4.028	0.989	98.88%	0.00	0.010
802.11ax HE20 OFDMA, RU size 52T	3.980	4.030	0.988	98.76%	0.00	0.010
802.11ax HE20 OFDMA, RU size 26T	3.979	4.029	0.988	98.76%	0.00	0.010

802.11ax HE40

Mode	ON Time B (msec)	Period (msec)	Duty Cycle x (linear)	Duty Cycle (%)	Duty Cycle Correction Factor (dB)	1/B Minimum VBW (kHz)
802.11ax HE40 OFDMA, SU	3.966	4.020	0.987	98.66%	0.00	0.010
802.11ax HE40 OFDMA, RU size 484T	3.976	4.030	0.987	98.66%	0.00	0.010
802.11ax HE40 OFDMA, RU size 242T	3.976	4.030	0.987	98.66%	0.00	0.010
802.11ax HE40 OFDMA, RU size 106T	3.976	4.020	0.989	98.91%	0.00	0.010
802.11ax HE40 OFDMA, RU size 52T	3.976	4.030	0.987	98.66%	0.00	0.010
802.11ax HE40 OFDMA, RU size 26T	3.976	4.020	0.989	98.91%	0.00	0.010


802.11ax HE80

Mode	ON Time B (msec)	Period (msec)	Duty Cycle x (linear)	Duty Cycle (%)	Duty Cycle Correction Factor (dB)	1/B Minimum VBW (kHz)
802.11ax HE80 OFDMA, SU	3.976	4.030	0.987	98.66%	0.00	0.010
802.11ax HE80 OFDMA, RU size 996T	3.976	4.030	0.987	98.66%	0.00	0.010
802.11ax HE80 OFDMA, RU size 484T	3.976	4.030	0.987	98.66%	0.00	0.010
802.11ax HE80 OFDMA, RU size 242T	3.966	4.020	0.987	98.66%	0.00	0.010
802.11ax HE80 OFDMA, RU size 106T	3.976	4.030	0.987	98.66%	0.00	0.010
802.11ax HE80 OFDMA, RU size 52T	3.966	4.020	0.987	98.66%	0.00	0.010
802.11ax HE80 OFDMA, RU size 26T	3.966	4.020	0.987	98.66%	0.00	0.010

802.11ax HE160

Mode	ON Time B (msec)	Period (msec)	Duty Cycle x (linear)	Duty Cycle (%)	Duty Cycle Correction Factor (dB)	1/B Minimum VBW (kHz)
802.11ax HE160 OFDMA, SU	2.279	2.324	0.981	98.06%	0.00	0.010
802.11ax HE160 OFDMA, RU size 2x996T	3.985	4.029	0.989	98.91%	0.00	0.010
802.11ax HE160 OFDMA, RU size 996T	3.975	4.020	0.989	98.88%	0.00	0.010
802.11ax HE160 OFDMA, RU size 484T	3.985	4.029	0.989	98.91%	0.00	0.010
802.11ax HE160 OFDMA, RU size 242T	3.975	4.029	0.987	98.66%	0.00	0.010
802.11ax HE160 OFDMA, RU size 106T	3.975	4.020	0.989	98.88%	0.00	0.010
802.11ax HE160 OFDMA, RU size 52T	3.975	4.020	0.989	98.88%	0.00	0.010
802.11ax HE160 OFDMA, RU size 26T	3.975	4.029	0.987	98.66%	0.00	0.010


DUTY CYCLE PLOTS














8.2. 26 dB BANDWIDTH

LIMITS

None; for reporting purposes only.



RESULTS

8.2.1. 802.11ax HE20 MODE IN THE 5.6 GHz BAND



2TX Chain 0 + Chain 1 OFDMA MODE

RU Size (Tones)	RU Index	Channel	Frequency (MHz)	26 dB Bandwidth Chain 0 (MHz)	26 dB Bandwidth Chain 1 (MHz)
242T	61	Low	5500	25.45	25.50
		Mid	5580	25.10	25.30
		High	5700	25.00	25.25
		144	5720	25.30	24.75
106T	53	Low	5500	22.35	22.20
		Mid	5580	20.65	22.15
	54	High	5700	23.25	23.75
		144	5720	23.05	22.90
52T	37	Low	5500	21.10	21.80
	38	Mid	5580	19.50	19.75
	40	High	5700	21.10	20.15
		144	5720	20.70	20.45
26T	0	Low	5500	20.50	20.40
	4	Mid	5580	18.40	18.25
	8	High	5700	20.45	19.95
		144	5720	20.55	20.35


242-Tones, RU Index 61




106-Tones, RU Index 53




106-Tones, RU Index 54




52-Tones, RU Index 37




52-Tones, RU Index 38




52-Tones, RU Index 40




26-Tones, RU Index 0



26-Tones, RU Index 4



26-Tones, RU Index 8





8.2.2. 802.11ax HE40 MODE IN THE 5.6 GHz BAND



2TX Chain 0 + Chain 1 OFDMA MODE

RU Size (Tones)	RU Index	Channel	Frequency (MHz)	26 dB Bandwidth Chain 0 (MHz)	26 dB Bandwidth Chain 1 (MHz)
484T	65	Low	5510	45.30	44.80
		Mid	5550	45.10	44.10
		High	5670	44.50	44.60
		142	5710	44.60	44.50
242T	61	Low	5510	23.00	23.00
		Mid	5550	23.70	23.20
	62	High	5670	22.30	22.90
		142	5710	22.60	22.50
106T	53	Low	5510	22.20	22.70
	54	Mid	5550	22.20	21.10
	56	High	5670	22.10	20.60
		142	5710	22.10	20.20
52T	37	Low	5510	20.50	20.00
	40	Mid	5550	22.10	21.80
	44	High	5670	21.50	20.50
		142	5710	21.40	21.10
26T	0	Low	5510	20.20	19.80
	8	Mid	5550	21.20	20.70
	17	High	5670	21.10	21.10
		142	5710	20.70	19.80



484-Tones, RU Index 65




242-Tones, RU Index 61




242-Tones, RU Index 62




106-Tones, RU Index 53




106-Tones, RU Index 54




106-Tones, RU Index 56




52-Tones, RU Index 37




52-Tones, RU Index 40




52-Tones, RU Index 44




26-Tones, RU Index 0



26-Tones, RU Index 8



26-Tones, RU Index 17




8.2.3. 802.11ax HE80 MODE IN THE 5.6 GHz BAND


2TX Chain 0 + Chain 1 OFDMA MODE

RU Size (Tones)	RU Index	Channel	Frequency (MHz)	26 dB Bandwidth Chain 0 (MHz)	26 dB Bandwidth Chain 1 (MHz)
996T	67	Low	5530	85.20	84.80
		High	5610	84.20	85.00
		138	5690	84.00	83.80
484T	65	Low	5530	44.80	44.00
	66	High	5610	44.40	44.60
		138	5690	44.60	45.40
242T	61	Low	5530	25.00	25.00
	62	Low	5530	46.80	44.20
	64	High	5610	26.00	25.60
		138	5690	25.20	24.40
106T	53	Low	5530	21.80	23.00
	56	Low	5530	25.40	26.00
	60	High	5610	23.80	23.60
		138	5690	26.00	26.00
52T	37	Low	5530	22.60	22.40
	44	Low	5530	21.20	21.20
	52	High	5610	21.40	21.40
		138	5690	21.40	21.40
26T	0	Low	5530	21.00	21.20
	18	Low	5530	39.00	38.80
	36	High	5610	21.20	20.80
		138	5690	21.00	21.20


996-Tones, RU Index 67




484-Tones, RU Index 65




484-Tones, RU Index 66




242-Tones, RU Index 61




242-Tones, RU Index 62




242-Tones, RU Index 64




106-Tones, RU Index 53




106-Tones, RU Index 56




106-Tones, RU Index 60




52-Tones, RU Index 37




52-Tones, RU Index 44




52-Tones, RU Index 52




26-Tones, RU Index 0



26-Tones, RU Index 18



26-Tones, RU Index 36



8.2.4. 802.11ax HE160 MODE IN THE 5.6 GHz BAND


2TX Chain 0 + Chain 1 OFDMA MODE

RU Size (Tones)	RU Index	Channel	Frequency (MHz)	26 dB Bandwidth Chain 0 (MHz)	26 dB Bandwidth Chain 1 (MHz)
2*996T	68	Mid	5570	167.2	166.80
996T	67	Mid	5570	85.20	85.20
	S67	Mid	5570	85.60	84.80
484T	65	Mid	5570	46.40	46.80
	66	Mid	5570	46.00	45.60
	S66	Mid	5570	46.80	46.80
242T	61	Mid	5570	23.60	24.00
	64	Mid	5570	23.60	23.20
	S64	Mid	5570	23.20	23.20
106T	53	Mid	5570	23.20	23.60
	60	Mid	5570	22.00	22.40
	S53	Mid	5570	22.00	22.40
52T	37	Mid	5570	22.40	22.00
	52	Mid	5570	21.60	21.60
	S52	Mid	5570	21.60	22.40
26T	0	Mid	5570	21.20	21.20
	36	Mid	5570	21.60	21.20
	S36	Mid	5570	21.60	22.00


2*996-Tones, RU Index 68




996-Tones, RU Index 67




996-Tones, RU Index S67




484-Tones, RU Index 65




484-Tones, RU Index 66



484-Tones, RU Index S66



242-Tones, RU Index 61




242-Tones, RU Index 64




242-Tones, RU Index S64



106-Tones, RU Index 53




106-Tones, RU Index 60




106-Tones, RU Index S60




52-Tones, RU Index 37




52-Tones, RU Index 52




52-Tones, RU Index S52




26-Tones, RU Index 0



26-Tones, RU Index 36



26-Tones, RU Index S36



8.3. 99% BANDWIDTH

LIMITS

None; for reporting purposes only.

RESULTS

8.3.1. 802.11ax HE20 MODE IN THE 5.6 GHz BAND

2TX Chain 0 + Chain 1 OFDMA MODE

RU Size (Tones)	RU Index	Channel	Frequency (MHz)	99% Bandwidth Chain 0 (MHz)	99% Bandwidth Chain 1 (MHz)
242T	61	Low	5500	18.9321	19.0053
		Mid	5580	19.0935	19.0412
		High	5700	18.9954	19.0942
		144	5720	18.9722	18.9645
106T	53	Low	5500	18.106	18.132
		Mid	5580	17.502	18.045
	54	High	5700	18.3845	18.3965
		144	5720	18.2595	18.1732
52T	37	Low	5500	17.989	18.450
	38	Mid	5580	16.8914	16.9143
	40	High	5700	18.0430	18.1551
		144	5720	18.2534	18.1883
26T	0	Low	5500	18.5769	18.5848
	4	Mid	5580	16.8645	16.8376
	8	High	5700	18.5396	18.3845
		144	5720	18.4965	18.4001