

1 APPENDIX A: SAR TEST RESULTS FOR P_{Limit} CALCULATIONS

1.1 Head Data

Table 1-1
DSI = 2 P_{Limit} Calculations – NR Band n41 Head SAR

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	DUT Configuration	Conducted Power [dBm]	Antenna Config	MPR [dB]	Side	Test Position	Waveform	Modulation	RB Size	RB Offset	Serial Number	Duty Cycle	SAR (1g)	Plimit	Overall Plimit	
MHz	Ch.															(W/kg)			
2592.99	518598	Mid	NR Band n41	100	Flip	19.56	MM004	0	Right	Cheek	DFT-S-OFDM	QPSK	1	1	LG211	1:1	0.025	35.58	35.58
2592.99	518598	Mid	NR Band n41	100	Flip	19.39	MM004	0	Right	Cheek	DFT-S-OFDM	QPSK	135	69	LG211	1:1	0.022	35.97	
2592.99	518598	Mid	NR Band n41	100	Flip	18.80	MM004	1.5	Right	Cheek	CP-OFDM	QPSK	1	1	LG211	1:1	0.017	36.50	
2592.99	518598	Mid	NR Band n41	100	Flip	19.56	MM004	0	Right	Tilt	DFT-S-OFDM	QPSK	1	1	LG211	1:1	0.008	40.53	
2592.99	518598	Mid	NR Band n41	100	Flip	19.39	MM004	0	Right	Tilt	DFT-S-OFDM	QPSK	135	69	LG211	1:1	0.007	40.94	
2592.99	518598	Mid	NR Band n41	100	Flip	19.56	MM004	0	Left	Cheek	DFT-S-OFDM	QPSK	1	1	LG211	1:1	0.008	40.53	
2592.99	518598	Mid	NR Band n41	100	Flip	19.39	MM004	0	Left	Cheek	DFT-S-OFDM	QPSK	135	69	LG211	1:1	0.011	38.98	
2592.99	518598	Mid	NR Band n41	100	Flip	19.56	MM004	0	Left	Tilt	DFT-S-OFDM	QPSK	1	1	LG211	1:1	0.008	40.53	
2592.99	518598	Mid	NR Band n41	100	Flip	19.39	MM004	0	Left	Tilt	DFT-S-OFDM	QPSK	135	69	LG211	1:1	0.004	43.37	18.20
2592.99	518598	Mid	NR Band n41	100	Flip	9.68	MM003	0	Right	Cheek	DFT-S-OFDM	QPSK	1	137	X2211	1:1	0.132	18.47	
2592.99	518598	Mid	NR Band n41	100	Flip	9.63	MM003	0	Right	Cheek	DFT-S-OFDM	QPSK	135	0	X2211	1:1	0.139	18.20	
2592.99	518598	Mid	NR Band n41	100	Flip	9.41	MM003	0	Right	Cheek	CP-OFDM	QPSK	1	1	X2211	1:1	0.130	18.27	
2592.99	518598	Mid	NR Band n41	100	Flip	9.68	MM003	0	Right	Tilt	DFT-S-OFDM	QPSK	1	137	X2211	1:1	0.125	18.71	
2592.99	518598	Mid	NR Band n41	100	Flip	9.63	MM003	0	Right	Tilt	DFT-S-OFDM	QPSK	135	0	X2211	1:1	0.128	18.56	
2592.99	518598	Mid	NR Band n41	100	Flip	9.68	MM003	0	Left	Cheek	DFT-S-OFDM	QPSK	1	137	X2211	1:1	0.032	24.63	
2592.99	518598	Mid	NR Band n41	100	Flip	9.63	MM003	0	Left	Cheek	DFT-S-OFDM	QPSK	135	0	X2211	1:1	0.025	25.65	
2592.99	518598	Mid	NR Band n41	100	Flip	9.68	MM003	0	Left	Tilt	DFT-S-OFDM	QPSK	1	137	X2211	1:1	0.037	24.00	18.20
2592.99	518598	Mid	NR Band n41	100	Flip	9.63	MM003	0	Left	Tilt	DFT-S-OFDM	QPSK	135	0	X2211	1:1	0.028	25.16	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population									Head 1.6 W/kg (mW/g) averaged over 1 gram										

For some bands/modes, a lower P_{Limit} was selected as a more conservative evaluation.

1.2 Body-Worn Data

Table 1-2
DSI = 4 P_{Limit} Calculations – NR n41 Flip Configuration Body-Worn SAR

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	DUT Configuration	Conducted Power [dBm]	Antenna Config	MPR [dB]	Serial Number	Waveform	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g)	Plimit	Overall Plimit	
MHz	Ch.															(W/kg)			
2592.99	518598	Mid	NR Band n41	100	Flip	15.35	MIMO04	0	LG211	DFT-S-OFDM	QPSK	135	0	10 mm	back	1:1	0.064	27.29	22.05
2592.99	518598	Mid	NR Band n41	100	Flip	15.41	MIMO04	0	LG211	DFT-S-OFDM	QPSK	1	1	10 mm	front	1:1	0.205	22.29	
2592.99	518598	Mid	NR Band n41	100	Flip	15.35	MIMO04	0	LG211	DFT-S-OFDM	QPSK	135	0	10 mm	front	1:1	0.214	22.05	
2592.99	518598	Mid	NR Band n41	100	Flip	15.47	MIMO04	0	LG211	CP-OFDM	QPSK	1	1	10 mm	front	1:1	0.172	23.11	
2592.99	518598	Mid	NR Band n41	100	Flip	15.80	MIMO03	0	X2211	DFT-S-OFDM	QPSK	1	137	10 mm	back	1:1	0.016	33.76	26.52
2592.99	518598	Mid	NR Band n41	100	Flip	15.77	MIMO03	0	X2211	DFT-S-OFDM	QPSK	135	138	10 mm	back	1:1	0.017	33.47	
2592.99	518598	Mid	NR Band n41	100	Flip	15.80	MIMO03	0	X2211	DFT-S-OFDM	QPSK	1	137	10 mm	front	1:1	0.076	26.99	
2592.99	518598	Mid	NR Band n41	100	Flip	15.77	MIMO03	0	X2211	DFT-S-OFDM	QPSK	135	138	10 mm	front	1:1	0.068	27.44	
2592.99	518598	Mid	NR Band n41	100	Flip	15.50	MIMO03	0	X2211	CP-OFDM	QPSK	1	1	10 mm	front	1:1	0.079	26.52	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population									Body 1.6 W/kg (mW/g) averaged over 1 gram										

For some bands/modes, a lower P_{Limit} was selected as a more conservative evaluation.

FCC ID: C3K1995		PART 0 SAR CHAR REPORT		Approved by: Quality Manager
Test Dates: 09/08/2021– 10/04/2021	DUT Type: Portable Handset	APPENDIX A: Page 1 of 4		

© 2020 PCTEST

© 2020 PCTEST. All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact INFO@PCTEST.COM.

REV 1.0
06/01/2019

Table 1-3
DSI = 4 P_{Limit} Calculations – NR n41 Closed Configuration Body-Worn SAR

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	DUT Configuration	Conducted Power [dBm]	Antenna Config	MPR [dB]	Serial Number	Waveform	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g)	Plimit	Overall Plimit	
MHz	Ch.															(W/kg)			
2592.99	518598	Mid	NR Band n41	100	Closed	15.41	MIMO04	0	LG211	DFT-S-OFDM	QPSK	1	1	10 mm	back	1:1	0.062	27.49	25.81
2592.99	518598	Mid	NR Band n41	100	Closed	15.35	MIMO04	0	LG211	DFT-S-OFDM	QPSK	135	0	10 mm	back	1:1	0.070	26.90	
2592.99	518598	Mid	NR Band n41	100	Closed	15.41	MIMO04	0	LG211	DFT-S-OFDM	QPSK	1	1	10 mm	front	1:1	0.083	26.22	
2592.99	518598	Mid	NR Band n41	100	Closed	15.35	MIMO04	0	LG211	DFT-S-OFDM	QPSK	135	0	10 mm	front	1:1	0.090	25.81	
2592.99	518598	Mid	NR Band n41	100	Closed	15.47	MIMO04	0	LG211	CP-OFDM	QPSK	1	1	10 mm	front	1:1	0.077	26.61	
2592.99	518598	Mid	NR Band n41	100	Closed	15.80	MIMO03	0	X2211	DFT-S-OFDM	QPSK	1	137	10 mm	back	1:1	0.022	32.38	31.30
2592.99	518598	Mid	NR Band n41	100	Closed	15.77	MIMO03	0	X2211	DFT-S-OFDM	QPSK	135	138	10 mm	back	1:1	0.028	31.30	
2592.99	518598	Mid	NR Band n41	100	Closed	15.50	MIMO03	0	X2211	CP-OFDM	QPSK	1	1	10 mm	back	1:1	0.016	33.46	
2592.99	518598	Mid	NR Band n41	100	Closed	15.80	MIMO03	0	X2211	DFT-S-OFDM	QPSK	1	137	10 mm	front	1:1	0.025	31.82	
2592.99	518598	Mid	NR Band n41	100	Closed	15.77	MIMO03	0	X2211	DFT-S-OFDM	QPSK	135	138	10 mm	front	1:1	0.024	31.97	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population									Body 1.6 W/kg (mW/g) averaged over 1 gram										

For some bands/modes, a lower P_{Limit} was selected as a more conservative evaluation.

1.3 Hotspot Data

Table 1-4
DSI = 4 P_{Limit} Calculations – NR Band n41 Flip Configuration Hotspot SAR

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	DUT Configuration	Conducted Power [dBm]	Antenna Config	MPR [dB]	Serial Number	Waveform	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g)	Plimit	Overall Plimit	
MHz	Ch.															(W/kg)			
2592.99	518598	Mid	NR Band n41	100	Flip	15.41	MIMO04	0	LG211	DFT-S-OFDM	QPSK	1	1	10 mm	back	1:1	0.068	27.08	22.05
2592.99	518598	Mid	NR Band n41	100	Flip	15.35	MIMO04	0	LG211	DFT-S-OFDM	QPSK	135	0	10 mm	back	1:1	0.064	27.29	
2592.99	518598	Mid	NR Band n41	100	Flip	15.41	MIMO04	0	LG211	DFT-S-OFDM	QPSK	1	1	10 mm	front	1:1	0.205	22.29	
2592.99	518598	Mid	NR Band n41	100	Flip	15.35	MIMO04	0	LG211	DFT-S-OFDM	QPSK	135	0	10 mm	front	1:1	0.214	22.05	
2592.99	518598	Mid	NR Band n41	100	Flip	15.47	MIMO04	0	LG211	CP-OFDM	QPSK	1	1	10 mm	front	1:1	0.172	23.11	
2592.99	518598	Mid	NR Band n41	100	Flip	15.41	MIMO04	0	LG211	DFT-S-OFDM	QPSK	1	1	10 mm	bottom	1:1	0.198	22.44	
2592.99	518598	Mid	NR Band n41	100	Flip	15.35	MIMO04	0	LG211	DFT-S-OFDM	QPSK	135	0	10 mm	bottom	1:1	0.149	23.62	
2592.99	518598	Mid	NR Band n41	100	Flip	15.80	MIMO03	0	X2211	DFT-S-OFDM	QPSK	1	137	10 mm	back	1:1	0.016	33.76	
2592.99	518598	Mid	NR Band n41	100	Flip	15.77	MIMO03	0	X2211	DFT-S-OFDM	QPSK	135	138	10 mm	back	1:1	0.017	33.47	
2592.99	518598	Mid	NR Band n41	100	Flip	15.80	MIMO03	0	X2211	DFT-S-OFDM	QPSK	1	137	10 mm	front	1:1	0.076	26.99	
2592.99	518598	Mid	NR Band n41	100	Flip	15.77	MIMO03	0	X2211	DFT-S-OFDM	QPSK	135	138	10 mm	front	1:1	0.068	27.44	
2592.99	518598	Mid	NR Band n41	100	Flip	15.50	MIMO03	0	X2211	CP-OFDM	QPSK	1	1	10 mm	front	1:1	0.079	26.52	
2592.99	518598	Mid	NR Band n41	100	Flip	15.80	MIMO03	0	X2211	DFT-S-OFDM	QPSK	1	137	10 mm	top	1:1	0.065	27.67	
2592.99	518598	Mid	NR Band n41	100	Flip	15.77	MIMO03	0	X2211	DFT-S-OFDM	QPSK	135	138	10 mm	top	1:1	0.069	27.38	
2592.99	518598	Mid	NR Band n41	100	Flip	15.80	MIMO03	0	X2211	DFT-S-OFDM	QPSK	1	137	10 mm	left	1:1	0.011	35.39	
2592.99	518598	Mid	NR Band n41	100	Flip	15.77	MIMO03	0	X2211	DFT-S-OFDM	QPSK	135	138	10 mm	left	1:1	0.009	36.23	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Body 1.6 W/kg (mW/g) averaged over 1 gram											

For some bands/modes, a lower P_{Limit} was selected as a more conservative evaluation.

FCC ID: C3K1995	 Proud to be part of 	PART 0 SAR CHAR REPORT	 Microsoft	Approved by: Quality Manager
Test Dates: 09/08/2021– 10/04/2021	DUT Type: Portable Handset	APPENDIX A: Page 2 of 4		

Table 1-5
DSI = 4 P_{Limit} Calculations – NR Band n41 Closed Configuration Hotspot SAR

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	DUT Configuration	Conducted Power [dBm]	Antenna Config	MPR [dB]	Serial Number	Waveform	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g)	Plimit	Overall Plimit	
MHz	Ch.															(W/kg)			
2592.99	518598	Mid	NR Band n41	100	Closed	15.41	MIMO04	0	LG211	DFT-S-OFDM	QPSK	1	1	10 mm	back	1:1	0.062	27.49	23.45
2592.99	518598	Mid	NR Band n41	100	Closed	15.35	MIMO04	0	LG211	DFT-S-OFDM	QPSK	135	0	10 mm	back	1:1	0.070	26.90	
2592.99	518598	Mid	NR Band n41	100	Closed	15.41	MIMO04	0	LG211	DFT-S-OFDM	QPSK	1	1	10 mm	front	1:1	0.083	26.22	
2592.99	518598	Mid	NR Band n41	100	Closed	15.35	MIMO04	0	LG211	DFT-S-OFDM	QPSK	135	0	10 mm	front	1:1	0.090	25.81	
2592.99	518598	Mid	NR Band n41	100	Closed	15.41	MIMO04	0	LG211	DFT-S-OFDM	QPSK	1	1	10 mm	bottom	1:1	0.128	24.34	
2592.99	518598	Mid	NR Band n41	100	Closed	15.35	MIMO04	0	LG211	DFT-S-OFDM	QPSK	135	0	10 mm	bottom	1:1	0.155	23.45	
2592.99	518598	Mid	NR Band n41	100	Closed	15.47	MIMO04	0	LG211	CP-OFDM	QPSK	1	1	10 mm	bottom	1:1	0.131	24.30	26.36
2592.99	518598	Mid	NR Band n41	100	Closed	15.80	MIMO03	0	X2211	DFT-S-OFDM	QPSK	1	137	10 mm	back	1:1	0.022	32.38	
2592.99	518598	Mid	NR Band n41	100	Closed	15.77	MIMO03	0	X2211	DFT-S-OFDM	QPSK	135	138	10 mm	back	1:1	0.028	31.30	
2592.99	518598	Mid	NR Band n41	100	Closed	15.80	MIMO03	0	X2211	DFT-S-OFDM	QPSK	1	137	10 mm	front	1:1	0.025	31.82	
2592.99	518598	Mid	NR Band n41	100	Closed	15.77	MIMO03	0	X2211	DFT-S-OFDM	QPSK	135	138	10 mm	front	1:1	0.024	31.97	
2592.99	518598	Mid	NR Band n41	100	Closed	15.80	MIMO03	0	X2211	DFT-S-OFDM	QPSK	1	137	10 mm	top	1:1	0.069	27.41	
2592.99	518598	Mid	NR Band n41	100	Closed	15.77	MIMO03	0	X2211	DFT-S-OFDM	QPSK	135	138	10 mm	top	1:1	0.073	27.14	
2592.99	518598	Mid	NR Band n41	100	Closed	15.50	MIMO03	0	X2211	CP-OFDM	QPSK	1	1	10 mm	top	1:1	0.082	26.36	
2592.99	518598	Mid	NR Band n41	100	Closed	15.80	MIMO03	0	X2211	DFT-S-OFDM	QPSK	1	137	10 mm	left	1:1	0.010	35.80	
2592.99	518598	Mid	NR Band n41	100	Closed	15.77	MIMO03	0	X2211	DFT-S-OFDM	QPSK	135	138	10 mm	left	1:1	0.009	36.23	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population							Body 1.6 W/kg (mW/g) averaged over 1 gram												

For some bands/modes, a lower P_{Limit} was selected as a more conservative evaluation.

1.4 Phablet Data

Table 1-6
DSI = 4 P_{Limit} Calculations – NR Band n41 Phablet SAR

MEASUREMENT RESULTS																			
FREQUENCY			Mode	Bandwidth [MHz]	DUT Configuration	Conducted Power [dBm]	Antenna Config	MPR [dB]	Serial Number	Waveform	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (10g)	Plimit	Overall Plimit
MHz	Ch.	(W/kg)																	
2592.99	518598	Mid	NR Band n41	100	Flip	15.41	MM004	0	LG211	DFT-S-OFDM	QPSK	1	1	0 mm	back	1:1	0.187	26.67	20.93
2592.99	518598	Mid	NR Band n41	100	Flip	15.41	MM004	0	LG211	DFT-S-OFDM	QPSK	1	1	0 mm	front	1:1	0.702	20.93	
2592.99	518598	Mid	NR Band n41	100	Flip	15.41	MM004	0	LG211	DFT-S-OFDM	QPSK	1	1	0 mm	bottom	1:1	0.530	22.15	
2592.99	518598	Mid	NR Band n41	100	Flip	15.80	MM003	0	X2211	DFT-S-OFDM	QPSK	1	137	0 mm	back	1:1	0.056	32.30	23.73
2592.99	518598	Mid	NR Band n41	100	Flip	15.80	MM003	0	X2211	DFT-S-OFDM	QPSK	1	137	0 mm	front	1:1	0.403	23.73	
2592.99	518598	Mid	NR Band n41	100	Flip	15.80	MM003	0	X2211	DFT-S-OFDM	QPSK	1	137	0 mm	top	1:1	0.384	23.94	
2592.99	518598	Mid	NR Band n41	100	Flip	15.80	MM003	0	X2211	DFT-S-OFDM	QPSK	1	137	0 mm	left	1:1	0.013	38.64	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population							Phablet 4.0 W/kg (mW/g) averaged over 10 grams												

For some bands/modes, a lower P_{Limit} was selected as a more conservative evaluation.

FCC ID: C3K1995	 Proud to be part of 	PART 0 SAR CHAR REPORT	 Microsoft	Approved by: Quality Manager
Test Dates: 09/08/2021– 10/04/2021	DUT Type: Portable Handset	APPENDIX A: Page 3 of 4		

1.5 UMPC Data

Table 1-7
DSI = 5 P_{Limit} Calculations – NR Band n41 UMPC Body SAR

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	DUT Configuration	Conducted Power [dBm]	Antenna Config	MPR [dB]	Serial Number	Waveform	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g)	Plimit	Overall Plimit	
MHz	Ch.															(W/kg)			
2592.99	518598	Mid	NR Band n41	100	Read	13.18	MIMO4	0	LG211	DFT-S-OFDM	QPSK	1	1	5 mm	back	1:1	0.281	18.69	18.46
2592.99	518598	Mid	NR Band n41	100	Read	13.10	MIMO4	0	LG211	DFT-S-OFDM	QPSK	135	0	5 mm	back	1:1	0.291	18.46	
2592.99	518598	Mid	NR Band n41	100	Read	13.21	MIMO4	0	LG211	CP-OFDM	QPSK	1	1	5 mm	back	1:1	0.273	18.85	
2592.99	518598	Mid	NR Band n41	100	Read	13.18	MIMO4	0	LG211	DFT-S-OFDM	QPSK	1	1	5 mm	bottom	1:1	0.212	19.92	
2592.99	518598	Mid	NR Band n41	100	Read	13.10	MIMO4	0	LG211	DFT-S-OFDM	QPSK	135	0	5 mm	bottom	1:1	0.219	19.70	
2592.99	518598	Mid	NR Band n41	100	Read	13.67	MIMO3	0	X2211	DFT-S-OFDM	QPSK	1	137	5 mm	back	1:1	0.083	24.48	21.88
2592.99	518598	Mid	NR Band n41	100	Read	13.69	MIMO3	0	X2211	DFT-S-OFDM	QPSK	135	69	5 mm	back	1:1	0.050	26.70	
2592.99	518598	Mid	NR Band n41	100	Read	13.67	MIMO3	0	X2211	DFT-S-OFDM	QPSK	1	137	5 mm	top	1:1	0.133	22.43	
2592.99	518598	Mid	NR Band n41	100	Read	13.69	MIMO3	0	X2211	DFT-S-OFDM	QPSK	135	69	5 mm	top	1:1	0.088	24.25	
2592.99	518598	Mid	NR Band n41	100	Read	13.31	MIMO3	0	X2211	CP-OFDM	QPSK	1	1	5 mm	top	1:1	0.139	21.88	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak							Body 1.6 W/kg (mW/g) averaged over 1 gram												
Uncontrolled Exposure/General Population																			

For some bands/modes, a lower P_{Limit} was selected as a more conservative evaluation

1.6 Body Data

Table 1-8
DSI = 5 P_{Limit} Calculations – NR Band n41 Body SAR

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	DUT Configuration	Conducted Power [dBm]	Antenna Config	MPR [dB]	Serial Number	Waveform	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g)	Plim it	Overall Plim it	
MHz	Ch.															(W/kg)			
2592.99	518598	Mid	NR Band n41	100	Flat	6.08	MIMO4	0	LG211	DFT-S-OFDM	QPSK	1	1	0 mm	back	1:1	0.217	12.72	12.40
2592.99	518598	Mid	NR Band n41	100	Flat	6.15	MIMO4	0	LG211	DFT-S-OFDM	QPSK	135	0	0 mm	back	1:1	0.229	12.55	
2592.99	518598	Mid	NR Band n41	100	Flat	6.20	MIMO4	0	LG211	CP-OFDM	QPSK	1	1	0 mm	back	1:1	0.240	12.40	
2592.99	518598	Mid	NR Band n41	100	Flat	6.08	MIMO4	0	LG211	DFT-S-OFDM	QPSK	1	1	0 mm	bottom	1:1	0.177	13.60	
2592.99	518598	Mid	NR Band n41	100	Flat	6.15	MIMO4	0	LG211	DFT-S-OFDM	QPSK	135	0	0 mm	bottom	1:1	0.196	13.23	
2592.99	518598	Mid	NR Band n41	100	Flat	6.59	MIMO3	0	X2211	DFT-S-OFDM	QPSK	1	137	0 mm	back	1:1	0.069	18.20	14.86
2592.99	518598	Mid	NR Band n41	100	Flat	6.63	MIMO3	0	X2211	DFT-S-OFDM	QPSK	135	69	0 mm	back	1:1	0.070	18.18	
2592.99	518598	Mid	NR Band n41	100	Flat	6.59	MIMO3	0	X2211	DFT-S-OFDM	QPSK	1	137	0 mm	top	1:1	0.136	15.25	
2592.99	518598	Mid	NR Band n41	100	Flat	6.63	MIMO3	0	X2211	DFT-S-OFDM	QPSK	135	69	0 mm	top	1:1	0.127	15.59	
2592.99	518598	Mid	NR Band n41	100	Flat	6.50	MIMO3	0	X2211	CP-OFDM	QPSK	1	1	0 mm	top	1:1	0.146	14.86	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population							Body 1.6 W/kg (mW/g) averaged over 1 gram												

For some bands/modes, a lower P_{Limit} was selected as a more conservative evaluation.

FCC ID: C3K1995	 PCTEST Proud to be part of 	PART 0 SAR CHAR REPORT		Approved by: Quality Manager
Test Dates: 09/08/2021– 10/04/2021	DUT Type: Portable Handset	APPENDIX A: Page 4 of 4		