



Operation Frequency Range of 20dB Bandwidth within Hopping Mode


DH5 - Channel 00 (2402MHz)




DH5 - Channel 78 (2480MHz)




2DH5 - Channel 00 (2402MHz)




2DH5 - Channel 78 (2480MHz)



3DH5 - Channel 00 (2402MHz)



3DH5 - Channel 78 (2480MHz)



7.8. Conducted Spurious Emissions Measurement

7.8.1. Test Limit

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.


7.8.2. Test Procedure Used

ANSI C63.10-2013 - Section 7.8.8

7.8.3. Test Setting

1. Span = Wide enough to capture the peak level of the in-band emission and all spurious emissions (e.g., harmonics) from the lowest frequency generated in the EUT up through the 10th harmonic. Typically, several plots are required to cover this entire span.
2. RBW = 100kHz
3. VBW = 300kHz
4. Detector = Peak
5. Sweep time = Auto couple
6. Trace mode = Max hold
7. Trace was allowed to stabilize
8. Set the marker on the peak of any spurious emission recorded. The level displayed must comply with the limit specified in this section.

7.8.4.Test Setup




7.8.5. Test Result

Product	Tablet	Temperature	25°C
Test Engineer	Flag Yang	Relative Humidity	52%
Test Site	TR3	Test Date	2019/04/29


Test Mode	Channel No.	Frequency (MHz)	Limit (MHz)	Result
DH5	00	2402	20dBc	Pass
DH5	39	2441	20dBc	Pass
DH5	78	2480	20dBc	Pass
2DH5	00	2402	20dBc	Pass
2DH5	39	2441	20dBc	Pass
2DH5	78	2480	20dBc	Pass
3DH5	00	2402	20dBc	Pass
3DH5	39	2441	20dBc	Pass
3DH5	78	2480	20dBc	Pass

DH5 Conducted Spurious Emissions


Channel 00 (2402MHz)



Channel 39 (2441MHz)




Channel 78 (2480MHz)




2DH5 Conducted Spurious Emissions


Channel 00 (2402MHz)



Channel 39 (2441MHz)




Channel 78 (2480MHz)




3DH5 Conducted Spurious Emissions


Channel 00 (2402MHz)



Channel 39 (2441MHz)



Channel 78 (2480MHz)



7.9. Radiated Spurious Emission Measurement

7.9.1. Test Limit

All out of band emissions appearing in a restricted band as specified in Section 15.205 of the Title 47 CFR must not exceed the limits shown in Table per Section 15.209.

FCC Part 15 Subpart C Paragraph 15.209		
Frequency (MHz)	Field Strength ($\mu\text{V/m}$)	Measured Distance (m)
0.009 - 0.490	2400/F (kHz)	300
0.490 - 1.705	24000/F (kHz)	30
1.705 - 30	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3

7.9.2. Test Procedure Used

ANSI C63.10 - Section 6.3 (General Requirements)

ANSI C63.10 - Section 6.4 (Standard test method below 30MHz)

ANSI C63.10 - Section 6.5 (Standard test method above 30MHz to 1GHz)

ANSI C63.10 - Section 6.6 (Standard test method above 1GHz)

7.9.3. Test Setting

Table 1 - RBW as a function of frequency

Frequency	RBW
9 ~ 150 kHz	200 ~ 300 Hz
0.15 ~ 30 MHz	9 ~ 10 kHz
30 ~ 1000 MHz	100 ~ 120 kHz
> 1000 MHz	1 MHz

Quasi-Peak Measurements below 1GHz

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. Span was set greater than 1MHz
3. RBW = As specified in Table 1
4. Detector = CISPR quasi-peak
5. Sweep time = Auto couple
6. Trace was allowed to stabilize

Peak Measurements above 1GHz


1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 1MHz
3. VBW = 3MHz
4. Detector = Peak
5. Sweep time = Auto couple
6. Trace mode = Max hold
7. Trace was allowed to stabilize

Average Measurements above 1GHz (Method VB)


1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 1MHz
3. VBW; If the EUT is configured to transmit with duty cycle $\geq 98\%$, set VBW = 10Hz
If the EUT duty cycle is $< 98\%$, set VBW $\geq 1/T$. T is the minimum transmission duration
4. Detector = Peak
5. Sweep time = Auto
6. Trace mode = Max hold
7. Trace was allowed to stabilize

7.9.4. Test Setup

Below 1GHz Test Setup:



Above 1GHz Test Setup:



7.9.5. Test Result

Product	Tablet	Temperature	25°C
Test Engineer	Snake Ni	Relative Humidity	56%
Test Site	AC2	Test Date	2019/05/11
Test Mode	DH5	Test Channel	00
Remark	1. Average measurement was not performed if peak level lower than average limit. 2. Other frequency was 20dB below limit line within 1-18GHz, there is not show in the report.		

Mark	Frequency (MHz)	Reading Level (dBμV)	Factor (dB)	Measure Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector	Polarization
	4213.0	36.5	1.2	37.7	74.0	-36.3	Peak	Horizontal
	4804.0	33.7	3.5	37.2	74.0	-36.8	Peak	Horizontal
*	6185.0	35.0	6.8	41.8	74.2	-32.4	Peak	Horizontal
*	7206.0	32.0	11.7	43.7	74.2	-30.5	Peak	Horizontal
	4085.5	37.3	0.9	38.2	74.0	-35.8	Peak	Vertical
	4804.0	34.2	3.5	37.7	74.0	-36.3	Peak	Vertical
*	6389.0	35.6	7.4	43.0	74.2	-31.2	Peak	Vertical
*	7206.0	32.2	11.7	43.9	74.2	-30.3	Peak	Vertical

Note 1: "*" is not in restricted band, its limit is 20dBc of the fundamental emission level (94.2dBμV/m) or 15.209 which is higher.

Note 2: Measure Level (dBμV/m) = Reading Level (dBμV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Product	Tablet	Temperature	25°C
Test Engineer	Snake Ni	Relative Humidity	56%
Test Site	AC2	Test Date	2019/05/11
Test Mode	DH5	Test Channel	39
Remark	1. Average measurement was not performed if peak level lower than average limit. 2. Other frequency was 20dB below limit line within 1-18GHz, there is not show in the report.		

Mark	Frequency (MHz)	Reading Level (dBμV)	Factor (dB)	Measure Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector	Polarization
	4882.0	35.2	3.6	38.8	74.0	-35.2	Peak	Horizontal
	7323.0	32.3	12.0	44.3	74.0	-29.7	Peak	Horizontal
*	7851.0	32.8	11.5	44.3	76.8	-32.5	Peak	Horizontal
*	8650.0	33.0	12.3	45.3	76.8	-31.5	Peak	Horizontal
	4882.0	33.8	3.6	37.4	74.0	-36.6	Peak	Vertical
	7323.0	32.3	12.0	44.3	74.0	-29.7	Peak	Vertical
*	7927.5	32.4	11.5	43.9	76.8	-32.9	Peak	Vertical
*	8658.5	32.8	12.3	45.1	76.8	-31.7	Peak	Vertical

Note 1: “*” is not in restricted band, its limit is 20dBc of the fundamental emission level (96.8dBμV/m) or 15.209 which is higher.

Note 2: Measure Level (dBμV/m) = Reading Level (dBμV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Product	Tablet	Temperature	25°C
Test Engineer	Snake Ni	Relative Humidity	56%
Test Site	AC2	Test Date	2019/05/11
Test Mode	DH5	Test Channel	78
Remark	1. Average measurement was not performed if peak level lower than average limit. 2. Other frequency was 20dB below limit line within 1-18GHz, there is not show in the report.		

Mark	Frequency (MHz)	Reading Level (dBμV)	Factor (dB)	Measure Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector	Polarization
	4960.0	34.8	3.5	38.3	74.0	-35.7	Peak	Horizontal
	7440.0	32.3	11.8	44.1	74.0	-29.9	Peak	Horizontal
*	7902.0	32.6	11.6	44.2	76.2	-32.0	Peak	Horizontal
*	8650.0	32.8	12.3	45.1	76.2	-31.1	Peak	Horizontal
	4960.0	34.1	3.5	37.6	74.0	-36.4	Peak	Vertical
	7440.0	32.1	11.8	43.9	74.0	-30.1	Peak	Vertical
*	7876.5	32.2	11.6	43.8	76.2	-32.4	Peak	Vertical
*	8735.0	32.7	12.8	45.5	76.2	-30.7	Peak	Vertical

Note 1: “*” is not in restricted band, its limit is 20dBc of the fundamental emission level (96.2dBμV/m) or 15.209 which is higher.

Note 2: Measure Level (dBμV/m) = Reading Level (dBμV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Product	Tablet	Temperature	25°C
Test Engineer	Snake Ni	Relative Humidity	56%
Test Site	AC2	Test Date	2019/05/11
Test Mode	2DH5	Test Channel	00
Remark	1. Average measurement was not performed if peak level lower than average limit. 2. Other frequency was 20dB below limit line within 1-18GHz, there is not show in the report.		

Mark	Frequency (MHz)	Reading Level (dBμV)	Factor (dB)	Measure Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector	Polarization
	4102.5	38.0	0.9	38.9	74.0	-35.1	Peak	Horizontal
	4804.0	34.2	3.5	37.7	74.0	-36.3	Peak	Horizontal
*	6499.5	34.2	8.3	42.5	74.0	-31.5	Peak	Horizontal
*	7206.0	32.3	11.7	44.0	74.0	-30.0	Peak	Horizontal
	4119.5	37.1	0.9	38.0	74.0	-36.0	Peak	Vertical
	4804.0	34.2	3.5	37.7	74.0	-36.3	Peak	Vertical
*	6219.0	35.2	6.7	41.9	74.0	-32.1	Peak	Vertical
*	7206.0	32.2	11.7	43.9	74.0	-30.1	Peak	Vertical

Note 1: “*” is not in restricted band, its limit is 20dBc of the fundamental emission level (93.9dBμV/m) or 15.209 which is higher.

Note 2: Measure Level (dBμV/m) = Reading Level (dBμV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Product	Tablet	Temperature	25°C
Test Engineer	Snake Ni	Relative Humidity	56%
Test Site	AC2	Test Date	2019/05/11
Test Mode	2DH5	Test Channel	39
Remark	1. Average measurement was not performed if peak level lower than average limit. 2. Other frequency was 20dB below limit line within 1-18GHz, there is not show in the report.		

Mark	Frequency (MHz)	Reading Level (dBμV)	Factor (dB)	Measure Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector	Polarization
	4882.0	34.4	3.6	38.0	74.0	-36.0	Peak	Horizontal
	7323.0	32.0	12.0	44.0	74.0	-30.0	Peak	Horizontal
*	8012.5	34.2	11.7	45.9	76.3	-30.4	Peak	Horizontal
*	8667.0	33.0	12.3	45.3	76.3	-31.0	Peak	Horizontal
	4882.0	34.5	3.6	38.1	74.0	-35.9	Peak	Vertical
	7323.0	32.2	12.0	44.2	74.0	-29.8	Peak	Vertical
*	7919.0	32.9	11.5	44.4	76.3	-31.9	Peak	Vertical
*	8667.0	32.8	12.3	45.1	76.3	-31.2	Peak	Vertical

Note 1: “*” is not in restricted band, its limit is 20dBc of the fundamental emission level (96.3dBμV/m) or 15.209 which is higher.

Note 2: Measure Level (dBμV/m) = Reading Level (dBμV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Product	Tablet	Temperature	25°C
Test Engineer	Snake Ni	Relative Humidity	56%
Test Site	AC2	Test Date	2019/05/11
Test Mode	2DH5	Test Channel	78
Remark	1. Average measurement was not performed if peak level lower than average limit. 2. Other frequency was 20dB below limit line within 1-18GHz, there is not show in the report.		

Mark	Frequency (MHz)	Reading Level (dBμV)	Factor (dB)	Measure Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector	Polarization
	4960.0	34.4	3.5	37.9	74.0	-36.1	Peak	Horizontal
	7440.0	32.4	11.8	44.2	74.0	-29.8	Peak	Horizontal
*	7876.5	31.8	11.6	43.4	76.0	-32.6	Peak	Horizontal
*	8769.0	30.6	12.7	43.3	76.0	-32.7	Peak	Horizontal
	4960.0	34.9	3.5	38.4	74.0	-35.6	Peak	Vertical
	7440.0	32.2	11.8	44.0	74.0	-30.0	Peak	Vertical
*	7919.0	32.8	11.5	44.3	76.0	-31.7	Peak	Vertical
*	8692.5	32.9	12.4	45.3	76.0	-30.7	Peak	Vertical

Note 1: “*” is not in restricted band, its limit is 20dBc of the fundamental emission level (96.0dBμV/m) or 15.209 which is higher.

Note 2: Measure Level (dBμV/m) = Reading Level (dBμV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Product	Tablet	Temperature	25°C
Test Engineer	Snake Ni	Relative Humidity	56%
Test Site	AC2	Test Date	2019/05/11
Test Mode	3DH5	Test Channel	00
Remark	1. Average measurement was not performed if peak level lower than average limit. 2. Other frequency was 20dB below limit line within 1-18GHz, there is not show in the report.		

Mark	Frequency (MHz)	Reading Level (dBμV)	Factor (dB)	Measure Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector	Polarization
	4315.0	36.6	1.7	38.3	74.0	-35.7	Peak	Horizontal
	4804.0	34.0	3.5	37.5	74.0	-36.5	Peak	Horizontal
*	6134.0	35.2	6.4	41.6	74.0	-32.4	Peak	Horizontal
*	7206.0	33.0	11.7	44.7	74.0	-29.3	Peak	Horizontal
	4323.5	37.4	1.7	39.1	74.0	-34.9	Peak	Vertical
	4804.0	34.2	3.5	37.7	74.0	-36.3	Peak	Vertical
*	6219.0	35.8	6.7	42.5	74.0	-31.5	Peak	Vertical
*	7206.0	32.0	11.7	43.7	74.0	-30.3	Peak	Vertical

Note 1: “*” is not in restricted band, its limit is 20dBc of the fundamental emission level (94.0dBμV/m) or 15.209 which is higher.

Note 2: Measure Level (dBμV/m) = Reading Level (dBμV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Product	Tablet	Temperature	25°C
Test Engineer	Snake Ni	Relative Humidity	56%
Test Site	AC2	Test Date	2019/05/11
Test Mode	3DH5	Test Channel	39
Remark	1. Average measurement was not performed if peak level lower than average limit. 2. Other frequency was 20dB below limit line within 1-18GHz, there is not show in the report.		

Mark	Frequency (MHz)	Reading Level (dBμV)	Factor (dB)	Measure Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector	Polarization
	4882.0	34.8	3.6	38.4	74.0	-35.6	Peak	Horizontal
	7323.0	32.8	12.0	44.8	74.0	-29.2	Peak	Horizontal
*	7944.5	33.1	11.6	44.7	76.9	-32.2	Peak	Horizontal
*	8726.5	32.7	12.8	45.5	76.9	-31.4	Peak	Horizontal
	4882.0	34.6	3.6	38.2	74.0	-35.8	Peak	Vertical
	7323.0	32.4	12.0	44.4	74.0	-29.6	Peak	Vertical
*	7876.5	32.7	11.6	44.3	76.9	-32.6	Peak	Vertical
*	8888.0	32.7	12.7	45.4	76.9	-31.5	Peak	Vertical

Note 1: “*” is not in restricted band, its limit is 20dBc of the fundamental emission level (96.9dBμV/m) or 15.209 which is higher.

Note 2: Measure Level (dBμV/m) = Reading Level (dBμV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Product	Tablet	Temperature	25°C
Test Engineer	Snake Ni	Relative Humidity	56%
Test Site	AC2	Test Date	2019/05/11
Test Mode	3DH5	Test Channel	78
Remark	1. Average measurement was not performed if peak level lower than average limit. 2. Other frequency was 20dB below limit line within 1-18GHz, there is not show in the report.		

Mark	Frequency (MHz)	Reading Level (dBμV)	Factor (dB)	Measure Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector	Polarization
	4960.0	34.6	3.5	38.1	74.0	-35.9	Peak	Horizontal
	7440.0	32.2	11.8	44.0	74.0	-30.0	Peak	Horizontal
*	7910.5	32.1	11.6	43.7	76.3	-32.6	Peak	Horizontal
*	8684.0	32.6	12.4	45.0	76.3	-31.3	Peak	Horizontal
	4960.0	34.4	3.5	37.9	74.0	-36.1	Peak	Vertical
	7440.0	32.0	11.8	43.8	74.0	-30.2	Peak	Vertical
*	7910.5	31.9	11.6	43.5	76.3	-32.8	Peak	Vertical
*	8692.5	32.1	12.4	44.5	76.3	-31.8	Peak	Vertical


Note 1: “*” is not in restricted band, its limit is 20dBc of the fundamental emission level (96.3dBμV/m) or 15.209 which is higher.

Note 2: Measure Level (dBμV/m) = Reading Level (dBμV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

The Worst Case of Radiated Emission below 1GHz:

Site: AC2	Time: 2019/04/21 - 20:40
Limit: FCC_Part15.209_RE(3m)	Engineer: Messiah Li
Probe: VULB9162_0.03-8GHz	Polarity: Horizontal
EUT: Tablet	Power: By Battery
Worst Case Mode: Transmit by Bluetooth DH5 at Channel 2441MHz	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		*	38.245	19.247	5.791	-20.753	40.000	13.455	QP
2			45.520	18.545	3.717	-21.455	40.000	14.828	QP
3			59.585	16.878	3.030	-23.122	40.000	13.848	QP
4			110.995	16.069	3.462	-27.431	43.500	12.608	QP
5			195.870	15.369	3.425	-28.131	43.500	11.944	QP
6			489.780	22.362	4.548	-23.638	46.000	17.814	QP

Note 1: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Note 2: The test trace is same as the ambient noise and the amplitude of the emissions are attenuated more than 20dB below the permissible (the test frequency range: 9kHz ~ 30MHz, 18GHz ~ 25GHz), therefore no data appear in the report.

Site: AC2	Time: 2019/04/21 - 20:41
Limit: FCC_Part15.209_RE(3m)	Engineer: Messiah Li
Probe: VULB9162_0.03-8GHz	Polarity: Vertical
EUT: Tablet	Power: By Battery
Worst Case Mode: Transmit by Bluetooth DH5 at Channel 2441MHz	



No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1			30.480	25.311	13.260	-14.689	40.000	12.051	QP
2		*	36.310	29.367	16.250	-10.633	40.000	13.117	QP
3			37.750	27.625	14.260	-12.375	40.000	13.365	QP
4			63.984	19.025	6.250	-20.975	40.000	12.775	QP
5			105.660	16.665	3.712	-26.835	43.500	12.953	QP
6			217.150	17.748	5.360	-28.252	46.000	12.388	QP

Note 1: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Note 2: The test trace is same as the ambient noise and the amplitude of the emissions are attenuated more than 20dB below the permissible (the test frequency range: 9kHz ~ 30MHz, 18GHz ~ 25GHz), therefore no data appear in the report.

7.10. Radiated Restricted Band Edge Measurement

7.10.1. Test Limit

For 15.205 requirement:

Radiated emissions which fall in the restricted bands, as defined in Section 15.205(a) of FCC part 15, must also comply with the radiated emission limits specified in Section 15.209(a).

Frequency (MHz)	Frequency (MHz)	Frequency (MHz)	Frequency (GHz)
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
¹ 0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 - 156.52525	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.7 - 156.9	2690 - 2900	22.01 - 23.12
8.41425 - 8.41475	162.0125 - 167.17	3260 - 3267	23.6 - 24.0
12.29 - 12.293	167.72 - 173.2	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	240 - 285	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	322 - 335.4	3600 - 4400	(²)
13.36 - 13.41	--	--	--

All out of band emissions appearing in a restricted band as specified in Section 15.205 of the Title 47 CFR must not exceed the limits shown in Table per Section 15.209.

FCC Part 15 Subpart C Paragraph 15.209		
Frequency (MHz)	Field Strength (μ V/m)	Measured Distance (m)
0.009 - 0.490	2400/F (kHz)	300
0.490 - 1.705	24000/F (kHz)	30
1.705 - 30	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3

For RSS-Gen Section 8.10 requirement:

Radiated emissions which fall in the restricted bands, as defined in Section 8.10 of RSS-Gen, must also comply with the radiated emission limits specified in Section 8.9.

Frequency (MHz)	Frequency (MHz)	Frequency (GHz)
0.090 - 0.110	149.9 - 150.05	9.0 - 9.2
0.495 - 0.505	156.52475 - 156.52525	9.3 - 9.5
2.1735 - 2.1905	156.7 - 156.9	10.6 - 12.7
3.020 - 3.026	162.0125 - 167.17	13.25 - 13.4
4.125 - 4.128	167.72 - 173.2	14.47 - 14.5
4.17725 - 4.17775	240 - 285	15.35 - 16.2
4.20725 - 4.20775	322 - 335.4	17.7 - 21.4
5.677 - 5.683	399.9 - 410	22.01 - 23.12
6.215 - 6.218	608 - 614	23.6 - 24.0
6.26775 - 6.26825	960 - 1427	31.2 - 31.8
6.31175 - 6.31225	1435 - 1626.5	36.43 - 36.5
8.291 - 8.294	1645.5 - 1646.5	Above 38.6
8.362 - 8.366	1660 - 1710	* Certain frequency bands listed in table 7 and in bands above 38.6 GHz are designated for license exempt applications. These frequency bands and the requirements that apply to related devices are set out in the 200 and 300 series of RSSs.
8.37625 - 8.38675	1718.8 - 1722.2	
8.41425 - 8.41475	2200 - 2300	
12.29 - 12.293	2310 - 2390	
12.51975 - 12.52025	2483.5 - 2500	
12.57675 - 12.57725	2655 - 2900	
13.36 - 13.41	3260 - 3267	
16.42 - 16.423	3332 - 3339	
16.69475 - 16.69525	3345.8 - 3358	
16.80425 - 16.80475	3500 - 4400	
25.5 - 25.67	4500 - 5150	
37.5 - 38.25	5350 - 5460	
73 - 74.6	7250 - 7750	
74.8 - 75.2	8025 - 8500	
108 - 138	--	

All out of band emissions appearing in a restricted band as specified in Section 8.10 of the RSS-Gen must not exceed the limits shown in Table per Section 8.9.

RSS-Gen Section 8.9			
Frequency (MHz)	Field Strength ($\mu\text{V/m}$)	Magnetic Field Strength (H-Field) ($\mu\text{A/m}$)	Measured Distance (m)
0.009 - 0.490 1	--	6.37/F (F in kHz)	300
0.490 - 1.705	--	6.37/F (F in kHz)	30
1.705 - 30	--	0.08	30
30 - 88	100	--	3
88 - 216	150	--	3
216 - 960	200	--	3
Above 960	500	--	3

7.10.2.Test Procedure Used

ANSI C63.10 - Section 6.3 (General Requirements)

ANSI C63.10 - Section 6.6 (Standard test method above 1GHz)

7.10.3.Test Setting


Peak Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 1MHz
3. VBW = 3MHz
4. Detector = Peak
5. Sweep time = Auto couple
6. Trace mode = Max hold
7. Trace was allowed to stabilize

Average Measurements above 1GHz (Method VB)


1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 1MHz
3. VBW; If the EUT is configured to transmit with duty cycle $\geq 98\%$, set VBW = 10Hz
4. If the EUT duty cycle is $< 98\%$, set VBW $\geq 1/T$. T is the minimum transmission duration
5. Detector = Peak
6. Sweep time = Auto
7. Trace mode = Max hold
8. Trace was allowed to stabilize

7.10.4.Test Setup



7.10.5.Test Result

Site: AC2	Time: 2019/05/11 - 16:55
Limit: FCC_Part15.209_RE(3m)	Engineer: Snake Ni
Probe: BBHA9120D_1-18GHz	Polarity: Horizontal
EUT: Tablet	Power: By Battery
Test Mode: Transmit by DH5 at Channel 2402MHz	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1			2386.950	59.632	28.184	-14.368	74.000	31.449	PK
2			2390.000	58.290	26.841	-15.710	74.000	31.449	PK
3		*	2401.722	90.061	58.638	N/A	N/A	31.422	PK

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Site: AC2	Time: 2019/05/11 - 16:56
Limit: FCC_Part15.209_RE(3m)	Engineer: Snake Ni
Probe: BBHA9120D_1-18GHz	Polarity: Horizontal
EUT: Tablet	Power: By Battery
Test Mode: Transmit by DH5 at Channel 2402MHz	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1			2390.000	45.892	14.443	-8.108	54.000	31.449	AV
2		*	2402.008	87.960	56.538	N/A	N/A	31.422	AV

Note: Measure Level (dBμV/m) = Reading Level (dBμV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Site: AC2	Time: 2019/05/11 - 16:58
Limit: FCC_Part15.209_RE(3m)	Engineer: Snake Ni
Probe: BBHA9120D_1-18GHz	Polarity: Vertical
EUT: Tablet	Power: By Battery
Test Mode: Transmit by DH5 at Channel 2402MHz	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1			2367.095	59.649	28.187	-14.351	74.000	31.462	PK
2			2390.000	58.054	26.605	-15.946	74.000	31.449	PK
3		*	2402.150	94.178	62.757	N/A	N/A	31.421	PK

Note: Measure Level (dBμV/m) = Reading Level (dBμV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Site: AC2	Time: 2019/05/11 - 16:59
Limit: FCC_Part15.209_RE(3m)	Engineer: Snake Ni
Probe: BBHA9120D_1-18GHz	Polarity: Vertical
EUT: Tablet	Power: By Battery
Test Mode: Transmit by DH5 at Channel 2402MHz	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1			2390.000	45.544	14.095	-8.456	54.000	31.449	AV
2		*	2402.008	93.697	62.275	N/A	N/A	31.422	AV

Note: Measure Level (dBμV/m) = Reading Level (dBμV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Site: AC2	Time: 2019/05/11 - 17:00
Limit: FCC_Part15.209_RE(3m)	Engineer: Snake Ni
Probe: BBHA9120D_1-18GHz	Polarity: Horizontal
EUT: Tablet	Power: By Battery
Test Mode: Transmit by DH5 at Channel 2480MHz	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		*	2480.139	91.223	59.832	N/A	N/A	31.392	PK
2			2483.500	57.877	26.474	-16.123	74.000	31.403	PK
3			2484.866	59.884	28.477	-14.116	74.000	31.407	PK

Note: Measure Level (dBμV/m) = Reading Level (dBμV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Site: AC2	Time: 2019/05/11 - 17:01
Limit: FCC_Part15.209_RE(3m)	Engineer: Snake Ni
Probe: BBHA9120D_1-18GHz	Polarity: Horizontal
EUT: Tablet	Power: By Battery
Test Mode: Transmit by DH5 at Channel 2480MHz	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		*	2480.059	90.846	59.455	N/A	N/A	31.391	AV
2			2483.500	45.750	14.347	-8.250	54.000	31.403	AV

Note: Measure Level (dBμV/m) = Reading Level (dBμV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Site: AC2	Time: 2019/05/11 - 17:02
Limit: FCC_Part15.209_RE(3m)	Engineer: Snake Ni
Probe: BBHA9120D_1-18GHz	Polarity: Vertical
EUT: Tablet	Power: By Battery
Test Mode: Transmit by DH5 at Channel 2480MHz	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		*	2480.059	96.150	64.759	N/A	N/A	31.391	PK
2			2483.500	58.087	26.684	-15.913	74.000	31.403	PK
3			2487.729	59.294	27.877	-14.706	74.000	31.417	PK

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Site: AC2	Time: 2019/05/11 - 17:04
Limit: FCC_Part15.209_RE(3m)	Engineer: Snake Ni
Probe: BBHA9120D_1-18GHz	Polarity: Vertical
EUT: Tablet	Power: By Battery
Test Mode: Transmit by DH5 at Channel 2480MHz	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		*	2480.024	95.757	64.366	N/A	N/A	31.391	AV
2			2483.500	45.946	14.543	-8.054	54.000	31.403	AV

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Site: AC2	Time: 2019/05/11 - 17:05
Limit: FCC_Part15.209_RE(3m)	Engineer: Snake Ni
Probe: BBHA9120D_1-18GHz	Polarity: Horizontal
EUT: Tablet	Power: By Battery
Test Mode: Transmit by 2DH5 at Channel 2402MHz	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1			2366.145	59.370	27.906	-14.630	74.000	31.464	PK
2			2390.000	58.158	26.709	-15.842	74.000	31.449	PK
3		*	2402.150	89.903	58.482	N/A	N/A	31.421	PK

Note: Measure Level (dBμV/m) = Reading Level (dBμV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Site: AC2	Time: 2019/05/11 - 17:07
Limit: FCC_Part15.209_RE(3m)	Engineer: Snake Ni
Probe: BBHA9120D_1-18GHz	Polarity: Horizontal
EUT: Tablet	Power: By Battery
Test Mode: Transmit by 2DH5 at Channel 2402MHz	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1			2390.000	45.601	14.152	-8.399	54.000	31.449	AV
2		*	2402.150	86.322	54.901	N/A	N/A	31.421	AV

Note: Measure Level (dBμV/m) = Reading Level (dBμV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Site: AC2	Time: 2019/05/11 - 17:07
Limit: FCC_Part15.209_RE(3m)	Engineer: Snake Ni
Probe: BBHA9120D_1-18GHz	Polarity: Vertical
EUT: Tablet	Power: By Battery
Test Mode: Transmit by 2DH5 at Channel 2402MHz	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1			2373.080	59.680	28.227	-14.320	74.000	31.453	PK
2			2390.000	58.041	26.592	-15.959	74.000	31.449	PK
3		*	2402.150	93.880	62.459	N/A	N/A	31.421	PK

Note: Measure Level (dBμV/m) = Reading Level (dBμV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Site: AC2	Time: 2019/05/11 - 17:09
Limit: FCC_Part15.209_RE(3m)	Engineer: Snake Ni
Probe: BBHA9120D_1-18GHz	Polarity: Vertical
EUT: Tablet	Power: By Battery
Test Mode: Transmit by 2DH5 at Channel 2402MHz	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1			2390.000	45.516	14.067	-8.484	54.000	31.449	AV
2		*	2402.150	89.787	58.366	N/A	N/A	31.421	AV

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Site: AC2	Time: 2019/05/11 - 17:09
Limit: FCC_Part15.209_RE(3m)	Engineer: Snake Ni
Probe: BBHA9120D_1-18GHz	Polarity: Horizontal
EUT: Tablet	Power: By Battery
Test Mode: Transmit by 2DH5 at Channel 2480MHz	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		*	2480.024	90.759	59.368	N/A	N/A	31.391	PK
2			2483.500	58.346	26.943	-15.654	74.000	31.403	PK
3			2486.695	59.508	28.094	-14.492	74.000	31.413	PK

Note: Measure Level (dBμV/m) = Reading Level (dBμV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Site: AC2	Time: 2019/05/11 - 17:11
Limit: FCC_Part15.209_RE(3m)	Engineer: Snake Ni
Probe: BBHA9120D_1-18GHz	Polarity: Horizontal
EUT: Tablet	Power: By Battery
Test Mode: Transmit by 2DH5 at Channel 2480MHz	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		*	2480.024	87.057	55.666	N/A	N/A	31.391	AV
2			2483.500	45.652	14.249	-8.348	54.000	31.403	AV

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Site: AC2	Time: 2019/05/11 - 17:11
Limit: FCC_Part15.209_RE(3m)	Engineer: Snake Ni
Probe: BBHA9120D_1-18GHz	Polarity: Vertical
EUT: Tablet	Power: By Battery
Test Mode: Transmit by 2DH5 at Channel 2480MHz	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		*	2480.139	95.963	64.572	N/A	N/A	31.392	PK
2			2483.500	58.296	26.893	-15.704	74.000	31.403	PK
3			2492.031	59.931	28.499	-14.069	74.000	31.432	PK

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Site: AC2	Time: 2019/05/11 - 17:13
Limit: FCC_Part15.209_RE(3m)	Engineer: Snake Ni
Probe: BBHA9120D_1-18GHz	Polarity: Vertical
EUT: Tablet	Power: By Battery
Test Mode: Transmit by 2DH5 at Channel 2480MHz	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		*	2480.024	92.397	61.006	N/A	N/A	31.391	AV
2			2483.500	45.782	14.379	-8.218	54.000	31.403	AV

Note: Measure Level (dBμV/m) = Reading Level (dBμV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Site: AC2	Time: 2019/05/11 - 17:14
Limit: FCC_Part15.209_RE(3m)	Engineer: Snake Ni
Probe: BBHA9120D_1-18GHz	Polarity: Horizontal
EUT: Tablet	Power: By Battery
Test Mode: Transmit by 3DH5 at Channel 2402MHz	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1			2368.900	59.915	28.455	-14.085	74.000	31.460	PK
2			2390.000	57.580	26.131	-16.420	74.000	31.449	PK
3		*	2402.055	90.409	58.988	N/A	N/A	31.421	PK

Note: Measure Level (dBμV/m) = Reading Level (dBμV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Site: AC2	Time: 2019/05/11 - 17:15
Limit: FCC_Part15.209_RE(3m)	Engineer: Snake Ni
Probe: BBHA9120D_1-18GHz	Polarity: Horizontal
EUT: Tablet	Power: By Battery
Test Mode: Transmit by 3DH5 at Channel 2402MHz	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1			2390.000	45.671	14.222	-8.329	54.000	31.449	AV
2		*	2402.150	85.495	54.074	N/A	N/A	31.421	AV

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Site: AC2	Time: 2019/05/11 - 17:16
Limit: FCC_Part15.209_RE(3m)	Engineer: Snake Ni
Probe: BBHA9120D_1-18GHz	Polarity: Vertical
EUT: Tablet	Power: By Battery
Test Mode: Transmit by 3DH5 at Channel 2402MHz	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1			2367.238	59.377	27.915	-14.623	74.000	31.462	PK
2			2390.000	57.088	25.639	-16.912	74.000	31.449	PK
3		*	2402.150	93.958	62.537	N/A	N/A	31.421	PK

Note: Measure Level (dBμV/m) = Reading Level (dBμV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Site: AC2	Time: 2019/05/11 - 17:17
Limit: FCC_Part15.209_RE(3m)	Engineer: Snake Ni
Probe: BBHA9120D_1-18GHz	Polarity: Vertical
EUT: Tablet	Power: By Battery
Test Mode: Transmit by 3DH5 at Channel 2402MHz	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1			2390.000	45.520	14.071	-8.480	54.000	31.449	AV
2		*	2401.865	89.738	58.316	N/A	N/A	31.422	AV

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Site: AC2	Time: 2019/05/11 - 17:18
Limit: FCC_Part15.209_RE(3m)	Engineer: Snake Ni
Probe: BBHA9120D_1-18GHz	Polarity: Horizontal
EUT: Tablet	Power: By Battery
Test Mode: Transmit by 3DH5 at Channel 2480MHz	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		*	2479.990	91.383	59.992	N/A	N/A	31.391	PK
2			2483.500	57.378	25.975	-16.622	74.000	31.403	PK
3			2487.350	59.890	28.474	-14.110	74.000	31.416	PK

Note: Measure Level (dBμV/m) = Reading Level (dBμV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Site: AC2	Time: 2019/05/11 - 17:21
Limit: FCC_Part15.209_RE(3m)	Engineer: Snake Ni
Probe: BBHA9120D_1-18GHz	Polarity: Horizontal
EUT: Tablet	Power: By Battery
Test Mode: Transmit by 3DH5 at Channel 2480MHz	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		*	2480.059	87.433	56.042	N/A	N/A	31.391	AV
2			2483.500	45.650	14.247	-8.350	54.000	31.403	AV

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Site: AC2	Time: 2019/05/11 - 17:21
Limit: FCC_Part15.209_RE(3m)	Engineer: Snake Ni
Probe: BBHA9120D_1-18GHz	Polarity: Vertical
EUT: Tablet	Power: By Battery
Test Mode: Transmit by 3DH5 at Channel 2480MHz	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		*	2479.979	96.255	64.864	N/A	N/A	31.391	PK
2			2483.500	57.964	26.561	-16.036	74.000	31.403	PK
3			2486.326	59.826	28.414	-14.174	74.000	31.413	PK

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Site: AC2	Time: 2019/05/11 - 17:22
Limit: FCC_Part15.209_RE(3m)	Engineer: Snake Ni
Probe: BBHA9120D_1-18GHz	Polarity: Vertical
EUT: Tablet	Power: By Battery
Test Mode: Transmit by 3DH5 at Channel 2480MHz	



No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		*	2480.059	92.288	60.897	N/A	N/A	31.391	AV
2			2483.500	45.553	14.150	-8.447	54.000	31.403	AV

Note: Measure Level (dBμV/m) = Reading Level (dBμV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

7.11. AC Conducted Emissions Measurement


7.11.1. Test Limit

FCC Part 15 Subpart C Paragraph 15.207 Limits		
Frequency (MHz)	QP (dB μ V)	Average (dB μ V)
0.15 - 0.50	66 - 56	56 - 46
0.50 - 5.0	56	46
5.0 - 30	60	50

Note 1: The lower limit shall apply at the transition frequencies.


Note 2: The limit decreases linearly with the logarithm of the frequency in the range 0.15MHz to 0.5MHz.

7.11.2. Test Setup



7.11.3.Test Result

Site: SR2	Time: 2019/05/07 - 10:08
Limit: FCC_Part15.207_CE_AC Power	Engineer: Liz Yuan
Probe: ENV216_101683_Filter On	Polarity: Line
EUT: Tablet	Power: AC 120V/60Hz
Test Mode: Transmit by DH5 at Channel 2402MHz	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV)	Factor (dB)	Type
1			0.162	35.544	25.447	-29.817	65.361	10.097	QP
2			0.162	18.052	7.955	-37.309	55.361	10.097	AV
3			0.190	33.341	23.312	-30.696	64.037	10.029	QP
4			0.190	15.756	5.727	-38.281	54.037	10.029	AV
5			0.470	35.291	25.149	-21.223	56.514	10.142	QP
6			0.470	23.980	13.838	-22.534	46.514	10.142	AV
7		*	0.502	36.025	25.868	-19.975	56.000	10.157	QP
8			0.502	25.102	14.945	-20.898	46.000	10.157	AV
9			0.710	29.041	18.983	-26.959	56.000	10.058	QP
10			0.710	17.219	7.161	-28.781	46.000	10.058	AV
11			2.714	27.914	18.065	-28.086	56.000	9.850	QP
12			2.714	15.761	5.912	-30.239	46.000	9.850	AV

Note: Measure Level (dBμV) = Reading Level (dBμV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + LISN Factor (dB)

Site: SR2	Time: 2019/05/07 - 10:08
Limit: FCC_Part15.207_CE_AC Power	Engineer: Liz Yuan
Probe: ENV216_101683_Filter On	Polarity: Neutral
EUT: Tablet	Power: AC 120V/60Hz
Test Mode: Transmit by DH5 at Channel 2402MHz	



No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV)	Factor (dB)	Type
1			0.170	40.718	30.654	-24.242	64.960	10.064	QP
2			0.170	17.914	7.850	-37.046	54.960	10.064	AV
3			0.290	26.637	16.607	-33.887	60.524	10.030	QP
4			0.290	17.040	7.009	-33.485	50.524	10.030	AV
5			0.334	29.270	19.207	-30.082	59.351	10.063	QP
6			0.334	20.573	10.510	-28.779	49.351	10.063	AV
7			0.366	26.577	16.490	-32.015	58.591	10.087	QP
8			0.366	16.126	6.039	-32.465	48.591	10.087	AV
9		*	0.494	39.218	29.039	-16.882	56.100	10.178	QP
10			0.494	28.759	18.581	-17.341	46.100	10.178	AV
11			1.022	32.425	22.517	-23.575	56.000	9.908	QP
12			1.022	20.566	10.658	-25.434	46.000	9.908	AV

Note: Measure Level (dBμV) = Reading Level (dBμV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + LISN Factor (dB)

8. CONCLUSION

The data collected relate only the item(s) tested and show that the **Tablet** is in compliance with Part 15C of the FCC rules and ISED rules.

The End

Appendix A - Test Setup Photograph

Refer to "1904RSU029-UT" file.

Appendix B - EUT Photograph

Refer to "1904RSU029-UE" file.