

Prüfbericht - Nr.:


Test Report No.:

ULR-TC568821300000034F

Seite 95 von 143

Page 95 of 143

S



Only MCS0 graphs are copied

8.4 Dynamic Frequency Selection (DFS)

Result

Pass

Test Specification 15.407 (h) / RSS 247 Issue 2 Section 6.3

Test Method FCC KDB Publication 905462 D02 & 905462 D03

Port of testing Conducted method


UUT Type Client without radar detection capabilities

1. Transmit power control (TPC). U-NII devices operating in the 5.25-5.35 GHz band and the 5.47-5.725 GHz band shall employ a TPC mechanism. The U-NII device is required to have the capability to operate at least 6 dB below the mean EIRP value of 30 dBm. A TPC mechanism is not required for systems with an e.i.r.p. of less than 500 mW

2. Radar Detection Function of Dynamic Frequency Selection (DFS). U-NII devices operating with any part of its 26 dB emission bandwidth in the 5.25-5.35 GHz and 5.47-5.725 GHz bands shall employ a DFS radar detection mechanism to detect the presence of radar systems and to avoid co-channel operation with radar systems. Operators shall only use equipment with a DFS mechanism that is turned on when operating in these bands

Test Setup :

Setup for Client with injection at the Master



Note: FCC Certified Access Point is used for testing with FCC ID: LDK102087

Limits :

Applicability of DFS Requirements Prior to Use of a Channel

Requirement	Operational Mode		
	Master	Client Without Radar Detection	Client With Radar Detection
<i>Non-Occupancy Period</i>	Yes	Not required	Yes
<i>DFS Detection Threshold</i>	Yes	Not required	Yes
<i>Channel Availability Check Time</i>	Yes	Not required	Not required
<i>U-NII Detection Bandwidth</i>	Yes	Not required	Yes

Applicability of DFS requirements during normal operation

Requirement	Operational Mode	
	Master Device or Client with Radar Detection	Client Without Radar Detection
<i>DFS Detection Threshold</i>	Yes	Not required
<i>Channel Closing Transmission Time</i>	Yes	Yes
<i>Channel Move Time</i>	Yes	Yes
<i>U-NII Detection Bandwidth</i>	Yes	Not required

The operational behavior and individual DFS requirements that are associated with these modes are as follows: as per KDB 905462 D02 UNII DFS Compliance Procedures New Rules v02

Client Devices

- A *Client Device* will not transmit before having received appropriate control signals from a *Master Device*.
- A *Client Device* will stop all its transmissions whenever instructed by a *Master Device* to which it is associated and will meet the *Channel Move Time* and *Channel Closing Transmission Time* requirements. The *Client Device* will not resume any transmissions until it has again received control signals from a *Master Device*.
- If a *Client Device* is performing *In-Service Monitoring* and detects a *Radar Waveform* above the *DFS Detection Threshold*, it will inform the *Master Device*. This is equivalent to the *Master Device* detecting the *Radar Waveform* and d) through f) of section 5.1.1 apply.
- Irrespective of *Client Device* or *Master Device* detection the *Channel Move Time* and *Channel Closing Transmission Time* requirements remain the same.
- The client test frequency must be monitored to ensure no transmission of any type has occurred for 30 minutes. Note: If the client moves with the master, the device is considered compliant if nothing appears in the client non-occupancy period test. For devices that shut down (rather than moving channels), no beacons should appear.

DFS Detection Thresholds

below provides the *DFS Detection Thresholds* for *Master Devices* as well as *Client Devices* incorporating *In-Service Monitoring*.

DFS Detection Thresholds for Master Devices and Client Devices with Radar Detection

Maximum Transmit Power	Value (See Notes 1, 2, and 3)
EIRP $\geq$ 200 milliwatt	-64 dBm
EIRP $<$ 200 milliwatt and power spectral density $<$ 10 dBm/MHz	-62 dBm
EIRP $<$ 200 milliwatt that do not meet the power spectral density requirement	-64 dBm
Note 1: This is the level at the input of the receiver assuming a 0 dBi receive antenna. Note 2: Throughout these test procedures an additional 1 dB has been added to the amplitude of the test transmission waveforms to account for variations in measurement equipment. This will ensure that the test signal is at or above the detection threshold level to trigger a DFS response. Note3: EIRP is based on the highest antenna gain. For MIMO devices refer to KDB Publication 662911 D01.	

Response Requirements

provides the response requirements for *Master* and *Client Devices* incorporating DFS.

DFS Response Requirement Values

Parameter	Value
<i>Non-occupancy period</i>	Minimum 30 minutes
<i>Channel Availability Check Time</i>	60 seconds
<i>Channel Move Time</i>	10 seconds See Note 1.
<i>Channel Closing Transmission Time</i>	200 milliseconds + an aggregate of 60 milliseconds over remaining 10 second period. See Notes 1 and 2.
<i>U-NII Detection Bandwidth</i>	Minimum 100% of the U- NII 99% transmission power bandwidth. See Note 3.
Note 1: <i>Channel Move Time</i> and the <i>Channel Closing Transmission Time</i> should be performed with Radar Type 0. The measurement timing begins at the end of the Radar Type 0 burst. Note 2: The <i>Channel Closing Transmission Time</i> is comprised of 200 milliseconds starting at the beginning of the <i>Channel Move Time</i> plus any additional intermittent control signals required to facilitate a <i>Channel</i> move (an aggregate of 60 milliseconds) during the remainder of the 10 second period. The aggregate duration of control signals will not count quiet periods in between transmissions. Note 3: During the <i>U-NII Detection Bandwidth</i> detection test, radar type 0 should be used. For each frequency step the minimum percentage of detection is 90 percent. Measurements are performed with no data traffic.	

Prüfbericht - Nr.:
Test Report No.:

ULR-TC568821300000034F

Seite 99 von 143
Page 99 of 143

Note :

1. This UUT is classified as Client device without radar detection capabilities, hence only *Channel Move Time* and *Channel Closing Transmission Time* are applicable
2. *Channel Move Time* and *Channel Closing Transmission Time* is performed with Radar Type 0
3. *U-NII Detection Bandwidth* is not applicable for this device

Test Condition:

Normal Test Condition:

Temperature (Norm) = + 25 °C

Voltage = 5.0 V DC

Relative humidity: 62 %

KDB Guidelines applied:

Measurements were made following the guidelines of 905462 D02 UNII DFS Compliance Procedures New Rules v02 & 905462 D03 Client Without DFS New Rules v01r02

Test results:


DFS In-Service Monitoring

UNII band : UNII 2a

Channel Bandwidth : 20MHz


Operating Frequency (MHz)	Test	Measured Value	Limit
5320	Channel move Time	0.579 s	10 sec
	Channel Closing Transmission Time	0.784 ms + 1.424 ms	200 milliseconds + an aggregate of 60 milliseconds over remaining 10 second period
	Non Occupancy Time	0	Min 30 minutes

Channel Move Time




- Channel Move Time
- Threshold
- Start of Radar
- Trigger at end of Radar
- First 200ms of Channel Closing Tx Time
- 10sec Channel Move Time Limit
- Last measured edge of Channel Closing Tx Time

Channel Move Time first 200ms



Non-occupancy period



Prüfbericht - Nr.:
Test Report No.:


ULR-TC568821300000034F

Seite 101 von 143
Page 101 of 143

UNII band : UNII 2a
Channel Bandwidth : 40MHz


Operating Frequency (MHz)	Test	Measured Value	Limit
5260	Channel move Time	0.580 s	10 sec
	Channel Closing Transmission Time	0.704 ms + 1.424 ms	200 milliseconds + an aggregate of 60 milliseconds over remaining 10 second period
	Non Occupancy Time	0	Min 30 minutes

Channel Move Time




- Channel Move Time
- Threshold
- Start of Radar
- Trigger at end of Radar
- First 200ms of Channel Closing Tx Time
- 10sec Channel Move Time Limit
- Last measured edge of Channel Closing Tx Time

Channel Move Time first 200ms



- Channel Move Time first 200ms
- Threshold
- Start of Radar
- Trigger at end of Radar
- First 200ms of Channel Closing Tx Time

Non-occupancy period




— Non-occupancy period — Threshold

UNII band : UNII 2c

Channel Bandwidth : 20MHz


Operating Frequency (MHz)	Test	Measured Value	Limit
5500	Channel move Time	0.575 s	10 sec
	Channel Closing Transmission Time	0.760 ms + 1.384ms	200 milliseconds + an aggregate of 60 milliseconds over remaining 10 second period
	Non Occupancy Time	0	Min 30 minutes

Channel Move Time




— Channel Move Time
— Threshold
- - - Start of Radar
- - - Trigger at end of Radar
- - - First 200ms of Channel Closing Tx Time
- - - 10sec Channel Move Time Limit
- - - Last measured edge of Channel Closing Tx Time

Channel Move Time first 200ms



— Channel Move Time first 200ms
- - - Start of Radar
- - - First 200ms of Channel Closing Tx Time
— Threshold
- - - Trigger at end of Radar

Non-occupancy period




— Non-occupancy period
— Threshold

UNII band : UNII 2c
Channel Bandwidth : 40MHz


Operating Frequency (MHz)	Test	Measured Value	Limit
5700	Channel move Time	2.056 s	10 sec
	Channel Closing Transmission Time	0.704 ms + 1.180ms	200 milliseconds + an aggregate of 60 milliseconds over remaining 10 second period
	Non Occupancy Time	0	Min 30 minutes

Channel Move Time




- Channel Move Time
- Threshold
- Start of Radar
- Trigger at end of Radar
- First 200ms of Channel Closing Tx Time
- 10sec Channel Move Time Limit
- Last measured edge of Channel Closing Tx Time

Channel Move Time first 200ms



- Channel Move Time first 200ms
- Threshold
- Start of Radar
- First 200ms of Channel Closing Tx Time
- Trigger at end of Radar

Non-occupancy period



— Non-occupancy period — Threshold

8.5 Spurious Radiated Emissions & Restricted Bands of Operation

Result **Pass**

Test Specification	FCC part 15 Subpart C Section 15.407 (b) (15.205 & 15.209) / RSS 247 Issue 2 Section 6.2.1; 6.2.2; 6.2.3; 6.2.4 / RSS Gen Issue 5 Section 8.9 & 8.10
Test Method	ANSI C 63.10 – 2013
Measurement Bandwidth	100kHz for below 1GHz 1MHz for above 1GHz
Measurement Location	Semi Anechoic Chamber 30MHz - 1 GHz Fully Anechoic Chamber 1 GHz - 40GHz
Measuring Distance	3 m
Detector	Refer Remark
Requirement	As per the limits mentioned in the below table
Test setup	Refer TEST METHODOLOGY

Limit:

Table 6: Undesirable emission limits

Frequency Band	Limit
5.15-5.25 GHz	e.i.r.p. -27dBm [68.2 dBuV/3m]
5.25-5.35 GHz	e.i.r.p. -27dBm [68.2 dBuV/3m]
5.47-5.725 GHz	e.i.r.p. -27dBm [68.2 dBuV/3m]
5.725-5.85 GHz	5.715 GHz to 5.725 GHz - e.i.r.p. -17dBm [78.2 dBuV/3m] 5.85 GHz to 5.86 GHz - e.i.r.p. -17dBm [78.2 dBuV/3m] other frequency range - e.i.r.p. -27dBm [68.2 dBuV/3m]

Prüfbericht - Nr.:
Test Report No.:

ULR-TC568821300000034F

Seite 107 von 143
Page 107 of 143

Table 7: Transmitter limits for Radiated emission

Frequency (MHz)	Field strength (μV/m)	Field strength (dBμV/m)	Distance of Measurement (m)
0.009 – 0.490	2400/F(kHz)	48.50 – 13.80	300*
0.490 – 1.705	24000/F(kHz)	33.80 – 23.00	30*
1.705 -30	30	29.54	30*
30-88	100	40.0	3
88-216	150	43.5	3
216-960	200	46.0	3
Above 960	500	54.0	3

Remark: * The limit shows in the table above of frequency range 0.009 – 0.490, 0.490 – 1.705 MHz and 1.705-30MHz is at 300 meter, 30 meter and 30 meter range respectively, which corresponds to 128.51 – 93.80, 73.80 – 62.96 and 69.54 dBμV/m at 3m range by extrapolation calculation and the measurement of loop antenna.

The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9–90 kHz, 110–490 kHz and above 1000 MHz Radiated emission limits in these three bands are based on measurements employing an average detector.

Test Condition:

Normal Test Condition:

Temperature (Norm) = + 25 °C

Voltage = 5.0 V DC

Relative humidity: 62 %

Prüfbericht - Nr.:
Test Report No.:

ULR-TC568821300000034F

Seite 108 von 143
Page 108 of 143

Test results:


Note: All the losses are included during measurement and final values are mentioned in the test report. Refer TEST METHODOLOGY for more details

Test results for Frequency range : 9kHz – 30MHz

No Emissions found in the frequency range 9kHz – 30MHz


Test results for frequency range 30MHz – 1GHz

Antenna Polarization	Measured Frequency (MHz)	Measured value (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
Vertical	80.02	27.24	40.00	-12.76
	119.97	28.78	43.50	-14.72
	139.46	29.50	43.50	-14.00
	177.53	30.40	43.50	-13.10
	290.57	27.91	46.00	-18.09
	341.14	25.70	46.00	-20.30
	495.08	40.38	46.00	-5.62
	540.28	29.01	46.00	-16.99
Horizontal	79.96	26.53	40.00	-13.47
	119.97	27.60	43.50	-15.90
	141.95	32.71	43.50	-10.79
	177.53	31.06	43.50	-12.44
	316.69	31.90	46.00	-14.10
	356.75	31.95	46.00	-14.05
	396.02	34.00	46.00	-12.00
	490.42	30.22	46.00	-15.78




Channel Frequency 30MHz – 200MHz

Polarization Vertical




Channel Frequency 30MHz – 200MHz

Polarization Horizontal



Channel Frequency 200MHz – 1GHz

Polarization Vertical



Channel Frequency 200MHz – 1GHz

Polarization Horizontal

Prüfbericht - Nr.:
Test Report No.:

ULR-TC568821300000034F

Seite 111 von 143
Page 111 of 143

Test results for frequency range – 1GHz to 40 GHz

Modulation: 802.11a
Data rate: 6Mbps

Channel Frequency (MHz)	Frequency (MHz)	Polarization	Emission (dBµV/m)	Limit (dBm)	Margin (dB)
5180	5180 (Pk)	Vertical	104.86	*	-
	5180 (Av)		95.65	*	-
	5150 (Pk)		59.54	74	-14.46
	5150 (Av)		46.47	54	-7.53
	10360 (Pk)		49.91	68.23	-18.32
	10360 (Av)		37.96	68.23	-30.27
	15540 (Pk)		53.06	68.23	-15.17
	15540 (Av)		40.98	68.23	-27.25
	5180 (Pk)	Horizontal	98.91	*	-
	5180 (Av)		89.65	*	-
	5150 (Pk)		54.11	74	-19.89
	5150 (Av)		41.46	54	-12.54
	10360 (Pk)		49.30	68.23	-18.93
	10360 (Av)		37.82	68.23	-30.41
	15540 (Pk)		52.89	68.23	-15.34
	15540 (Av)		40.82	68.23	-27.41
5240	5240 (Pk)	Vertical	106.64	*	-
	5240 (Av)		98.85	*	-
	5350 (Pk)		50.67	74	-23.33
	5350 (Av)		37.88	54	-16.12
	10480 (Pk)		50.75	68.23	-17.48
	10480 (Av)		38.04	68.23	-30.19
	15720 (Pk)		52.98	68.23	-15.25
	15720 (Av)		40.38	68.23	-27.85
	5240 (Pk)	Horizontal	98.27	*	-
	5240 (Av)		88.68	*	-
	5350 (Pk)		45.18	74	-28.82
	5350 (Av)		33.46	54	-20.54
	10480 (Pk)		49.90	68.23	-18.33
	10480 (Av)		38.13	68.23	-30.10
	15720 (Pk)		52.99	68.23	-15.24
	15720 (Av)		40.76	68.23	-27.47

Note:

* :- Indicate restricted band frequency in 15.205

Pk: Peak Detector; Av: Average Detector

Prüfbericht - Nr.:
Test Report No.:

ULR-TC568821300000034F

Seite 112 von 143
Page 112 of 143

5260	5260 (Pk)	Vertical	98.32	*	-
	5260 (Av)		88.88	*	-
	5350 (Pk)		44.43	74	-29.57
	5350 (Av)		33.42	54	-20.58
	10520 (Pk)		49.86	68.23	-18.37
	10520 (Av)		37.77	68.23	-30.46
	15780 (Pk)		51.56	68.23	-16.67
	15780 (Av)		39.25	68.23	-28.98
	5260 (Pk)	Horizontal	98.68	*	-
	5260 (Av)		88.96	*	-
	5350 (Pk)		45.52	74	-28.48
	5350 (Av)		33.47	54	-20.53
	10520 (Pk)		50.13	68.23	-18.10
	10520 (Av)		37.71	68.23	-30.52
	15780 (Pk)		53.02	68.23	-15.21
	15780 (Av)		39.23	68.23	-29.00
5320	5320 (Pk)	Vertical	106.42	*	-
	5320 (Av)		96.99	*	-
	5350 (Pk)		60.27	74	-13.73
	5350 (Av)		46.66	54	-7.34
	10640 (Pk)		49.89	68.23	-18.34
	10640 (Av)		37.75	68.23	-30.48
	15960 (Pk)		51.27	68.23	-16.96
	15960 (Av)		39.18	68.23	-29.05
	5320 (Pk)	Horizontal	97.74	*	-
	5320 (Av)		88.30	*	-
	5350 (Pk)		51.11	74	-22.89
	5350 (Av)		37.38	54	-16.62
	10640 (Pk)		50.33	68.23	-17.90
	10640 (Av)		37.71	68.23	-30.52
	15960 (Pk)		51.50	68.23	-16.73
	15960 (Av)		39.25	68.23	-28.98
5500	5500 (Pk)	Vertical	107.35	*	-
	5500 (Av)		97.27	*	-
	5460 (Pk)		63.44	74	-10.56
	5460 (Av)		51.55	54	-2.45
	11000 (Pk)		49.21	68.23	-19.02
	11000 (Av)		37.36	68.23	-30.87
	16500 (Pk)		52.63	68.23	-15.60
	16500 (Av)		40.30	68.23	-27.93
	5500 (Pk)	Horizontal	97.17	*	-
	5500 (Av)		87.57	*	-
	5460 (Pk)		54.06	74	-19.94
	5460 (Av)		41.81	54	-12.19
	11000 (Pk)		49.94	68.23	-18.29
	11000 (Av)		37.26	68.23	-30.97
	16500 (Pk)		52.39	68.23	-15.84
	16500 (Av)		40.31	68.23	-27.92

Note:

* :- Indicate restricted band frequency in 15.205

Pk: Peak Detector; Av: Average Detector

Prüfbericht - Nr.:
Test Report No.:

ULR-TC568821300000034F

Seite 113 von 143
Page 113 of 143

5700	5700 (Pk)	Vertical	106.56	*	-
	5700 (Av)		96.81	*	-
	5460 (Pk)		43.43	74	-30.57
	5460 (Av)		31.50	54	-22.50
	11400 (Pk)		50.94	68.23	-17.29
	11400 (Av)		38.79	68.23	-29.44
	17100 (Pk)		56.25	68.23	-11.98
	17100 (Av)		42.49	68.23	-25.74
	5700 (Pk)	Horizontal	96.39	*	-
	5700 (Av)		86.64	*	-
	5460 (Pk)		42.63	74	-31.37
	5460 (Av)		29.28	54	-24.72
	11400 (Pk)		49.99	68.23	-18.24
	11400 (Av)		37.76	68.23	-30.47
	17100 (Pk)		54.84	68.23	-13.39
	17100 (Av)		42.56	68.23	-25.67
5720	5720 (Pk)	Vertical	106.01	*	-
	5720 (Av)		96.17	*	-
	5460 (Pk)		47.74	74	-26.26
	5460 (Av)		35.81	54	-18.19
	11440 (Pk)		50.67	68.23	-17.56
	11440 (Av)		39.62	68.23	-28.61
	17160 (Pk)		No Harmonics Found		
	17160 (Av)				
	5720 (Pk)	Horizontal	85.40	*	-
	5720 (Av)		95.20	*	-
	5460 (Pk)		47.43	74	-26.57
	5460 (Av)		34.27	54	-19.73
	11440 (Pk)		50.16	68.23	-18.07
	11440 (Av)		38.05	68.23	-30.18
	17160 (Pk)		No Harmonics Found		
	17160 (Av)				
5745	5715(Pk)	Vertical	50.43	78.2	-27.77
	5725(Pk)		54.81	78.2	-23.39
	5745 (Pk)		103.55	*	-
	5745 (Av)		94.01	*	-
	11490 (Pk)		54.96	68.23	-13.27
	11490 (Av)		41.33	68.23	-26.90
	17235 (Pk)		55.08	68.23	-13.15
	17235 (Av)		42.62	68.23	-25.61
	5715(Pk)	Horizontal	43.39	78.2	-34.81
	5725(Pk)		46.12	78.2	-32.08
	5745 (Pk)		92.76	*	-
	5745 (Av)		83.07	*	-
	11490 (Pk)		50.50	68.23	-17.73
	11490 (Av)		38.21	68.23	-30.02
	17235 (Pk)		54.96	68.23	-13.27
	17235 (Av)		42.61	68.23	-25.62

Prüfbericht - Nr.:
Test Report No.:

ULR-TC568821300000034F

Seite 114 von 143
Page 114 of 143

5825	5825 (Pk)	Vertical	103.67	*	-
	5825 (Av)		94.16	*	-
	5850 (Pk)		51.03	78.2	-27.17
	5860 (Pk)		48.76	78.2	-29.44
	11650 (Pk)		56.24	68.23	-11.99
	11650 (Av)		42.91	68.23	-25.32
	17475 (Pk)		54.98	68.23	-13.25
	17475 (Av)		42.78	68.23	-25.45
	5825 (Pk)	Horizontal	94.25	*	-
	5825 (Av)		84.59	*	-
	5850 (Pk)		45.43	78.2	-32.77
	5860 (Pk)		42.80	78.2	-35.40
	11650 (Pk)		51.13	68.23	-17.10
	11650 (Av)		38.41	68.23	-29.82
	17475 (Pk)		55.31	68.23	-12.92
	17475 (Av)		42.83	68.23	-25.40

Note:

* :- Indicate restricted band frequency in 15.205

Pk: Peak Detector; Av: Average Detector

Prüfbericht - Nr.:
Test Report No.:

ULR-TC568821300000034F

Seite 115 von 143
Page 115 of 143

Modulation: 802.11a
Data rate: 54Mbps

Channel Frequency (MHz)	Frequency (MHz)	Polarization	Emission (dBμV/m)	Limit (dBm)	Margin (dB)
5180	5180 (Pk)	Vertical	105.18	*	-
	5180 (Av)		92.11	*	-
	5150 (Pk)		63.98	74	-10.02
	5150 (Av)		51.18	54	-2.82
	10360 (Pk)		49.99	68.23	-18.24
	10360 (Av)		37.50	68.23	-30.73
	15540 (Pk)		51.93	68.23	-16.30
	15540 (Av)		40.19	68.23	-28.04
	5180 (Pk)	Horizontal	96.92	*	-
	5180 (Av)		83.26	*	-
	5150 (Pk)		54.85	74	-19.15
	5150 (Av)		41.32	54	-12.68
	10360 (Pk)		49.43	68.23	-18.80
	10360 (Av)		37.46	54	-16.54
	15540 (Pk)		52.00	68.23	-16.23
	15540 (Av)		40.18	54	-13.82
5240	5240 (Pk)	Vertical	97.37	*	-
	5240 (Av)		83.88	*	-
	5350 (Pk)		45.10	74	-28.90
	5350 (Av)		33.24	54	-20.76
	10480 (Pk)		49.87	68.23	-18.36
	10480 (Av)		37.80	68.23	-30.43
	15720 (Pk)		52.00	68.23	-16.23
	15720 (Av)		39.57	68.23	-28.66
	5240 (Pk)	Horizontal	97.37	*	-
	5240 (Av)		83.85	*	-
	5350 (Pk)		45.84	74	-28.16
	5350 (Av)		33.29	54	-20.71
	10480 (Pk)		50.17	68.23	-18.06
	10480 (Av)		37.84	68.23	-30.39
	15720 (Pk)		51.51	68.23	-16.72
	15720 (Av)		39.61	68.23	-28.62
5260	5260 (Pk)	Vertical	104.70	*	-
	5260 (Av)		91.47	*	-
	5350 (Pk)		49.76	74	-24.24
	5350 (Av)		37.37	54	-16.63
	10520 (Pk)		50.48	68.23	-17.75
	10520 (Av)		37.54	68.23	-30.69
	15780 (Pk)		51.58	68.23	-16.65
	15780 (Av)		38.99	68.23	-29.24
	5260 (Pk)	Horizontal	98.13	*	-
	5260 (Av)		84.57	*	-
	5350 (Pk)		45.65	74	-28.35
	5350 (Av)		33.32	54	-20.68
	10520 (Pk)		49.82	68.23	-18.41
	10520 (Av)		37.60	68.23	-30.63
	15780 (Pk)		50.79	68.23	-17.44
	15780 (Av)		39.07	68.23	-29.16

Prüfbericht - Nr.:
Test Report No.:

ULR-TC568821300000034F

Seite 116 von 143
Page 116 of 143

5320	5320 (Pk)	Vertical	106.25	*	-
	5320 (Av)		92.79	*	-
	5350 (Pk)		58.93	74	-15.07
	5350 (Av)		43.46	54	-10.54
	10640 (Pk)		49.87	68.23	-18.36
	10640 (Av)		37.66	68.23	-30.57
	15960 (Pk)		51.01	68.23	-17.22
	15960 (Av)		39.07	68.23	-29.16
	5320 (Pk)	Horizontal	97.02	*	-
	5320 (Av)		83.61	*	-
	5350 (Pk)		51.48	74	-22.52
	5350 (Av)		35.04	54	-18.96
	10640 (Pk)		49.80	68.23	-18.43
	10640 (Av)		37.60	68.23	-30.63
	15960 (Pk)		51.13	68.23	-17.10
	15960 (Av)		39.09	68.23	-29.14
5500	5500 (Pk)	Vertical	106.07	*	-
	5500 (Av)		92.74	*	-
	5460 (Pk)		64.28	74	-9.72
	5460 (Av)		51.51	54	-2.49
	11000 (Pk)		49.14	68.23	-19.09
	11000 (Av)		37.33	68.23	-30.90
	16500 (Pk)		52.79	68.23	-15.44
	16500 (Av)		40.31	68.23	-27.92
	5500 (Pk)	Horizontal	96.02	*	-
	5500 (Av)		81.92	*	-
	5460 (Pk)		53.30	74	-20.70
	5460 (Av)		41.72	54	-12.28
	11000 (Pk)		49.01	68.23	-19.22
	11000 (Av)		37.23	68.23	-31.00
	16500 (Pk)		51.81	68.23	-16.42
	16500 (Av)		40.31	68.23	-27.92
5700	5700 (Pk)	Vertical	105.59	*	-
	5700 (Av)		92.04	*	-
	5460 (Pk)		44.47	74	-29.53
	5460 (Av)		30.65	54	-23.35
	11400 (Pk)		50.69	68.23	-17.54
	11400 (Av)		38.59	68.23	-29.64
	17100 (Pk)		54.90	68.23	-13.33
	17100 (Av)		42.61	68.23	-25.62
	5700 (Pk)	Horizontal	98.08	*	-
	5700 (Av)		84.37	*	-
	5460 (Pk)		41.83	74	-32.17
	5460 (Av)		28.98	54	-25.02
	11400 (Pk)		49.85	68.23	-18.38
	11400 (Av)		37.59	68.23	-30.64
	17100 (Pk)		55.21	68.23	-13.02
	17100 (Av)		42.54	68.23	-25.69

Prüfbericht - Nr.:
Test Report No.:

ULR-TC568821300000034F

Seite 117 von 143
Page 117 of 143

5720	5720 (Pk)	Vertical	105.35	*	-
	5720 (Av)		95.53	*	-
	5460 (Pk)		48.91	74	-25.09
	5460 (Av)		35.92	54	-18.08
	11440 (Pk)		51.66	68.23	-16.57
	11440 (Av)		39.10	68.23	-29.13
	17160 (Pk)		No Harmonics Found		
	17160 (Av)				
	5720 (Pk)	Horizontal	94.04	*	-
	5720 (Av)		84.51	*	-
	5460 (Pk)		47.07	74	-26.93
	5460 (Av)		34.26	54	-19.74
	11440 (Pk)		49.40	68.23	-18.83
	11440 (Av)		37.99	68.23	-30.24
	17160 (Pk)		No Harmonics Found		
	17160 (Av)				
5745	5715(Pk)	Vertical	54.85	78.2	-23.35
	5725(Pk)		68.72	78.2	-9.48
	5745 (Pk)		103.14	*	-
	5745 (Av)		89.76	*	-
	11490 (Pk)		53.78	68.23	-14.45
	11490 (Av)		39.42	68.23	-28.81
	17235 (Pk)		54.74	68.23	-13.49
	17235 (Av)		42.70	68.23	-25.53
	5715(Pk)	Horizontal	48.20	78.2	-30.00
	5725(Pk)		59.86	78.2	-18.34
	5745 (Pk)		96.53	*	-
	5745 (Av)		83.07	*	-
	11490 (Pk)		50.14	68.23	-18.09
	11490 (Av)		38.21	68.23	-30.02
	17235 (Pk)		54.73	68.23	-13.50
	17235 (Av)		42.71	68.23	-25.52
5825	5825 (Pk)	Vertical	104.45	*	-
	5825 (Av)		91.14	*	-
	5850 (Pk)		56.88	78.2	-21.32
	5860 (Pk)		50.93	78.2	-27.27
	11650 (Pk)		55.05	68.23	-13.18
	11650 (Av)		40.43	68.23	-27.80
	17475 (Pk)		54.75	68.23	-13.48
	17475 (Av)		42.85	68.23	-25.38
	5825 (Pk)	Horizontal	97.03	*	-
	5825 (Av)		82.71	*	-
	5850 (Pk)		49.46	78.2	-28.74
	5860 (Pk)		44.74	78.2	-33.46
	11650 (Pk)		51.14	68.23	-17.09
	11650 (Av)		38.27	68.23	-29.96
	17475 (Pk)		55.84	68.23	-12.39
	17475 (Av)		42.82	68.23	-25.41

Note:

* :- Indicate restricted band frequency in 15.205

Pk: Peak Detector; Av: Average Detector

Prüfbericht - Nr.:

ULR-TC568821300000034F

Seite 118 von 143

Test Report No.:

Page 118 of 143

Modulation: 802.11n _ HT 20MHz

Data rate: MCS0

Channel Frequency (MHz)	Frequency (MHz)	Polarization	Emission (dBμV/m)	Limit (dBm)	Margin (dB)
5180	5180 (Pk)	Vertical	105.72	*	-
	5180 (Av)		95.37	*	-
	5150 (Pk)		62.10	74	-11.90
	5150 (Av)		51.00	54	-3.00
	10360 (Pk)		49.73	68.23	-18.50
	10360 (Av)		38.40	68.23	-29.83
	15540 (Pk)		52.43	68.23	-15.80
	15540 (Av)		40.35	68.23	-27.88
	5180 (Pk)	Horizontal	94.92	*	-
	5180 (Av)		85.32	*	-
	5150 (Pk)		52.88	74	-21.12
	5150 (Av)		41.22	54	-12.78
	10360 (Pk)		50.22	68.23	-18.01
	10360 (Av)		37.59	68.23	-30.64
	15540 (Pk)		53.44	68.23	-14.79
	15540 (Av)		40.30	68.23	-27.93
5240	5240 (Pk)	Vertical	106.44	*	-
	5240 (Av)		96.41	*	-
	5350 (Pk)		54.74	74	-19.26
	5350 (Av)		42.02	54	-11.98
	10480 (Pk)		50.80	68.23	-17.43
	10480 (Av)		37.96	68.23	-30.27
	15720 (Pk)		53.10	68.23	-15.13
	15720 (Av)		39.70	68.23	-28.53
	5240 (Pk)	Horizontal	95.00	*	-
	5240 (Av)		85.37	*	-
	5350 (Pk)		43.08	74	-30.92
	5350 (Av)		30.84	54	-23.16
	10480 (Pk)		50.33	68.23	-17.90
	10480 (Av)		37.98	68.23	-30.25
	15720 (Pk)		52.08	68.23	-16.15
	15720 (Av)		39.68	68.23	-28.55

Prüfbericht - Nr.:
Test Report No.:

ULR-TC568821300000034F

Seite 119 von 143
Page 119 of 143

5260	5260 (Pk)	Vertical	106.61	*	-
	5260 (Av)		96.78	*	-
	5350 (Pk)		54.00	74	-20.00
	5350 (Av)		42.09	54	-11.91
	10520 (Pk)		49.88	68.23	-18.35
	10520 (Av)		37.79	68.23	-30.44
	15780 (Pk)		51.07	68.23	-17.16
	15780 (Av)		39.14	68.23	-29.09
	5260 (Pk)	Horizontal	95.37	*	-
	5260 (Av)		85.35	*	-
	5350 (Pk)		43.32	74	-30.68
	5350 (Av)		30.96	54	-23.04
	10520 (Pk)		49.93	68.23	-18.30
	10520 (Av)		37.76	68.23	-30.47
	15780 (Pk)		51.29	68.23	-16.94
	15780 (Av)		39.14	68.23	-29.09
5320	5320 (Pk)	Vertical	106.45	*	-
	5320 (Av)		97.04	*	-
	5350 (Pk)		57.87	74	-16.13
	5350 (Av)		44.58	54	-9.42
	10640 (Pk)		50.11	68.23	-18.12
	10640 (Av)		37.74	68.23	-30.49
	15960 (Pk)		51.16	68.23	-17.07
	15960 (Av)		39.07	68.23	-29.16
	5320 (Pk)	Horizontal	94.72	*	-
	5320 (Av)		84.72	*	-
	5350 (Pk)		46.36	74	-27.64
	5350 (Av)		33.93	54	-20.07
	10640 (Pk)		49.33	68.23	-18.90
	10640 (Av)		37.68	68.23	-30.55
	15960 (Pk)		51.14	68.23	-17.09
	15960 (Av)		39.04	68.23	-29.19
5500	5500 (Pk)	Vertical	106.50	*	-
	5500 (Av)		96.58	*	-
	5460 (Pk)		63.54	74	-10.46
	5460 (Av)		51.60	54	-2.40
	11000 (Pk)		50.53	68.23	-17.70
	11000 (Av)		37.43	68.23	-30.80
	16500 (Pk)		52.33	68.23	-15.90
	16500 (Av)		40.34	68.23	-27.89
	5500 (Pk)	Horizontal	94.61	*	-
	5500 (Av)		85.05	*	-
	5460 (Pk)		54.00	74	-20.00
	5460 (Av)		41.78	54	-12.22
	11000 (Pk)		49.53	68.23	-18.70
	11000 (Av)		37.30	68.23	-30.93
	16500 (Pk)		52.78	68.23	-15.45
	16500 (Av)		40.32	68.23	-27.91

Prüfbericht - Nr.:
Test Report No.:

ULR-TC568821300000034F

Seite 120 von 143
Page 120 of 143

5720	5720 (Pk)	Vertical	104.13	*	-
	5720 (Av)		94.27	*	-
	5460 (Pk)		49.22	74	-24.78
	5460 (Av)		35.03	54	-18.97
	11440 (Pk)		50.47	68.23	-17.76
	11440 (Av)		38.78	68.23	-29.45
	17160 (Pk)		No Harmonics Found		
	17160 (Av)				
	5720 (Pk)	Horizontal	93.90	*	-
	5720 (Av)		84.22	*	-
	5460 (Pk)		48.10	74	-25.90
	5460 (Av)		34.27	54	-19.73
	11440 (Pk)		50.95	68.23	-17.28
	11440 (Av)		38.03	68.23	-30.20
	17160 (Pk)		No Harmonics Found		
	17160 (Av)				
5700	5700 (Pk)	Vertical	105.47	*	-
	5700 (Av)		95.75	*	-
	5460 (Pk)		45.89	74	-28.11
	5460 (Av)		32.26	54	-21.74
	11400 (Pk)		50.66	68.23	-17.57
	11400 (Av)		38.27	68.23	-29.96
	17100 (Pk)		55.22	68.23	-13.01
	17100 (Av)		42.67	68.23	-25.56
	5700 (Pk)	Horizontal	94.93	*	-
	5700 (Av)		85.26	*	-
	5460 (Pk)		41.66	74	-32.34
	5460 (Av)		28.97	54	-25.03
	11400 (Pk)		50.19	68.23	-18.04
	11400 (Av)		37.44	68.23	-30.79
	17100 (Pk)		54.67	68.23	-13.56
	17100 (Av)		42.68	68.23	-25.55
5745	5715(Pk)	Vertical	52.15	78.2	-26.05
	5725(Pk)		55.72	78.2	-22.48
	5745 (Pk)		104.57	*	-
	5745 (Av)		95.03	*	-
	11490 (Pk)		52.50	68.23	-15.73
	11490 (Av)		40.20	68.23	-28.03
	17235 (Pk)		55.16	68.23	-13.07
	17235 (Av)		42.71	68.23	-25.52
	5715(Pk)	Horizontal	45.07	78.2	-33.13
	5725(Pk)		45.94	78.2	-32.26
	5745 (Pk)		95.32	*	-
	5745 (Av)		85.72	*	-
	11490 (Pk)		50.75	68.23	-17.48
	11490 (Av)		38.03	68.23	-30.20
	17235 (Pk)		55.14	68.23	-13.09
	17235 (Av)		42.67	68.23	-25.56

Prüfbericht - Nr.:
Test Report No.:

ULR-TC568821300000034F

Seite 121 von 143
Page 121 of 143

5825	5825 (Pk)	Vertical	105.08	*	-
	5825 (Av)		94.91	*	-
	5850 (Pk)		51.24	78.2	-26.96
	5860 (Pk)		49.52	78.2	-28.68
	11650 (Pk)		55.29	68.23	-12.94
	11650 (Av)		41.88	68.23	-26.35
	17475 (Pk)		54.87	68.23	-13.36
	17475 (Av)		42.78	68.23	-25.45
	5825 (Pk)	Horizontal	95.71	*	-
	5825 (Av)		85.74	*	-
	5850 (Pk)		46.31	78.2	-31.89
	5860 (Pk)		44.00	78.2	-34.20
	11650 (Pk)		50.05	68.23	-18.18
	11650 (Av)		38.09	68.23	-30.14
	17475 (Pk)		55.59	68.23	-12.64
	17475 (Av)		42.80	68.23	-25.43

Note:

* :- Indicate restricted band frequency in 15.205

Pk: Peak Detector; Av: Average Detector

Prüfbericht - Nr.:

Test Report No.:

ULR-TC568821300000034F

Seite 122 von 143

Page 122 of 143

Modulation: 802.11n _ HT 20MHz

Data rate: MCS7

Channel Frequency (MHz)	Frequency (MHz)	Polarization	Emission (dBμV/m)	Limit (dBm)	Margin (dB)
5180	5180 (Pk)	Vertical	107.14	*	-
	5180 (Av)		92.66	*	-
	5150 (Pk)		63.45	74	-10.55
	5150 (Av)		51.08	54	-2.92
	10360 (Pk)		49.01	68.23	-19.22
	10360 (Av)		36.76	68.23	-31.47
	15540 (Pk)		53.44	68.23	-14.79
	15540 (Av)		41.20	68.23	-27.03
	5180 (Pk)	Horizontal	97.07	*	-
	5180 (Av)		82.34	*	-
	5150 (Pk)		53.67	74	-20.33
	5150 (Av)		41.31	54	-12.69
	10360 (Pk)		48.54	68.23	-19.69
	10360 (Av)		36.51	68.23	-31.72
	15540 (Pk)		52.44	68.23	-15.79
	15540 (Av)		41.05	68.23	-27.18
5240	5240 (Pk)	Vertical	108.23	*	-
	5240 (Av)		93.13	*	-
	5350 (Pk)		54.16	74	-19.84
	5350 (Av)		42.00	54	-12.00
	10480 (Pk)		49.58	68.23	-18.65
	10480 (Av)		37.63	68.23	-30.60
	15720 (Pk)		52.46	68.23	-15.77
	15720 (Av)		40.05	68.23	-28.18
	5240 (Pk)	Horizontal	96.86	*	-
	5240 (Av)		82.19	*	-
	5350 (Pk)		43.54	74	-30.46
	5350 (Av)		30.87	54	-23.13
	10480 (Pk)		50.24	68.23	-17.99
	10480 (Av)		37.81	68.23	-30.42
	15720 (Pk)		52.56	68.23	-15.67
	15720 (Av)		40.17	68.23	-28.06

5260	5260 (Pk)	Vertical	108.55	*	-
	5260 (Av)		94.05	*	-
	5350 (Pk)		54.29	74	-19.71
	5350 (Av)		42.03	54	-11.97
	10520 (Pk)		50.63	68.23	-17.60
	10520 (Av)		37.76	68.23	-30.47
	15780 (Pk)		51.55	68.23	-16.68
	15780 (Av)		39.13	68.23	-29.10
	5260 (Pk)	Horizontal	96.74	*	-
	5260 (Av)		82.29	*	-
	5350 (Pk)		44.26	74	-29.74
	5350 (Av)		30.95	54	-23.05
	10520 (Pk)		50.38	68.23	-17.85
	10520 (Av)		37.76	68.23	-30.47
	15780 (Pk)		51.75	68.23	-16.48
	15780 (Av)		39.13	68.23	-29.10
5320	5320 (Pk)	Vertical	108.78	*	-
	5320 (Av)		94.21	*	-
	5350 (Pk)		60.70	74	-13.30
	5350 (Av)		44.80	54	-9.20
	10640 (Pk)		49.90	68.23	-18.33
	10640 (Av)		37.78	68.23	-30.45
	15960 (Pk)		51.66	68.23	-16.57
	15960 (Av)		39.08	68.23	-29.15
	5320 (Pk)	Horizontal	96.51	*	-
	5320 (Av)		82.02	*	-
	5350 (Pk)		50.31	74	-23.69
	5350 (Av)		35.22	54	-18.78
	10640 (Pk)		49.92	68.23	-18.31
	10640 (Av)		37.72	68.23	-30.51
	15960 (Pk)		51.26	68.23	-16.97
	15960 (Av)		39.13	68.23	-29.10
5500	5500 (Pk)	Vertical	108.73	*	-
	5500 (Av)		94.37	*	-
	5460 (Pk)		63.73	74	-10.27
	5460 (Av)		51.62	54	-2.38
	11000 (Pk)		49.76	68.23	-18.47
	11000 (Av)		37.43	68.23	-30.80
	16500 (Pk)		53.03	68.23	-15.20
	16500 (Av)		40.40	68.23	-27.83
	5500 (Pk)	Horizontal	95.77	*	-
	5500 (Av)		81.40	*	-
	5460 (Pk)		54.63	74	-19.37
	5460 (Av)		41.78	54	-12.22
	11000 (Pk)		49.63	68.23	-18.60
	11000 (Av)		37.88	68.23	-30.35
	16500 (Pk)		52.68	68.23	-15.55
	16500 (Av)		40.38	68.23	-27.85

Prüfbericht - Nr.:
Test Report No.:

ULR-TC568821300000034F

Seite 124 von 143
Page 124 of 143

5720	5720 (Pk)	Vertical	106.03	*	-
	5720 (Av)		90.79	*	-
	5460 (Pk)		47.86	74	-26.14
	5460 (Av)		34.83	54	-19.17
	11440 (Pk)		51.39	68.23	-16.84
	11440 (Av)		38.72	68.23	-29.51
	17160 (Pk)	Horizontal	No Harmonics Found		
	17160 (Av)				
	5720 (Pk)		81.20	*	-
	5720 (Av)		96.05	*	-
	5460 (Pk)		46.83	74	-27.17
	5460 (Av)		34.19	54	-19.81
	11440 (Pk)		50.38	68.23	-17.85
	11440 (Av)		37.99	68.23	-30.24
	17160 (Pk)		No Harmonics Found		
	17160 (Av)				
5700	5700 (Pk)	Vertical	107.28	*	-
	5700 (Av)		92.79	*	-
	5460 (Pk)		44.20	74	-29.80
	5460 (Av)		31.64	54	-22.36
	11400 (Pk)		50.22	68.23	-18.01
	11400 (Av)		38.05	68.23	-30.18
	17100 (Pk)	Horizontal	54.73	68.23	-13.50
	17100 (Av)		42.64	68.23	-25.59
	5700 (Pk)		97.50	*	-
	5700 (Av)		82.77	*	-
	5460 (Pk)		41.94	74	-32.06
	5460 (Av)		29.03	54	-24.97
	11400 (Pk)		49.96	68.23	-18.27
	11400 (Av)		37.44	68.23	-30.79
	17100 (Pk)		54.89	68.23	-13.34
	17100 (Av)		42.70	68.23	-25.53
5745	5715(Pk)	Vertical	56.51	78.2	-21.69
	5725(Pk)		70.01	78.2	-8.19
	5745 (Pk)		106.94	*	-
	5745 (Av)		92.38	*	-
	11490 (Pk)		51.87	68.23	-16.36
	11490 (Av)		39.72	68.23	-28.51
	17235 (Pk)	Horizontal	54.87	68.23	-13.36
	17235 (Av)		42.67	68.23	-25.56
	5715(Pk)		48.03	78.2	-30.17
	5725(Pk)		58.20	78.2	-20.00
	5745 (Pk)		97.19	*	-
	5745 (Av)		82.45	*	-
	11490 (Pk)		49.65	68.23	-18.58
	11490 (Av)		38.04	68.23	-30.19
	17235 (Pk)		54.82	68.23	-13.41
	17235 (Av)		42.67	68.23	-25.56

Prüfbericht - Nr.:

Test Report No.:

ULR-TC568821300000034F

Seite 125 von 143

Page 125 of 143

5825	5825 (Pk)	Vertical	106.48	*	-
	5825 (Av)		92.23	*	-
	5850 (Pk)		63.22	78.2	-14.98
	5860 (Pk)		51.29	78.2	-26.91
	11650 (Pk)		53.32	68.23	-14.91
	11650 (Av)		39.69	68.23	-28.54
	17475 (Pk)		54.79	68.23	-13.44
	17475 (Av)		42.78	68.23	-25.45
	5825 (Pk)	Horizontal	97.16	*	-
	5825 (Av)		82.74	*	-
	5850 (Pk)		52.10	78.2	-26.10
	5860 (Pk)		45.24	78.2	-32.96
	11650 (Pk)		50.43	68.23	-17.80
	11650 (Av)		38.01	68.23	-30.22
	17475 (Pk)		54.83	68.23	-13.40
	17475 (Av)		43.79	68.23	-24.44

Prüfbericht - Nr.:

ULR-TC568821300000034F

Seite 126 von 143

Test Report No.:

Page 126 of 143

Modulation: 802.11n _ HT 40MHz

Data rate: MCS0

Channel Frequency (MHz)	Frequency (MHz)	Polarization	Emission (dBμV/m)	Limit (dBm)	Margin (dB)
5190	5190 (Pk)	Vertical	103.70	*	-
	5190 (Av)		92.63	*	-
	5150 (Pk)		64.00	74	-10.00
	5150 (Av)		42.25	54	-11.75
	10380 (Pk)		47.96	68.23	-20.27
	10380 (Av)		35.00	68.23	-33.23
	15570 (Pk)		52.85	68.23	-15.38
	15570 (Av)		40.22	68.23	-28.01
	5190 (Pk)	Horizontal	91.20	*	-
	5190 (Av)		80.77	*	-
	5150 (Pk)		54.11	74	-19.89
	5150 (Av)		32.86	54	-21.14
	10380 (Pk)		47.00	68.23	-21.23
	10380 (Av)		35.03	68.23	-33.20
	15570 (Pk)		52.63	68.23	-15.60
	15570 (Av)		40.24	68.23	-27.99
5230	5230 (Pk)	Vertical	102.90	*	-
	5230 (Av)		92.74	*	-
	5150 (Pk)		56.07	74	-17.93
	5150 (Av)		35.15	54	-18.85
	10460 (Pk)		47.70	68.23	-20.53
	10460 (Av)		35.64	68.23	-32.59
	15690 (Pk)		52.23	68.23	-16.00
	15690 (Av)		40.05	68.23	-28.18
	5230 (Pk)	Horizontal	91.08	*	-
	5230 (Av)		80.61	*	-
	5150 (Pk)		46.53	74	-27.47
	5150 (Av)		30.35	54	-23.65
	10460 (Pk)		47.58	68.23	-20.65
	10460 (Av)		35.60	68.23	-32.63
	15690 (Pk)		52.22	68.23	-16.01
	15690 (Av)		40.02	68.23	-28.21

5270	5270 (Pk)	Vertical	103.40	*	-
	5270 (Av)		93.14	*	-
	5350 (Pk)		58.41	74	-15.59
	5350 (Av)		36.64	54	-17.36
	10540 (Pk)		48.57	68.23	-19.66
	10540 (Av)		36.12	68.23	-32.11
	15810 (Pk)		51.33	68.23	-16.90
	15810 (Av)		39.45	68.23	-28.78
	5270 (Pk)	Horizontal	91.73	*	-
	5270 (Av)		80.80	*	-
	5350 (Pk)		44.77	74	-29.23
	5350 (Av)		30.01	54	-23.99
	10540 (Pk)		48.92	68.23	-19.31
	10540 (Av)		36.15	68.23	-32.08
	15810 (Pk)		51.62	68.23	-16.61
	15810 (Av)		39.44	68.23	-28.79
5510	5510 (Pk)	Vertical	103.10	*	-
	5510 (Av)		93.05	*	-
	5460 (Pk)		62.22	74	-11.78
	5460 (Av)		43.53	54	-10.47
	11020 (Pk)		51.82	68.23	-16.41
	11020 (Av)		39.04	68.23	-29.19
	16530 (Pk)		52.65	68.23	-15.58
	16530 (Av)		40.27	68.23	-27.96
	5510 (Pk)	Horizontal	90.77	*	-
	5510 (Av)		80.24	*	-
	5460 (Pk)		51.88	74	-22.12
	5460 (Av)		32.68	54	-21.32
	11020 (Pk)		51.12	68.23	-17.11
	11020 (Av)		38.98	68.23	-29.25
	16530 (Pk)		52.62	68.23	-15.61
	16530 (Av)		40.34	68.23	-27.89
5590	5590 (Pk)	Vertical	102.71	*	-
	5590 (Av)		92.59	*	-
	5460 (Pk)		55.65	74	-18.35
	5460 (Av)		34.01	54	-19.99
	11180 (Pk)		51.39	68.23	-16.84
	11180 (Av)		39.00	68.23	-29.23
	16770 (Pk)		54.30	68.23	-13.93
	16770 (Av)		41.49	68.23	-26.74
	5590 (Pk)	Horizontal	90.60	*	-
	5590 (Av)		80.38	*	-
	5460 (Pk)		45.40	74	-28.60
	5460 (Av)		29.62	54	-24.38
	11180 (Pk)		50.54	68.23	-17.69
	11180 (Av)		38.79	68.23	-29.44
	16770 (Pk)		53.86	68.23	-14.37
	16770 (Av)		41.50	68.23	-26.73

Prüfbericht - Nr.:
Test Report No.:

ULR-TC568821300000034F

Seite 128 von 143
Page 128 of 143

5670	5670 (Pk)	Vertical	102.29	*	-
	5670 (Av)		92.19	*	-
	5460 (Pk)		49.12	74	-24.88
	5460 (Av)		32.88	54	-21.12
	11340 (Pk)		52.30	68.23	-15.93
	11340 (Av)		40.14	68.23	-28.09
	17010 (Pk)		52.90	68.23	-15.33
	17010 (Av)		40.61	68.23	-27.62
	5670 (Pk)	Horizontal	91.50	*	-
	5670 (Av)		81.37	*	-
	5460 (Pk)		42.46	74	-31.54
	5460 (Av)		29.63	54	-24.37
	11340 (Pk)		52.02	68.23	-16.21
	11340 (Av)		39.59	68.23	-28.64
	17010 (Pk)		53.23	68.23	-15.00
	17010 (Av)		40.60	68.23	-27.63
5710	5720 (Pk)	Vertical	100.86	*	-
	5720 (Av)		89.92	*	-
	5460 (Pk)		49.71	74	-24.29
	5460 (Av)		35.46	54	-18.54
	11420 (Pk)		49.73	68.23	-18.50
	11420 (Av)		38.17	68.23	-30.06
	17130 (Pk)		No Harmonics Found		
	17130 (Av)				
	5720 (Pk)	Horizontal	90.13	*	-
	5720 (Av)		80.11	*	-
	5460 (Pk)		47.12	74	-26.88
	5460 (Av)		34.28	54	-19.72
	11420 (Pk)		50.43	68.23	-17.80
	11420 (Av)		37.87	68.23	-30.36
	17130 (Pk)		No Harmonics Found		
	17130 (Av)				
5755	5755 (Pk)	Vertical	102.50	*	-
	5755 (Av)		91.51	*	-
	11510 (Pk)		52.59	68.23	-15.64
	11510 (Av)		40.65	68.23	-27.58
	17265 (Pk)		55.54	68.23	-12.69
	17265 (Av)		42.98	68.23	-25.25
	5755 (Pk)	Horizontal	91.82	*	-
	5755 (Av)		81.74	*	-
	11510 (Pk)		53.66	68.23	-14.57
	11510 (Av)		40.19	54	-13.81
	17265 (Pk)		55.55	68.23	-12.68
	17265 (Av)		42.98	54	-11.02

Prüfbericht - Nr.:

Test Report No.:

ULR-TC568821300000034F

Seite 129 von 143

Page 129 of 143

5795	5795 (Pk)	Vertical	101.40	*	-
	5795 (Av)		90.88	*	-
	11590 (Pk)		53.27	68.23	-14.96
	11590 (Av)		41.37	68.23	-26.86
	17385 (Pk)		55.25	68.23	-12.98
	17385 (Av)		42.84	68.23	-25.39
	5795 (Pk)	Horizontal	91.36	*	-
	5795 (Av)		81.02	*	-
	11590 (Pk)		52.29	68.23	-15.94
	11590 (Av)		40.12	68.23	-28.11
	17385 (Pk)		54.75	68.23	-13.48
	17385 (Av)		42.81	68.23	-25.42

The testing is performed for **802.11n _ HT 40MHz**, **802.11n _ VHT 40MHz** MCS 0 & MCS 7 but not reported here, only the MCS 0 reported as a worst case senario

Prüfbericht - Nr.:

ULR-TC568821300000034F

Seite 130 von 143

Test Report No.:

Page 130 of 143

Modulation: 802.11ac _ VHT 20MHz

Data rate: MCS0

Channel Frequency (MHz)	Frequency (MHz)	Polarization	Emission (dBµV/m)	Limit (dBm)	Margin (dB)
5180	5180 (Pk)	Vertical	106.54	*	-
	5180 (Av)		96.58	*	-
	5150 (Pk)		63.27	74	-10.73
	5150 (Av)		51.02	54	-2.98
	10360 (Pk)		49.59	68.23	-18.64
	10360 (Av)		37.47	68.23	-30.76
	15540 (Pk)		52.06	68.23	-16.17
	15540 (Av)		40.11	68.23	-28.12
	5180 (Pk)	Horizontal	96.43	*	-
	5180 (Av)		85.54	*	-
	5150 (Pk)		54.67	74	-19.33
	5150 (Av)		41.27	54	-12.73
	10360 (Pk)		49.22	68.23	-19.01
	10360 (Av)		37.54	68.23	-30.69
	15540 (Pk)		52.62	68.23	-15.61
	15540 (Av)		40.24	68.23	-27.99
5240	5240 (Pk)	Vertical	106.21	*	-
	5240 (Av)		97.33	*	-
	5350 (Pk)		54.01	74	-19.99
	5350 (Av)		42.02	54	-11.98
	10480 (Pk)		49.86	68.23	-18.37
	10480 (Av)		37.91	68.23	-30.32
	15720 (Pk)		51.18	68.23	-17.05
	15720 (Av)		39.67	68.23	-28.56
	5240 (Pk)	Horizontal	96.96	*	-
	5240 (Av)		86.35	*	-
	5350 (Pk)		44.28	74	-29.72
	5350 (Av)		33.37	54	-20.63
	10480 (Pk)		49.58	68.23	-18.65
	10480 (Av)		37.92	68.23	-30.31
	15720 (Pk)		51.27	68.23	-16.96
	15720 (Av)		39.72	68.23	-28.51

Prüfbericht - Nr.:
Test Report No.:

ULR-TC568821300000034F

Seite 131 von 143
Page 131 of 143

5260	5260 (Pk)	Vertical	107.16	*	-
	5260 (Av)		97.46	*	-
	5350 (Pk)		54.19	74	-19.81
	5350 (Av)		42.06	54	-11.94
	10520 (Pk)		49.73	68.23	-18.50
	10520 (Av)		37.72	68.23	-30.51
	15780 (Pk)		51.02	68.23	-17.21
	15780 (Av)		39.14	68.23	-29.09
	5260 (Pk)	Horizontal	96.42	*	-
	5260 (Av)		86.50	*	-
	5350 (Pk)		45.28	74	-28.72
	5350 (Av)		33.42	54	-20.58
	10520 (Pk)		50.93	68.23	-17.30
	10520 (Av)		37.76	68.23	-30.47
	15780 (Pk)		52.76	68.23	-15.47
	15780 (Av)		39.16	68.23	-29.07
5320	5320 (Pk)	Vertical	106.99	*	-
	5320 (Av)		97.49	*	-
	5350 (Pk)		56.77	74	-17.23
	5350 (Av)		44.66	54	-9.34
	10640 (Pk)		50.32	68.23	-17.91
	10640 (Av)		37.72	68.23	-30.51
	15960 (Pk)		51.01	68.23	-17.22
	15960 (Av)		39.12	68.23	-29.11
	5320 (Pk)	Horizontal	97.07	*	-
	5320 (Av)		86.14	*	-
	5350 (Pk)		48.97	74	-25.03
	5350 (Av)		34.89	54	-19.11
	10640 (Pk)		49.77	68.23	-18.46
	10640 (Av)		37.67	68.23	-30.56
	15960 (Pk)		52.26	68.23	-15.97
	15960 (Av)		39.80	68.23	-28.43
5500	5500 (Pk)	Vertical	106.38	*	-
	5500 (Av)		96.74	*	-
	5460 (Pk)		63.82	74	-10.18
	5460 (Av)		51.51	54	-2.49
	11000 (Pk)		49.25	68.23	-18.98
	11000 (Av)		37.37	68.23	-30.86
	16500 (Pk)		52.01	68.23	-16.22
	16500 (Av)		40.34	68.23	-27.89
	5500 (Pk)	Horizontal	95.36	*	-
	5500 (Av)		84.79	*	-
	5460 (Pk)		54.12	74	-19.88
	5460 (Av)		41.73	54	-12.27
	11000 (Pk)		49.78	68.23	-18.45
	11000 (Av)		37.51	68.23	-30.72
	16500 (Pk)		52.69	68.23	-15.54
	16500 (Av)		40.62	68.23	-27.61

Prüfbericht - Nr.:
Test Report No.:

ULR-TC568821300000034F

Seite 132 von 143
Page 132 of 143

5700	5700 (Pk)	Vertical	104.36	*	-
	5700 (Av)		94.37	*	-
	5460 (Pk)		45.34	74	-28.66
	5460 (Av)		32.31	54	-21.69
	11400 (Pk)		50.85	68.23	-17.38
	11400 (Av)		38.39	68.23	-29.84
	17100 (Pk)		54.50	68.23	-13.73
	17100 (Av)		42.84	68.23	-25.39
	5700 (Pk)	Horizontal	82.03	*	-
	5700 (Av)		84.59	*	-
	5460 (Pk)		41.56	74	-32.44
	5460 (Av)		28.99	54	-25.01
	11400 (Pk)		49.64	68.23	-18.59
	11400 (Av)		37.72	68.23	-30.51
	17100 (Pk)		55.12	68.23	-13.11
	17100 (Av)		42.84	68.23	-25.39
5720	5720 (Pk)	Vertical	103.56	*	-
	5720 (Av)		93.11	*	-
	5460 (Pk)		48.38	74	-25.62
	5460 (Av)		35.65	54	-18.35
	11440 (Pk)		51.43	68.23	-16.80
	11440 (Av)		38.85	68.23	-29.38
	17160 (Pk)		No Harmonics Found		
	17160 (Av)				
	5720 (Pk)	Horizontal	94.05	*	-
	5720 (Av)		83.79	*	-
	5460 (Pk)		47.51	74	-26.49
	5460 (Av)		34.29	54	-19.71
	11440 (Pk)		50.22	68.23	-18.01
	11440 (Av)		38.04	68.23	-30.19
	17160 (Pk)		No Harmonics Found		
	17160 (Av)				
5745	5715(Pk)	Vertical	51.73	78.2	-26.47
	5725(Pk)		54.05	78.2	-24.15
	5745 (Pk)		103.96	*	-
	5745 (Av)		94.22	*	-
	11490 (Pk)		53.61	68.23	-14.62
	11490 (Av)		39.40	68.23	-28.83
	17235 (Pk)		55.15	68.23	-13.08
	17235 (Av)		42.79	68.23	-25.44
	5715(Pk)	Horizontal	44.34	78.2	-33.86
	5725(Pk)		45.54	78.2	-32.66
	5745 (Pk)		94.44	*	-
	5745 (Av)		85.14	*	-
	11490 (Pk)		50.46	68.23	-17.77
	11490 (Av)		38.19	68.23	-30.04
	17235 (Pk)		55.45	68.23	-12.78
	17235 (Av)		42.80	68.23	-25.43

Prüfbericht - Nr.:

ULR-TC568821300000034F

Seite 133 von 143


Test Report No.:

Page 133 of 143

5825	5825 (Pk)	Vertical	103.88	*	-
	5825 (Av)		94.06	*	-
	5850 (Pk)		51.55	78.2	-26.65
	5860 (Pk)		48.28	78.2	-29.92
	11650 (Pk)		57.25	68.23	-10.98
	11650 (Av)		42.48	68.23	-25.75
	17475 (Pk)		55.16	68.23	-13.07
	17475 (Av)		42.94	68.23	-25.29
	5825 (Pk)	Horizontal	95.49	*	-
	5825 (Av)		86.01	*	-
	5850 (Pk)		43.79	78.2	-34.41
	5860 (Pk)		43.30	78.2	-34.90
	11650 (Pk)		51.08	68.23	-17.15
	11650 (Av)		38.29	68.23	-29.94
	17475 (Pk)		55.01	68.23	-13.22
	17475 (Av)		42.98	68.23	-25.25


The testing is performed for **802.11ac _ VHT 20MHz**, **802.11ac _ VHT 80MHz** MCS 0 & MCS 7 but not reported here, only the MCS 0 reported as a worst case senario

Worst case emissions for restricted band of operation



Channel Frequency: 5180MHz

Polarization: Vertical




Channel Frequency: 5180MHz

Polarization: Horizontal

Worst case emissions for Spurious radiated emissions above 1GHz


Data rate: 6Mbps

Channel Frequency: 5180MHz




Frequency Range: 1 to 18GHz

Polarization: Vertical




Frequency Range: 1 to 18GHz

Polarization: Horizontal



Frequency Range: 18-40GHz

Polarization: Vertical



Frequency Range: 18-40GHz

Polarization: Horizontal

9 Frequency Stability

Result

Pass

Test Specification

FCC part 15 Subpart C 15.407 (g) / RSS Gen Issue 5, Section 8.11

Test Method

Subclause 6.8.1 of ANSI C63.10


Port of testing

Antenna port

Requirement

Manufacturers of U-NII devices are responsible for ensuring frequency stability such that an emission is maintained within the band of operation under all conditions of normal operation as specified in the users manual

Test Method:



Test Condition:

Normal Test Condition:

Temperature (Norm) = + 25 °C

Voltage = 5.0V DC

Relative humidity: 62%

KDB Guidelines applied:

Measurements were made as per section 3 in KDB 789033 D02 General UNII Test Procedures New Rules v02r01

Prüfbericht - Nr.:

Test Report No.:

ULR-TC568821300000034F

Seite 138 von 143

Page 138 of 143

Test results:

Channel Frequency (MHz)	Temperature	Frequency deviation for different time interval (MHz)				Limit
		0Min	2Min	5Min	10Min	
5180	0	1.57	-1.50	0.06	-1.83	Emission drift measured are maintained within the authorised band
	25	-2.06	-1.47	1.89	-1.98	
	35	-1.2	2.14	-0.91	-0.43	
5240	0	-2.07	-0.47	0.88	-1.75	
	25	-1.3	2.04	-0.75	-1.43	
	35	2.57	-1.07	0.76	-0.83	
5745	0	2.5	-0.80	-1.98	-1.29	
	25	-1.97	-1.62	-1.95	1.70	
	35	1.13	-1.59	-0.82	-1.35	
5825	0	1.5	-0.90	2.97	-0.28	
	25	-1.68	-1.56	-2.05	1.87	
	35	1.49	-2.55	-1.83	-1.04	

Prüfbericht - Nr.:
Test Report No.:

ULR-TC568821300000034F

Seite 139 von 143
Page 139 of 143

10 Conducted Spurious Emission test on AC Power Line

Result

Pass

Test Specification : FCC Part 15 Section 15.207 / RSS Gen Issue 5 Section 8.8
Test Method : ANSI C 63.10-2013
Testing Location : Screened room
Measurement Bandwidth : 9kHz
Frequency Range : 150kHz – 30MHz
Supply Voltage : 110VAC,60Hz
Test Method : Refer TEST METHODOLOGY

***Note: The product has tested with AC to DC adapter and Wireless Qi charger**

Limits of section 15.207

Frequency of emission (MHz)	QP Limit (dBμV)	AV Limit (dBμV/m)
0.15 – 0.5	66 – 56*	56 – 46*
0.5 – 5	56	46
5 – 30	60	50


* Decreases with the logarithm of the frequency

Test Conditions:

Normal Temperature = +24°C Voltage (V norm) = 110V AC (Through AC to DC Adapter)
RH = 64 %

Test result:

Power: 110V 60HZ_LINE




Line Graph

Quasipeak (23)										
Frequency (MHz)	SR	Level (dBμV)	Limit (dBμV)	Margin (dB)	Pos	Measuring time	RBW	Meas.Time	Comments	Correction (dB)
0.215	1	38.06	63.05	-24.99	Phase 1	1	9k	0.02	Pass	20.16
21.26465	1	34.62	60	-25.38	Phase 1	1	9k	0.02	Pass	20.14
0.1653	1	38.56	65.16	-26.6	Phase 1	1	9k	0.02	Pass	20.22
0.29535	1	31.3	60.41	-29.11	Phase 1	1	9k	0.02	Pass	20.06
0.3503	1	27.85	58.96	-31.11	Phase 1	1	9k	0.02	Pass	20.07
1.1863	1	23.61	56	-32.39	Phase 1	1	9k	0.02	Pass	20.43
0.4315	1	24.4	57.25	-32.85	Phase 1	1	9k	0.02	Pass	20.08
0.2715	1	28.12	61.12	-33	Phase 1	1	9k	0.02	Pass	20.09
0.33795	1	24.46	59.25	-34.79	Phase 1	1	9k	0.02	Pass	20.06
5.68075	1	24.6	60	-35.4	Phase 1	1	9k	0.02	Pass	20.54
5.3592	1	23	60	-37	Phase 1	1	9k	0.02	Pass	20.54

Average (23)										
Frequency (MHz)	SR	Level (dBμV)	Limit (dBμV)	Margin (dB)	Pos	Measuring time	RBW	Meas.Time	Comments	Correction (dB)
0.1653	1	22.29	55.16	-32.87	Phase 1	1	9k	0.02	Pass	20.22
0.215	1	17.61	53.05	-35.44	Phase 1	1	9k	0.02	Pass	20.16
0.2715	1	13.51	51.12	-37.61	Phase 1	1	9k	0.02	Pass	20.09
0.29535	1	20.33	50.41	-30.08	Phase 1	1	9k	0.02	Pass	20.06
0.33795	1	15.19	49.25	-34.06	Phase 1	1	9k	0.02	Pass	20.06
0.3503	1	15.93	48.96	-33.03	Phase 1	1	9k	0.02	Pass	20.07
0.4315	1	13.57	47.25	-33.68	Phase 1	1	9k	0.02	Pass	20.08
1.1863	1	12.09	46	-33.91	Phase 1	1	9k	0.02	Pass	20.43
5.3592	1	17.01	50	-32.99	Phase 1	1	9k	0.02	Pass	20.54
5.68075	1	17.42	50	-32.58	Phase 1	1	9k	0.02	Pass	20.54
21.26465	1	27.9	50	-22.1	Phase 1	1	9k	0.02	Pass	20.14

Line Table

Power: 110V60HZ_NEUTRAL



Neutral Graph

Prüfbericht - Nr.:
Test Report No.:

ULR-TC568821300000034F

Seite 142 von 143
Page 142 of 143

Quasipeak (23)										
Frequency (MHz)	SR	Level (dBμV)	Limit (dBμV)	Margin (dB)	Pos	Measuring time	RBW	Meas. Time	Comments	Correction (dB)
0.29665	2	39.24	60.3	-21.06	Neutral	1	9k	0.02	Pass	19.96
0.15675	2	39.99	65.57	-25.58	Neutral	1	9k	0.02	Pass	20.3
0.16805	2	38.24	64.96	-26.72	Neutral	1	9k	0.02	Pass	20.27
0.1795	2	37.25	64.58	-27.33	Neutral	1	9k	0.02	Pass	20.24
0.1916	2	36.02	64.04	-28.01	Neutral	1	9k	0.02	Pass	20.21
0.3442	2	29.58	59.06	-29.47	Neutral	1	9k	0.02	Pass	20.01
21.4065	2	30.08	60	-29.92	Neutral	1	9k	0.02	Pass	20.43
0.2262	2	32.15	62.6	-30.45	Neutral	1	9k	0.02	Pass	20.13
0.41605	2	26.37	57.49	-31.12	Neutral	1	9k	0.02	Pass	20.12
0.39895	2	26.43	57.9	-31.47	Neutral	1	9k	0.02	Pass	20.09
1.15335	2	23.55	56	-32.45	Neutral	1	9k	0.02	Pass	20.51
6.4893	2	20.28	60	-39.72	Neutral	1	9k	0.02	Pass	20.69

Average (23)										
Frequency (MHz)	SR	Level (dBμV)	Limit (dBμV)	Margin (dB)	Pos	Measuring time	RBW	Meas. Time	Comments	Correction (dB)
0.29665	2	26.41	50.3	-23.89	Neutral	1	9k	0.02	Pass	19.96
21.4065	2	23.85	50	-26.15	Neutral	1	9k	0.02	Pass	20.43
0.3442	2	19.24	49.06	-29.82	Neutral	1	9k	0.02	Pass	20.01
0.41605	2	16.58	47.49	-30.91	Neutral	1	9k	0.02	Pass	20.12
0.39895	2	16.71	47.9	-31.19	Neutral	1	9k	0.02	Pass	20.09
0.15675	2	22.95	55.57	-32.62	Neutral	1	9k	0.02	Pass	20.3
0.16805	2	21.18	54.96	-33.78	Neutral	1	9k	0.02	Pass	20.27
0.1795	2	20.11	54.58	-34.47	Neutral	1	9k	0.02	Pass	20.24
1.15335	2	11.44	46	-34.56	Neutral	1	9k	0.02	Pass	20.51
0.1916	2	19.27	54.04	-34.76	Neutral	1	9k	0.02	Pass	20.21
6.4893	2	14.7	50	-35.3	Neutral	1	9k	0.02	Pass	20.69
0.2262	2	16.31	52.6	-36.29	Neutral	1	9k	0.02	Pass	20.13

Neutral Table

11 LIST OF TABLES

Table 1: List of test and measurement instruments	6
Table 2: Instrument application Software versions	6
Table 3: Ratings and System Details as declared by the Client*	7
Table 4: Measurement Uncertainty	8
Table 5: List of Wi-Fi center Frequencies	10
Table 6: Undesirable emission limits	106
Table 7: Transmitter limits for Radiated emission	107

12 Power level used for testing

6Mbps		HT20_MCS0		VHT40_MCS0	
5180	17	5180	16	5190	15
5240	17	5240	16	5230	15
5260	17	5260	16	5270	15
5320	17	5320	16	5510	15
5500	17	5500	16	5590	15
5700	17	5700	16	5670	15
5745	17	5745	16	5755	15
5825	17	5825	16	5795	15
54Mbps		HT20_MCS7		VHT40_MCS9	
5180	17	5180	16	5190	15
5240	17	5240	16	5230	15
5260	17	5260	16	5270	15
5320	17	5320	16	5510	15
5500	17	5500	16	5590	15
5700	17	5700	16	5670	15
5745	16	5745	16	5755	15
5825	16	5825	16	5795	15
VHT20_MCS0		HT40_MCS0		ac_VHT80_MCS0	
5180	16	5190	15	5210	14
5240	16	5230	15	5290	14
5260	16	5270	15	5530	14
5320	16	5510	15	5690	14
5500	16	5590	15	5755	14
5700	16	5670	15	ac_VHT80_MCS9	
5745	16	5755	15	5210	14
5825	16	5795	15	5290	14
VHT20_MCS8		HT40_MCS7		5530	14
5180	15	5190	15	5690	14
5240	15	5230	15	5755	14
5260	15	5270	15	ac_VHT80_MCS9	
5320	15	5510	15	5210	14
5500	15	5590	15	5290	14
5700	15	5670	15	5530	14
5745	15	5755	15	5690	14
5825	15	5795	15	5755	14

END OF TEST REPORT