

RF Antenna Cable Assembly

Specification

1. Electrical Properties :



- 1.1 Frequency Rang..... 2.4GHz ~ 2.5GHz ; 4.9GHz ~ 5.825GHz
- 1.2 Impedance 50Ω Nominal
- 1.3 VSWR 1.92 Max.
- 1.4 Return Loss..... -10 dB Maximum
- 1.5 Radiation Omni-directional
- 1.6 Antenna Gain..... 2.05dBi@2.4GHz~2.5GHz
2.65dBi@ 4.9GHz~5.825GHz
- 1.7 Polarization..... Linear Vertical
- 1.8 Admitted Power..... 1W

2. Physical Properties :

- 2.1 Cable..... RG-178 Coaxial Cable
- 2.2 Antenna Cover..... TPE
- 2.3 Antenna Base..... PC
- 2.4 Antenna Base..... PBT
- 2.5 Operating Temp. -20°C ~ +65°C
- 2.6 Storage Temp. -30°C ~ +75°C
- 2.7 Color WHITE
- 2.8 Connector..... SMA Plug Reverse

CG-

REV	DATE	DESCRIPTION
X1	3/29-2006	New Issue




Packing : 10 pcs/bag

NO	DESCRIPTION	QTY	REMARK
6	Cable	RG-178 Cable	1
5	Connector	Big SMA Plug Reverse(Ni Plated)	1
4	Rivet	POM ; Pure White	2
3	Antenna Base	PBT ; Color : Pure White	1
2	Antenna Base	PC ; Color : Pure White	1
1	Antenna Body	TPE ; Color : Pure White	1

CUSTOMER'S SINGATURE

XX. ±5 APPROVED
 X. ±3.0
 .X ±1.0 CHECKED
 .XX ±0.5
 .XXX ±0.1 DRAWING
 3/29/06
 鄭春正
 程淑娟

CUSTOMER: 合勤
 PART NO :
 PARTNAME: RF Antenna Assembly
 W.Y P/NO : C034-510579-A
 REV UNIT FILE :
 X1 m/m SHEET : 1/1


Wha Yu INDUSTRIAL CO.,LTD.
 譚裕實業股份有限公司
 THIS DRAWING, AND ITS INHERANT DESIGN CONCEPTS, ARE THE PROPERTY OF WHA YU AND AS SUCH MAY NOT BE COPIED, REPRODUCED, OR GIVEN TO THIRD PARTIES WITHOUT THE WRITTEN CONSENT OF WHA YU.