



FCC RADIO TEST REPORT

FCC ID : J9CQSIP7180P
Equipment : 7c Modular Platform
Brand Name : Qualcomm
Model Name : QSIP7180P
Applicant : Qualcomm Technologies, Inc.
5775 Morehouse Dr.San Diego, CA 92121-1714 (USA)
Manufacturer : Qualcomm Technologies, Inc.
5775 Morehouse Dr.San Diego, CA 92121-1714 (USA)
Standard : FCC Part 15 Subpart C §15.247

The product was received on Jun. 08, 2020 and testing was started from Jun. 11, 2020 and completed on Jul. 31, 2020. We, SPORTON INTERNATIONAL INC., EMC & Wireless Communications Laboratory, would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory, the test report shall not be reproduced except in full.

Louis Wu

Approved by: Louis Wu

SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory

No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.)



Table of Contents

History of this test report.....	3
Summary of Test Result.....	4
1 General Description.....	5
1.1 Product Feature of Equipment Under Test.....	5
1.2 Modification of EUT	5
1.3 Testing Location	6
1.4 Applicable Standards.....	6
2 Test Configuration of Equipment Under Test	7
2.1 Carrier Frequency Channel	7
2.2 Test Mode.....	8
2.3 Connection Diagram of Test System.....	9
2.4 Support Unit used in test configuration and system	9
2.5 EUT Operation Test Setup	10
2.6 Measurement Results Explanation Example.....	10
3 Test Result.....	11
3.1 6dB and 99% Bandwidth Measurement	11
3.2 Output Power Measurement.....	18
3.3 Power Spectral Density Measurement	19
3.4 Conducted Band Edges and Spurious Emission Measurement	26
3.5 Radiated Band Edges and Spurious Emission Measurement	35
3.6 Antenna Requirements	39
4 List of Measuring Equipment	40
5 Uncertainty of Evaluation.....	42
Appendix A. Conducted Test Results	
Appendix B. Radiated Spurious Emission	
Appendix C. Radiated Spurious Emission Plots	
Appendix D. Duty Cycle Plots	
Appendix E Setup Photographs	



History of this test report

Report No.	Version	Description	Issued Date
FR042002-06B	01	Initial issue of report	Sep. 17, 2020



Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
3.1	15.247(a)(2)	6dB Bandwidth	Pass	-
3.1	2.1049	99% Occupied Bandwidth	Reporting only	-
3.2	15.247(b)(3)	Output Power	Pass	-
3.3	15.247(e)	Power Spectral Density	Pass	-
3.4	15.247(d)	Conducted Band Edges and Spurious Emission	Pass	-
3.5	15.247(d)	Radiated Band Edges and Spurious Emission	Pass	Under limit 5.73 dB at 2312.660 MHz
-	15.207	AC Conducted Emission	Not Required	-
3.6	15.203 & 15.247(b)	Antenna Requirement	Pass	-

Note: Not required means after assessing, test items are not necessary to carry out.

Declaration of Conformity:

The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.

Comments and Explanations:

The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.

Reviewed by: Wii Chang

Report Producer: Celery Wei

1 General Description

1.1 Product Feature of Equipment Under Test

Bluetooth, Wi-Fi 2.4GHz 802.11b/g/n/ac, Wi-Fi 5GHz 802.11a/n/ac.

Antenna Information								
Antenna No.	Brand	Model	Antenna Net gain	Frequency Range (MHz)	Cable Loss (dBi)	Ant. Type	Connector Type	Cable Length (mm)
1	WNC	81.EBJ15.005	3.00	2400-2500 MHz	1.15	PIFA	IPEX	300
			2.56	5150-5350 MHz	1.7			
			4.76	5470-5725MHz	1.74			
			4.76	5725-5825 MHz	1.79			
2	WNC	81.EBJ15.005	3.62	2400-2500 MHz	1.15	PIFA	IPEX	300
			3.08	5150-5350 MHz	1.7			
			3.31	5470-5725MHz	1.74			
			2.42	5725-5825 MHz	1.79			

Remark:

1. Above antenna gains of antenna are Total (H+V).
2. For Bluetooth mode was fixed transmission on Chain (0)
3. The maximum gain was chosen for test.

1.2 Modification of EUT

No modifications are made to the EUT during all test items.

1.3 Testing Location

Test Site	SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory
Test Site Location	No.52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.) TEL: +886-3-327-3456 FAX: +886-3-328-4978
Test Site No.	Sporton Site No.
	TH05-HY

Test Site	SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory
Test Site Location	No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.) TEL: +886-3-327-0868 FAX: +886-3-327-0855
Test Site No.	Sporton Site No.
	03CH15-HY

Note: The test site complies with ANSI C63.4 2014 requirement.

FCC designation No.: TW1190 and TW0007

1.4 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC Part 15 Subpart C §15.247
- ♦ FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v05r02
- ♦ FCC KDB 414788 D01 Radiated Test Site v01r01
- ♦ ANSI C63.10-2013

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. The TAF code is not including all the FCC KDB listed without accreditation.
3. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.



2 Test Configuration of Equipment Under Test

2.1 Carrier Frequency Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
2400-2483.5 MHz	0	2402	21	2444
	1	2404	22	2446
	2	2406	23	2448
	3	2408	24	2450
	4	2410	25	2452
	5	2412	26	2454
	6	2414	27	2456
	7	2416	28	2458
	8	2418	29	2460
	9	2420	30	2462
	10	2422	31	2464
	11	2424	32	2466
	12	2426	33	2468
	13	2428	34	2470
	14	2430	35	2472
	15	2432	36	2474
	16	2434	37	2476
	17	2436	38	2478
	18	2438	39	2480
	19	2440	-	-
	20	2442	-	-

2.2 Test Mode

The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: radiation emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, pre-scanned in two degree (0 and 90). The worst cases (Degree 0) were recorded in this report.

The following summary table is showing all test modes to demonstrate in compliance with the standard.

Summary table of Test Cases	
Test Item	Data Rate / Modulation
	Bluetooth – LE / GFSK
Conducted Test Cases	Mode 1: Bluetooth Tx CH00_2402 MHz_1Mbps
	Mode 2: Bluetooth Tx CH19_2440 MHz_1Mbps
	Mode 3: Bluetooth Tx CH39_2480 MHz_1Mbps
	Mode 4: Bluetooth Tx CH00_2402 MHz_2Mbps
	Mode 5: Bluetooth Tx CH19_2440 MHz_2Mbps
	Mode 6: Bluetooth Tx CH39_2480 MHz_2Mbps
Radiated Test Cases	Mode 1: Bluetooth Tx CH00_2402 MHz_1Mbps
	Mode 2: Bluetooth Tx CH19_2440 MHz_1Mbps
	Mode 3: Bluetooth Tx CH39_2480 MHz_1Mbps
	Mode 4: Bluetooth Tx CH00_2402 MHz_2Mbps
	Mode 5: Bluetooth Tx CH19_2440 MHz_2Mbps
	Mode 6: Bluetooth Tx CH39_2480 MHz_2Mbps

2.3 Connection Diagram of Test System



2.4 Support Unit used in test configuration and system

Item	Equipment	Brand Name	Model Name	FCC ID	Data Cable	Power Cord
1.	Notebook	Dell	Latitude 3400	FCC DoC	N/A	AC I/P : Unshielded, 1.2m DC O/P : Shielded, 1.8m
2.	Power Supply	GW Instek	GPE-2323	N/A	N/A	N/A



2.5 EUT Operation Test Setup

The RF test items, utility "QRCT v4.0.00156.0" was installed in Notebook which was programmed in order to make the EUT get into the engineering modes to provide channel selection, power level, data rate and the application type and for continuous transmitting signals.

2.6 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example :

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 4.2 dB and 10dB attenuator.

$$\begin{aligned}\text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)} \\ &= 4.2 + 10 = 14.2 \text{ (dB)}\end{aligned}$$

3 Test Result

3.1 6dB and 99% Bandwidth Measurement

3.1.1 Limit of 6dB and 99% Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.

3.1.2 Measuring Instruments

See list of measuring equipment of this test report.

3.1.3 Test Procedures

1. The testing follows the ANSI C63.10 Section 6.9.3 (OBW) and 11.8.1 (6dB BW).
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. Set the Video bandwidth (VBW) = 300 kHz. In order to make an accurate measurement. The 6 dB bandwidth must be greater than 500 kHz.
5. For 99% Bandwidth Measurement, the spectrum analyzer's resolution bandwidth (RBW) is set 1-5% of the emission bandwidth and set the Video bandwidth (VBW) $\geq 3 * RBW$.
6. Measure and record the results in the test report.

3.1.4 Test Setup




3.1.5 Test Result of 6dB Bandwidth

Please refer to Appendix A.




<1Mbps>

6 dB Bandwidth Plot on Channel 00



Date: 3.JUL.2020 09:45:57


6 dB Bandwidth Plot on Channel 19



Date: 3.JUL.2020 09:54:58




6 dB Bandwidth Plot on Channel 19



Date: 3.JUL.2020 10:36:49

6 dB Bandwidth Plot on Channel 39



Date: 3.JUL.2020 10:41:57




3.1.6 Test Result of 99% Occupied Bandwidth

Please refer to Appendix A.


<1Mbps>

99% Bandwidth Plot on Channel 00



Date: 3.JUL.2020 09:51:34


99% Occupied Bandwidth Plot on Channel 19



Date: 3.JUL.2020 09:58:41



99% Occupied Bandwidth Plot on Channel 39




Date: 3.JUL.2020 10:19:51

Note: The occupied channel bandwidth is maintained within the band of operation for all of the modulations.

<2Mbps>


99% Bandwidth Plot on Channel 00



Date: 3.JUL.2020 10:28:35




99% Occupied Bandwidth Plot on Channel 19



Date: 3.JUL.2020 10:39:50

99% Occupied Bandwidth Plot on Channel 39



Date: 3.JUL.2020 10:46:56

Note: The occupied channel bandwidth is maintained within the band of operation for all of the modulations.

3.2 Output Power Measurement

3.2.1 Limit of Output Power

For systems using digital modulation in the 2400-2483.5MHz, the limit for output power is 30dBm. If transmitting antenna of directional gain greater than 6dBi is used, the peak output power from the intentional radiator shall be reduced below the above stated value by the amount in dB that the directional gain of the antenna exceeds 6 dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.


3.2.2 Measuring Instruments

See list of measuring equipment of this test report.

3.2.3 Test Procedures

1. For Average Power, the testing follows ANSI C63.10 Section 11.9.2.3.2 Method AVGPM-G
2. The RF output of EUT was connected to the power meter by RF cable and attenuator.
3. The path loss was compensated to the results for each measurement.
4. Set to the maximum power setting and enable the EUT transmit continuously.
5. Measure the conducted output power and record the results in the test report.

3.2.4 Test Setup



3.2.5 Test Result of Average Output Power

Please refer to Appendix A.

3.3 Power Spectral Density Measurement

3.3.1 Limit of Power Spectral Density

The peak power spectral density shall not be greater than 8dBm in any 3kHz band at any time interval of continuous transmission.

3.3.2 Measuring Instruments

See list of measuring equipment of this test report.

3.3.3 Test Procedures

1. The testing follows the ANSI C63.10 Section 11.10.2 Method PKPSD.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 3 kHz. Video bandwidth VBW = 10 kHz In order to make an accurate measurement, set the span to 1.5 times DTS Channel Bandwidth. (6dB BW)
5. Detector = peak, Sweep time = auto couple, Trace mode = max hold, Allow trace to fully stabilize. Use the peak marker function to determine the maximum power level.
6. Measure and record the results in the test report.
7. The Measured power density (dBm)/ 100kHz is a reference level and used as 20dBc down limit line for Conducted Band Edges and Conducted Spurious Emission.

3.3.4 Test Setup



3.3.5 Test Result of Power Spectral Density


Please refer to Appendix A.



3.3.6 Test Result of Power Spectral Density Plots (100kHz)


<1Mbps>

PSD 100kHz Plot on Channel 00



Date: 3.JUL.2020 09:48:02


PSD 100kHz Plot on Channel 19



Date: 3.JUL.2020 09:56:56




PSD 100kHz Plot on Channel 39



Date: 3.JUL.2020 10:15:59

<2Mbps>


PSD 100kHz Plot on Channel 00



Date: 3.JUL.2020 10:26:03




PSD 100kHz Plot on Channel 19



Date: 3.JUL.2020 10:38:29

PSD 100kHz Plot on Channel 39




Date: 3.JUL.2020 10:43:16

3.3.7 Test Result of Power Spectral Density Plots (3kHz)


<1Mbps>

PSD 3kHz Plot on Channel 00



Date: 3.JUL.2020 09:47:09


PSD 3kHz Plot on Channel 19



Date: 3.JUL.2020 09:56:13




PSD 3kHz Plot on Channel 39



Date: 3.JUL.2020 10:15:32

<2Mbps>


PSD 3kHz Plot on Channel 00



Date: 3.JUL.2020 10:24:58




PSD 3kHz Plot on Channel 19



Date: 3.JUL.2020 10:37:28

PSD 3kHz Plot on Channel 39



Date: 3.JUL.2020 10:42:59

3.4 Conducted Band Edges and Spurious Emission Measurement

3.4.1 Limit of Conducted Band Edges and Spurious Emission

All harmonics/spurious must be at least 20 dB down from the highest emission level within the authorized band.

3.4.2 Measuring Instruments

See list of measuring equipment of this test report.

3.4.3 Test Procedure

1. The testing follows the ANSI C63.10 Section 11.11.3 Emission level measurement.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Set RBW = 100 kHz, VBW=300 kHz, Peak Detector. Unwanted Emissions measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when maximum peak conducted output power procedure is used. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.
5. Measure and record the results in the test report.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

3.4.4 Test Setup






3.4.5 Test Result of Conducted Band Edges Plots


<1Mbps>

Low Band Edge Plot on Channel 00



Date: 3.JUL.2020 09:48:25

High Band Edge Plot on Channel 39




Date: 3.JUL.2020 10:17:22




<2Mbps>

Low Band Edge Plot on Channel 00



Date: 3.JUL.2020 10:26:30

High Band Edge Plot on Channel 39




Date: 3.JUL.2020 10:43:40




3.4.6 Test Result of Conducted Spurious Emission Plots

Conducted Spurious Emission Plot on Bluetooth LE 1Mbps GFSK Channel 00




Date: 3.JUL.2020 09:50:23


Conducted Spurious Emission Plot on Bluetooth LE 1Mbps GFSK Channel 00



Date: 3.JUL.2020 09:50:39

**Conducted Spurious Emission Plot on Bluetooth LE 1Mbps
GFSK Channel 19**


Date: 3.JUL.2020 09:57:21

**Conducted Spurious Emission Plot on Bluetooth LE 1Mbps
GFSK Channel 19**

Date: 3.JUL.2020 09:57:58




Conducted Spurious Emission Plot on Bluetooth LE 1Mbps GFSK Channel 39



Date: 3.JUL.2020 10:19:00


Conducted Spurious Emission Plot on Bluetooth LE 1Mbps GFSK Channel 39



Date: 3.JUL.2020 10:19:15




Conducted Spurious Emission Plot on Bluetooth LE 2Mbps GFSK Channel 00



Date: 3.JUL.2020 10:27:47


Conducted Spurious Emission Plot on Bluetooth LE 2Mbps GFSK Channel 00



Date: 3.JUL.2020 10:28:01




Conducted Spurious Emission Plot on Bluetooth LE 2Mbps GFSK Channel 19



Date: 3.JUL.2020 10:39:02


Conducted Spurious Emission Plot on Bluetooth LE 2Mbps GFSK Channel 19



Date: 3.JUL.2020 10:39:19




Conducted Spurious Emission Plot on Bluetooth LE 2Mbps GFSK Channel 39



Date: 3.JUL.2020 10:46:07

Conducted Spurious Emission Plot on Bluetooth LE 2Mbps GFSK Channel 39



Date: 3.JUL.2020 10:46:24



3.5 Radiated Band Edges and Spurious Emission Measurement

3.5.1 Limit of Band Edges and Spurious Emission

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. If the output power of this device was measured by spectrum analyzer, the attenuation under this paragraph shall be 30 dB instead of 20 dB. In addition, radiated emissions which fall in the restricted bands must also comply with the limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.5.2 Measuring Instruments


See list of measuring equipment of this test report.

3.5.3 Test Procedures


1. The testing follows the ANSI C63.10 Section 11.12.1 Radiated emission measurements.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level.
3. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
6. For testing below 1GHz, if the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then peak values of EUT will be reported, otherwise, the emissions will be repeated one by one using the CISPR quasi-peak method and reported.
7. For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than average limit (that means the emission level in average mode also complies with the limit in average mode), then peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
8. Use the following spectrum analyzer settings:
 - (1) Span shall wide enough to fully capture the emission being measured;
 - (2) Set RBW=100 kHz for $f < 1$ GHz; $VBW \geq RBW$; Sweep = auto; Detector function = peak; Trace = max hold;
 - (3) Set RBW = 1 MHz, VBW= 3MHz for $f \geq 1$ GHz for peak measurement.
For average measurement:
 - $VBW = 10$ Hz, when duty cycle is no less than 98 percent.
 - $VBW \geq 1/T$, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.

3.5.4 Test Setup


For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz



3.5.5 Test Results of Radiated Spurious Emissions (9 kHz ~ 30 MHz)

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

There is a comparison data of both open-field test site and alternative test site - semi-Anechoic chamber according to 414788 D01 Radiated Test Site v01r01, and the result came out very similar.

3.5.6 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix B and C.

3.5.7 Duty Cycle

Please refer to Appendix D.

3.5.8 Test Result of Radiated Spurious Emission (30MHz ~ 10th Harmonic)

Please refer to Appendix B and C.



3.6 Antenna Requirements

3.6.1 Standard Applicable

If directional gain of transmitting antennas is greater than 6dBi, the power shall be reduced by the same level in dB comparing to gain minus 6dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the rule.

3.6.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.

3.6.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.



4 List of Measuring Equipment

Instrument	Brand Name	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Loop Antenna	Rohde & Schwarz	HFH2-Z2	100488	9 kHz~30 MHz	Jan. 09, 2020	Jul. 01, 2020~ Jul. 31, 2020	Jan. 08, 2021	Radiation (03CH15-HY)
Bilog Antenna	TESEQ	CBL6111D&0 0800N1D01N- 06	41912&05	30MHz to 1GHz	Feb. 09, 2020	Jul. 01, 2020~ Jul. 31, 2020	Feb. 08, 2021	Radiation (03CH15-HY)
Amplifier	SONOMA	310N	363440	9kHz~1GHz	Dec. 27, 2019	Jul. 01, 2020~ Jul. 31, 2020	Dec. 26, 2020	Radiation (03CH15-HY)
Horn Antenna	SCHWARZBE CK	BBHA 9120 D	9120D-162 0	1-18GHz	Oct. 28, 2019	Jul. 01, 2020~ Jul. 31, 2020	Oct. 27, 2020	Radiation (03CH15-HY)
SHF-EHF Horn Antenna	SCHWARZBE CK	BBHA 9170	BBHA9170 584	18GHz- 40GHz	Dec. 10, 2019	Jul. 01, 2020~ Jul. 31, 2020	Dec. 09, 2020	Radiation (03CH15-HY)
Preamplifier	Jet-Power	JPA0118-55-3 03	171000180 0055006	1GHz~18GHz	May 07, 2020	Jul. 01, 2020~ Jul. 31, 2020	May 06, 2021	Radiation (03CH15-HY)
Preamplifier	Keysight	83017A	MY532701 95	1GHz~26.5GHz	Aug. 23, 2019	Jul. 01, 2020~ Jul. 31, 2020	Aug. 22, 2020	Radiation (03CH15-HY)
Preamplifier	EMEC	EM18G40G	060715	18GHz ~ 40GHz	Dec. 13, 2019	Jul. 01, 2020~ Jul. 31, 2020	Dec. 12, 2020	Radiation (03CH15-HY)
EMI Test Receiver	Keysight	N9038A(MXE)	MY541300 85	20MHz~8.4GHz	Nov. 01, 2019	Jul. 01, 2020~ Jul. 31, 2020	Oct. 31, 2020	Radiation (03CH15-HY)
Spectrum Analyzer	Agilent	E4446A	MY501801 36	3Hz~44GHz	May 04, 2020	Jul. 01, 2020~ Jul. 31, 2020	May 03, 2021	Radiation (03CH15-HY)
Antenna Mast	ChainTek	MBS-520-1	N/A	1m~4m	N/A	Jul. 01, 2020~ Jul. 31, 2020	N/A	Radiation (03CH15-HY)
Turn Table	ChainTek	T-200-S-1	N/A	0~360 Degree	N/A	Jul. 01, 2020~ Jul. 31, 2020	N/A	Radiation (03CH15-HY)
Software	Audix	E3 6.2009-8-24(k 5)	RK-00045 1	N/A	N/A	Jul. 01, 2020~ Jul. 31, 2020	N/A	Radiation (03CH15-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104	MY9837/4 PE	9kHz~30MHz	Mar. 12, 2020	Jul. 01, 2020~ Jul. 31, 2020	Mar. 11, 2021	Radiation (03CH15-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104	MY36980/ 4	30M-18G	Apr. 14, 2020	Jul. 01, 2020~ Jul. 31, 2020	Apr. 13, 2021	Radiation (03CH15-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104	MY9838/4 PE	30M-18G	Apr. 14, 2020	Jul. 01, 2020~ Jul. 31, 2020	Apr. 13, 2021	Radiation (03CH15-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104	MY37710/ 4	30M-18G	Apr. 17, 2020	Jul. 01, 2020~ Jul. 31, 2020	Apr. 16, 2021	Radiation (03CH15-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	505134/2	30MHz-40GHz	Feb. 25, 2020	Jul. 01, 2020~ Jul. 31, 2020	Feb. 24, 2021	Radiation (03CH15-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	800740/2	30MHz-40GHz	Feb. 25, 2020	Jul. 01, 2020~ Jul. 31, 2020	Feb. 24, 2021	Radiation (03CH15-HY)
Filter	Wainwright	WLK4-1000-1 530-8000-40S S	SN4	1.53G Low Pass	Jul. 04, 2019	Jul. 01, 2020~ Jul. 02, 2020	Jul. 03, 2020	Radiation (03CH15-HY)
Filter	Wainwright	WLK4-1000-1 530-8000-40S S	SN4	1.53G Low Pass	Jul. 03, 2020	Jul. 03, 2020~ Jul. 31, 2020	Jul. 02, 2021	Radiation (03CH15-HY)
Filter	Wainwright	WHKX12-270 0-3000-18000 -60ST	SN4	3GHz High Pass Filter	Sep. 17, 2019	Jul. 01, 2020~ Jul. 31, 2020	Sep. 16, 2020	Radiation (03CH15-HY)



Instrument	Brand Name	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Hygrometer	Testo	608-H1	34893241	N/A	Mar. 02, 2020	Jun. 11, 2020~ Jul. 03, 2020	Mar. 01, 2021	Conducted (TH05-HY)
Power Sensor	DARE	RPR3006W	16I00054S NO10	10MHz~6GHz	Dec. 23, 2019	Jun. 11, 2020~ Jul. 03, 2020	Dec. 22, 2020	Conducted (TH05-HY)
Spectrum Analyzer	Rohde & Schwarz	FSP40	100055	9kHz-40GHz	Dec. 30, 2019	Jun. 11, 2020~ Jul. 03, 2020	Dec. 29, 2020	Conducted (TH05-HY)
Switch Box & RF Cable	Burgeon	ETF-058	EC130048 4	N/A	Aug. 22, 2019	Jun. 11, 2020~ Jul. 03, 2020	Aug. 21, 2020	Conducted (TH05-HY)
Power Supply	GW Instek	SPS-606	GES84293 1	NA	Aug. 19, 2019	Jun. 11, 2020~ Jul. 03, 2020	Aug. 18, 2020	Conducted (TH05-HY)

5 Uncertainty of Evaluation

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.0
--	-----

Uncertainty of Radiated Emission Measurement (1000 MHz ~ 18000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.4
--	-----

Uncertainty of Radiated Emission Measurement (18000 MHz ~ 40000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.0
--	-----

Appendix A. Test Result of Conducted Test Items

Test Engineer:	Kai Liao and Kathy Chen	Temperature:	23.2~23.9	°C
Test Date:	2020/6/11~2020/07/03	Relative Humidity:	52.7~53.8	%

TEST RESULTS DATA
6dB and 99% Occupied Bandwidth

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	99% Occupied BW (MHz)	6dB BW (MHz)	6dB BW Limit (MHz)	Pass/Fail
BLE	1Mbps	1	0	2402	1.024	0.668	0.50	Pass
BLE	1Mbps	1	19	2440	1.022	0.668	0.50	Pass
BLE	1Mbps	1	39	2480	1.020	0.664	0.50	Pass

TEST RESULTS DATA
Average Power Table

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Average Conducted Power (dBm)	Conducted Power Limit (dBm)	DG (dBi)	EIRP Power (dBm)	EIRP Power Limit (dBm)	Pass /Fail
BLE	1Mbps	1	0	2402	1.80	30.00	3.62	5.42	36.00	Pass
BLE	1Mbps	1	19	2440	3.60	30.00	3.62	7.22	36.00	Pass
BLE	1Mbps	1	39	2480	2.70	30.00	3.62	6.32	36.00	Pass

TEST RESULTS DATA
Peak Power Density

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Peak PSD (dBm /100kHz)	Peak PSD (dBm /3kHz)	DG (dBi)	Peak PSD Limit (dBm /3kHz)	Pass/Fail
BLE	1Mbps	1	0	2402	1.91	-12.71	3.62	8.00	Pass
BLE	1Mbps	1	19	2440	3.34	-11.24	3.62	8.00	Pass
BLE	1Mbps	1	39	2480	1.83	-12.79	3.62	8.00	Pass

Note: PSD (dBm/ 100kHz) is a reference level used for Conducted Band Edges and Conducted Spurious Emission 30dBc limit.

TEST RESULTS DATA
6dB and 99% Occupied Bandwidth

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	99% Occupied BW (MHz)	6dB BW (MHz)	6dB BW Limit (MHz)	Pass/Fail
BLE	2Mbps	1	0	2402	2.004	1.136	0.50	Pass
BLE	2Mbps	1	19	2440	2.008	1.128	0.50	Pass
BLE	2Mbps	1	39	2480	2.008	1.136	0.50	Pass

TEST RESULTS DATA
Average Power Table

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Average Conducted Power (dBm)	Conducted Power Limit (dBm)	DG (dBi)	EIRP Power (dBm)	EIRP Power Limit (dBm)	Pass /Fail
BLE	2Mbps	1	0	2402	1.70	30.00	3.62	5.32	36.00	Pass
BLE	2Mbps	1	19	2440	3.50	30.00	3.62	7.12	36.00	Pass
BLE	2Mbps	1	39	2480	2.60	30.00	3.62	6.22	36.00	Pass

TEST RESULTS DATA
Peak Power Density

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Peak PSD (dBm /100kHz)	Peak PSD (dBm /3kHz)	DG (dBi)	Peak PSD Limit (dBm /3kHz)	Pass/Fail
BLE	2Mbps	1	0	2402	1.84	-15.92	3.62	8.00	Pass
BLE	2Mbps	1	19	2440	3.27	-14.51	3.62	8.00	Pass
BLE	2Mbps	1	39	2480	1.77	-15.98	3.62	8.00	Pass

Note: PSD (dBm/ 100kHz) is a reference level used for Conducted Band Edges and Conducted Spurious Emission 30dBc limit.



Appendix B. Radiated Spurious Emission

Test Engineer :	Leo Lee, Mancy Chou, and Bigshow Wang	Temperature :	21.4~22.9°C
		Relative Humidity :	52~61%

<1Mbps>

2.4GHz 2400~2483.5MHz

BLE (Band Edge @ 3m)

BLE	Note	Frequency	Level	Over	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.
		(MHz)	(dBμV/m)	(dB)	Line (dBμV/m)	Level (dBμV)	Factor (dB/m)	Loss (dB)	Factor (dB)	Pos (cm)	Pos (deg)	Avg. (P/A)	(H/V)
BLE CH 00 2402MHz		2351.475	55.99	-18.01	74	41.89	27.99	17.27	31.16	400	232	P	H
		2375.31	46.5	-7.5	54	32.48	27.85	17.32	31.15	400	232	A	H
	*	2402	88.76	-	-	74.83	27.7	17.37	31.14	400	232	P	H
	*	2402	88.22	-	-	74.29	27.7	17.37	31.14	400	232	A	H
													H
													H
		2354.625	55.91	-18.09	74	41.82	27.97	17.28	31.16	400	121	P	V
		2349.06	46.78	-7.22	54	32.68	28	17.27	31.17	400	121	A	V
	*	2402	84.18	-	-	70.25	27.7	17.37	31.14	400	121	P	V
	*	2402	83.48	-	-	69.55	27.7	17.37	31.14	400	121	A	V
													V
													V
BLE CH 19 2440MHz		2346	55.63	-18.37	74	41.53	28.01	17.26	31.17	400	218	P	H
		2340.72	46.53	-7.47	54	32.43	28.02	17.25	31.17	400	218	A	H
	*	2440	94.29	-	-	80.35	27.62	17.44	31.12	400	218	P	H
	*	2440	93.89	-	-	79.95	27.62	17.44	31.12	400	218	A	H
		2484.43	55	-19	74	41.05	27.53	17.52	31.1	400	218	P	H
		2491.72	46.11	-7.89	54	32.15	27.52	17.53	31.09	400	218	A	H
		2369.04	56.56	-17.44	74	42.52	27.89	17.31	31.16	400	249	P	V
		2319.76	46.61	-7.39	54	32.52	28.06	17.21	31.18	400	249	A	V
	*	2440	89.16	-	-	75.22	27.62	17.44	31.12	400	249	P	V
	*	2440	88.72	-	-	74.78	27.62	17.44	31.12	400	249	A	V
		2487.67	55.16	-18.84	74	41.22	27.52	17.52	31.1	400	249	P	V
		2498.29	46.31	-7.69	54	32.36	27.5	17.54	31.09	400	249	A	V



BLE CH 39 2480MHz	*	2480	94.43	-	-	80.48	27.54	17.51	31.1	400	244	P	H
	*	2480	93.97	-	-	80.02	27.54	17.51	31.1	400	244	A	H
		2491.04	55.51	-18.49	74	41.55	27.52	17.53	31.09	400	244	P	H
		2488.28	46.25	-7.75	54	32.3	27.52	17.53	31.1	400	244	A	H
													H
													H
	*	2480	90.07	-	-	76.12	27.54	17.51	31.1	400	92	P	V
	*	2480	89.55	-	-	75.6	27.54	17.51	31.1	400	92	A	V
		2497.08	54.89	-19.11	74	40.93	27.51	17.54	31.09	400	92	P	V
		2490.2	46.44	-7.56	54	32.48	27.52	17.53	31.09	400	92	A	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



2.4GHz 2400~2483.5MHz

BLE (Harmonic @ 3m)

BLE	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
BLE CH 00 2402MHz		4804	41.26	-32.74	74	58.48	31.21	10.65	59.08	100	0	P	H
													H
													H
													H
		4804	46.63	-27.37	74	63.85	31.21	10.65	59.08	100	0	P	V
													V
													V
													V
BLE CH 19 2440MHz		4880	40.05	-33.95	74	57.22	31.24	10.72	59.13	100	0	P	H
		7320	44.83	-29.17	74	54.27	36.54	12.57	58.55	100	0	P	H
													H
													H
		4880	39.88	-34.12	74	57.05	31.24	10.72	59.13	100	0	P	V
		7320	45.11	-28.89	74	54.55	36.54	12.57	58.55	100	0	P	V
													V
													V
BLE CH 39 2480MHz		4960	40.05	-33.95	74	56.89	31.54	10.8	59.18	100	0	P	H
		7440	46.34	-27.66	74	55.45	36.56	12.71	58.38	100	0	P	H
													H
													H
		4960	41.67	-32.33	74	58.51	31.54	10.8	59.18	100	0	P	V
		7440	45.42	-28.58	74	54.53	36.56	12.71	58.38	100	0	P	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



<2Mbps>

2.4GHz 2400~2483.5MHz

BLE (Band Edge @ 3m)

BLE	Note	Frequency	Level	Over	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.
				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
BLE CH 00 2402MHz		2389.275	55.92	-18.08	74	41.96	27.76	17.35	31.15	100	160	P	H
		2377.2	47.94	-6.06	54	33.93	27.84	17.32	31.15	100	160	A	H
	*	2402	88.59	-	-	74.66	27.7	17.37	31.14	100	160	P	H
	*	2402	87.31	-	-	73.38	27.7	17.37	31.14	100	160	A	H
													H
													H
		2352.315	55.38	-18.62	74	41.28	27.99	17.27	31.16	400	259	P	V
		2377.305	48.17	-5.83	54	34.16	27.84	17.32	31.15	400	259	A	V
	*	2402	85.25	-	-	71.32	27.7	17.37	31.14	400	259	P	V
	*	2402	83.87	-	-	69.94	27.7	17.37	31.14	400	259	A	V
													V
													V
BLE CH 19 2440MHz		2337.44	55.44	-18.56	74	41.34	28.03	17.24	31.17	100	39	P	H
		2312.66	48.27	-5.73	54	34.19	28.07	17.19	31.18	100	39	A	H
	*	2440	92.28	-	-	78.34	27.62	17.44	31.12	100	39	P	H
	*	2440	90.94	-	-	77	27.62	17.44	31.12	100	39	A	H
		2487.05	55.18	-18.82	74	41.23	27.53	17.52	31.1	100	39	P	H
		2499.16	47.52	-6.48	54	33.57	27.5	17.54	31.09	100	39	A	H
		2350.46	55.55	-18.45	74	41.44	28	17.27	31.16	400	249	P	V
		2359.14	47.78	-6.22	54	33.7	27.95	17.29	31.16	400	249	A	V
	*	2440	90.35	-	-	76.41	27.62	17.44	31.12	400	249	P	V
	*	2440	89.02	-	-	75.08	27.62	17.44	31.12	400	249	A	V
		2499.72	55.04	-18.96	74	41.08	27.5	17.55	31.09	400	249	P	V
		2486.42	47.78	-6.22	54	33.83	27.53	17.52	31.1	400	249	A	V



BLE CH 39 2480MHz	*	2480	92.12	-	-	78.17	27.54	17.51	31.1	100	36	P	H
	*	2480	90.83	-	-	76.88	27.54	17.51	31.1	100	36	A	H
		2492.92	55.61	-18.39	74	41.66	27.51	17.53	31.09	100	36	P	H
		2485.8	47.48	-6.52	54	33.53	27.53	17.52	31.1	100	36	A	H
													H
													H
	*	2480	90.42	-	-	76.47	27.54	17.51	31.1	400	92	P	V
	*	2480	89.1	-	-	75.15	27.54	17.51	31.1	400	92	A	V
		2484.32	54.93	-19.07	74	40.98	27.53	17.52	31.1	400	92	P	V
		2496.36	47.59	-6.41	54	33.63	27.51	17.54	31.09	400	92	A	V
													V
													V
Remark	3. No other spurious found. 4. All results are PASS against Peak and Average limit line.												



2.4GHz 2400~2483.5MHz

BLE (Harmonic @ 3m)

BLE	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
BLE CH 00 2402MHz		4804	40.42	-33.58	74	57.64	31.21	10.65	59.08	100	0	P	H
													H
													H
													H
		4804	46.61	-27.39	74	63.83	31.21	10.65	59.08	100	0	P	V
													V
													V
													V
BLE CH 19 2440MHz		4880	40.14	-33.86	74	57.31	31.24	10.72	59.13	100	0	P	H
		7320	44.59	-29.41	74	54.03	36.54	12.57	58.55	100	0	P	H
													H
													H
		4880	39.81	-34.19	74	56.98	31.24	10.72	59.13	100	0	P	V
		7320	45.09	-28.91	74	54.53	36.54	12.57	58.55	100	0	P	V
													V
													V
BLE CH 39 2480MHz		4960	40.48	-33.52	74	57.32	31.54	10.8	59.18	100	0	P	H
		7440	46.15	-27.85	74	55.26	36.56	12.71	58.38	100	0	P	H
													H
													H
		4960	41.11	-32.89	74	57.95	31.54	10.8	59.18	100	0	P	V
		7440	46.11	-27.89	74	55.22	36.56	12.71	58.38	100	0	P	V
													V
													V
Remark	3. No other spurious found. 4. All results are PASS against Peak and Average limit line.												

Emission below 1GHz

2.4GHz BLE (LF)

BLE	Note	Frequency	Level	Over	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.
				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
2.4GHz BLE LF		60.07	26.49	-13.51	40	45.89	12.11	1.02	32.53	-	-	P	H
		95.96	31.96	-11.54	43.5	47.28	15.64	1.33	32.29	-	-	P	H
		135.73	31.58	-11.92	43.5	44.8	17.67	1.61	32.5	-	-	P	H
		359.8	39.14	-6.86	46	48.45	20.48	2.59	32.38	100	0	P	H
		720.64	38.79	-7.21	46	40.55	26.92	3.74	32.42	-	-	P	H
		889.42	35.19	-10.81	46	34.36	28.49	4.26	31.92	-	-	P	H
													H
													H
													H
													H
													H
													H
		56.19	32.89	-7.11	40	51.69	12.71	0.98	32.49	100	0	P	V
		120.21	30.72	-12.78	43.5	43.99	17.65	1.51	32.43	-	-	P	V
		191.99	32.15	-11.35	43.5	47.55	15.01	1.97	32.38	-	-	P	V
		359.8	37.67	-8.33	46	46.98	20.48	2.59	32.38	-	-	P	V
		408.3	35.2	-10.8	46	42.52	22.13	2.76	32.21	-	-	P	V
		886.51	35.1	-10.9	46	34.22	28.54	4.25	31.91	-	-	P	V
													V
													V
													V
													V
													V
													V
												V	
Remark	1. No other spurious found. 2. All results are PASS against limit line.												



Note symbol

*	Fundamental Frequency which can be ignored. However, the level of any unwanted emissions shall not exceed the level of the fundamental frequency.
!	Test result is over limit line.
P/A	P eak or A verage
H/V	H orizontal or V ertical

A calculation example for radiated spurious emission is shown as below:

BLE	Note	Frequency	Level	Over	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.
				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
BLE CH 00 2402MHz		2390	55.45	-18.55	74	54.51	32.22	4.58	35.86	103	308	P	H
		2390	43.54	-10.46	54	42.6	32.22	4.58	35.86	103	308	A	H

1. Path Loss(dB) = Cable loss(dB) + Filter loss(dB) + Attenuator loss(dB)
2. Level(dBμV/m) =
Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)
3. Over Limit(dB) = Level(dBμV/m) – Limit Line(dBμV/m)

For Peak Limit @ 2390MHz:

1. Level(dBμV/m)
= Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)
= 32.22(dB/m) + 4.58(dB) + 54.51(dBμV) – 35.86 (dB)
= 55.45 (dBμV/m)
2. Over Limit(dB)
= Level(dBμV/m) – Limit Line(dBμV/m)
= 55.45(dBμV/m) – 74(dBμV/m)
= -18.55(dB)

For Average Limit @ 2390MHz:

1. Level(dBμV/m)
= Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)
= 32.22(dB/m) + 4.58(dB) + 42.6(dBμV) – 35.86 (dB)
= 43.54 (dBμV/m)
2. Over Limit(dB)
= Level(dBμV/m) – Limit Line(dBμV/m)
= 43.54(dBμV/m) – 54(dBμV/m)
= -10.46(dB)

Both peak and average measured complies with the limit line, so test result is “PASS”.



Appendix C. Radiated Spurious Emission Plots

Test Engineer :	Leo Lee, Mancy Chou, and Bigshow Wang	Temperature :	21.4~22.9°C
		Relative Humidity :	52~61%

Note symbol





-L	Low channel location
-R	High channel location



<1Mbps>

2.4GHz 2400~2483.5MHz

BLE (Band Edge @ 3m)

BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
	BLE CH00 2402MHz	
	Horizontal	Fundamental
Peak	 Site : 03CH15-HY Condition : PEAK_BE_74 3m 91200_15_1620 HORIZONTAL	 Site : 03CH15-HY Condition : PEAK_74 3m 91200_15_1620 HORIZONTAL
Avg.	 Site : 03CH15-HY Condition : AVG_BE_54 3m 91200_15_1620 HORIZONTAL	 Site : 03CH15-HY Condition : AVG_54 3m 91200_15_1620 HORIZONTAL





BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
	BLE CH00 2402MHz	
	Vertical	Fundamental
Peak	Site : 03CH15-HY Condition : PEAK_BE_74 3m 91200_15_1620 VERTICAL	Site : 03CH15-HY Condition : PEAK_74 3m 91200_15_1620 VERTICAL
Avg	Site : 03CH15-HY Condition : AVG_BE_54 3m 91200_15_1620 VERTICAL	Site : 03CH15-HY Condition : AVG_54 3m 91200_15_1620 VERTICAL



BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
	BLE CH19 2440MHz - L	
	Horizontal	Fundamental
Peak	Site : 03CH15-HY Condition : PEAK_BE_74 3m 91200_15_1620 HORIZONTAL	Site : 03CH15-HY Condition : PEAK_74 3m 91200_15_1620 HORIZONTAL
Avg.	Site : 03CH15-HY Condition : AVG_BE_54 3m 91200_15_1620 HORIZONTAL	Site : 03CH15-HY Condition : AVG_54 3m 91200_15_1620 HORIZONTAL









BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
	BLE CH19 2440MHz - R	
	Horizontal	Fundamental
Peak	 Site : 03CH15-HY Condition : PEAK_BE_74 3m 91200_15_1620 HORIZONTAL	Left blank
Avg.	 Site : 03CH15-HY Condition : AVG_BE_54 3m 91200_15_1620 HORIZONTAL	Left blank







BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
	BLE CH19 2440MHz - L	
	Vertical	Fundamental
Peak	Site : 03CH15-HY Condition : PEAK_BE_74 3m 91200_15_1620 VERTICAL	Site : 03CH15-HY Condition : PEAK_74 3m 91200_15_1620 VERTICAL
Avg.	Site : 03CH15-HY Condition : AVG_BE_54 3m 91200_15_1620 VERTICAL	Site : 03CH15-HY Condition : AVG_54 3m 91200_15_1620 VERTICAL



BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
	BLE CH19 2440MHz - R	
	Vertical	Fundamental
Peak	 Site : 03CH15-HY Condition : PEAK_BE_74 3m 91200_15_1620 VERTICAL	Left blank
Avg.	 Site : 03CH15-HY Condition : AVG_BE_54 3m 91200_15_1620 VERTICAL	Left blank



BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
	BLE CH39 2480MHz	
	Horizontal	Fundamental
Peak	 Site : 03CH15-HY Condition : PEAK_BE_74 3m 91200_15_1620 HORIZONTAL	 Site : 03CH15-HY Condition : PEAK_74 3m 91200_15_1620 HORIZONTAL
Avg.	 Site : 03CH15-HY Condition : AVG_BE_54 3m 91200_15_1620 HORIZONTAL	 Site : 03CH15-HY Condition : AVG_54 3m 91200_15_1620 HORIZONTAL

BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
	BLE CH39 2480MHz	
	Vertical	Fundamental
Peak	 Site : 03CH15-HY Condition : PEAK_BE_74 3m 91200_15_1620 VERTICAL	 Site : 03CH15-HY Condition : PEAK_74 3m 91200_15_1620 VERTICAL
Avg.	 Site : 03CH15-HY Condition : AVG_BE_54 3m 91200_15_1620 VERTICAL	 Site : 03CH15-HY Condition : AVG_54 3m 91200_15_1620 VERTICAL



2.4GHz 2400~2483.5MHz

BLE (Harmonic @ 3m)

BLE	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
	BLE CH00 2402MHz	
	Horizontal	Vertical
Peak Avg.	 Site : 03CH15-HY Condition : PEAK_74 3m 91200_15_1620 HORIZONTAL	 Site : 03CH15-HY Condition : PEAK_74 3m 91200_15_1620 VERTICAL



BLE	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
	BLE CH19 2440MHz	
	Horizontal	Vertical
Peak Avg.	Level (dBu/V/m) Date: 2020-07-07 Site : 03CH15-HY Condition : PEAK_74 3m 91200_15_1620 HORIZONTAL	Level (dBu/V/m) Date: 2020-07-07 Site : 03CH15-HY Condition : PEAK_74 3m 91200_15_1620 VERTICAL







BLE	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
	BLE CH39 2480MHz	
	Horizontal	Vertical
Peak	Level (dBuV/m) Date: 2020-07-07 Site : 03CH15-HY Condition : PEAK_74 3m 91200_15_1620 HORIZONTAL	Level (dBuV/m) Date: 2020-07-07 Site : 03CH15-HY Condition : PEAK_74 3m 91200_15_1620 VERTICAL







<2Mbps>

2.4GHz 2400~2483.5MHz





BLE (Band Edge @ 3m)

BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
	BLE CH00 2402MHz	
	Horizontal	Fundamental
Peak	 Site : 03CH15-HY Condition : PEAK_BE_74 3m 91200_15_1620 HORIZONTAL	 Site : 03CH15-HY Condition : PEAK_74 3m 91200_15_1620 HORIZONTAL
Avg.	 Site : 03CH15-HY Condition : AVG_BE_54 3m 91200_15_1620 HORIZONTAL	 Site : 03CH15-HY Condition : AVG_54 3m 91200_15_1620 HORIZONTAL





BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
	BLE CH00 2402MHz	
	Vertical	Fundamental
Peak	 Site : 03CH15-HY Condition : PEAK_BE_74 3m 91200_15_1620 VERTICAL	 Site : 03CH15-HY Condition : PEAK_74 3m 91200_15_1620 VERTICAL
Avg	 Site : 03CH15-HY Condition : AVG_BE_54 3m 91200_15_1620 VERTICAL	 Site : 03CH15-HY Condition : AVG_54 3m 91200_15_1620 VERTICAL



BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
	BLE CH19 2440MHz - L	
	Horizontal	Fundamental
Peak	 Site : 03CH15-HY Condition : PEAK_BE_74 3m 91200_15_1620 HORIZONTAL	 Site : 03CH15-HY Condition : PEAK_74 3m 91200_15_1620 HORIZONTAL
Avg.	 Site : 03CH15-HY Condition : AVG_BE_54 3m 91200_15_1620 HORIZONTAL	 Site : 03CH15-HY Condition : AVG_54 3m 91200_15_1620 HORIZONTAL





BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
	BLE CH19 2440MHz - R	
	Horizontal	Fundamental
Peak	 Site : 03CH15-HY Condition : PEAK_BE_74 3m 91200_15_1620 HORIZONTAL	Left blank
Avg.	 Site : 03CH15-HY Condition : AVG_BE_54 3m 91200_15_1620 HORIZONTAL	Left blank







BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
	BLE CH19 2440MHz - L	
	Vertical	Fundamental
Peak	Site : 03CH15-HY Condition : PEAK_BE_74 3m 91200_15_1620 VERTICAL	Site : 03CH15-HY Condition : PEAK_74 3m 91200_15_1620 VERTICAL
Avg.	Site : 03CH15-HY Condition : AVG_BE_54 3m 91200_15_1620 VERTICAL	Site : 03CH15-HY Condition : AVG_54 3m 91200_15_1620 VERTICAL







BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
	BLE CH19 2440MHz - R	
	Vertical	Fundamental
Peak	 Site : 03CH15-HY Condition : PEAK_BE_74 3m 91200_15_1620 VERTICAL	Left blank
Avg.	 Site : 03CH15-HY Condition : AVG_BE_54 3m 91200_15_1620 VERTICAL	Left blank



BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
	BLE CH39 2480MHz	
	Horizontal	Fundamental
Peak	 Site : 03CH15-HY Condition : PEAK_BE_74 3m 91200_15_1620 HORIZONTAL	 Site : 03CH15-HY Condition : PEAK_74 3m 91200_15_1620 HORIZONTAL
Avg.	 Site : 03CH15-HY Condition : AVG_BE_54 3m 91200_15_1620 HORIZONTAL	 Site : 03CH15-HY Condition : AVG_54 3m 91200_15_1620 HORIZONTAL





BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
	BLE CH39 2480MHz	
	Vertical	Fundamental
Peak	 Site : 03CH15-HY Condition : PEAK_BE_74 3m 91200_15_1620 VERTICAL	 Site : 03CH15-HY Condition : PEAK_F4 3m 91200_15_1620 VERTICAL
Avg.	 Site : 03CH15-HY Condition : AVG_BE_54 3m 91200_15_1620 VERTICAL	 Site : 03CH15-HY Condition : AVG_F4 3m 91200_15_1620 VERTICAL



2.4GHz 2400~2483.5MHz

BLE (Harmonic @ 3m)

BLE	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
	BLE CH00 2402MHz	
	Horizontal	Vertical
Peak Avg.	 Site : 03CH15-HY Condition : PEAK_74 3m 91200_15_1620 HORIZONTAL	 Site : 03CH15-HY Condition : PEAK_74 3m 91200_15_1620 VERTICAL





BLE	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
	BLE CH19 2440MHz	
	Horizontal	Vertical
Peak Avg.	Level (dBuV/m) Date: 2020-07-07 Site : 03CH15-HY Condition : PEAK_74 3m 91200_15_1620 HORIZONTAL	Level (dBuV/m) Date: 2020-07-07 Site : 03CH15-HY Condition : PEAK_74 3m 91200_15_1620 VERTICAL



BLE	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
	BLE CH39 2480MHz	
	Horizontal	Vertical
Peak	Level (dBuV/m) Date: 2020-07-07 Site : 03CH15-HY Condition : PEAK_74 3m 91200_15_1620 HORIZONTAL	Level (dBuV/m) Date: 2020-07-07 Site : 03CH15-HY Condition : PEAK_74 3m 91200_15_1620 VERTICAL

Emission below 1GHz
2.4GHz BLE (LF)


BLE	2.4GHz 2400~2483.5MHz	
	BLE LF	
	Horizontal	Vertical
QP / Peak	 Site : 03CH15-HY Condition : QP 3m BIL06_15_41912 HORIZONTAL	 Site : 03CH15-HY Condition : QP 3m BIL06_15_41912 VERTICAL

Appendix D. Duty Cycle Plots

Band	Duty Cycle(%)	T(us)	1/T(kHz)	VBW Setting	Duty Factor(dB)
Bluetooth –LE for 1Mbps	61.78	388	2.58	3kHz	2.09
Bluetooth –LE for 2Mbps	32.48	204	4.90	10kHz	4.88

Bluetooth - LE


<1Mbps>



Date: 12.JUN.2020 00:35:38



<2Mbps>



Date: 12.JUN.2020 00:34:03