



## **Test Report**

# **AIR-CAP3502P-A-K9**

**Cisco Aironet 802.11n Dual Band Access Points**

**FCC ID: LDK102079P**

**IC: 2461B-102079P**

**(Also covers AIR-CAP3502P-N-K9)**

**5250-5350 MHz**

**Against the following Specifications:**

**CFR47 Part 15.407**

**RSS210**

**Cisco Systems**

170 West Tasman Drive

San Jose, CA 95134



This test report has been electronically authorized and archived using the CISCO Engineering Document Control system.

<b>SECTION 1: OVERVIEW .....</b>	<b>3</b>
1.1 TEST SUMMARY .....	3
<b>SECTION 2: ASSESSMENT INFORMATION.....</b>	<b>4</b>
2.1 GENERAL .....	4
2.4 TESTING FACILITIES .....	5
2.6 EUT DESCRIPTION.....	5
<b>SECTION 4: SAMPLE DETAILS.....</b>	<b>6</b>
<b>APPENDIX A:     EMISSION TEST RESULTS .....</b>	<b>7</b>
AVERAGE OUTPUT POWER .....	<b>ERROR! BOOKMARK NOT DEFINED.</b>
99% AND 26dB BANDWIDTH.....	8
PEAK OUTPUT POWER .....	13
POWER SPECTRAL DENSITY .....	13
PEAK EXCURSION .....	23
CONDUCTED SPURIOUS EMISSIONS .....	28
<b>APPENDIX B:     EMISSION TEST RESULTS .....</b>	<b>34</b>
RADIATED SPURIOUS .....	<b>ERROR! BOOKMARK NOT DEFINED.</b>
RADIATED SPURIOUS EMISSIONS .....	38
CONDUCTED EMISSIONS.....	45
RADIATED EMISSIONS .....	47
MAXIMUM PERMISSIBLE EXPOSURE (MPE) CALCULATIONS.....	49
<b>APPENDIX C:     TEST EQUIPMENT/SOFTWARE USED TO PERFORM THE TEST.....</b>	<b>51</b>

## Section 1: Overview

### 1.1 Test Summary

**samples were assessed against the tests detailed in section 3 under the requirements of the following specifications:**

Emission	Immunity
CFR47 Part 15.407 RSS210	N/A

The specifications listed above represent actual tests performed to demonstrate compliance against the specifications and basic standards listed on the front cover of this report. This list is not a one to one match to the front cover for one or more of the following reasons.

1. Basic standards call up many different test phenomena specifications such as the 61000-4-X series. The basic standards define which elements and levels shall be applied from these specifications and as such it is not appropriate to list the individual specifications on the front cover.
2. A Standard listed on the front cover may be required in a particular country but is not appropriate for the particular technologies included in the equipment under test. E.g. You cannot test a DC product to the mains Harmonics requirements in EN61000-3-2. See section 3.2.
3. Test results against a particular standard or specification may be included in a different test report. See section 3.2 for an EDCS reference of this data.
4. Where appropriate, Cisco may have substituted a later revision of a basic standard to those referenced in the specification on the front sheet of this test report. This decision was based upon improved test methodology and repeatability and/or where the newer revision represented a more stringent test.
5. Where relevant, testing has been carried out to the requirements of both EN and IEC Specifications. This was possible because of the similarities of the test methods involved and the Cisco EMC test procedures.
6. Testing may have been performed to an equivalent test that satisfies the requirements of the standards and specifications listed on the front cover of the report. See section 3.2.
7. Where radiated emissions testing has been performed to EN55022/CISPR22 the additional requirements of VCCI: V- 3/2006.04, EN55022: 1994 +A1/2 and CAN/CSA- CISPR 22-02 have also been evaluated unless otherwise stated.
8. Testing to the requirements of CFR47 Part 15 was performed against the CISPR22 limits. The results are therefore deemed satisfactory evidence of compliance with Industry Canada Interference Causing Equipment Standard ICES-003.
9. Where assessment has been performed to CISPR24, all the applicable test requirements may have not been covered. Refer to the results section for the tests performed.

#### Notes:

- 1) Where a specification listed on the front cover of this report has deviations from the basic standards listed above, the additional technical requirements of the specification were also assessed.
- 2) Where appropriate, Cisco may have substituted a later revision of a basic standard to those referenced in the specification on the front sheet of this test report. This decision was based upon improved test methodology and repeatability and/or where the newer revision represented a more stringent test.
- 3) Where relevant, testing has been carried out to the requirements of both EN and IEC Specifications. This was possible because of the similarities of the test methods involved and the Cisco EMC test procedures.



## **Section 2: Assessment Information**

### **2.1 General**

This report contains an assessment of an apparatus against Electromagnetic Compatibility Standards based upon tests carried out on the samples submitted. The testing was performed by and for the use of Cisco systems Inc:

With regard to this assessment, the following points should be noted:

- a) The results contained in this report relate only to the items tested and were obtained in the period between the date of the initial assessment and the date of issue of the report. Manufactured products will not necessarily give identical results due to production and measurement tolerances.
- b) The apparatus was set up and exercised using the configuration and modes of operation defined in this report only.
- c) Where relevant, the apparatus was only assessed using the susceptibility criteria defined in this report and the Test Assessment Plan (TAP).
- d) All testing was performed under the following environmental conditions:

Temperature	15°C to 35°C (54°F to 95°F)
Atmospheric Pressure	860mbar to 1060mbar (25.4" to 31.3")
Humidity	10% to 75*%

\*[Where applicable] For ESD testing the humidity limits used were 30% to 60% and for EFT/B tests the humidity limits used were 25% to 75%.
- e) All AC testing was performed at one or more of the following supply voltages:

110V 60 Hz (+/-20%)
220V 50 Hz (+/-20%)

**This report must not be reproduced except in full, without written approval of Cisco Systems.**



## **2.2 Date of start of testing**

7- June-2011

## **2.3 Report Issue Date**

Cisco uses an electronic system to issue, store and control the revision of test reports. This system is called the Engineering Document Control System (EDCS). The actual report issue date is embedded into the original file on EDCS. Any copies of this report, either electronic or paper, that are not on EDCS must be considered uncontrolled

## **2.4 Testing facilities**

This assessment was performed by:

### **Testing Laboratory**

Cisco Systems, Inc.,	Cisco Systems, Inc.
4125 Highlander Parkway	170 West Tasman Drive
Richfield, OH 44286	San Jose, CA 95134
USA	USA

### **Test Engineers**

James Nicholson

## **2.5 Equipment Assessed (EUT)**

AIR-CAP3502P-A-K9 Cisco Aironet 802.11n Dual Band Access Point

## **2.6 EUT Description**

3500 Series Cisco Aironet 802.11n Dual Band Access Point support the following modes of operation. The modes are further defined in the radio Theory of Operation. The modes included in this report represent the worst case data for all modes.

- Legacy OFDM, Non HT-20, Single Antenna, 6 to 54 Mbps
- Legacy OFDM, Non HT-20, Dual Antennas, 6 to 54 Mbps
- Legacy OFDM , Non HT-20 Dual Antennas with Beam Forming, 6 to 54 Mbps
- HT-20, Single Antenna, M0 to M7
- HT-20, Dual Antennas, M0-M7
- HT-20, Dual Antennas, M8 to M15
- Non HT-40 Duplicate, Single Antenna, 6-54 Mbps
- Non HT-40 Duplicate, Dual Antennas, 6-54 Mbps
- HT-40, Single Antenna, M0 to M7
- HT-40, Dual Antennas, M0 to M7
- HT-40, Dual Antennas, M8 to M15



The following antennas are supported by this product series. The items in bold will be specifically tested and cover all others. The data included in this report represent the worst case data for all antennas.

<b>5 GHz</b>	AIR-ANT5135D-R	Articulating dipole	3.5
	AIR-ANT5135DB-R	Articulating dipole	3.5
	AIR-ANT5135DG-R	Non-articulating gray dipole	3.5
	AIR-ANT5135DW-R	Articulating white dipole	3.5
	AIR-ANT5135SDW-R	Stubby monopole	3.5
	AIR-ANT5140V-R	3-element MIMO ceiling mount omni	4
	AIR-ANT5160NP-R	3-element MIMO patch antenna	6
<b>2.4/5 GHz</b>	AIR-ANT2451NV-R	MIMO 6-Element Dual Band Omni	2.5 / 3.5
	AIR-ANT25137NP-R	Patch	13/7

#### Section 4: Sample Details

Note: Each sample was evaluated to ensure that its condition was suitable to be used as a test sample prior to the commencement of testing. Please also refer to the "Justification for worst Case test Configuration" section of this report for further details on the selection of EUT samples.

##### 4.1 Sample Details (Photographs of the test samples, where appropriate can be found in appendix H)

Sample No.	Equipment Details	Part Number	Manufacturer	Hardware Rev.	Firmware Rev.	Software Rev.	Serial Number
S01	AIR-CAP3502P-A-K9		Cisco Systems	NA	NA	NA	
S02	AIR-PWR-B	341-0306-01	Cisco Systems	NA	NA	NA	
S05	AIR-ANT25137NP-R						

##### 4.2 System Details

System #	Description	Samples
1	EUT	S01, S02

##### 4.3 Mode of Operation Details

Mode#	Description	Comments
1	Continuous Transmitting	Continuous Transmitting

**Appendix A: Emission Test Results****Testing Laboratory:** Cisco Systems, Inc., 4125 Highlander Parkway, Richfield, OH, USA**Target Maximum Channel Power**

The following table details the maximum supported Total Channel Power for all operating modes.

<b>5260-5320 MHz</b>	
<b>Operating Mode</b>	<b>Max Chanel Power (dBm)</b>
HT-20 , M0 to M7, Single Tx	<b>17</b>
HT-20 , M0 to M7, Dual Tx	<b>18</b>
Non HT-20 Beam Forming, 6-54 Mbps	<b>17</b>
HT-20, M8-M15	<b>19</b>
Non HT-40 Duplicate, 6-54Mbps	<b>15</b>
HT-40, M0 to M7	<b>15</b>
Non HT-40 Duplicate, 6-54 Mbps	<b>17</b>
HT-40, M0 to M7	<b>17</b>
HT-40 ,M8-M15	<b>17</b>



## 99% and 26dB Bandwidth

Connect the antenna port(s) to the spectrum analyzer input. Using the spectrum analyzer Channel Bandwidth mode, configure the spectrum analyzer as shown below (enter all losses between the transmitter output and the spectrum analyzer).


Center Frequency: Frequency from table below  
 Span: 2 x Nominal Bandwidth (e.g. 40MHz for a 20MHz channel)  
 Reference Level: 20 dBm  
 Attenuation: 10 dB  
 Sweep Time: 5 s  
 Resolution Bandwidth: 1%-3% of 26 dB Bandwidth  
 Video Bandwidth: ≥Resolution Bandwidth  
 X dB Bandwidth: 26 dB  
 Detector: Peak  
 Trace: Single

Place the radio in continuous transmit mode. View the transmitter waveform on the spectrum analyzer, and record the pertinent measurements:


Frequency (MHz)	Mode	Data Rate (Mbps)	26dB BW (MHz)	99% BW (MHz)
5260	HT-20 , M0-M7	M7	24.4	18
	Non HT-20, 6-54 Mbps	54	23.2	16.9
5320	HT-20 , M0-M7	M7	23.4	18
	Non HT-20, 6-54 Mbps	54	23.7	16.9
5260/5280	Non HT-40 Duplicate, 6-54Mbps	54	61.0	36.8
	HT-40, M0-M7	M7	42.6	36.36
5300/5320	Non HT-40 Duplicate, 6-54Mbps	54	46.9	36.6
	HT-40, M0-M7	M7	42.7	36.37




## 99%/26 dB Bandwidth, 5260 MHz, m7, HT-20




## 99%/26 dB Bandwidth, 5260 MHz, 54Mbps , non HT-20




## 99%/26 dB Bandwidth, 5320 MHz, m7, HT-20




## 99%/26 dB Bandwidth, 5320 MHz, 54Mbps , non HT-20




99%/26 dB Bandwidth, 5260/5280 MHz, 54Mbps, non HT-40 Duplicate




99%/26 dB Bandwidth, 5260/5280 MHz, M7, HT-40



99%/26 dB Bandwidth, 5300/5320MHz, 54Mbps, non HT-40 Duplicate



99%/26 dB Bandwidth, 5300/5320MHz, M7, HT-40





## Peak Output Power

15.407: For the bands 5.25-5.35 GHz, the maximum conducted output power over the frequency band of operation shall not exceed the lesser of 250 mW or  $11 \text{ dBm} + 10 \log B$ , where B is the 26-dB emission bandwidth in MHz. If transmitting antennas of directional gain greater than 6 dBi are used, the maximum conducted output power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

The smallest 26dB bandwidth for all channels is 23.2 MHz. The maximum conducted output power is calculated as  $11\text{dBm} + 10 \cdot \log(23.2\text{MHz}) = 24.6\text{dBm}$

The maximum supported antenna gain for all bands is 7dBi. The peak correlated gain for each mode is listed in the table below. See the Theory of Operation for details on the correlated gain for each mode.

The “measure-and-sum technique” is used for measuring in-band transmit power of a device. In the measure-and-sum approach, the conducted emission level is measured at each antenna port. The measured results at the various antenna ports are then summed mathematically to determine the total emission level from the device. Summing is performed in linear power units.

## Power Spectral Density

15.407: For the bands 5.25-5.35 GHz, the peak power spectral density shall not exceed 11 dBm in any 1-MHz band. If transmitting antennas of directional gain greater than 6 dBi are used, the peak power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

The maximum supported antenna gain is 7dBi. The peak correlated gain for each mode is listed in the table below. See the Theory of Operation for details on the correlated gain for each mode.

The “Measure and add  $10 \log(N)$  dB technique”, where N is the number of outputs, is used for measuring in-band Power Spectral Density. With this technique, spectrum measurements are performed at each output of the device, and the quantity  $10 \log(4)$  (or 6dB) is added to the worst case spectrum value before comparing to the emission limit.



Connect the antenna port(s) to the spectrum analyzer input. Place the radio in continuous transmit mode. Configure the spectrum analyzer as shown below.

Enable "Channel Power" function of analyzer	
Center Frequency:	Frequency from table below
Span:	20 MHz (must be greater than 26dB bandwidth, adjust as necessary)
Ref Level Offset:	Correct for attenuator and cable loss.
Reference Level:	20 dBm
Attenuation:	20 dB
Sweep Time:	100ms, Single sweep
Resolution Bandwidth:	1 MHz
Video Bandwidth:	3 MHz
Detector:	Sample
Trace:	Trace Average 100 traces in Power Averaging Mode
Integration BW:	=26 dB BW from 26 dB Bandwidth Data

After averaging 100 traces of the transmitter waveform on the spectrum analyzer, record the spectrum analyzer Channel Power. Perform a Marker Peak Search function, and record this value as the Power Spectral Density.

**Peak Power Table**


	Operating Mode	Tx Paths	Correlated Antenna Gain (dBi)	Tx 1 Peak Power (dBm)	Tx 2 Peak Power (dBm)	Total Tx Channel Power (dBm)	Limit (dBm)	Margin (dBm)
5260	HT-20, M0-M7	1	7	16.9	—	16.9	24	6.7
	HT-20, M0-M7	2	7	14.9	14.7	17.8	24	6
	Non HT-20, 6-54 Mbps, Beam Forming	2	10	13.9	13.8	16.9	21	4
	HT-20, M8-M15	2	7	15.7	15.9	18.8	24	5
5320	HT-20, M0-M7	1	7	17.2	—	17.2	24	6
	HT-20, M0-M7	2	7	14.8	14.7	17.8	24	6
	Non HT-20, 6-54 Mbps, Beam Forming	2	10	13.8	13.9	16.9	21	4
	HT-20, M8-M15	2	7	16.3	15.6	19.0	24	5
5260/5280	Non HT-40 Duplicate, 6-54Mbps	1	7	14.8	—	14.8	24	9
	HT-40, M0-M7	1	7	14.8	—	14.8	24	9
	Non HT-40 Duplicate, 6-54Mbps	2	7	13.8	13.8	16.8	24	7
	HT-40, M0-M7	2	7	13.8	13.5	16.7	24	7
	HT-40, M8-M15	2	7	13.8	14.7	17.3	24	6
5300/5320	Non HT-40 Duplicate, 6-54Mbps	1	7	14.7	—	14.7	24	9
	HT-40, M0-M7	1	7	15.0	—	15.0	24	9
	Non HT-40 Duplicate, 6-54Mbps	2	7	13.8	13.8	16.8	24	7
	HT-40, M0-M7	2	7	14.1	13.5	16.8	24	7
	HT-40, M8-M15	2	7	13.8	13.8	16.8	24	7





Frequency (MHz)	Operating Mode	Tx Paths	Correlated Antenna Gain (dBi)	PSD / Antenna (dBm/MHz)	Total PSD (dBm/MHz)	Limit dBm/MHz	Margin (dB)
5260	HT-20, M0-M7	1	7	5.6	5.6	<b>10</b>	4.4
	HT-20, M0-M7	2	10	4.0	7.0	<b>7</b>	0.0
	Non HT-20, 6-54 Mbps, Beam Forming	2	10	3.3	6.3	<b>7</b>	0.7
	HT-20, M8-M15	2	7	5.1	8.1	<b>10</b>	1.9
5320	HT-20, M0-M7	1	7	6.1	6.1	<b>10</b>	3.9
	HT-20, M0-M7	2	10	3.9	6.9	<b>7</b>	0.1
	Non HT-20, 6-54 Mbps, Beam Forming	2	10	3.3	6.3	<b>7</b>	0.7
	HT-20, M8-M15	2	7	5.6	8.6	<b>10</b>	1.4
5260/5280	Non HT-40 Duplicate, 6-54Mbps	1	7	1.6	1.6	<b>10</b>	8.4
	HT-40, M0-M7	1	7	1.2	1.2	<b>10</b>	8.8
	Non HT-40 Duplicate,6-54Mbps	2	10	1.3	4.3	<b>7</b>	2.7
	HT-40, M0-M7	2	10	0.6	3.6	<b>7</b>	3.4
	HT-40,M8-M15	2	7	1.5	4.5	<b>10</b>	5.5
5300/5320	Non HT-40 Duplicate, 6-54Mbps	1	7	1.8	1.8	<b>10</b>	8.2
	HT-40, M0-M7	1	7	1.8	1.8	<b>10</b>	8.2
	Non HT-40 Duplicate,6-54Mbps	2	10	0.8	3.8	<b>7</b>	3.2
	HT-40, M0-M7	2	10	0.7	3.7	<b>7</b>	3.3
	HT-40,M8-M15	2	7	0.8	3.8	<b>10</b>	6.2





## Peak Power/PSD, 5260 MHz, m7, HT-20













## Peak Power/PSD, 5260 MHz, m7, HT-20












## Peak Power/PSD, 5260 MHz, 54 Mbps, non HT-20, Beam Forming









**Peak Power/PSD, 5260 MHz, m8, HT-20****Peak Power/PSD, 5320 MHz, m7, HT-20****Peak Power/PSD, 5320 MHz, m7, HT-20**

**Peak Power/PSD, 5320 MHz, 54 Mbps, non HT-20 , Beam Forming****Peak Power/PSD, 5320 MHz, m8, HT-20****Peak Power/PSD, 5260/5280 MHz, 54 Mbps, non HT-40 Duplicate**

**Peak Power/PSD, 5260/5280 MHz, M7, HT-40****Peak Power/PSD, 5260/5280 MHz, 54 Mbps, non HT-40 Duplicate****Peak Power/PSD, 5260/5280 MHz, M7, Non HT-40**

**Peak Power/PSD, 5260/5280 MHz, M8, Non HT-40****Peak Power/PSD, 5300/5320MHz, 54 Mbps, non HT-40 Duplicate****Peak Power/PSD, 5300/5320MHz, M7, HT-40**

**Peak Power/PSD, 5300/5320MHz, 54 Mbps, non HT-40 Duplicate****Peak Power/PSD, 5300/5320MHz, M7 , Non HT-40****Peak Power/PSD, 5300/5320MHz, M8, Non HT-40**

## Peak Excursion

15.407: The ratio of the peak excursion of the modulation envelope (measured using a peak hold function) to the maximum conducted output power (measured as specified above) shall not exceed 13 dB across any 1 MHz bandwidth or the emission bandwidth whichever is less.

Set the spectrum analyzer span to view the entire emission bandwidth. The largest difference between the following two traces must be  $\leq 13$  dB for all frequencies across the emission bandwidth.

Set the spectrum analyzer span to view the entire emission bandwidth. The largest difference between the following two traces must be  $\leq 13$  dB for all frequencies across the emission bandwidth.

1st Trace: (Peak)

Set Span to encompass the entire emission bandwidth of the signal.

RBW = 1 MHz, VBW = 3 MHz

Detector = Peak

Sweep = Auto

Trace 1 = Max-hold

Ref Level Offset = correct for attenuator and cable loss

Ref Level = 20dBm

Atten = 10dBm

2nd Trace: (Average)

Trace 2 = clear right

Detector = Sample

Avg/VBW type = Pwr(RMS)

Average = 100

Sweep = single

Set marker Deltas

Trace 1 & Peak search


Marker Delta

Trace 2 & Peak search


Record the difference between the Peak and Average Markers

Frequency			Peak Excursion	Limit	Margin
(MHz)	Mode	Data Rate	(dB)	(dB)	(dB)
5260	HT-20 , M0-M7	M7	7.8	13	5.2
	Non HT-20, 6-54 Mbps	54	8.8	13	4.2
5320	HT-20 , M0-M7	M7	8.1	13	4.9
	Non HT-20, 6-54 Mbps	54	8.6	13	4.4
5260/5280	Non HT-40 Duplicate, 6-54Mbps	54	8.3	13	4.7
	HT-40, M0-M7	M7	7.3	13	5.7
5300/5320	Non HT-40 Duplicate, 6-54Mbps	54	8.4	13	4.6
	HT-40, M0-M7	M7	8.3	13	4.7

## Peak Excursion, 5260 MHz, m7, HT-20




## Peak Excursion, 5260 MHz, 54 Mbps ,non HT-20







## Peak Excursion, 5320 MHz, m7, HT-20




## Peak Excursion, 5320 MHz, 54 Mbps ,non HT-20




## Peak Excursion, 5260/5280 MHz, 54 Mbps, non HT-40 Duplicate




## Peak Excursion, 5260/5280 MHz, m7, HT-40



## Peak Excursion, 5300/5320MHz, 54 Mbps, non HT-40 Duplicate



## Peak Excursion, 5300/5320MHz, m7, HT-40





## Conducted Spurious Emissions

15.407: For transmitters operating in the 5.25-5.35 GHz band: all emissions outside of the 5.25-5.35 GHz band shall not exceed an EIRP of -27dBm/MHz.


Connect the antenna port(s) to the spectrum analyzer input. Place the radio in continuous transmit mode. Configure the spectrum analyzer as shown below (be sure to enter all losses between the transmitter output and the spectrum analyzer).

Span:	30 MHz-40 GHz
Reference Level:	20 dBm
Attenuation:	10 dB
Sweep Time:	10 s
Resolution Bandwidth:	1 MHz
Video Bandwidth:	3 MHz
Detector:	Peak
Trace:	Single
Marker:	Peak


Record the marker waveform peak to spur difference

Frequency			Conducted Spurs	Limit	Margin
(MHz)	Mode	Data Rate	(dBm)	(dBm)	(dB)
5260	HT-20 , M0-M7	M7	-39.87	-27	12.87
	Non HT-20, 6-54 Mbps	54	-39.53	-27	12.53
5320	HT-20 , M0-M7	M7	-38.1	-27	11.1
	Non HT-20, 6-54 Mbps	54	-39.1	-27	12.1
5260/5280	Non HT-40 Duplicate, 6-54Mbps	54	-39.2	-27	12.2
	HT-40, M0-M7	M7	-39.8	-27	12.8
5300/5320	Non HT-40 Duplicate, 6-54Mbps	54	-39	-27	12
	HT-40, M0-M7	M7	-38.6	-27	11.6


## Conducted Spurs, 5260 MHz, m7, HT-20




## Conducted Spurs, 5260 MHz, 54 Mbps ,non HT-20



## Conducted Spurs, 5320 MHz, m7, HT-20




## Conducted Spurs, 5320 MHz, 54 Mbps ,non HT-20







## Conducted Spurs, 5260/5280 MHz, 54 Mbps, non HT-40 Duplicate




## Conducted Spurs, 5260/5280 MHz, m7, HT-40




## Conducted Spurs, 5300/5320MHz, 54 Mbps, non HT-40 Duplicate



## Conducted Spurs, 5300/5320MHz, m7, HT-40







**Title:** Conducted Test Setup



## Appendix B: Emission Test Results

**Testing Laboratory:** Cisco Systems, Inc., 170 West Tasman Drive, San Jose, CA 95134, USA

### Radiated Spurious

Radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).

Using Vasona, configure the spectrum analyzer as shown below (be sure to enter all losses between the transmitter output and the spectrum analyzer). Place the radio in continuous transmit mode.



Reference Level: 110 dBuV  
 Attenuation: 20 dB  
 Sweep Time: Coupled  
 Resolution Bandwidth: 1MHz  
 Video Bandwidth: 1 MHz for peak, 10 Hz for average  
 Detector: Peak



Maximize Turntable (find worst case table angle), Maximize Antenna (find worst case height)



Save 2 plots: 1) Average Plot (Vertical and Horizontal), Limit= 54dBuV @3m  
 2) Peak plot (Vertical and Horizontal), Limit = 74dBuV @3m

Place a marker at the end of the restricted band closest to the transmit frequency to show compliance. Also measure any emissions in the restricted bands.

Frequency (MHz)	Mode	Data Rate (Mbps)	Radiated Band Edge Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)
5320	HT-20 Dual Tx Paths	M7	53.66	54	0.34
5300/5320	HT-40 Single Tx Path	M7	53.30	54	0.7
5300/5320	HT-40 Dual Tx Paths	M7	52.84	54	1.16

**Radiated Bandedge, 5320 MHz, m7, HT-20, Dual Transmit Paths, Average****Radiated Bandedge, 5300/5320MHz, M7, HT-40, Single Transmit Path, Average**

**Radiated Bandedge, 5300/5320MHz, M7, HT-40, Dual Transmit Paths, Average****Radiated Bandedge, 5320 MHz, m7, HT-20, Dual Transmit Paths, Peak**

**Radiated Bandedge, 5300/5320MHz, M7, HT-40, Single Transmit Path, Peak****Radiated Bandedge, 5300/5320MHz, M7, HT-40, Dual Transmit Paths, Peak**



## Radiated Spurious Emissions

Radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).

Using Vasona, configure the spectrum analyzer as shown below (be sure to enter all losses between the transmitter output and the spectrum analyzer). Place the radio in continuous transmit mode.

Span: 1GHz – 18 GHz  
 Reference Level: 80 dBuV  
 Attenuation: 10 dB  
 Sweep Time: Coupled  
 Resolution Bandwidth: 1MHz  
 Video Bandwidth: 1 MHz for peak, 10 Hz for average  
 Detector: Peak

Maximize Turntable (find worst case table angle), Maximize Antenna (find worst case height)

Save 2 plots: 1) Average Plot (Vertical and Horizontal), Limit= 54dBuV @3m  
 2) Peak plot (Vertical and Horizontal), Limit = 74dBuV @3m

Place a marker at the end of the restricted band closest to the transmit frequency to show compliance. Also measure any emissions in the restricted bands.


Frequency (MHz)	Mode	Data Rate (Mbps)	Spurious Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)
5260	HT-20 Dual Tx Paths	M7	<b>49.7</b>	54	4.3
5320	HT-20 Dual Tx Paths	M7	<b>48.1</b>	54	5.9
5260/5280	HT-40 Dual Tx Paths	M7	<b>47.2</b>	54	6.8
5300/5320	HT-40 Dual Tx Paths	M7	<b>49.1</b>	54	4.9



## Radiated Bandedge, 5260 MHz, m7, HT-20, Dual Transmit Paths, Average




## Radiated Bandedge, 5320 MHz, m7, HT-20, Dual Transmit Paths, Average



## Radiated Bandedge, 5260/5280 MHz, M7, HT-40, Dual Transmit Paths, Average




## Radiated Bandedge, 5300/5320MHz, M7, HT-40, Dual Transmit Paths, Average







## Radiated Bandedge, 5260 MHz, m7, HT-20, Dual Transmit Paths, Peak




## Radiated Bandedge, 5320 MHz, m7, HT-20, Dual Transmit Paths, Peak






## Radiated Bandedge, 5260/5280 MHz, M7, HT-40, Dual Transmit Paths, Peak



## Radiated Bandedge, 5300/5320MHz, M7, HT-40, Dual Transmit Paths, Peak




**Radiated Receiver Spurs, All Rates, All Modes, Average****Radiated Receiver Spurs, All Rates, All Modes, Peak**



5GHz 7 dBi Omni Antennas


## Conducted emissions



### Test Results Table


Frequency MHz	Raw dBuV	Cable Loss	Factors dB	Level dBuV	Measurement Type	Line	Limit dBuV	Margin dB	Pass /Fail	Comments
0.15	11.3	10.1	1.8	23.2	Av	N	56	-32.8	Pass	
0.15	39	10.1	1.8	51	Qp	N	66	-15	Pass	
0.155	39	10.1	1.7	50.8	Qp	N	65.7	-14.9	Pass	
0.155	10.9	10.1	1.7	22.7	Av	N	55.7	-33	Pass	
0.326	23.7	10.2	0.8	34.7	Av	N	49.6	-14.8	Pass	
0.326	27.2	10.2	0.8	38.2	Qp	N	59.6	-21.4	Pass	
2.152	20.3	10.3	0.4	31	Qp	N	56	-25	Pass	
2.152	18.8	10.3	0.4	29.5	Av	N	46	-16.5	Pass	
12.769	19.2	10.8	0.5	30.5	Av	N	50	-19.5	Pass	
12.769	24.2	10.8	0.5	35.6	Qp	N	60	-24.4	Pass	
16.354	18	11	0.7	29.6	Av	N	50	-20.4	Pass	
16.354	22.3	11	0.7	33.9	Qp	N	60	-26.1	Pass	





**Title:** Conducted Emissions Configuration Photograph

## Radiated emissions



## Test Results Table

Frequency MHz	Raw dBuV	Cable Loss	AF dB	Level dBuV/m	Measureme nt Type	Pol	Hgt cm	Azt Deg	Limit dBuV/m	Margin dB	Pass /Fail	Comments
53.747	29.3	0.8	7.4	37.5	Qp	V	96	57	40.5	-3	Pass	
117.525	15.2	1.5	13.6	30.4	Qp	V	96	55	40.5	-10.2	Pass	
250.005	27.1	2.1	11.6	40.8	Qp	V	96	170	47.5	-6.7	Pass	
500.019	23.1	2.8	17.8	43.7	Qp	V	100	178	47.5	-3.8	Pass	
625.025	22.8	3.1	19	45	Qp	V	158	156	47.5	-2.5	Pass	
875.033	16	3.6	21.9	41.5	Qp	V	121	178	47.5	-6	Pass	



**Title:** Radiated Emissions Configuration Photograph





## Maximum Permissible Exposure (MPE) Calculations

15.407: U-NII devices are subject to the radio frequency radiation exposure requirements specified in Sec. 1.1307(b), Sec. 2.1091 and Sec. 2.1093 of this chapter, as appropriate. All equipment shall be considered to operate in a "general population/uncontrolled" environment. Applications for equipment authorization of devices operating under this section must contain a statement confirming compliance with these requirements for both fundamental emissions and unwanted emissions. Technical information showing the basis for this statement must be submitted to the Commission upon request.

Given

$$E = \sqrt{(30 \cdot P \cdot G)/d} \text{ and } S = E^2/3770$$

where

E=Field Strength in Volts/meter

P=Power in Watts

G=Numeric Antenna Gain

d=Distance in meters

S=Power Density in mW/cm<sup>2</sup>

Combine equations and rearrange the terms to express the distance as a function of the remaining variables:

$$d = \sqrt{((30 \cdot P \cdot G)/(3770 \cdot S))}$$

Changing to units of power in mW and distance in cm, using:

$$P(\text{mW}) = P(\text{W})/1000 \quad d(\text{cm}) = 100 \cdot d(\text{m})$$

yields

$$d = 100 \cdot \sqrt{((30 \cdot (P/1000) \cdot G)/(3770 \cdot S))}$$

$$d = 0.282 \cdot \sqrt{(P \cdot G/S)}$$

where

d=Distance in cm

P=Power in mW

G=Numerica Antenna Gain

S=Power Density in mW/cm<sup>2</sup>

Substituting the logarithmic form of power and gain using:

$$P(\text{mW}) = 10^{(P(\text{dBm})/10)} \quad G(\text{numeric}) = 10^{(G(\text{dBi})/10)}$$

yields

$$d = 0.282 \cdot 10^{((P+G)/20)/\sqrt{S}} \quad \text{Equation (1)}$$

and

$$s = ((0.282 \cdot 10^{((P+G)/20)})/d)^2 \quad \text{Equation (2)}$$

where

d=MPE distance in cm

P=Power in dBm

G=Antenna Gain in dBi

S=Power Density in mW/cm<sup>2</sup>



Equation (1) and the measured peak power are used to calculate the MPE distance. Note that for mobile or fixed location transmitters such as an access point, the minimum separation distance is 20 cm even if the calculations indicate that the MPE distance may be less.

$S=1\text{mW/cm}^2$  maximum. The highest supported antenna gain is 6 dBi (9dBi with beamforming). Using the peak power levels recorded in the test report along with Equation 1 above, the MPE distances are calculated as follows.

Frequency (MHz)	Bit Rate (Mbps)	Power Density (mW/cm <sup>2</sup> )	Peak Transmit Power (dBm)	Antenna Gain (dBi)	MPE Distance (cm)	Limit (cm)	Margin (cm)
5260	54	1	16.9	7	<b>4.42</b>	20	15.58
5320	54	1	19	7	<b>5.63</b>	20	14.37

### MPE Calculations

To maintain compliance, installations will assure a separation distance of at least 20cm.

Using Equation 2, the MPE levels (s) at 20 cm are calculated as follows:

Frequency (MHz)	Bit Rate (Mbps)	MPE Distance (cm)	Peak Transmit Power (dBm)	Antenna Gain (dBi)	Power Density (mW/cm <sup>2</sup> )	Limit (mW/cm <sup>2</sup> )	Margin (mW/cm <sup>2</sup> )
5260	54	20	16.9	7	<b>0.05</b>	1	0.95
5320	54	20	19	7	<b>0.08</b>	1	0.92

**Appendix C: Test Equipment/Software Used to perform the test**

Equip #	Manufacturer	Model	Description	Last Cal	Next Due
CIS037581	EMC Test Systems	3117	Double Ridged Guide Horn Antenna	27-Jul-10	27-Jul-11
CIS04927	Miteq	NSP1000-S1	Broadband Preamplifier	2-Feb-11	2-Feb-12
COM000210	TTE	H785-150K-50-21378	Hi Pass Filter - 150KHz cutoff	11-Aug-10	11-Aug-11
COM000214	Fischer	FCC-LISN-50-50-2M	Turntable LISN (150KHz-30MHz)	5-Mar-11	4-Mar-12
CIS021117	Micro-Coax	UFB311A-0-2484-520520	RF Coaxial Cable, to 18GHz, 248.4 in	24-Aug-10	24-Aug-11
CIS030564	Micro-Coax	UFB311A-1-0950-504504	RF Coaxial Cable, to 18GHz, 95 in	24-Aug-10	24-Aug-11
CIS044005	MegaPhase	EM18-NKNK-320	RF N Type Cable 18GHz	24-Aug-10	24-Aug-11
COM000233	Sunol Sciences	JB1	Combination Antenna, 30MHz-2GHz	19-Jul-10	19-Jul-11
CIS037227	Micro-Tronics	BRC50705	Notch Filter, SB:5.725-5.875GHz	7-Jul-10	7-Jul-11
CIS034972	Midwest Microwave	ATT-0640-20-29M-02	Attenuator, 20dB	17-May-11	16-May-12
CIS035610	Micro-Tronics	BRC50703-02	Notch Filter, SB:5.150-5.350GHz	7-Jul-10	7-Jul-11
CIS043116	Huber + Suhner	Sucoflex 104PE	N & SMA RF cable	19-Jul-10	19-Jul-11
CIS040603	Agilent	E4440A	Spectrum Analyzer	4-Aug-10	4-Aug-11
CIS040053	Agilent	E4448A	Spectrum Analyzer	29-Apr-11	28-Apr-12