

RF EXPOSURE REPORT (FOR BLUETOOTH)

REPORT NO.: SA111130C17

MODEL NO.: CP-DSKCH-7925G

FCC ID: LDKCPDSKCH7925

RECEIVED: Nov. 30, 2011

TESTED: Dec. 09 ~ Dec. 16, 2011

ISSUED: Dec. 27, 2011

APPLICANT: Cisco Systems, Inc.

ADDRESS: 170, West Tasman San Jose CA 95134 USA

ISSUED BY: Bureau Veritas Consumer Products Services (H.K.)

Ltd., Taoyuan Branch

LAB ADDRESS: No. 47, 14th Ling, Chia Pau Vil., Lin Kou Dist., New

Taipei City, Taiwan (R.O.C)

TEST LOCATION: No. 19, Hwa Ya 2nd Rd, Wen Hwa Tsuen, Kwei

Shan Hsiang, Taoyuan Hsien 333, Taiwan, R.O.C.

This test report consists of 5 pages in total. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The client should not use it to claim product certification, approval or endorsement by any government agency. The test results in the report only apply to the tested sample.



TABLE OF CONTENTS

RELE/	ASE CONTROL RECORD	3
	CERTIFICATION	
	REDUCED CONDITION FOR SAR	
	MAXIMUM MEASURED POWER OF EUT	
_	CONCLUSION	



RELEASE CONTROL RECORD

ISSUE NO. REASON FOR CHANGE		DATE ISSUED
Original release	NA	Dec. 27, 2011



1. CERTIFICATION

PRODUCT: Cisco UC Phone 7925G Desktop Charger

MODEL: CP-DSKCH-7925G

BRAND: Cisco

APPLICANT: Cisco Systems, Inc.

TESTED: Dec. 09 ~ Dec. 16, 2011

TEST SAMPLE: ENGINEERING SAMPLE

STANDARDS: FCC Part 2 (Section 2.1093)

FCC OET Bulletin 65, Supplement C (01-01)

IEEE C95.1

The above equipment (model: CP-DSKCH-7925G) have been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

PREPARED BY : ______, DATE: _______ Dec. 27, 2011

Ivonne Wu / Senior Specialist

APPROVED BY : Gary Chang / Technical Manager , DATE: Dec. 27, 2011



2. REDUCED CONDITION FOR SAR

When output power is \leq 60/f(GHz) mW, SAR evaluation is not required.

3. MAXIMUM MEASURED POWER OF EUT

Mode	Conducted power (dBm)	Antenna Gain (dBi)	EIRP (dBm)	Threshold for SAR (dBm)
Bluetooth	0.26	0	0.26	13.84

4. CONCLUSION

No SAR evaluation is required since output power of EUT is less than threshold of SAR.