

Title	標籤製作黏貼方式
DOC. No.	U58O346.00
Page	1 of 3
Rev:	S0

U58O346.00 標籤製作黏貼方式

1. Foxconn Blank Label: 503.01241.005 (70*30mm)

下列資訊將列印於 503.01241.005 這張標籤之中，如下圖的範例。列印此機種.00 料號及所含之 T 階板子料號與 bar codes。

PID: IXM-LPWA-900-16-K9 V00 U58O345.00  SN: FOCWWSSSS 	MAC: XX:XX:XX:XX:XX:XX  MAIN PCBA SN: FOCYYWWSSSS  LORA PCBA SN:FOCYYWWSSSS  MADE IN CHINA
---	--

PID: IXM-LPWA-900-16-K9 (U58O346.00)

VID:V00 (U58O346.00)

Title	標籤製作黏貼方式
DOC. No.	U58O346.00
Page	2 of 3
Rev:	S0

TITLE : LABEL PROCEDURE

LABEL TEXT :

1.Part Number: U58O345.00

2.LF: Lead-free product.

3.標籤版本：VVSS

VV:工程版本(參照製造文件封面 Foxconn Label Rev.欄位)

SS:A300/A400 產品之版本(參照製造文件封面 Doc Rev.之主版本)

4.BARCODE : using 128-auto (alpha/numeric), BARCODE 內容(左方): U58O345.00 LF VVSS , 內容(右方): FOCYYWWSSSS

5.S/N: serial number FOCYYWWSSSS

YY: Year base 10 numeric,

WW:Week (01 to52 weeks)

SSSS: Sequential serial ID base 34 alpha/numeric, The serial labels per week This number will be reset to 0001 each week.

MAC address 以跳號方式列印,間隔為 8,舉例

如果第一張卡的 Mac Address 為: 0022BDD60000, 那么下一張卡的 Mac Address 為: 0022BDD60008

再下一張卡的Mac Address為: 0022BDD60010次類推

Title	標籤製作黏貼方式
DOC. No.	U58O346.00
Page	3 of 3
Rev:	S0

標籤黏貼位置

