

FCC Test Report

Report No.: RF150507D03

FCC ID: PD5-RV134W

Test Model: RV134W

Received Date: May 7, 2015

Test Date: May 21 ~ Jun. 9, 2015

Issued Date: Jul. 8, 2015

Applicant: Delta Networks, Inc.

Address: No. 252, Shang Ying Rd., Kuei San District, Taoyuan City 33341 Taiwan

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch

Lab Address: No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan (R.O.C.)



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies

Table of Contents

Release Control Record.....	4
1 Certificate of Conformity.....	5
2 Summary of Test Results	6
2.1 Measurement Uncertainty.....	6
2.2 Modification Record.....	6
3 General Information.....	7
3.1 General Description of EUT	7
3.2 Description of Test Modes	8
3.2.1 Test Mode Applicability and Tested Channel Detail.....	9
3.3 Duty Cycle of Test Signal.....	11
3.4 Description of Support Units.....	12
3.4.1 Configuration of System under Test	13
3.5 General Description of Applied Standards.....	14
4 Test Types and Results.....	15
4.1 Radiated Emission and Bandedge Measurement.....	15
4.1.1 Limits of Radiated Emission and Bandedge Measurement	15
4.1.2 Test Instruments	16
4.1.3 Test Procedures	17
4.1.4 Deviation from Test Standard	17
4.1.5 Test Set Up.....	18
4.1.6 EUT Operating Conditions	19
4.1.7 Test Results.....	20
4.2 Conducted Emission Measurement	33
4.2.1 Limits of Conducted Emission Measurement.....	33
4.2.2 Test Instruments	33
4.2.3 Test Procedures	34
4.2.4 Deviation from Test Standard	34
4.2.5 Test Setup	34
4.2.6 EUT Operating Conditions	34
4.2.7 Test Results.....	35
4.3 6dB Bandwidth Measurement.....	37
4.3.1 Limits of 6dB Bandwidth Measurement	37
4.3.2 Test Setup	37
4.3.3 Test Instruments.....	37
4.3.4 Test Procedure	37
4.3.5 Deviation from Test Standard	37
4.3.6 EUT Operating Conditions	37
4.3.7 Test Result	38
4.4 Conducted Output Power Measurement.....	40
4.4.1 Limits of Conducted Output Power Measurement	40
4.4.2 Test Setup	40
4.4.3 Test Instruments.....	40
4.4.4 Test Procedures	40
4.4.5 Deviation from Test Standard	40
4.4.6 EUT Operating Conditions	40
4.4.7 Test Results.....	41
4.5 Power Spectral Density Measurement	43
4.5.1 Limits of Power Spectral Density Measurement.....	43
4.5.2 Test Setup	43
4.5.3 Test Instruments.....	43
4.5.4 Test Procedure	43
4.5.5 Deviation from Test Standard	43

4.5.6 EUT Operating Condition.....	43
4.5.7 Test Results.....	44
4.6 Conducted Out of Band Emission Measurement.....	46
4.6.1 Limits of Conducted Out of Band Emission Measurement.....	46
4.6.2 Test Setup	46
4.6.3 Test Instruments.....	46
4.6.4 Test Procedure	46
4.6.5 Deviation from Test Standard	46
4.6.6 EUT Operating Condition.....	46
4.6.7 Test Results.....	46
5 Pictures of Test Arrangements.....	54
Appendix – Information on the Testing Laboratories.....	55



A D T

Release Control Record

Issue No.	Description	Date Issued
RF150507D03	Original release.	Jul. 8, 2015

1 Certificate of Conformity

Product: Wireless-AC VPN Router

Brand: CISCO

Test Model: RV134W

Sample Status: Engineering sample

Applicant: Delta Networks, Inc.

Test Date: May 21 ~ Jun. 9, 2015

Standards: 47 CFR FCC Part 15, Subpart C (Section 15.247)
ANSI C63.10:2013

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

Prepared by :



Date:

Jul. 8, 2015

Jessica Cheng / Senior Specialist

Approved by :



Date:

Jul. 8, 2015

Rex Lai / Assistant Manager

2 Summary of Test Results

47 CFR FCC Part 15, Subpart C (SECTION 15.247)			
FCC Clause	Test Item	Result	Remarks
15.207	AC Power Conducted Emission	PASS	Meet the requirement of limit. Minimum passing margin is -16.62dB at 0.15000MHz.
15.205 / 15.209 / 15.247(d)	Radiated Emissions and Band Edge Measurement	PASS	Meet the requirement of limit. Minimum passing margin is -1.0dB at 2390.00MHz.
15.247(d)	Antenna Port Emission	PASS	Meet the requirement of limit.
15.247(a)(2)	6dB bandwidth	PASS	Meet the requirement of limit.
15.247(b)	Conducted power	PASS	Meet the requirement of limit.
15.247(e)	Power Spectral Density	PASS	Meet the requirement of limit.
15.203	Antenna Requirement	PASS	No antenna connector is used.

2.1 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

Measurement	Frequency	Expended Uncertainty (k=2) ($\pm$)
Conducted Emissions at mains ports	150kHz ~ 30MHz	3.43 dB
Radiated Emissions up to 1 GHz	30MHz ~ 1000MHz	4.00 dB
Radiated Emissions above 1 GHz	1GHz ~ 40GHz	3.36 dB

2.2 Modification Record

There were no modifications required for compliance.

3 General Information

3.1 General Description of EUT

Product	Wireless-AC VPN Router
Brand	CISCO
Test Model	RV134W
Status of EUT	Engineering sample
Power Supply Rating	12Vdc from Adapter
Modulation Type	CCK, DQPSK, DBPSK for DSSS 64QAM, 16QAM, QPSK, BPSK for OFDM
Modulation Technology	DSSS, OFDM
Transfer Rate	802.11b:11/5.5/2/1Mbps 802.11g: 54/48/36/24/18/12/9/6Mbps 802.11n: up to 300Mbps
Operating Frequency	2412 ~ 2462MHz
Number of Channel	11 for 802.11b, 802.11g, 802.11n (HT20) 7 for 802.11n (HT40)
Output Power	931.194mW
Antenna Type	Printed antenna with 3.73dBi gain
Antenna Connector	N/A
Accessory Device	Adapter, Stand
Data Cable Supplied	Non-shielded RJ 45 cable (1.5 m) , Non-shielded RJ11 cable (1.7 m), Non-shielded console cable (1.7 m)

Note:

1. The EUT incorporates a MIMO function. Physically, the EUT provides two completed transmitters and two receivers.

Modulation Mode	TX Function
802.11b	1TX
802.11g	2TX
802.11n (HT20)	2TX
802.11n (HT40)	2TX

2. The EUT uses following adapter.

Brand	DVE
Model	DSA-36PFH-12 FUS 120250AN
AC Input Power	100-240V, 50-60Hz, 1A
DC Output Power	+12V, 2.5A
Power Line	AC 2-Pin, Non-Shielded DC cable (1.5m)

3. The above EUT information is declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications or user's manual.

3.2 Description of Test Modes

11 channels are provided for 802.11b, 802.11g and 802.11n (HT20):

Channel	Frequency	Channel	Frequency
1	2412MHz	7	2442MHz
2	2417MHz	8	2447MHz
3	2422MHz	9	2452MHz
4	2427MHz	10	2457MHz
5	2432MHz	11	2462MHz
6	2437MHz		

7 channels are provided for 802.11n (HT40):

Channel	Frequency	Channel	Frequency
3	2422MHz	7	2442MHz
4	2427MHz	8	2447MHz
5	2432MHz	9	2452MHz
6	2437MHz		

3.2.1 Test Mode Applicability and Tested Channel Detail

EUT CONFIGURE MODE	APPLICABLE TO				DESCRIPTION
	RE ³ 1G	RE<1G	PLC	APCM	
-	√	√	√	√	-

Where **RE³1G**: Radiated Emission above 1GHz **RE<1G**: Radiated Emission below 1GHz
PLC: Power Line Conducted Emission **APCM**: Antenna Port Conducted Measurement

Radiated Emission Test (Above 1GHz):

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

- ☒ Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
-	802.11b	1 to 11	1, 6, 11	DSSS	DBPSK	1
-	802.11g	1 to 11	1, 6, 11	OFDM	BPSK	6
-	802.11n (HT20)	1 to 11	1, 6, 11	OFDM	BPSK	6.5
-	802.11n (HT40)	3 to 9	3, 6, 9	OFDM	BPSK	13.5

Radiated Emission Test (Below 1GHz):

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

- ☒ Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
-	802.11g	1 to 11	1	OFDM	BPSK	6

Power Line Conducted Emission Test:

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

- ☒ Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
-	802.11g	1 to 11	1	OFDM	BPSK	6

Bandedge Measurement:

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
-	802.11b	1 to 11	1, 11	DSSS	DBPSK	1
-	802.11g	1 to 11	1, 11	OFDM	BPSK	6
-	802.11n (HT20)	1 to 11	1, 11	OFDM	BPSK	6.5
-	802.11n (HT40)	3 to 9	3, 9	OFDM	BPSK	13.5

Antenna Port Conducted Measurement:

- ☒ This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.
- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
-	802.11b	1 to 11	1, 6, 11	DSSS	DBPSK	1
-	802.11g	1 to 11	1, 6, 11	OFDM	BPSK	6
-	802.11n (HT20)	1 to 11	1, 6, 11	OFDM	BPSK	6.5
-	802.11n (HT40)	3 to 9	3, 6, 9	OFDM	BPSK	13.5

Test Condition:

APPLICABLE TO	ENVIRONMENTAL CONDITIONS	INPUT POWER	TESTED BY
RE ³ 1G	25deg. C, 79%RH	120Vac, 60Hz	Aaron You
RE<1G	25deg. C, 79%RH	120Vac, 60Hz	Aaron You
PLC	25deg. C, 73%RH	120Vac, 60Hz	Dalen Dai
APCM	25deg. C, 60%RH	120Vac, 60Hz	Saxon Lee


3.3 Duty Cycle of Test Signal

802.11b: Duty cycle of test signal is 100 %, duty factor is not required.

802.11g: Duty cycle = $2/2.17 = 0.922$, Duty factor = $10 * \log(1/0.922) = 0.35$

802.11n (HT20): Duty cycle = $1.87/2 = 0.935$, Duty factor = $10 * \log(1/0.935) = 0.29$

802.11n (HT40): Duty cycle = $0.891/1.057 = 0.843$, Duty factor = $10 * \log(1/0.843) = 0.74$



3.4 Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

ID	Product	Brand	Model No.	Serial No.	FCC ID	Remarks
A.	EUT	CISCO	RV134W	-	-	-
B.	Adapter	DVE	DSA-36PFH-12 FUS 120250AN	N/A	FCC DoC Approved	Supplied by client
C.	NOTEBOOK COMPUTER	DELL	PP27L	8SNZ12S	FCC DoC Approved	Provided by Lab
D.	LOAD	N/A	N/A	N/A	N/A	Provided by Lab
E.	LOAD	N/A	N/A	N/A	N/A	Provided by Lab
F.	USB 3.0 Hard Disk	WD	WDBACY5000ABL- PESN	WX81E81SKT67	FCC DoC Approved	Provided by Lab


Note:

1. All power cords of the above support units are non-shielded (1.8m).
2. Item C acted as communication partners to transfer data.

ID	Descriptions	Qty.	Length (m)	Shielding (Yes/No)	Cores (Qty.)	Remarks
1.	DC cable	1	1.5	N	0	Supplied by client
2.	LAN cable	4	1.8	N	0	Provided by Lab
3.	LAN cable	1	1.8	N	0	Provided by Lab
4.	LAN cable	1	10	N	0	Provided by Lab
5.	RJ11 cable	1	1.8	N	0	Provided by Lab
6.	USB cable	1	0.3	Y	0	Provided by Lab

Note: The core(s) is(are) originally attached to the cable(s).

3.4.1 Configuration of System under Test



3.5 General Description of Applied Standards

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC Part 15, Subpart C (15.247)

558074 D01 DTS Meas Guidance v03r02

662911 D01 Multiple Transmitter Output v02r01

ANSI C63.10-2013

All test items have been performed and recorded as per the above standards.

NOTE: The EUT has been verified to comply with the requirements of FCC Part 15, Subpart B, Class B (DoC). The test report has been issued separately.

4 Test Types and Results

4.1 Radiated Emission and Bandedge Measurement

4.1.1 Limits of Radiated Emission and Bandedge Measurement

Radiated emissions which fall in the restricted bands must comply with the radiated emission limits specified as below table. Other emissions shall be at least 20dB below the highest level of the desired power:

Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

NOTE:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. For frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.

4.1.2 Test Instruments

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
HP Preamplifier	8447D	2432A03504	Feb. 26, 2015	Feb. 25, 2016
HP Preamplifier	8449B	3008A01201	Feb. 26, 2015	Feb. 25, 2016
MITEQ Preamplifier	AMF-6F-260400-3 3-8P	892164	Mar. 01, 2015	Feb. 28, 2016
Agilent Spectrum	E4446A	MY51100050	Oct. 24, 2014	Oct. 23, 2015
Agilent TEST RECEIVER	N9038A	MY51210129	Jan. 20, 2015	Jan. 19, 2016
Schwarzbeck Antenna	VULB 9168	139	Feb. 04, 2015	Feb. 03, 2016
Schwarzbeck Horn Antenna	BBHA-9170	212	Feb. 09, 2015	Feb. 08, 2016
Schwarzbeck Horn Antenna	BBHA 9120-D1	D130	Feb. 10, 2015	Feb. 09, 2016
ADT. Turn Table	TT100	0306	NA	NA
ADT. Tower	AT100	0306	NA	NA
Software	ADT_Radiated_V7. 6.15.9.4	NA	NA	NA
SUHNER RF cable	SF104	CABLE-CH6	Aug. 15, 2014	Aug. 14, 2015
SUHNER RF cable	SF102	Cable-CH8-3.6m	Aug. 15, 2014	Aug. 14, 2015
EMCO Horn Antenna	3115	00028257	Feb. 05, 2015	Feb. 04, 2016
Highpass filter Wainwright Instruments	WHK 3.1/18G-10SS	SN 8	NA	NA
ROHDE & SCHWARZ Spectrum Analyzer	FSV40	101042	Sep. 29, 2014	Sep. 28, 2015
Anritsu Power Sensor	MA2411B	0738404	Apr. 21, 2015	Apr. 20, 2016
Anritsu Power Meter	ML2495A	0842014	Apr. 21, 2015	Apr. 20, 2016

- NOTE:** 1. The calibration interval of the above test instruments is 12/24 months. And the calibrations are traceable to NML/ROC and NIST/USA.
2. The horn antenna and HP preamplifier (model: 8449B) are used only for the measurement of emission frequency above 1GHz if tested.
3. The test was performed in Chamber No. 6.
4. The Industry Canada Reference No. IC 7450E-6.
5. The FCC Site Registration No. is 447212.

4.1.3 Test Procedures

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
- f. The test-receiver system was set to peak and average detect function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz. If the peak reading value also meets average limit, measurement with the average detector is unnecessary.

Note:


1. For emission measurements above 1 GHz, the EUT shall be placed at a height of 1.5 m above the ground at 3 meter chamber room for test
2. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection (QP) at frequency below 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) at frequency above 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 3MHz for RMS Average (Duty cycle < 98%) for Average detection (AV) at frequency above 1GHz, then the measurement results was added to a correction factor ($10 \log(1/\text{duty cycle})$).
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 10Hz (Duty cycle $\geq 98\%$) for Average detection (AV) at frequency above 1GHz.
6. All modes of operation were investigated and the worst-case emissions are reported.

4.1.4 Deviation from Test Standard


No deviation.

4.1.5 Test Set Up

<Frequency Range below 1GHz>



<Frequency Range above 1GHz>



For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.1.6 EUT Operating Conditions

- a. Placed the EUT on the testing table.
- b. Prepared notebook to act as communication partner and placed it outside of testing area.
- c. The communication partner connected with EUT via RJ45 cable and ran a test program (provided by manufacturer) to enable EUT under transmission condition continuously at specific channel frequency.
- d. The communication partner sent data to EUT by command "PING".
- e. The notebook (kept in a remote area) read and wrote messages to/ from USB Hard Disk via EUT.
- f. The necessary accessories enable the system in full functions.

4.1.7 Test Results

Above 1GHz Data : 802.11b

CHANNEL	TX Channel 1	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	52.2 PK	74.0	-21.8	1.58 H	145	56.55	-4.34
2	2390.00	39.5 AV	54.0	-14.5	1.58 H	145	43.83	-4.34
3	*2412.00	100.9 PK			1.58 H	145	105.13	-4.21
4	*2412.00	96.3 AV			1.58 H	145	100.52	-4.21
5	4824.00	54.0 PK	74.0	-20.0	1.35 H	230	51.01	2.95
6	4824.00	50.8 AV	54.0	-3.2	1.35 H	230	47.81	2.95
7	#7236.00	51.7 PK	80.9	-29.3	1.03 H	309	42.79	8.86
8	#7236.00	42.4 AV	76.3	-33.9	1.03 H	309	33.55	8.86
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	53.8 PK	74.0	-20.2	1.61 V	49	58.16	-4.34
2	2390.00	41.6 AV	54.0	-12.5	1.61 V	49	45.89	-4.34
3	*2412.00	106.1 PK			1.61 V	49	110.33	-4.21
4	*2412.00	101.4 AV			1.61 V	49	105.62	-4.21
5	4824.00	53.5 PK	74.0	-20.5	1.56 V	279	50.55	2.95
6	4824.00	49.8 AV	54.0	-4.2	1.56 V	279	46.87	2.95
7	#7236.00	54.2 PK	86.1	-32.0	1.15 V	297	45.30	8.86
8	#7236.00	46.5 AV	81.4	-34.9	1.15 V	297	37.62	8.86

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

CHANNEL	TX Channel 6	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2437.00	99.7 PK			1.92 H	157	103.80	-4.09
2	*2437.00	95.2 AV			1.92 H	157	99.29	-4.09
3	4874.00	53.5 PK	74.0	-20.5	1.73 H	228	50.46	3.06
4	4874.00	50.7 AV	54.0	-3.3	1.73 H	228	47.62	3.06
5	7311.00	51.4 PK	74.0	-22.6	1.02 H	316	42.27	9.11
6	7311.00	41.2 AV	54.0	-12.8	1.02 H	316	32.13	9.11
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2437.00	106.0 PK			1.80 V	50	110.10	-4.09
2	*2437.00	101.3 AV			1.80 V	50	105.35	-4.09
3	4874.00	53.0 PK	74.0	-21.0	1.70 V	277	49.92	3.06
4	4874.00	49.2 AV	54.0	-4.9	1.70 V	277	46.09	3.06
5	7311.00	54.1 PK	74.0	-19.9	1.39 V	296	45.00	9.11
6	7311.00	45.8 AV	54.0	-8.2	1.39 V	296	36.71	9.11

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.

CHANNEL	TX Channel 11	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	100.5 PK			1.52 H	143	104.40	-3.95
2	*2462.00	96.0 AV			1.52 H	143	99.94	-3.95
3	2483.50	54.4 PK	74.0	-19.6	1.52 H	143	58.28	-3.85
4	2483.50	41.0 AV	54.0	-13.1	1.52 H	143	44.80	-3.85
5	4924.00	54.0 PK	74.0	-20.0	1.59 H	231	50.76	3.21
6	4924.00	50.6 AV	54.0	-3.4	1.59 H	231	47.42	3.21
7	7386.00	50.7 PK	74.0	-23.3	1.00 H	314	41.80	8.91
8	7386.00	40.5 AV	54.0	-13.5	1.00 H	314	31.59	8.91
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	106.6 PK			1.59 V	51	110.52	-3.95
2	*2462.00	101.8 AV			1.59 V	51	105.77	-3.95
3	2483.50	57.7 PK	74.0	-16.3	1.59 V	51	61.56	-3.85
4	2483.50	44.8 AV	54.0	-9.3	1.59 V	51	48.60	-3.85
5	4924.00	53.9 PK	74.0	-20.1	1.43 V	276	50.66	3.21
6	4924.00	50.2 AV	54.0	-3.8	1.43 V	276	46.96	3.21
7	7386.00	53.4 PK	74.0	-20.6	1.17 V	299	44.51	8.91
8	7386.00	45.1 AV	54.0	-8.9	1.17 V	299	36.18	8.91

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.

802.11g

CHANNEL	TX Channel 1	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	71.1 PK	74.0	-2.9	1.41 H	102	75.42	-4.34
2	2390.00	52.4 AV	54.0	-1.6	1.41 H	102	56.72	-4.34
3	*2412.00	111.2 PK			1.41 H	102	115.40	-4.21
4	*2412.00	101.0 AV			1.41 H	102	105.22	-4.21
5	4824.00	55.8 PK	74.0	-18.2	1.44 H	230	52.86	2.95
6	4824.00	41.9 AV	54.0	-12.1	1.44 H	230	38.95	2.95
7	#7236.00	54.9 PK	91.2	-36.3	1.00 H	316	46.01	8.86
8	#7236.00	40.2 AV	81.0	-40.8	1.00 H	316	31.36	8.86
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	73.0 PK	74.0	-1.0	1.29 V	46	77.32	-4.34
2	2390.00	53.0 AV	54.0	-1.1	1.29 V	46	57.29	-4.34
3	*2412.00	112.4 PK			1.29 V	46	116.61	-4.21
4	*2412.00	100.7 AV			1.29 V	46	104.89	-4.21
5	4824.00	55.4 PK	74.0	-18.7	1.56 V	280	52.40	2.95
6	4824.00	41.8 AV	54.0	-12.2	1.56 V	280	38.82	2.95
7	#7236.00	60.4 PK	92.4	-32.0	1.00 V	290	51.50	8.86
8	#7236.00	44.7 AV	80.7	-36.0	1.00 V	290	35.86	8.86

REMARKS:

- Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
- Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
- The other emission levels were very low against the limit.
- Margin value = Emission Level – Limit value
- " * ": Fundamental frequency.
- " # ": The radiated frequency is out of the restricted band.

CHANNEL	TX Channel 6	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2437.00	113.4 PK			1.73 H	81	117.46	-4.09
2	*2437.00	102.5 AV			1.73 H	81	106.60	-4.09
3	4874.00	58.0 PK	74.0	-16.0	1.74 H	236	54.93	3.06
4	4874.00	44.2 AV	54.0	-9.8	1.74 H	236	41.18	3.06
5	7311.00	57.9 PK	74.0	-16.1	1.01 H	315	48.81	9.11
6	7311.00	44.2 AV	54.0	-9.8	1.01 H	315	35.08	9.11
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2437.00	113.7 PK			1.44 V	48	117.74	-4.09
2	*2437.00	102.7 AV			1.44 V	48	106.82	-4.09
3	4874.00	57.9 PK	74.0	-16.1	1.64 V	275	54.88	3.06
4	4874.00	44.0 AV	54.0	-10.0	1.64 V	275	40.92	3.06
5	7311.00	64.3 PK	74.0	-9.7	1.34 V	286	55.20	9.11
6	7311.00	50.7 AV	54.0	-3.3	1.34 V	286	41.61	9.11

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.

CHANNEL	TX Channel 11	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	110.2 PK			1.22 H	81	114.16	-3.95
2	*2462.00	99.6 AV			1.22 H	81	103.58	-3.95
3	2483.50	71.2 PK	74.0	-2.8	1.22 H	81	75.06	-3.85
4	2483.50	52.4 AV	54.0	-1.6	1.22 H	81	56.21	-3.85
5	4924.00	57.2 PK	74.0	-16.8	1.60 H	234	53.98	3.21
6	4924.00	42.5 AV	54.0	-11.5	1.60 H	234	39.27	3.21
7	7386.00	53.0 PK	74.0	-21.0	1.00 H	320	44.08	8.91
8	7386.00	38.9 AV	54.0	-15.1	1.00 H	320	30.02	8.91
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	110.3 PK			1.39 V	345	114.22	-3.95
2	*2462.00	99.7 AV			1.39 V	345	103.67	-3.95
3	2483.50	71.5 PK	74.0	-2.5	1.39 V	345	75.39	-3.85
4	2483.50	52.7 AV	54.0	-1.3	1.39 V	345	56.57	-3.85
5	4924.00	57.1 PK	74.0	-16.9	1.60 V	268	53.85	3.21
6	4924.00	42.5 AV	54.0	-11.6	1.60 V	268	39.24	3.21
7	7386.00	58.3 PK	74.0	-15.7	1.07 V	300	49.39	8.91
8	7386.00	41.4 AV	54.0	-12.6	1.07 V	300	32.48	8.91

REMARKS:

- Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
- Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
- The other emission levels were very low against the limit.
- Margin value = Emission Level – Limit value
- " * ": Fundamental frequency.

802.11n (20MHz)

CHANNEL	TX Channel 1	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	69.1 PK	74.0	-4.9	2.06 H	102	73.43	-4.34
2	2390.00	51.2 AV	54.0	-2.8	2.06 H	102	55.53	-4.34
3	*2412.00	109.0 PK			2.06 H	102	113.18	-4.21
4	*2412.00	96.9 AV			2.06 H	102	101.13	-4.21
5	4824.00	52.6 PK	74.0	-21.4	1.66 H	228	49.67	2.95
6	4824.00	38.7 AV	54.0	-15.3	1.66 H	228	35.79	2.95
7	#7236.00	52.3 PK	89.0	-36.7	1.00 H	313	43.44	8.86
8	#7236.00	38.2 AV	76.9	-38.8	1.00 H	313	29.30	8.86
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	71.8 PK	74.0	-2.2	1.26 V	42	76.17	-4.34
2	2390.00	52.5 AV	54.0	-1.5	1.26 V	42	56.87	-4.34
3	*2412.00	109.5 PK			1.26 V	42	113.69	-4.21
4	*2412.00	97.9 AV			1.26 V	42	102.15	-4.21
5	4824.00	51.9 PK	74.0	-22.1	1.72 V	271	48.99	2.95
6	4824.00	38.3 AV	54.0	-15.7	1.72 V	271	35.36	2.95
7	#7236.00	56.7 PK	89.5	-32.8	1.40 V	294	47.82	8.86
8	#7236.00	41.5 AV	77.9	-36.5	1.40 V	294	32.62	8.86

REMARKS:

- Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
- Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
- The other emission levels were very low against the limit.
- Margin value = Emission Level – Limit value
- " * ": Fundamental frequency.
- " # ": The radiated frequency is out of the restricted band.

CHANNEL	TX Channel 6	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2437.00	112.8 PK			1.68 H	80	116.93	-4.09
2	*2437.00	101.2 AV			1.68 H	80	105.28	-4.09
3	2483.50	69.1 PK	74.0	-4.9	1.68 H	80	72.93	-3.85
4	2483.50	51.0 AV	54.0	-3.0	1.68 H	80	54.89	-3.85
5	4874.00	57.4 PK	74.0	-16.6	1.63 H	235	54.30	3.06
6	4874.00	43.2 AV	54.0	-10.8	1.63 H	235	40.10	3.06
7	7311.00	55.9 PK	74.0	-18.1	1.00 H	317	46.75	9.11
8	7311.00	43.2 AV	54.0	-10.8	1.00 H	317	34.12	9.11
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2437.00	113.0 PK			1.77 V	51	117.05	-4.09
2	*2437.00	101.7 AV			1.77 V	51	105.77	-4.09
3	2483.50	69.7 PK	74.0	-4.3	1.77 V	51	73.51	-3.85
4	2483.50	52.6 AV	54.0	-1.4	1.77 V	51	56.41	-3.85
5	4874.00	54.0 PK	74.0	-20.0	1.47 V	265	50.92	3.06
6	4874.00	41.2 AV	54.0	-12.8	1.47 V	265	38.14	3.06
7	7311.00	63.3 PK	74.0	-10.7	1.78 V	291	54.22	9.11
8	7311.00	49.8 AV	54.0	-4.2	1.78 V	291	40.66	9.11

REMARKS:

- Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
- Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
- The other emission levels were very low against the limit.
- Margin value = Emission Level – Limit value
- " * ": Fundamental frequency.

CHANNEL	TX Channel 11	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	106.7 PK			1.67 H	84	110.66	-3.95
2	*2462.00	95.1 AV			1.67 H	84	99.07	-3.95
3	2483.50	71.7 PK	74.0	-2.3	1.67 H	84	75.51	-3.85
4	2483.50	52.0 AV	54.0	-2.0	1.67 H	84	55.87	-3.85
5	4924.00	54.0 PK	74.0	-20.0	1.63 H	226	50.82	3.21
6	4924.00	39.3 AV	54.0	-14.7	1.63 H	226	36.06	3.21
7	7386.00	50.9 PK	74.0	-23.2	1.00 H	307	41.94	8.91
8	7386.00	36.9 AV	54.0	-17.1	1.00 H	307	27.98	8.91
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	107.1 PK			1.14 V	196	111.07	-3.95
2	*2462.00	95.7 AV			1.14 V	196	99.62	-3.95
3	2483.50	72.7 PK	74.0	-1.3	1.14 V	196	76.53	-3.85
4	2483.50	52.4 AV	54.0	-1.6	1.14 V	196	56.23	-3.85
5	4924.00	52.7 PK	74.0	-21.3	1.70 V	269	49.47	3.21
6	4924.00	38.5 AV	54.0	-15.5	1.70 V	269	35.28	3.21
7	7386.00	54.4 PK	74.0	-19.6	1.43 V	275	45.49	8.91
8	7386.00	41.3 AV	54.0	-12.7	1.43 V	275	32.36	8.91

REMARKS:

- Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
- Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
- The other emission levels were very low against the limit.
- Margin value = Emission Level – Limit value
- " * ": Fundamental frequency.

802.11n (40MHz)

CHANNEL	TX Channel 3	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	67.1 PK	74.0	-7.0	1.70 H	98	71.39	-4.34
2	2390.00	51.1 AV	54.0	-2.9	1.70 H	98	55.48	-4.34
3	*2422.00	101.1 PK			1.70 H	98	105.23	-4.16
4	*2422.00	88.5 AV			1.70 H	98	92.66	-4.16
5	4844.00	46.6 PK	74.0	-27.5	1.74 H	224	43.56	2.99
6	4844.00	34.7 AV	54.0	-19.3	1.74 H	224	31.73	2.99
7	7266.00	49.0 PK	74.0	-25.0	1.00 H	311	39.99	9.00
8	7266.00	36.1 AV	54.0	-18.0	1.00 H	311	27.05	9.00

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	69.5 PK	74.0	-4.5	1.00 V	193	73.82	-4.34
2	2390.00	52.8 AV	54.0	-1.2	1.00 V	193	57.14	-4.34
3	*2422.00	104.3 PK			1.00 V	193	108.41	-4.16
4	*2422.00	91.8 AV			1.00 V	193	95.98	-4.16
5	4844.00	45.7 PK	74.0	-28.3	1.63 V	270	42.70	2.99
6	4844.00	33.3 AV	54.0	-20.7	1.63 V	270	30.28	2.99
7	7266.00	49.3 PK	74.0	-24.7	1.27 V	296	40.33	9.00
8	7266.00	36.2 AV	54.0	-17.8	1.27 V	296	27.17	9.00

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.

CHANNEL	TX Channel 6	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2437.00	103.2 PK			1.69 H	80	107.25	-4.09
2	*2437.00	91.0 AV			1.69 H	80	95.11	-4.09
3	2483.50	67.4 PK	74.0	-6.6	1.69 H	80	71.26	-3.85
4	2483.50	51.9 AV	54.0	-2.1	1.69 H	80	55.78	-3.85
5	4874.00	51.3 PK	74.0	-22.7	1.77 H	231	48.25	3.06
6	4874.00	38.1 AV	54.0	-16.0	1.77 H	231	34.99	3.06
7	#7236.00	51.0 PK	83.2	-32.1	1.00 H	309	42.17	8.86
8	#7236.00	38.7 AV	71.0	-32.3	1.00 H	309	29.83	8.86

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2437.00	103.4 PK			1.13 V	194	107.46	-4.09
2	*2437.00	91.8 AV			1.13 V	194	95.87	-4.09
3	2483.50	68.5 PK	74.0	-5.5	1.13 V	194	72.32	-3.85
4	2483.50	52.5 AV	54.0	-1.5	1.13 V	194	56.34	-3.85
5	4874.00	50.7 PK	74.0	-23.3	1.68 V	275	47.65	3.06
6	4874.00	37.9 AV	54.0	-16.1	1.68 V	275	34.81	3.06
7	#7236.00	55.4 PK	83.4	-27.9	1.30 V	299	46.58	8.86
8	#7236.00	41.0 AV	71.8	-30.8	1.30 V	299	32.10	8.86

REMARKS:

- Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
- Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
- The other emission levels were very low against the limit.
- Margin value = Emission Level – Limit value
- " * ": Fundamental frequency.
- " # ": The radiated frequency is out of the restricted band.

CHANNEL	TX Channel 9	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2452.00	99.8 PK			1.85 H	96	103.84	-4.01
2	*2452.00	88.4 AV			1.85 H	96	92.44	-4.01
3	2483.50	67.8 PK	74.0	-6.3	1.85 H	96	71.60	-3.85
4	2483.50	50.5 AV	54.0	-3.5	1.85 H	96	54.39	-3.85
5	4904.00	47.0 PK	74.0	-27.0	1.69 H	230	43.87	3.14
6	4904.00	35.2 AV	54.0	-18.8	1.69 H	230	32.05	3.14
7	7356.00	49.0 PK	74.0	-25.0	1.00 H	300	40.05	8.99
8	7356.00	37.0 AV	54.0	-17.0	1.00 H	300	28.00	8.99
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2452.00	103.4 PK			1.66 V	198	107.39	-4.01
2	*2452.00	92.1 AV			1.66 V	198	96.10	-4.01
3	2483.50	72.9 PK	74.0	-1.1	1.66 V	198	76.73	-3.85
4	2483.50	52.0 AV	54.0	-2.0	1.66 V	198	55.88	-3.85
5	4904.00	46.2 PK	74.0	-27.9	1.55 V	273	43.01	3.14
6	4904.00	34.0 AV	54.0	-20.0	1.55 V	273	30.86	3.14
7	7356.00	49.9 PK	74.0	-24.1	1.15 V	297	40.91	8.99
8	7356.00	37.0 AV	54.0	-17.0	1.15 V	297	28.05	8.99

REMARKS:

- Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
- Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
- The other emission levels were very low against the limit.
- Margin value = Emission Level – Limit value
- " * ": Fundamental frequency.

Below 1GHz Data: 802.11g

CHANNEL	TX Channel 1	DETECTOR FUNCTION	Quasi-Peak (QP)
FREQUENCY RANGE	30MHz ~ 1GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	66.86	27.4 QP	40.0	-12.6	4.00 H	140	42.71	-15.27
2	125.01	30.1 QP	43.5	-13.4	4.00 H	108	45.82	-15.72
3	148.15	30.3 QP	43.5	-13.2	4.00 H	99	44.03	-13.70
4	200.04	36.3 QP	43.5	-7.2	4.00 H	248	52.58	-16.28
5	235.98	34.1 QP	46.0	-11.9	4.00 H	241	49.45	-15.31
6	325.22	29.7 QP	46.0	-16.4	2.87 H	119	41.33	-11.68
7	566.26	29.8 QP	46.0	-16.2	1.93 H	168	37.32	-7.49
8	800.03	33.1 QP	46.0	-12.9	1.00 H	269	36.12	-3.04
9	875.06	38.6 QP	46.0	-7.4	1.00 H	258	40.71	-2.07
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	34.03	36.6 QP	40.0	-3.4	1.64 V	144	51.96	-15.37
2	53.28	36.6 QP	40.0	-3.4	1.48 V	230	50.25	-13.69
3	200.14	35.1 QP	43.5	-8.4	1.00 V	297	51.39	-16.28
4	235.98	33.5 QP	46.0	-12.5	1.00 V	130	48.82	-15.31
5	400.06	29.5 QP	46.0	-16.5	1.66 V	14	39.89	-10.38
6	625.05	30.9 QP	46.0	-15.1	2.87 V	175	36.84	-5.94
7	875.06	31.9 QP	46.0	-14.1	2.99 V	178	33.95	-2.07
8	999.99	32.0 QP	54.0	-22.0	1.95 V	254	32.20	-0.22

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value

4.2 Conducted Emission Measurement

4.2.1 Limits of Conducted Emission Measurement

Frequency (MHz)	Conducted Limit (dBuV)	
	Quasi-peak	Average
0.15 - 0.5	66 - 56	56 - 46
0.50 - 5.0	56	46
5.0 - 30.0	60	50

Note: 1. The lower limit shall apply at the transition frequencies.

2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

4.2.2 Test Instruments

Description & Manufacturer	Model No.	Serial No.	Cal. Date	Cal. Due
ROHDE & SCHWARZ TEST RECEIVER	ESCS 30	100292	Dec. 18, 2014	Dec. 17, 2015
ROHDE & SCHWARZ Artificial Mains Network (for EUT)	ESH2-Z5	100104	Dec. 04, 2014	Dec. 03, 2015
LISN With Adapter (for EUT)	AD10	C09Ada-001	Dec. 04, 2014	Dec. 03, 2015
ROHDE & SCHWARZ Artificial Mains Network (for peripherals)	ESH3-Z5	847265/023	Oct. 21, 2014	Oct. 20, 2015
SCHWARZBECK Artificial Mains Network (For EUT)	NNLK8129	8129229	May 06, 2015	May 05, 2016
Software	ADT_Cond_V7.3.7	NA	NA	NA
RF cable (JYEBAO)	5D-FB	Cable-C09.01	Feb. 24, 2015	Feb. 23, 2016
SUHNER Terminator (For ROHDE & SCHWARZ LISN)	65BNC-5001	E1-010789	May 19, 2015	May 18, 2016
ROHDE & SCHWARZ Artificial Mains Network (For TV EUT)	ESH3-Z5	100220	Nov. 20, 2014	Nov. 19, 2015
LISN With Adapter (for TV EUT)	100220	N/A	Nov. 20, 2014	Nov. 19, 2015

Notes: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

2. The test was performed in Shielded Room No. 9.

3. The VCCI Site Registration No. C-1312.

4.2.3 Test Procedures


- The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit - 20dB) was not recorded.

NOTE: The resolution bandwidth and video bandwidth of test receiver is 9kHz for quasi-peak detection (QP) and average detection (AV) at frequency 0.15MHz-30MHz.

4.2.4 Deviation from Test Standard

No deviation.

4.2.5 Test Setup



Note: 1.Support units were connected to second LISN.

For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.2.6 EUT Operating Conditions

Same as 4.1.6.

4.2.7 Test Results


802.11g CH 1

Phase	Line (L)	Detector Function	Quasi-Peak (QP) / Average (AV)
-------	----------	-------------------	--------------------------------

No	Freq. [MHz]	Corr. Factor	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
		(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.15000	0.21	49.17	31.27	49.38	31.48	66.00	56.00	-16.62	-24.52
2	0.16562	0.21	45.94	28.10	46.15	28.31	65.18	55.18	-19.03	-26.87
3	0.41172	0.27	35.51	28.80	35.78	29.07	57.61	47.61	-21.83	-18.54
4	0.67344	0.32	25.23	18.19	25.55	18.51	56.00	46.00	-30.45	-27.49
5	1.50391	0.42	24.71	18.25	25.13	18.67	56.00	46.00	-30.87	-27.33
6	3.47656	0.53	24.20	16.01	24.73	16.54	56.00	46.00	-31.27	-29.46

REMARKS:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value.




Phase	Neutral (N)	Detector Function	Quasi-Peak (QP) / Average (AV)
-------	-------------	-------------------	--------------------------------

No	Freq. [MHz]	Corr.	Reading Value		Emission Level		Limit		Margin	
		Factor	[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
		(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.15000	0.21	48.56	28.59	48.77	28.80	66.00	56.00	-17.23	-27.20
2	0.16172	0.21	45.99	25.53	46.20	25.74	65.38	55.38	-19.17	-29.63
3	0.40773	0.28	30.39	23.91	30.67	24.19	57.69	47.69	-27.02	-23.50
4	0.76719	0.34	20.47	12.36	20.81	12.70	56.00	46.00	-35.19	-33.30
5	1.66406	0.44	23.97	18.43	24.41	18.87	56.00	46.00	-31.59	-27.13
6	3.61328	0.55	24.65	15.52	25.20	16.07	56.00	46.00	-30.80	-29.93

REMARKS:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value.




4.3 6dB Bandwidth Measurement

4.3.1 Limits of 6dB Bandwidth Measurement

The minimum of 6dB Bandwidth Measurement is 0.5 MHz.

4.3.2 Test Setup



4.3.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.3.4 Test Procedure

- Set resolution bandwidth (RBW) = 100kHz
- Set the video bandwidth (VBW) $\geq 3 \times$ RBW, Detector = Peak.
- Trace mode = max hold.
- Sweep = auto couple.
- Measure the maximum width of the emission that is constrained by the frequencies associated with the two amplitude points (upper and lower) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission

4.3.5 Deviation from Test Standard

No deviation.

4.3.6 EUT Operating Conditions

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

4.3.7 Test Result

802.11b

Channel	Frequency (MHz)	6db Bandwidth (MHz)	Minimum Limit (MHz)	Pass / Fail
1	2412	8.10	0.5	PASS
6	2437	8.12	0.5	PASS
11	2462	8.09	0.5	PASS

802.11g

Channel	Frequency (MHz)	6db Bandwidth (MHz)		Minimum Limit (MHz)	Pass / Fail
		CHAIN 0	CHAIN 1		
1	2412	15.14	15.15	0.5	PASS
6	2437	15.13	15.14	0.5	PASS
11	2462	15.13	15.16	0.5	PASS

802.11n (HT20)


Channel	Frequency (MHz)	6db Bandwidth (MHz)		Minimum Limit (MHz)	Pass / Fail
		CHAIN 0	CHAIN 1		
1	2412	15.15	16.93	0.5	Pass
6	2437	15.15	15.74	0.5	Pass
11	2462	15.15	16.95	0.5	Pass

802.11n (HT40)


Channel	Frequency (MHz)	6db Bandwidth (MHz)		Minimum Limit (MHz)	Pass / Fail
		CHAIN 0	CHAIN 1		
3	2422	35.83	36.39	0.5	Pass
6	2437	35.85	36.41	0.5	Pass
9	2452	35.86	36.41	0.5	Pass

Spectrum Plot of Worst Value


802.11b




802.11g



802.11n (HT20)



802.11n (HT40)



4.4 Conducted Output Power Measurement

4.4.1 Limits of Conducted Output Power Measurement

For systems using digital modulation in the 2400–2483.5 MHz bands: 1 Watt (30dBm)

Per KDB 662911 D01 Multiple Transmitter Output Method of conducted output power measurement on IEEE 802.11 devices,


Array Gain = 0 dB (i.e., no array gain) for $NANT \leq 4$;

Array Gain = 0 dB (i.e., no array gain) for channel widths ≥ 40 MHz for any NANT;

Array Gain = $5 \log(NANT/NSS)$ dB or 3 dB, whichever is less for 20-MHz channel widths with $NANT \geq 5$.

For power measurements on all other devices: Array Gain = $10 \log(NANT/NSS)$ dB.

4.4.2 Test Setup



4.4.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.4.4 Test Procedures

A peak / average power sensor was used on the output port of the EUT. A power meter was used to read the response of the peak / average power sensor. Record the power level.

4.4.5 Deviation from Test Standard

No deviation.

4.4.6 EUT Operating Conditions

Same as Item 4.3.6.

4.4.7 Test Results

FOR PEAK POWER

802.11b

Channel	Frequency (MHz)	Peak Power (mW)	Peak Power (dBm)	Limit (dBm)	Pass/Fail
1	2412	127.057	21.04	30	Pass
6	2437	145.211	21.62	30	Pass
11	2462	141.906	21.52	30	Pass

802.11g

Chan.	Freq. (MHz)	Peak Power (dBm)		Total Power (mW)	Total Power (dBm)	Limit (dBm)	Pass / Fail
		Chain 0	Chain 1				
1	2412	25.95	26.04	795.341	29.01	30	Pass
6	2437	26.56	26.59	908.935	29.59	30	Pass
11	2462	26.07	26.13	814.780	29.11	30	Pass

802.11n (HT20)

Chan.	Freq. (MHz)	Peak Power (dBm)		Total Power (mW)	Total Power (dBm)	Limit (dBm)	Pass / Fail
		Chain 0	Chain 1				
1	2412	25.69	25.76	747.385	28.74	30	Pass
6	2437	26.65	26.71	931.194	29.69	30	Pass
11	2462	25.86	25.90	774.523	28.89	30	Pass

802.11n (HT40)

Chan.	Freq. (MHz)	Peak Power (dBm)		Total Power (mW)	Total Power (dBm)	Limit (dBm)	Pass / Fail
		Chain 0	Chain 1				
3	2422	22.17	22.28	333.860	25.24	30	Pass
6	2437	23.96	24.12	507.112	27.05	30	Pass
9	2452	22.83	23.07	394.635	25.96	30	Pass

FOR AVERAGE POWER

802.11b

Channel	Frequency (MHz)	Average Power (mW)	Average Power (dBm)
1	2412	52.966	17.24
6	2437	59.841	17.77
11	2462	58.884	17.70

802.11g

Chan.	Frequency (MHz)	Avg. Power (dBm)		Total Power (mW)	Total Power (dBm)
		Chain 0	Chain 1		
1	2412	17.33	17.37	108.651	20.36
6	2437	20.57	20.60	228.840	23.60
11	2462	17.61	17.64	115.753	20.64

802.11n (HT20)

Chan.	Frequency (MHz)	Avg. Power (dBm)		Total Power (mW)	Total Power (dBm)
		Chain 0	Chain 1		
1	2412	16.82	16.86	96.613	19.85
6	2437	20.79	20.83	241.010	23.82
11	2462	17.48	17.52	112.470	20.51

802.11n (HT40)


Chan.	Frequency (MHz)	Avg. Power (dBm)		Total Power (mW)	Total Power (dBm)
		Chain 0	Chain 1		
3	2422	13.42	13.61	44.940	16.53
6	2437	15.73	15.98	77.039	18.87
9	2452	14.06	14.31	52.445	17.20

4.5 Power Spectral Density Measurement

4.5.1 Limits of Power Spectral Density Measurement

The Maximum of Power Spectral Density Measurement is 8dBm.

4.5.2 Test Setup



4.5.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.5.4 Test Procedure

- Set analyzer center frequency to DTS channel center frequency.
- Set the span to 1.5 times the DTS bandwidth.
- Set the RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.
- Set the VBW $\geq 3 \times \text{RBW}$.
- Detector = peak.
- Sweep time = auto couple.
- Trace mode = max hold.
- Allow trace to fully stabilize.
- Use the peak marker function to determine the maximum amplitude level within the RBW.

4.5.5 Deviation from Test Standard

No deviation.

4.5.6 EUT Operating Condition

Same as Item 4.3.6

4.5.7 Test Results

802.11b

Channel	Freq. (MHz)	PSD (dBm)	Limit (dBm)	Pass /Fail
1	2412	-4.44	8	Pass
6	2437	-4.55	8	Pass
11	2462	-5.03	8	Pass

802.11g

TX chain	Channel	Freq. (MHz)	PSD (dBm)	10 log (N=2) dB	Total PSD (dBm)	Limit (dBm)	Pass /Fail
0	1	2412	-7.67	3.01	-4.66	7.26	Pass
	6	2437	-3.92	3.01	-0.91	7.26	Pass
	11	2462	-7.61	3.01	-4.60	7.26	Pass
1	1	2412	-7.20	3.01	-4.19	7.26	Pass
	6	2437	-3.29	3.01	-0.28	7.26	Pass
	11	2462	-7.63	3.01	-4.62	7.26	Pass

NOTE: Directional gain = 3.73dBi + 10log(2) = 6.74dBi > 6dBi , so the power density limit shall be reduced to 8-(6.74-6) = 7.26Bm.

802.11n (HT20)

TX chain	Channel	Freq. (MHz)	PSD (dBm)	10 log (N=2) dB	Total PSD (dBm)	Limit (dBm)	Pass /Fail
0	1	2412	-7.81	3.01	-4.80	7.26	Pass
	6	2437	-3.94	3.01	-0.93	7.26	Pass
	11	2462	-7.33	3.01	-4.32	7.26	Pass
1	1	2412	-8.33	3.01	-5.32	7.26	Pass
	6	2437	-3.67	3.01	-0.66	7.26	Pass
	11	2462	-7.36	3.01	-4.35	7.26	Pass

NOTE: Directional gain = 3.73dBi + 10log(2) = 6.74dBi > 6dBi , so the power density limit shall be reduced to 8-(6.74-6) = 7.26Bm.


802.11n (HT40)

TX chain	Channel	Freq. (MHz)	PSD (dBm)	10 log (N=2) dB	Total PSD (dBm)	Limit (dBm)	Pass /Fail
0	3	2422	-14.32	3.01	-11.31	7.26	Pass
	6	2437	-12.68	3.01	-9.67	7.26	Pass
	9	2452	-13.16	3.01	-10.15	7.26	Pass
1	3	2422	-13.75	3.01	-10.74	7.26	Pass
	6	2437	-13.09	3.01	-10.08	7.26	Pass
	9	2452	-14.08	3.01	-11.07	7.26	Pass


NOTE: Directional gain = 3.73dBi + 10log(2) = 6.74dBi > 6dBi , so the power density limit shall be reduced to 8-(6.74-6) = 7.26Bm.

Spectrum Plot of Worst Value


802.11b




802.11g



802.11n (HT20)



802.11n (HT40)




4.6 Conducted Out of Band Emission Measurement

4.6.1 Limits of Conducted Out of Band Emission Measurement

Below 20dB of the highest emission level of operating band (in 100kHz Resolution Bandwidth).

4.6.2 Test Setup



4.6.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.6.4 Test Procedure

MEASUREMENT PROCEDURE REF

1. Set the RBW = 100 kHz.
2. Set the VBW $\geq$ 300 kHz.
3. Detector = peak.
4. Sweep time = auto couple.
5. Trace mode = max hold.
6. Allow trace to fully stabilize.
7. Use the peak marker function to determine the maximum power level in any 100 kHz band segment within the fundamental EBW.

MEASUREMENT PROCEDURE OOB

1. Set RBW = 100 kHz.
2. Set VBW $\geq$ 300 kHz.
3. Detector = peak.
4. Sweep = auto couple.
5. Trace Mode = max hold.
6. Allow trace to fully stabilize.
7. Use the peak marker function to determine the maximum amplitude level.

4.6.5 Deviation from Test Standard

No deviation.

4.6.6 EUT Operating Condition


Same as Item 4.3.6

4.6.7 Test Results


The spectrum plots are attached on the following pages. D1 line indicates the highest level, and D2 line indicates the 20dB offset below D1. It shows compliance with the requirement.

802.11b


CH 1




CH 6




CH 11



CH 1 Band edge





CH 11 Band edge





802.11g: CHAIN 0



CH 1




CH 6




CH 11



CH 1 Band edge





CH 11 Band edge





802.11g: CHAIN 1



CH 1




CH 6




CH 11



CH 1 Band edge





CH 11 Band edge





802.11n (HT20): CHAIN 0



CH 1




CH 6




CH 11



CH 1 Band edge




CH 11 Band edge




802.11n (HT20): CHAIN 1


CH 1




CH 6




CH 11



CH 1 Band edge





CH 11 Band edge





802.11n (HT40): CHAIN 0



CH 3




CH 6




CH 9



CH 3 Band edge




CH 9 Band edge




802.11n (HT40): CHAIN 1


CH 3




CH 6




CH 9



CH 3 Band edge



CH 9 Band edge



5 Pictures of Test Arrangements

Please refer to the attached file (Test Setup Photo).

Appendix – Information on the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Linko EMC/RF Lab

Tel: 886-2-26052180

Fax: 886-2-26051924

Hsin Chu EMC/RF/Telecom Lab

Tel: 886-3-5935343

Fax: 886-3-5935342

Hwa Ya EMC/RF/Safety Lab

Tel: 886-3-3183232

Fax: 886-3-3270892

Email: service.adt@tw.bureauveritas.com

Web Site: www.bureauveritas-adt.com

The address and road map of all our labs can be found in our web site also.

--- END ---