

Section 8. Host PC labeling

The description of the regulatory information is secured and the users cannot modify it.

<E-label screen>

To access the E-label screen, do one of the following:

- Restart the computer. When the logo screen is displayed, press F9. The E-label screen is displayed.
- Restart the computer. When the logo screen is displayed, press Enter or tap the prompt to enter the Startup Interrupt menu. Then press F9 or tap the Regulatory Information option. The E-label screen is displayed.

For AX211D2W + NFC

Contains FCC ID: PD9AX211D2, IC: 1000M-AX211D2
Contains FCC ID: MCLT77H747, IC: 2878D-T77H747

Lenovo

Regulatory Information

FCC

VCCI

10

MCME
CIDF15000051

TCO
CERTIFIED

R-NZ

CAN ICES-3(B)/NMB-3(B)
ご使用のコンピュータにIEEE802.11a標準の無線機が搭載されている場合は、電波法の規定により5.15-5.35GHz周波数帯での使用は屋内に限られます。
This product contains a lithium-ion battery and a lithium battery; dispose of according to local, state, or federal laws.
Copyrighted code and parts contained herein.
© Copyright Lenovo 2005, 2018.

Contains FCC ID: PD9AX211D2, IC: 1000M-AX211D2
Contains FCC ID: MCLT77H747, IC: 2878D-T77H747

R-R-LVK-TPXXXXXX
MSIP-CRM-XXX-XXXXXX
MSIP-CRB-XXX-XXXXXX
MSIP-CRM-XXX-XXXXXX

TA-2016/3502
TA-2016/2773
TA-2016/2877
APPROVED

R

T

XXXXXXX
XXXXXXXXXX

R

T

003-170244
D170150003

MIC/KS

總務省指定
第AC-1607号

Press Enter to exit and restart your computer

v0.01