

40-00601-01R



Navini Networks®
Ripwave MX2 BTS

Model No. 2.5-2.6-BTS4A-R1
Part No. 92-82500-00R
Input: 100-240 VAC, 50/60 Hz
5 A
Freq. Range: 2496 - 2690 MHz, 5 MHz



FCC ID: PL6-2496-BTS4-R1



E112524



Made in U.S.A



92-82500-00R B 072600147

MX2, 2496 – 2690 MHz, 100-240 VAC

40-00601-01R



Navini Networks®
Ripwave MX2 BTS

Model No. 2.5-2.6-BTS4T-R1
Part No. 92-82524-00R
Input: + 24 VDC
15 A
Freq. Range: 2496 - 2690 MHz, 5 MHz



FCC ID: PL8-2496-BTS4-R1



E112524



Made in U.S.A



92-82524-00R B 072600148

MX2, 2496 – 2690 MHz, +24 VDC

40-00601-01R



Navini Networks®
Ripwave MX2 BTS

Model No. 2.5-2.6-BTS4F-R1
Part No. 92-82548-00R
Input: - 48 VDC
10 A
Freq. Range: 2496 - 2690 MHz, 5 MHz



FCC ID: PL8-2496-BTS4-R1



E112524



Made in U.S.A



92-82548-00R B 072600149

MX2, 2496 – 2690 MHz, -48 VDC

Regulatory & ID(barcode) labels (BTS-MX Bottom) Applicable to all BTS-MX Models

1. Affix the Product ID and barcode label in line with PEM screws as shown.

QTY = 1

