

FCC CERTIFICATION  
On Behalf of  
Atake Digital Technology ShenZhen Co., Ltd.

Wireless Mouse  
Model No.: AMB4, AMH, AMR, AMX

FCC ID: WWLAMB4

Prepared for : Atake Digital Technology ShenZhen Co., Ltd.  
Address : 13<sup>th</sup> Building, The 4<sup>th</sup> Industry park, Han Shui Ko, Kong  
Ming Town, ShenZhen City, China

Prepared by : ACCURATE TECHNOLOGY CO. LTD  
Address : F1, Bldg. A, Changyuan New Material Port, Keyuan Rd.  
Science & Industry Park, Nanshan, Shenzhen, Guangdong  
P.R. China

Tel: (0755) 26503290  
Fax: (0755) 26503396

Report Number : ATE20100158  
Date of Test : February 2-3, 2010  
Date of Report : February 6, 2010

## TABLE OF CONTENTS

Description	Page
Test Report Certification	
<b>1. GENERAL INFORMATION .....</b>	<b>4</b>
1.1. Description of Device (EUT).....	4
1.2. Description of Test Facility .....	4
1.3. Measurement Uncertainty .....	5
<b>2. MEASURING DEVICE AND TEST EQUIPMENT .....</b>	<b>6</b>
<b>3. SUMMARY OF TEST RESULTS.....</b>	<b>7</b>
<b>4. FUNDAMENTAL AND HARMONICS RADIATED EMISSION FOR SECTION 15.249(A) 8</b>	<b>8</b>
4.1. Block Diagram of Test Setup.....	8
4.2. The Emission Limit .....	9
4.3. Configuration of EUT on Measurement .....	9
4.4. Operating Condition of EUT .....	9
4.5. Test Procedure .....	10
4.6. The Field Strength of Radiation Emission Measurement Results .....	11
<b>5. SPURIOUS RADIATED EMISSION FOR SECTION 15.249(D) .....</b>	<b>14</b>
5.1. Block Diagram of Test Setup.....	14
5.2. The Emission Limit For Section 15.249(d) .....	15
5.3. EUT Configuration on Measurement .....	15
5.4. Operating Condition of EUT .....	15
5.5. Test Procedure .....	16
5.6. The Emission Measurement Result .....	17
<b>6. BAND EDGES .....</b>	<b>20</b>
6.1. The Requirement .....	20
6.2. EUT Configuration on Measurement .....	20
6.3. Operating Condition of EUT .....	20
6.4. Test Procedure .....	20
6.5. The Measurement Result .....	21
<b>7. ANTENNA REQUIREMENT.....</b>	<b>23</b>
7.1. The Requirement .....	23
7.2. Antenna Construction .....	23

APPENDIX I ( TEST CURVES) (22 pages)

## Test Report Certification

Applicant : Atake Digital Technology ShenZhen Co., Ltd.  
Manufacturer : Atake Digital Technology ShenZhen Co., Ltd.  
EUT Description : Wireless Mouse  
(A) MODEL NO.: AMB4, AMH, AMR, AMX  
(B) SERIAL NO.: N/A  
(C) POWER SUPPLY: 3V DC ("AAA" batteries 2×)

Measurement Procedure Used:


**FCC Rules and Regulations Part 15 Subpart C Section 15.249**  
**ANSI C63.4: 2003**

The device described above is tested by ACCURATE TECHNOLOGY CO. LTD to determine the maximum emission levels emanating from the device. The maximum emission levels are compared to the FCC Part 15 Subpart C Section 15.249 limits. The measurement results are contained in this test report and ACCURATE TECHNOLOGY CO. LTD is assumed full responsibility for the accuracy and completeness of these measurements. Also, this report shows that the Equipment Under Test (EUT) is to be technically compliant with the FCC requirements.

This report applies to above tested sample only. This report shall not be reproduced in part without written approval of ACCURATE TECHNOLOGY CO. LTD.


Date of Test : February 2-3, 2010

Prepared by :



(Engineer)

Approved & Authorized Signer :



(Manager)

# 1. GENERAL INFORMATION

## 1.1. Description of Device (EUT)

EUT	:	Wireless Mouse
Model Number	:	AMB4, AMH, AMR, AMX
		(Note: The model names are different only for the model number. Therefore only model AMB4 is tested.)
Power Supply	:	3V DC (“AAA” batteries 2×)
Operate Frequency	:	2403-2473MHz
Applicant	:	Atake Digital Technology ShenZhen Co., Ltd.
Address	:	13 <sup>th</sup> Building, The 4 <sup>th</sup> Industry park, Han Shui Ko, Kong Ming Town, ShenZhen City, China
Manufacturer	:	Atake Digital Technology ShenZhen Co., Ltd.
Address	:	13 <sup>th</sup> Building, The 4 <sup>th</sup> Industry park, Han Shui Ko, Kong Ming Town, ShenZhen City, China
Date of sample received	:	January 22, 2010
Date of Test	:	February 2-3, 2010

## 1.2. Description of Test Facility

EMC Lab	:	Accredited by TUV Rheinland Shenzhen
		Listed by FCC
		The Registration Number is 752051
		Listed by Industry Canada
		The Registration Number is 5077A-2
		Accredited by China National Accreditation Committee for Laboratories
		The Certificate Registration Number is L3193
Name of Firm	:	ACCURATE TECHNOLOGY CO. LTD
Site Location	:	F1, Bldg. A, Changyuan New Material Port, Keyuan Rd. Science & Industry Park, Nanshan, Shenzhen, Guangdong P.R. China

### 1.3.Measurement Uncertainty

Conducted Emission Expanded Uncertainty = 2.23dB, k=2

Radiated emission expanded uncertainty  
(9kHz-30MHz) = 3.08dB, k=2

Radiated emission expanded uncertainty  
(30MHz-1000MHz) = 4.42dB, k=2

Radiated emission expanded uncertainty  
(Above 1GHz) = 4.06dB, k=2

## 2. MEASURING DEVICE AND TEST EQUIPMENT

**Table 1: List of Test and Measurement Equipment**

Kind of equipment	Manufacturer	Type	S/N	Calibrated until
EMI Test Receiver	Rohde&Schwarz	ESCS30	100307	Jan. 9, 2011
EMI Test Receiver	Rohde&Schwarz	ESPI3	101526/003	Jan. 9, 2011
Spectrum Analyzer	Agilent	E7405A	MY45115511	Jan. 9, 2011
Pre-Amplifier	Rohde&Schwarz	CBLU118354 0-01	3791	Jan. 9, 2011
Loop Antenna	Schwarzbeck	FMZB1516	1516131	Jan. 9, 2011
Bilog Antenna	Schwarzbeck	VULB9163	9163-323	Jan. 9, 2011
Horn Antenna	Schwarzbeck	BBHA9120D	9120D-655	Jan. 9, 2011
Horn Antenna	Schwarzbeck	BBHA9170	9170-359	Jan. 9, 2011
LISN	Rohde&Schwarz	ESH3-Z5	100305	Jan. 9, 2011
LISN	Schwarzbeck	NSLK8126	8126431	Jan. 9, 2011

### 3. SUMMARY OF TEST RESULTS


FCC Rules	Description of Test	Result
Section 15.207	Conducted Emission	N/A
Section 15.249(a)	Fundamental and Harmonics Radiated Emission	Compliant
Section 15.249(d)	Spurious Radiated Emission	Compliant
Section 15.249(d)	Band Edge	Compliant
Section 15.203	Antenna Requirement	Compliant

Remark: “N/A” means “Not applicable”.


## 4. FUNDAMENTAL AND HARMONICS RADIATED EMISSION FOR SECTION 15.249(A)

### 4.1. Block Diagram of Test Setup

#### 4.1.1. Block diagram of connection between the EUT and simulators



#### 4.1.2. Semi-Anechoic Chamber Test Setup Diagram





## 4.2.The Emission Limit

4.2.1.For intentional radiators, According to section 15.249(a), Operation within the frequency band of 2.4 to 2.4835GHz, The fundamental field strength shall not exceed 94 dB $\mu$ V/m and the harmonics shall not exceed 54 dB $\mu$ V/m.

Fundamental Frequency	Field Strength of Fundamental (millivolts/meter)	Field Strength of harmonics (microvolts/meter)
902-928MHz	50	500
2400-2483.5MHz	50	500
5725-5875MHz	50	500
24.0-24.25GHz	250	2500

4.2.2.According to section 15.249(e), as shown in section 15.35(b), the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

## 4.3.Configuration of EUT on Measurement

The following equipment are installed on Radiated Emission Measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

### 4.3.1. Wireless Mouse (EUT)

Model Number : AMB4  
 Serial Number : N/A  
 Manufacturer : Atake Digital Technology ShenZhen Co., Ltd.

## 4.4.Operating Condition of EUT

4.4.1.Setup the EUT and simulator as shown as Section 4.1.

4.4.2.Turn on the power of all equipment.

4.4.3. Let the EUT work in TX modes measure it. The transmit frequency are 2403-2473MHz. We are select 2403MHz, 2443MHz, 2473MHz TX frequency to transmit.

#### 4.5. Test Procedure

The EUT and its simulators are placed on a turntable, which is 0.8 meter high above ground. The turntable can rotate 360 degrees to determine the position of the maximum emission level. EUT is set 3.0 meters away from the receiving antenna, which is mounted on an antenna tower. The antenna can be moved up and down between 1.0 meter and 4 meters to find out the maximum emission level. Broadband antenna (calibrated bilog antenna) is used as receiving antenna. Both horizontal and vertical polarizations of the antenna are set on measurement. In order to find the maximum emission levels, all of the interface cables must be manipulated according to ANSI C63.4: 2003 on radiated emission measurement. The EUT was tested in 3 orthogonal planes.

The bandwidth of test receiver is set at 1MHz.

## 4.6. The Field Strength of Radiation Emission Measurement Results

### PASS.

Date of Test:	February 2-3, 2010	Temperature:	25°C
EUT:	Wireless Mouse	Humidity:	50%
Model No.:	AMB4	Power Supply:	3V DC ("AAA" batteries 2 ×)
Test Mode:	TX 2403MHz	Test Engineer:	Joe

### Fundamental Radiated Emissions

Frequency (MHz)	Reading(dBμV/m)		Factor(dB) Corr.	Result(dBμV/m)		Limit(dBμV/m)		Margin(dB)		Polarization
	AV	PEAK		AV	PEAK	AV	PEAK	AV	PEAK	
2403.019	81.51	83.75	-7.45	74.06	76.30	94	114	-19.94	-37.70	Vertical
2403.019	83.52	85.70	-7.45	76.07	78.25	94	114	-17.93	-35.75	Horizontal

### Harmonics Radiated Emissions

Frequency (MHz)	Reading(dBμV/m)		Factor(dB) Corr.	Result(dBμV/m)		Limit(dBμV/m)		Margin(dB)		Polarization
	AV	PEAK		AV	PEAK	AV	PEAK	AV	PEAK	
4806.036	43.53	45.81	-0.28	43.25	45.53	54	74	-10.75	-28.47	Vertical
4806.036	45.84	48.09	-0.28	45.56	47.81	54	74	-8.44	-26.19	Horizontal

Note:

1. Emissions attenuated more than 20 dB below the permissible value are not reported.
2. The field strength is calculated by adding the antenna factor, high pass filter loss(if used) and cable loss, and subtracting the amplifier gain(if any)from the measured reading. The basic equation calculation is as follows:

$$\text{Result} = \text{Reading} + \text{Corrected Factor}$$

$$\text{Where Corrected Factor} = \text{Antenna Factor} + \text{Cable Loss} + \text{High Pass Filter Loss} - \text{Amplifier Gain}$$

3. The spectral diagrams in appendix I display the measurement of peak values.

Date of Test:	February 2-3, 2010	Temperature:	25°C
EUT:	Wireless Mouse	Humidity:	50%
Model No.:	AMB4	Power Supply:	3V DC ("AAA" batteries 2×)
Test Mode:	TX 2443MHz	Test Engineer:	Joe

### Fundamental Radiated Emissions

Frequency (MHz)	Reading(dBμV/m)		Factor(dB) Corr.	Result(dBμV/m)		Limit(dBμV/m)		Margin(dB)		Polarization
	AV	PEAK		AV	PEAK	AV	PEAK	AV	PEAK	
2443.026	81.26	83.58	-7.35	73.91	76.23	94	114	-20.09	-37.77	Vertical
2443.026	82.18	84.44	-7.35	74.83	77.09	94	114	-19.17	-36.91	Horizontal

### Harmonics Radiated Emissions

Frequency (MHz)	Reading(dBμV/m)		Factor(dB) Corr.	Result(dBμV/m)		Limit(dBμV/m)		Margin(dB)		Polarization
	AV	PEAK		AV	PEAK	AV	PEAK	AV	PEAK	
4886.050	43.96	46.22	0.16	44.12	46.38	54	74	-9.88	-27.62	Vertical
4886.050	45.78	48.04	0.16	45.94	48.20	54	74	-8.06	-25.80	Horizontal

Note:

1. Emissions attenuated more than 20 dB below the permissible value are not reported.
2. The field strength is calculated by adding the antenna factor, high pass filter loss(if used) and cable loss, and subtracting the amplifier gain(if any)from the measured reading. The basic equation calculation is as follows:

$$\text{Result} = \text{Reading} + \text{Corrected Factor}$$

$$\text{Where Corrected Factor} = \text{Antenna Factor} + \text{Cable Loss} + \text{High Pass Filter Loss} - \text{Amplifier Gain}$$

3. The spectral diagrams in appendix I display the measurement of peak values.

Date of Test:	February 2-3, 2010	Temperature:	25°C
EUT:	Wireless Mouse	Humidity:	50%
Model No.:	AMB4	Power Supply:	3V DC ("AAA" batteries 2×)
Test Mode:	TX 2473MHz	Test Engineer:	Joe

### Fundamental Radiated Emissions

Frequency (MHz)	Reading(dBμV/m)		Factor(dB) Corr.	Result(dBμV/m)		Limit(dBμV/m)		Margin(dB)		Polarization
	AV	PEAK		AV	PEAK	AV	PEAK	AV	PEAK	
2473.032	82.01	84.28	-7.36	74.65	76.92	94	114	-19.35	-37.08	Vertical
2473.032	83.16	85.42	-7.36	75.80	78.06	94	114	-18.20	-35.94	Horizontal

### Harmonics Radiated Emissions

Frequency (MHz)	Reading(dBμV/m)		Factor(dB) Corr.	Result(dBμV/m)		Limit(dBμV/m)		Margin(dB)		Polarization
	AV	PEAK		AV	PEAK	AV	PEAK	AV	PEAK	
4946.061	43.96	46.23	0.46	44.42	46.69	54	74	-9.58	-27.31	Vertical
4946.061	44.91	47.17	0.46	45.37	47.63	54	74	-8.63	-26.37	Horizontal

Note:

1. Emissions attenuated more than 20 dB below the permissible value are not reported.
2. The field strength is calculated by adding the antenna factor, high pass filter loss(if used) and cable loss, and subtracting the amplifier gain(if any)from the measured reading. The basic equation calculation is as follows:

$$\text{Result} = \text{Reading} + \text{Corrected Factor}$$

$$\text{Where Corrected Factor} = \text{Antenna Factor} + \text{Cable Loss} + \text{High Pass Filter Loss} - \text{Amplifier Gain}$$

3. The spectral diagrams in appendix I display the measurement of peak values.

## 5. SPURIOUS RADIATED EMISSION FOR SECTION 15.249(D)


### 5.1. Block Diagram of Test Setup

#### 5.1.1. Block diagram of connection between the EUT and simulators



(EUT: Wireless Mouse)

#### 5.1.2. Semi-Anechoic Chamber Test Setup Diagram



(EUT: Wireless Mouse)

## 5.2.The Emission Limit For Section 15.249(d)

5.2.1.Emission radiated outside of the specified frequency bands, except for harmonics, shall be comply with the general radiated emission limits in Section 15.209.

### Radiation Emission Measurement Limits According to Section 15.209

Frequency (MHz)	Limit		The final measurement in band 9-90kHz, 110-490kHz and above 1000MHz is performed with Average detector. Except those frequency bands mention above, the final measurement for frequencies below 1000MHz is performed with Quasi Peak detector.
	Field Strength of Quasi-peak Value (microvolts/m)	Field Strength of Quasi-peak Value (dB $\mu$ V/m)	
30 - 88	100	40	
88 - 216	150	43.5	
216 - 960	200	46	
Above 960	500	54	

## 5.3.EUT Configuration on Measurement

The following equipment are installed on the emission Measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

### 5.3.1. Wireless Mouse (EUT)

Model Number : AMB4  
 Serial Number : N/A  
 Manufacturer : Atake Digital Technology ShenZhen Co., Ltd.

## 5.4.Operating Condition of EUT

5.4.1.Setup the EUT and simulator as shown as Section 5.1.

5.4.2.Turn on the power of all equipment.

5.4.3. Let the EUT work in TX modes measure it. The transmit frequency are 2403-2473MHz. We are select 2403MHz, 2443MHz, 2473MHz TX frequency to transmit.

## 5.5. Test Procedure

The EUT and its simulators are placed on a turntable, which is 0.8 meter high above ground. The turntable can rotate 360 degrees to determine the position of the maximum emission level. EUT is set 3.0 meters away from the receiving antenna, which is mounted on an antenna tower. The antenna can be moved up and down between 1.0 meter and 4 meters to find out the maximum emission level. Broadband antenna (calibrated bilog antenna) is used as receiving antenna. Both horizontal and vertical polarizations of the antenna are set on measurement. In order to find the maximum emission levels, all of the interface cables must be manipulated according to ANSI C63.4: 2003 on radiated emission measurement. The EUT was tested in 3 orthogonal planes.

The bandwidth of test receiver is set at 120kHz in 30-1000MHz. and set at 1MHz in above 1000MHz.

The frequency range from 30MHz to 25000MHz is checked.

The final measurement in band 9-90kHz, 110-490kHz and above 1000MHz is performed with Average detector. Except those frequency bands mention above, the final measurement for frequencies below 1000MHz is performed with Quasi Peak detector.



## 5.6.The Emission Measurement Result

**PASS.**

Date of Test:	February 2-3, 2010	Temperature:	25°C
EUT:	Wireless Mouse	Humidity:	50%
Model No.:	AMB4	Power Supply:	3V DC (“AAA” batteries 2×)
Test Mode:	TX 2403MHz	Test Engineer:	Joe

Frequency (MHz)	Reading (dBμV/m)	Factor(dB) Corr.	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Polarization
	QP		QP	QP	QP	
-	-	-	-	-	-	Vertical
-	-	-	-	-	-	Horizontal

Note:

1. Emissions attenuated more than 20 dB below the permissible value are not reported.
2. The field strength is calculated by adding the antenna factor, high pass filter loss(if used) and cable loss, and subtracting the amplifier gain(if any)from the measured reading. The basic equation calculation is as follows:

$$\text{Result} = \text{Reading} + \text{Corrected Factor}$$

$$\text{Where Corrected Factor} = \text{Antenna Factor} + \text{Cable Loss} + \text{High Pass Filter Loss} - \text{Amplifier Gain}$$

3. The spectral diagrams in appendix I display the measurement of peak values.

Date of Test:	February 2-3, 2010	Temperature:	25°C
EUT:	Wireless Mouse	Humidity:	50%
Model No.:	AMB4	Power Supply:	3V DC (“AAA” batteries 2×)
Test Mode:	TX 2443MHz	Test Engineer:	Joe

Frequency (MHz)	Reading (dB $\mu$ V/m)	Factor(dB) Corr.	Result (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)	Polarization
	QP		QP	QP	QP	
-	-	-	-	-	-	Vertical
-	-	-	-	-	-	Horizontal

Note:

1. Emissions attenuated more than 20 dB below the permissible value are not reported.
2. The field strength is calculated by adding the antenna factor, high pass filter loss(if used) and cable loss, and subtracting the amplifier gain(if any)from the measured reading. The basic equation calculation is as follows:

$$\text{Result} = \text{Reading} + \text{Corrected Factor}$$

$$\text{Where Corrected Factor} = \text{Antenna Factor} + \text{Cable Loss} + \text{High Pass Filter Loss} - \text{Amplifier Gain}$$

3. The spectral diagrams in appendix I display the measurement of peak values.

Date of Test:	February 2-3, 2010	Temperature:	25°C
EUT:	Wireless Mouse	Humidity:	50%
Model No.:	AMB4	Power Supply:	3V DC (“AAA” batteries 2×)
Test Mode:	TX 2473MHz	Test Engineer:	Joe

Frequency (MHz)	Reading (dBμV/m)	Factor(dB) Corr.	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Polarization
	QP		QP	QP	QP	
-	-	-	-	-	-	Vertical
-	-	-	-	-	-	Horizontal

Note:

1. Emissions attenuated more than 20 dB below the permissible value are not reported.
2. The field strength is calculated by adding the antenna factor, high pass filter loss(if used) and cable loss, and subtracting the amplifier gain(if any)from the measured reading. The basic equation calculation is as follows:

$$\text{Result} = \text{Reading} + \text{Corrected Factor}$$

$$\text{Where Corrected Factor} = \text{Antenna Factor} + \text{Cable Loss} + \text{High Pass Filter Loss} - \text{Amplifier Gain}$$

3. The spectral diagrams in appendix I display the measurement of peak values.

## 6. BAND EDGES

### 6.1.The Requirement

6.1.1.Band Edge from 2400MHz to 2483.5MHz. Emission radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in Section 15.209, whichever is the lesser attenuation.

### 6.2.EUT Configuration on Measurement

The following equipment are installed on the emission Measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

#### 6.2.1. Wireless Mouse (EUT)

Model Number : AMB4  
Serial Number : N/A  
Manufacturer : Atake Digital Technology ShenZhen Co., Ltd.

### 6.3.Operating Condition of EUT

6.3.1.Setup the EUT and simulator as shown as Section 4.1.

6.3.2.Turn on the power of all equipment.

6.3.3. Let the EUT work in TX modes measure it. The transmit frequency are 2403-2473MHz. We are select 2403MHz, 2473MHz TX frequency to transmit.

### 6.4.Test Procedure

1. The EUT is placed on a turntable, which is 0.8m above the ground plane and worked at highest radiated power.
2. The turntable was rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emission.
4. Set the spectrum analyzer in the following setting in order to capture the lower and upper band-edges of the emission:  
RBW=1MHz, VBW=1MHz

## 6.5.The Measurement Result

**Pass.**

Date of Test:	February 3, 2010	Temperature:	25°C
EUT:	Wireless Mouse	Humidity:	50%
Model No.:	AMB4	Power Supply:	3V DC (“AAA” batteries 2×)
Test Mode:	TX 2403MHz	Test Engineer:	Joe

Frequency (MHz)	Reading(dBμV/m)		Factor(dB) Corr.	Result(dBμV/m)		Limit(dBμV/m)		Margin(dB)		Polarization
	AV	PEAK		AV	PEAK	AV	PEAK	AV	PEAK	
-	-	-	-	-	-	-	-	-	-	Vertical
-	-	-	-	-	-	-	-	-	-	Horizontal

Note:

1. Emissions attenuated more than 20 dB below the permissible value are not reported.
2. The field strength is calculated by adding the antenna factor, high pass filter loss(if used) and cable loss, and subtracting the amplifier gain(if any)from the measured reading. The basic equation calculation is as follows:

$$\text{Result} = \text{Reading} + \text{Corrected Factor}$$

$$\text{Where Corrected Factor} = \text{Antenna Factor} + \text{Cable Loss} + \text{High Pass Filter Loss} - \text{Amplifier Gain}$$

3. The spectral diagrams in appendix I display the measurement of peak values.

Date of Test:	February 3, 2010	Temperature:	25°C
EUT:	Wireless Mouse	Humidity:	50%
Model No.:	AMB4	Power Supply:	3V DC (“AAA” batteries 2×)
Test Mode:	TX 2473MHz	Test Engineer:	Joe

Frequency (MHz)	Reading(dBμV/m)		Factor(dB) Corr.	Result(dBμV/m)		Limit(dBμV/m)		Margin(dB)		Polarization
	AV	PEAK		AV	PEAK	AV	PEAK	AV	PEAK	
-	-	-	-	-	-	-	-	-	-	Vertical
-	-	-	-	-	-	-	-	-	-	Horizontal

Note:

1. Emissions attenuated more than 20 dB below the permissible value are not reported.
2. The field strength is calculated by adding the antenna factor, high pass filter loss(if used) and cable loss, and subtracting the amplifier gain(if any)from the measured reading. The basic equation calculation is as follows:

$$\text{Result} = \text{Reading} + \text{Corrected Factor}$$

$$\text{Where Corrected Factor} = \text{Antenna Factor} + \text{Cable Loss} + \text{High Pass Filter Loss} - \text{Amplifier Gain}$$

3. The spectral diagrams in appendix I display the measurement of peak values.


## 7. ANTENNA REQUIREMENT

### 7.1.The Requirement

7.1.1.According to Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

### 7.2.Antenna Construction

The antenna is PCB Layout antenna, no consideration of replacement.



Antenna

# APPENDIX I (Test Curves)





# **ACCURATE TECHNOLOGY CO., LTD.**

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,  
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 966 chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: RTTE #4073

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.( C)/Hum.(%) 25 C / 50 %

EUT: Wireless mouse

Mode: TX 2403MHz

Model: AMB4

Manufacturer: Atake Digital

Polarization: Horizontal

Power Source: DC 3V


Date: 2010/02/02

Time: 20:18:47

Engineer Signature: Joe

Distance: 3m

Note: Sample No.:100211 Report No.:ATE20100158



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
-----	----------------	---------------------	----------------	--------------------	-------------------	----------------	----------	----------------	------------------	--------



# **ACCURATE TECHNOLOGY CO., LTD.**

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,  
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 966 chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: RTTE #4074

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.( C)/Hum.(%) 25 C / 50 %

EUT: Wireless mouse

Mode: TX 2403MHz

Model: AMB4

Manufacturer: Atake Digital

Polarization: Vertical

Power Source: DC 3V


Date: 2010/02/02

Time: 20:22:31

Engineer Signature: Joe

Distance: 3m

Note: Sample No.:100211 Report No.:ATE20100158



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
-----	----------------	---------------------	----------------	--------------------	-------------------	----------------	----------	----------------	------------------	--------



# **ACCURATE TECHNOLOGY CO., LTD.**

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,  
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 966 chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: RTTE #4085

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.( C)/Hum.(%) 25 C / 50 %

EUT: Wireless mouse

Mode: TX 2403MHz

Model: AMB4

Manufacturer: Atake Digital

Polarization: Horizontal

Power Source: DC 3V


Date: 2010/02/03

Time: 10:01:06

Engineer Signature: Joe

Distance: 3m

Note: Sample No.:100211 Report No.:ATE20100158



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2403.019	85.70	-7.45	78.25	114.00	-35.75	peak			
2	2403.019	83.52	-7.45	76.07	94.00	-17.93	AVG			
3	4806.036	48.09	-0.28	47.81	74.00	-26.19	peak			
4	4806.036	45.84	-0.28	45.56	54.00	-8.44	AVG			



# **ACCURATE TECHNOLOGY CO., LTD.**

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,  
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 966 chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: RTTE #4086

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.( C)/Hum.(%) 25 C / 50 %

EUT: Wireless mouse

Mode: TX 2403MHz

Model: AMB4

Manufacturer: Atake Digital

Polarization: Vertical

Power Source: DC 3V


Date: 2010/02/03

Time: 10:05:01

Engineer Signature: Joe

Distance: 3m

Note: Sample No.:100211 Report No.:ATE20100158



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2403.019	83.75	-7.45	76.30	114.00	-37.70	peak			
2	2403.019	81.51	-7.45	74.06	94.00	-19.94	AVG			
3	4806.036	45.81	-0.28	45.53	74.00	-28.47	peak			
4	4806.036	43.53	-0.28	43.25	54.00	-10.75	AVG			


**ACCURATE TECHNOLOGY CO., LTD.**

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,  
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 966 chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: RTTE #4080

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.( C)/Hum.(%) 25 C / 50 %

EUT: Wireless mouse

Mode: TX 2403MHz

Model: AMB4

Manufacturer: Atake Digital

Polarization: Horizontal

Power Source: DC 3V


Date: 2010/02/02

Time: 20:50:59

Engineer Signature: Joe

Distance: 3m

Note: Sample No.:100211 Report No.:ATE20100158



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
-----	----------------	---------------------	----------------	--------------------	-------------------	----------------	----------	----------------	------------------	--------




**ACCURATE TECHNOLOGY CO., LTD.**

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,  
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 966 chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: RTTE #4079

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.( C)/Hum.(%) 25 C / 50 %

EUT: Wireless mouse

Mode: TX 2403MHz

Model: AMB4

Manufacturer: Atake Digital

Polarization: Vertical

Power Source: DC 3V


Date: 2010/02/02

Time: 20:47:46

Engineer Signature: Joe

Distance: 3m

Note: Sample No.:100211 Report No.:ATE20100158



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
-----	----------------	---------------------	----------------	--------------------	-------------------	----------------	----------	----------------	------------------	--------



# **ACCURATE TECHNOLOGY CO., LTD.**

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,  
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 966 chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: RTTE #4076

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.( C)/Hum.(%) 25 C / 50 %

EUT: Wireless mouse

Mode: TX 2443MHz

Model: AMB4

Manufacturer: Atake Digital

Polarization: Horizontal

Power Source: DC 3V


Date: 2010/02/02

Time: 20:30:31

Engineer Signature: Joe

Distance: 3m

Note: Sample No.:100211 Report No.:ATE20100158



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
-----	----------------	---------------------	----------------	--------------------	-------------------	----------------	----------	----------------	------------------	--------



# **ACCURATE TECHNOLOGY CO., LTD.**

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,  
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 966 chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: RTTE #4075

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.( C)/Hum.(%) 25 C / 50 %

EUT: Wireless mouse

Mode: TX 2443MHz

Model: AMB4

Manufacturer: Atake Digital

Polarization: Vertical

Power Source: DC 3V


Date: 2010/02/02

Time: 20:26:58

Engineer Signature: Joe

Distance: 3m

Note: Sample No.:100211 Report No.:ATE20100158



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
-----	----------------	---------------------	----------------	--------------------	-------------------	----------------	----------	----------------	------------------	--------





# **ACCURATE TECHNOLOGY CO., LTD.**

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,  
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 966 chamber  
Tel:+86-0755-26503290  
Fax:+86-0755-26503396

Job No.: RTTE #4088

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.( C)/Hum.(%) 25 C / 50 %

EUT: Wireless mouse

Mode: TX 2443MHz

Model: AMB4

Manufacturer: Atake Digital

Polarization: Horizontal

Power Source: DC 3V


Date: 2010/02/03

Time: 10:14:00

Engineer Signature: Joe

Distance: 3m

Note: Sample No.:100211 Report No.:ATE20100158



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2443.026	84.44	-7.35	77.09	114.00	-36.91	peak			
2	2443.026	82.18	-7.35	74.83	94.00	-19.17	AVG			
3	4886.050	48.04	0.16	48.20	74.00	-25.80	peak			
4	4886.050	45.78	0.16	45.94	54.00	-8.06	AVG			



# **ACCURATE TECHNOLOGY CO., LTD.**

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,  
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 966 chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: RTTE #4087

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.( C)/Hum.(%) 25 C / 50 %

EUT: Wireless mouse

Mode: TX 2443MHz

Model: AMB4

Manufacturer: Atake Digital

Polarization: Vertical

Power Source: DC 3V


Date: 2010/02/03

Time: 10:09:43

Engineer Signature: Joe

Distance: 3m

Note: Sample No.:100211 Report No.:ATE20100158



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2443.026	83.58	-7.35	76.23	114.00	-37.77	peak			
2	2443.026	81.26	-7.35	73.91	94.00	-20.09	AVG			
3	4886.050	46.22	0.16	46.38	74.00	-27.62	peak			
4	4886.050	43.96	0.16	44.12	54.00	-9.88	AVG			


**ACCURATE TECHNOLOGY CO., LTD.**

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,  
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 966 chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: RTTE #4081

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.( C)/Hum.(%) 25 C / 50 %

EUT: Wireless mouse

Mode: TX 2443MHz

Model: AMB4

Manufacturer: Atake Digital

Polarization: Horizontal

Power Source: DC 3V


Date: 2010/02/02

Time: 20:54:32

Engineer Signature: Joe

Distance: 3m

Note: Sample No.:100211 Report No.:ATE20100158



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
-----	----------------	---------------------	----------------	--------------------	-------------------	----------------	----------	----------------	------------------	--------


**ACCURATE TECHNOLOGY CO., LTD.**

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,  
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 966 chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: RTTE #4082

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.( C)/Hum.(%) 25 C / 50 %

EUT: Wireless mouse

Mode: TX 2443MHz

Model: AMB4

Manufacturer: Atake Digital

Polarization: Vertical

Power Source: DC 3V


Date: 2010/02/02

Time: 20:57:50

Engineer Signature: Joe

Distance: 3m

Note: Sample No.:100211 Report No.:ATE20100158



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
-----	----------------	---------------------	----------------	--------------------	-------------------	----------------	----------	----------------	------------------	--------



# **ACCURATE TECHNOLOGY CO., LTD.**

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,  
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 966 chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: RTTE #4077

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.( C)/Hum.(%) 25 C / 50 %

EUT: Wireless mouse

Mode: TX 2473MHz

Model: AMB4

Manufacturer: Atake Digital

Polarization: Horizontal

Power Source: DC 3V


Date: 2010/02/02

Time: 20:35:03

Engineer Signature: Joe

Distance: 3m

Note: Sample No.:100211 Report No.:ATE20100158



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
-----	----------------	---------------------	----------------	--------------------	-------------------	----------------	----------	----------------	------------------	--------





# **ACCURATE TECHNOLOGY CO., LTD.**

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,  
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 966 chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: RTTE #4078

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.( C)/Hum.(%) 25 C / 50 %

EUT: Wireless mouse

Mode: TX 2473MHz

Model: AMB4

Manufacturer: Atake Digital

Polarization: Vertical

Power Source: DC 3V


Date: 2010/02/02

Time: 20:38:50

Engineer Signature: Joe

Distance: 3m

Note: Sample No.:100211 Report No.:ATE20100158



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
-----	----------------	---------------------	----------------	--------------------	-------------------	----------------	----------	----------------	------------------	--------


**ACCURATE TECHNOLOGY CO., LTD.**

 F1,Bldg,A,Changyuan New Material Port Keyuan Rd,  
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 966 chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: RTTE #4089

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.( C)/Hum.(%) 25 C / 50 %

EUT: Wireless mouse

Mode: TX 2473MHz

Model: AMB4

Manufacturer: Atake Digital

Polarization: Horizontal

Power Source: DC 3V


Date: 2010/02/03

Time: 10:18:50

Engineer Signature: Joe

Distance: 3m

Note: Sample No.:100211 Report No.:ATE20100158



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2473.032	85.42	-7.36	78.06	114.00	-35.94	peak			
2	2473.032	83.16	-7.36	75.80	94.00	-18.20	AVG			
3	4946.061	47.17	0.46	47.63	74.00	-26.37	peak			
4	4946.061	44.91	0.46	45.37	54.00	-8.63	AVG			



# **ACCURATE TECHNOLOGY CO., LTD.**

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,  
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 966 chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: RTTE #4090

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.( C)/Hum.(%) 25 C / 50 %

EUT: Wireless mouse

Mode: TX 2473MHz

Model: AMB4

Manufacturer: Atake Digital

Polarization: Vertical

Power Source: DC 3V


Date: 2010/02/03

Time: 10:23:02

Engineer Signature: Joe

Distance: 3m

Note: Sample No.:100211 Report No.:ATE20100158



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2473.032	84.28	-7.36	76.92	114.00	-37.08	peak			
2	2473.032	82.01	-7.36	74.65	94.00	-19.35	AVG			
3	4946.061	46.23	0.46	46.69	74.00	-27.31	peak			
4	4946.061	43.96	0.46	44.42	54.00	-9.58	AVG			




**ACCURATE TECHNOLOGY CO., LTD.**

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,  
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 966 chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: RTTE #4084

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.( C)/Hum.(%) 25 C / 50 %

EUT: Wireless mouse

Mode: TX 2473MHz

Model: AMB4

Manufacturer: Atake Digital

Polarization: Horizontal

Power Source: DC 3V


Date: 2010/02/02

Time: 21:04:53

Engineer Signature: Joe

Distance: 3m

Note: Sample No.:100211 Report No.:ATE20100158



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
-----	----------------	---------------------	----------------	--------------------	-------------------	----------------	----------	----------------	------------------	--------


**ACCURATE TECHNOLOGY CO., LTD.**

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,  
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 966 chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: RTTE #4083

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.( C)/Hum.(%) 25 C / 50 %

EUT: Wireless mouse

Mode: TX 2473MHz

Model: AMB4

Manufacturer: Atake Digital

Polarization: Vertical

Power Source: DC 3V


Date: 2010/02/02

Time: 21:01:26

Engineer Signature: Joe

Distance: 3m

Note: Sample No.:100211 Report No.:ATE20100158



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
-----	----------------	---------------------	----------------	--------------------	-------------------	----------------	----------	----------------	------------------	--------


**ACCURATE TECHNOLOGY CO., LTD.**

 F1,Bldg,A,Changyuan New Material Port Keyuan Rd,  
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 966 chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: RTTE #4093

Standard: FCC Part 15 PEAK 2.4G

Test item: Radiation Test

Temp.( C)/Hum.(%) 25 C / 50 %

EUT: Wireless mouse

Mode: TX 2403MHz

Model: AMB4

Manufacturer: Atake Digital

Polarization: Horizontal

Power Source: DC 3V


Date: 2010/02/03

Time: 10:38:21

Engineer Signature: Joe

Distance: 3m

Note: Sample No.:100211 Report No.:ATE20100158



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
-----	----------------	---------------------	----------------	--------------------	-------------------	----------------	----------	----------------	------------------	--------


**ACCURATE TECHNOLOGY CO., LTD.**

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,  
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 966 chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: RTTE #4094

Standard: FCC Part 15 PEAK 2.4G

Test item: Radiation Test

Temp.( C)/Hum.(%) 25 C / 50 %

EUT: Wireless mouse

Mode: TX 2403MHz

Model: AMB4

Manufacturer: Atake Digital

Polarization: Vertical

Power Source: DC 3V


Date: 2010/02/03

Time: 10:42:25

Engineer Signature: Joe

Distance: 3m

Note: Sample No.:100211 Report No.:ATE20100158



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
-----	----------------	---------------------	----------------	--------------------	-------------------	----------------	----------	----------------	------------------	--------


**ACCURATE TECHNOLOGY CO., LTD.**

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,  
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 966 chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: RTTE #4092

Standard: FCC Part 15 PEAK 2.4G

Test item: Radiation Test

Temp.( C)/Hum.(%) 25 C / 50 %

EUT: Wireless mouse

Mode: TX 2473MHz

Model: AMB4

Manufacturer: Atake Digital

Polarization: Horizontal

Power Source: DC 3V


Date: 2010/02/03

Time: 10:33:12

Engineer Signature: Joe

Distance: 3m

Note: Sample No.:100211 Report No.:ATE20100158



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
-----	----------------	---------------------	----------------	--------------------	-------------------	----------------	----------	----------------	------------------	--------




**ACCURATE TECHNOLOGY CO., LTD.**

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,  
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 966 chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: RTTE #4091

Standard: FCC Part 15 PEAK 2.4G

Test item: Radiation Test

Temp.( C)/Hum.(%) 25 C / 50 %

EUT: Wireless mouse

Mode: TX 2473MHz

Model: AMB4

Manufacturer: Atake Digital

Polarization: Vertical

Power Source: DC 3V


Date: 2010/02/03

Time: 10:29:03

Engineer Signature: Joe

Distance: 3m

Note: Sample No.:100211 Report No.:ATE20100158



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
-----	----------------	---------------------	----------------	--------------------	-------------------	----------------	----------	----------------	------------------	--------