

Maximum Permissible Exposure (MPE)

Standard Applicable

According to §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

This is a Mobile device, the MPE is required.

According to §1.1310 and §2.1091 RF exposure is calculated.

Limits for Maximum Permissive Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Averaging Time (minute)
Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	F/1500	30
1500-15000	/	/	1.0	30

F = frequency in MHz

* = Plane-wave equipment power density

According to RSS 102 issue 5.

2.5.2 Exemption Limits for Routine Evaluation – RF Exposure Evaluation

RF exposure evaluation is required if the separation distance between the user and/or bystander and the device's radiating element is greater than 20 cm, except when the device operates as follows:

- below 20 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 1 W (adjusted for tune-up tolerance);
- at or above 20 MHz and below 48 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than $22.48/f^{0.5} \text{ W}$ (adjusted for tune-up tolerance), where f is in MHz;
- at or above 48 MHz and below 300 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 0.6 W (adjusted for tune-up tolerance);
- at or above 300 MHz and below 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than $1.31 \times 10^{-2} f^{0.6834} \text{ W}$ (adjusted for tune-up tolerance), where f is in MHz;
- at or above 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 5 W (adjusted for tune-up tolerance).

In these cases, the information contained in the RF exposure technical brief may be limited to information that demonstrates how the e.i.r.p. was derived.

Maximum Permissible Exposure (MPE) Evaluation

PCB Antenna

Maximum output power at antenna input terminal:	15.38	(dBm)
Maximum output power at antenna input terminal:	34.51437393	(mW)
Tune-Up power Tolerance:	1	dB
Duty cycle:	100	(%)
Maximum Pav :	43.45102242	(mW)
Antenna gain (typical):	-3.58	(dBi)
Maximum antenna gain:	0.438530698	(numeric)
Prediction distance:	20	(cm)
MPE limit for uncontrolled exposure at prediction	1	(mW/cm ²)
Power density at predication frequency at 20 (cm)	0.0037927	(mW/cm ²)

Prediction of MPE limit at a given distance

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = PG / 4 \pi R^2$$

Where: S = Power density

P = Power input to antenna

G = Power gain of the antenna in the direction of interest relative to an isotropic radiator

R = Distance to the center of radiation of the antenna

Measurement Result:

The predicted power density level at 20 cm is 0.0037927 mW/cm². This is below the uncontrolled exposure limit of 1 mW/cm².

Maximum Permissible Exposure (MPE) Evaluation

Dipole Antenna

Maximum output power at antenna input terminal:	15.38	(dBm)
Maximum output power at antenna input terminal:	34.51437393	(mW)
Tune-Up power Tolerance:	1	dB
Duty cycle:	100	(%)
Maximum Pav :	43.45102242	(mW)
Antenna gain (typical):	6	(dBi)
Maximum antenna gain:	3.981071706	(numeric)
Prediction distance:	20	(cm)
MPE limit for uncontrolled exposure at prediction	1	(mW/cm ²)
Power density at predication frequency at 20 (cm)	0.0344311	(mW/cm ²)

Prediction of MPE limit at a given distance

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = PG / 4 \pi R^2$$

Where: S = Power density

P = Power input to antenna

G = Power gain of the antenna in the direction of interest relative to an isotropic radiator

R = Distance to the center of radiation of the antenna

Measurement Result:

The predicted power density level at 20 cm is 0.0344311 mW/cm². This is below the uncontrolled exposure limit of 1 mW/cm².

Power measurement:

IC EIRP level

PCB Antenna

Frequency:	2480	MHz
Maximum output power at antenna input terminal:	15.38	(dBm)
Tune-Up power Tolerance:	1	dB
Duty cycle:	100	(%)
Antenna gain (typical):	-3.58	(dBi)
EIRP:	19.055	mW
EIRP:	0.01905	W
EIRP Limit	2.736	W

Measurement Result:

The EIRP level is 0.01905W which less than RSS102 section 2.5.2 Exemption Limits above 300 MHz and below 6 GHz condition.

IC EIRP level

Dipole Antenna

Frequency:	2480	MHz
Maximum output power at antenna input terminal:	15.38	(dBm)
Tune-Up power Tolerance:	1	dB
Duty cycle:	100	(%)
Antenna gain (typical):	6	(dBi)
EIRP:	172.982	mW
EIRP:	0.17298	W
EIRP Limit	2.736	W

Measurement Result:

The EIRP level is 0.17298W which less than RSS102 section 2.5.2 Exemption Limits above 300 MHz and below 6 GHz condition.

~ end ~