

6.4 Band Edge Emissions at Antenna Terminal

§2.1051 §22.917(a) §24.238(a) §27.53(g) §27.53(h)

Test Overview

All out of band emissions are measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates were investigated to determine the worst case configuration. All modes of operation were investigated and the worst case configuration results are reported in this section.

The minimum permissible attenuation level of any spurious emission is $43 + \log_{10}(P_{\text{Watts}})$, where P is the transmitter power in Watts.

Test Procedure Used

KDB 971168 v02r02 – Section 6.0

Test Settings

1. Start and stop frequency were set such that the band edge would be placed in the center of the plot
2. Span was set large enough so as to capture all out of band emissions near the band edge
3. RBW $\geq 1\%$ of the emission bandwidth
4. VBW $\geq 3 \times$ RBW
5. Detector = RMS
6. Number of sweep points $\geq 2 \times$ Span/RBW
7. Trace mode = trace average for continuous emissions, max hold for pulse emissions
8. Sweep time = auto couple
9. The trace was allowed to stabilize

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.





Figure 6-3. Test Instrument & Measurement Setup

Test Notes

Per 22.917(b) 24.238(a) 27.53(h) in the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed to demonstrate compliance with the out-of-band emissions limit. The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emission are attenuated at least 26 dB below the transmitter power.

Per 27.53(g) for operations in the 698-746 MHz band, in the 100 kHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least 30 kHz may be employed to demonstrate compliance with the out-of-band emissions limit.

FCC ID: ZNFH634		FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)			Reviewed by: Quality Manager
Test Report S/N: 0Y1504200766.ZNF	Test Dates: 4/20 - 5/4/2015	EUT Type: Portable Handset			Page 50 of 109



Plot 6-73. Lower Band Edge Plot (Band 17 – 5.0MHz QPSK – RB Size 25)



Plot 6-74. Lower Extended Band Edge Plot (Band 17 – 5.0MHz QPSK – RB Size 25)

FCC ID: ZNFH634		FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1504200766.ZNF	Test Dates: 4/20 - 5/4/2015	EUT Type: Portable Handset		Page 51 of 109



Plot 6-75. Upper Band Edge Plot (Band 17 – 5.0MHz QPSK – RB Size 25)



Plot 6-76. Upper Extended Band Edge Plot (Band 17 – 5.0MHz QPSK – RB Size 25)

FCC ID: ZNFH634		FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)			Reviewed by: Quality Manager
Test Report S/N: 0Y1504200766.ZNF	Test Dates: 4/20 - 5/4/2015	EUT Type: Portable Handset			Page 52 of 109




Plot 6-77. Lower Band Edge Plot (Band 17 – 10.0MHz QPSK – RB Size 50)




Plot 6-78. Lower Extended Band Edge Plot (Band 17 – 10.0MHz QPSK – RB Size 50)

FCC ID: ZNFH634		FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1504200766.ZNF	Test Dates: 4/20 - 5/4/2015	EUT Type: Portable Handset		Page 53 of 109



Plot 6-79. Upper Band Edge Plot (Band 17 – 10.0MHz QPSK – RB Size 50)



Plot 6-80. Upper Extended Band Edge Plot (Band 17 – 10.0MHz QPSK – RB Size 50)

FCC ID: ZNFH634		FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1504200766.ZNF	Test Dates: 4/20 - 5/4/2015	EUT Type: Portable Handset		Page 54 of 109



Plot 6-81. Lower Band Edge Plot (Band 5 – 1.4MHz QPSK – RB Size 6)




Plot 6-82. Lower Extended Band Edge Plot (Band 5 – 1.4MHz QPSK – RB Size 6)

FCC ID: ZNFH634		FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)			Reviewed by: Quality Manager
Test Report S/N: 0Y1504200766.ZNF	Test Dates: 4/20 - 5/4/2015	EUT Type: Portable Handset			Page 55 of 109




Plot 6-83. Upper Band Edge Plot (Band 5 – 1.4MHz QPSK – RB Size 6)



Plot 6-84. Upper Extended Band Edge Plot (Band 5 – 1.4MHz QPSK – RB Size 6)

FCC ID: ZNFH634		FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)			Reviewed by: Quality Manager
Test Report S/N: 0Y1504200766.ZNF	Test Dates: 4/20 - 5/4/2015	EUT Type: Portable Handset			Page 56 of 109



Plot 6-85. Lower Band Edge Plot (Band 5 – 3.0MHz QPSK – RB Size 15)



Plot 6-86. Lower Extended Band Edge Plot (Band 5 – 3.0MHz QPSK – RB Size 15)

FCC ID: ZNFH634		FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1504200766.ZNF	Test Dates: 4/20 - 5/4/2015	EUT Type: Portable Handset		Page 57 of 109




Plot 6-87. Upper Band Edge Plot (Band 5 – 3.0MHz QPSK – RB Size 15)



Plot 6-88. Upper Extended Band Edge Plot (Band 5 – Band 5 – 3.0MHz QPSK – RB Size 15)

FCC ID: ZNFH634		FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1504200766.ZNF	Test Dates: 4/20 - 5/4/2015	EUT Type: Portable Handset		Page 58 of 109




Plot 6-89. Lower Band Edge Plot (Band 5 – 5.0MHz QPSK – RB Size 25)



Plot 6-90. Lower Extended Band Edge Plot (Band 5 – 5.0MHz QPSK – RB Size 25)

FCC ID: ZNFH634		FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)			Reviewed by: Quality Manager
Test Report S/N: 0Y1504200766.ZNF	Test Dates: 4/20 - 5/4/2015	EUT Type: Portable Handset			Page 59 of 109




Plot 6-91. Upper Band Edge Plot (Band 5 – 5.0MHz QPSK – RB Size 25)




Plot 6-92. Upper Extended Band Edge Plot (Band 5 – 5.0MHz QPSK – RB Size 25)

FCC ID: ZNFH634		FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1504200766.ZNF	Test Dates: 4/20 - 5/4/2015	EUT Type: Portable Handset		Page 60 of 109




Plot 6-93. Lower Band Edge Plot (Band 5 – 10.0MHz QPSK – RB Size 50)




Plot 6-94. Upper Band Edge Plot (Band 5 – 10.0MHz QPSK – RB Size 50)

FCC ID: ZNFH634		FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)			Reviewed by: Quality Manager
Test Report S/N: 0Y1504200766.ZNF	Test Dates: 4/20 - 5/4/2015	EUT Type: Portable Handset			Page 61 of 109



Plot 6-95. Lower Band Edge Plot (Band 4 – 1.4MHz QPSK – RB Size 6)




Plot 6-96. Lower Extended Band Edge Plot (Band 4 – 1.4MHz QPSK – RB Size 6)

FCC ID: ZNFH634		FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1504200766.ZNF	Test Dates: 4/20 - 5/4/2015	EUT Type: Portable Handset		Page 62 of 109




Plot 6-97. Upper Band Edge Plot (Band 4 – 1.4MHz QPSK – RB Size 6)




Plot 6-98. Upper Extended Band Edge Plot (Band 4 – 1.4MHz QPSK – RB Size 6)

FCC ID: ZNFH634		FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)			Reviewed by: Quality Manager
Test Report S/N: 0Y1504200766.ZNF	Test Dates: 4/20 - 5/4/2015	EUT Type: Portable Handset			Page 63 of 109



Plot 6-99. Lower Band Edge Plot (Band 4 – 3.0MHz QPSK – RB Size 15)




Plot 6-100. Lower Extended Band Edge Plot (Band 4 – 3.0MHz QPSK – RB Size 15)

FCC ID: ZNFH634		FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)			Reviewed by: Quality Manager
Test Report S/N: 0Y1504200766.ZNF	Test Dates: 4/20 - 5/4/2015	EUT Type: Portable Handset			Page 64 of 109




Plot 6-101. Upper Band Edge Plot (Band 4 – 3.0MHz QPSK – RB Size 15)




Plot 6-102. Upper Extended Band Edge Plot (Band 4 – 3.0MHz QPSK – RB Size 15)

FCC ID: ZNFH634	 PCTEST[®] ENGINEERING LABORATORY, INC.	FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		 LG	Reviewed by: Quality Manager
Test Report S/N: 0Y1504200766.ZNF	Test Dates: 4/20 - 5/4/2015	EUT Type: Portable Handset			Page 65 of 109
© 2015 PCTEST Engineering Laboratory, Inc. V 2.5					




Plot 6-103. Lower Band Edge Plot (Band 4 – 5.0MHz QPSK – RB Size 25)




Plot 6-104. Lower Extended Band Edge Plot (Band 4 – 5.0MHz QPSK – RB Size 25)

FCC ID: ZNFH634		FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1504200766.ZNF	Test Dates: 4/20 - 5/4/2015	EUT Type: Portable Handset		Page 66 of 109
© 2015 PCTEST Engineering Laboratory, Inc.				V 2.5




Plot 6-105. Upper Band Edge Plot (Band 4 – 5.0MHz QPSK – RB Size 25)




Plot 6-106. Upper Extended Band Edge Plot (Band 4 – 5.0MHz QPSK – RB Size 25)

FCC ID: ZNFH634		FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1504200766.ZNF	Test Dates: 4/20 - 5/4/2015	EUT Type: Portable Handset		Page 67 of 109




Plot 6-107. Lower Band Edge Plot (Band 4 – 10.0MHz QPSK – RB Size 50)



Plot 6-108. Upper Band Edge Plot (Band 4 – 10.0MHz QPSK – RB Size 50)

FCC ID: ZNFH634		FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1504200766.ZNF	Test Dates: 4/20 - 5/4/2015	EUT Type: Portable Handset		Page 68 of 109




Plot 6-109. Lower Band Edge Plot (Band 4 – 15.0MHz QPSK – RB Size 75)



Plot 6-110. Upper Band Edge Plot (Band 4 – 15.0MHz QPSK – RB Size 75)

FCC ID: ZNFH634		FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)			Reviewed by: Quality Manager
Test Report S/N: 0Y1504200766.ZNF	Test Dates: 4/20 - 5/4/2015	EUT Type: Portable Handset			Page 69 of 109




Plot 6-111. Lower Band Edge Plot (Band 4 – 20.0MHz QPSK – RB Size 100)



Plot 6-112. Upper Band Edge Plot (Band 4 – 20.0MHz QPSK – RB Size 100)

FCC ID: ZNFH634		FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1504200766.ZNF	Test Dates: 4/20 - 5/4/2015	EUT Type: Portable Handset		Page 70 of 109



Plot 6-113. Lower Band Edge Plot (Band 2 – 1.4MHz QPSK – RB Size 6)



Plot 6-114. Lower Extended Band Edge Plot (Band 2 – 1.4MHz QPSK – RB Size 6)

FCC ID: ZNFH634		FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)			Reviewed by: Quality Manager
Test Report S/N: 0Y1504200766.ZNF	Test Dates: 4/20 - 5/4/2015	EUT Type: Portable Handset			Page 71 of 109




Plot 6-115. Upper Band Edge Plot (Band 2 – 1.4MHz QPSK – RB Size 6)



Plot 6-116. Upper Extended Band Edge Plot (Band 2 – 1.4MHz QPSK – RB Size 6)

FCC ID: ZNFH634		FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)			Reviewed by: Quality Manager
Test Report S/N: 0Y1504200766.ZNF	Test Dates: 4/20 - 5/4/2015	EUT Type: Portable Handset			Page 72 of 109



Plot 6-117. Lower Band Edge Plot (Band 2 – 3.0MHz QPSK – RB Size 15)




Plot 6-118. Lower Extended Band Edge Plot (Band 2 – 3.0MHz QPSK – RB Size 15)

FCC ID: ZNFH634		FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1504200766.ZNF	Test Dates: 4/20 - 5/4/2015	EUT Type: Portable Handset		Page 73 of 109




Plot 6-119. Upper Band Edge Plot (Band 2 – 3.0MHz QPSK – RB Size 15)




Plot 6-120. Upper Extended Band Edge Plot (Band 2 – 3.0MHz QPSK – RB Size 15)

FCC ID: ZNFH634		FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1504200766.ZNF	Test Dates: 4/20 - 5/4/2015	EUT Type: Portable Handset		Page 74 of 109



Plot 6-121. Lower Band Edge Plot (Band 2 – 5.0MHz QPSK – RB Size 25)




Plot 6-122. Lower Extended Band Edge Plot (Band 2 – 5.0MHz QPSK – RB Size 25)

FCC ID: ZNFH634		FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1504200766.ZNF	Test Dates: 4/20 - 5/4/2015	EUT Type: Portable Handset		Page 75 of 109




Plot 6-123. Upper Band Edge Plot (Band 2 – 5.0MHz QPSK – RB Size 25)



Plot 6-124. Upper Extended Band Edge Plot (Band 2 – 5.0MHz QPSK – RB Size 25)

FCC ID: ZNFH634		FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)			Reviewed by: Quality Manager
Test Report S/N: 0Y1504200766.ZNF	Test Dates: 4/20 - 5/4/2015	EUT Type: Portable Handset			Page 76 of 109




Plot 6-125. Lower Band Edge Plot (Band 2 – 10.0MHz QPSK – RB Size 50)




Plot 6-126. Upper Band Edge Plot (Band 2 – 10.0MHz QPSK – RB Size 50)

FCC ID: ZNFH634		FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1504200766.ZNF	Test Dates: 4/20 - 5/4/2015	EUT Type: Portable Handset		Page 77 of 109




Plot 6-127. Lower Band Edge Plot (Band 2 – 15.0MHz QPSK – RB Size 75)




Plot 6-128. Upper Band Edge Plot (Band 2 – 15.0MHz QPSK – RB Size 75)

FCC ID: ZNFH634		FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1504200766.ZNF	Test Dates: 4/20 - 5/4/2015	EUT Type: Portable Handset		Page 78 of 109



Plot 6-129. Lower Band Edge Plot (Band 2 – 20.0MHz QPSK – RB Size 100)



Plot 6-130. Upper Band Edge Plot (Band 2 – 20.0MHz QPSK – RB Size 100)

FCC ID: ZNFH634		FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)			Reviewed by: Quality Manager
Test Report S/N: 0Y1504200766.ZNF	Test Dates: 4/20 - 5/4/2015	EUT Type: Portable Handset			Page 79 of 109

6.5 Peak-Average Ratio

§24.232(d)

Test Overview

A peak to average ratio measurement is performed at the conducted port of the EUT. The spectrum analyzers Complementary Cumulative Distribution Function (CCDF) measurement profile is used to determine the largest deviation between the average and the peak power of the EUT in a given bandwidth. The CCDF curve shows how much time the peak waveform spends at or above a given average power level. The percent of time the signal spends at or above the level defines the probability for that particular power level.

Test Procedure Used

KDB 971168 v02r02 – Section 5.7.1

Test Settings

1. The signal analyzer's CCDF measurement profile is enabled
2. Frequency = carrier center frequency
3. Measurement BW > Emission bandwidth of signal
4. The signal analyzer was set to collect one million samples to generate the CCDF curve
5. The measurement interval was set depending on the type of signal analyzed. For continuous signals (>98% duty cycle), the measurement interval was set to 1ms.

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.





Figure 6-4. Test Instrument & Measurement Setup


Test Notes

None.

FCC ID: ZNFH634		FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1504200766.ZNF	Test Dates: 4/20 - 5/4/2015	EUT Type: Portable Handset		Page 80 of 109




Plot 6-131. PAR Plot (Band 2 – 1.4MHz QPSK – RB Size 6)




Plot 6-132. PAR Plot (Band 2 – 1.4MHz 16-QAM – RB Size 6)

FCC ID: ZNFH634		FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1504200766.ZNF	Test Dates: 4/20 - 5/4/2015	EUT Type: Portable Handset		Page 81 of 109




Plot 6-133. PAR Plot (Band 2 – 3.0MHz QPSK – RB Size 15)




Plot 6-134. PAR Plot (Band 2 – 3.0MHz 16-QAM – RB Size 15)

FCC ID: ZNFH634		FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1504200766.ZNF	Test Dates: 4/20 - 5/4/2015	EUT Type: Portable Handset		Page 82 of 109




Plot 6-135. PAR Plot (Band 2 – 5.0MHz QPSK – RB Size 25)




Plot 6-136. PAR Plot (Band 2 – 5.0MHz 16-QAM – RB Size 25)

FCC ID: ZNFH634		FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1504200766.ZNF	Test Dates: 4/20 - 5/4/2015	EUT Type: Portable Handset		Page 83 of 109




Plot 6-137. PAR Plot (Band 2 – 10.0MHz QPSK – RB Size 50)




Plot 6-138. PAR Plot (Band 2 – 10.0MHz 16-QAM – RB Size 50)

FCC ID: ZNFH634		FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1504200766.ZNF	Test Dates: 4/20 - 5/4/2015	EUT Type: Portable Handset		Page 84 of 109




Plot 6-139. PAR Plot (Band 2 – 15.0MHz QPSK – RB Size 75)




Plot 6-140. PAR Plot (Band 2 – 15.0MHz 16-QAM – RB Size 75)

FCC ID: ZNFH634		FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1504200766.ZNF	Test Dates: 4/20 - 5/4/2015	EUT Type: Portable Handset		Page 85 of 109



Plot 6-141. PAR Plot (Band 2 – 20.0MHz QPSK – RB Size 100)



Plot 6-142. PAR Plot (Band 2 – 20.0MHz 16-QAM – RB Size 100)

FCC ID: ZNFH634		FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1504200766.ZNF	Test Dates: 4/20 - 5/4/2015	EUT Type: Portable Handset		Page 86 of 109

6.6 Radiated Power (ERP/EIRP)

§22.913(a.2) §24.232(c.2) §27.50(c.10) §27.50(d.4)

Test Overview

Effective Radiated Power (ERP) and Equivalent Isotropic Radiated Power (EIRP) measurements are performed using the substitution method described in ANSI/TIA-603-C-2004 with the EUT transmitting into an integral antenna. Measurements on signals operating below 1GHz are performed using vertically polarized tuned dipole antennas. Measurements on signals operating above 1GHz are performed using vertically polarized broadband horn antennas. All measurements are performed as RMS average measurements while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies.

Test Procedures Used

KDB 971168 v02r02 – Section 5.2.1

ANSI/TIA-603-C-2004 – Section 2.2.17

Test Settings

1. Radiated power measurements are performed using the signal analyzer's "channel power" measurement capability for signals with continuous operation.
2. RBW = 1 – 5% of the expected OBW, not to exceed 1MHz
3. VBW \geq 3 x RBW
4. Span = 1.5 times the OBW
5. No. of sweep points \geq 2 x span / RBW
6. Detector = RMS
7. Trigger is set to "free run" for signals with continuous operation with the sweep times set to "auto".
8. The integration bandwidth was roughly set equal to the measured OBW of the signal for signals with continuous operation.
9. Trace mode = trace averaging (RMS) over 100 sweeps
10. The trace was allowed to stabilize

FCC ID: ZNFH634		FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1504200766.ZNF	Test Dates: 4/20 - 5/4/2015	EUT Type: Portable Handset		Page 87 of 109

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




Figure 6-5. Test Instrument & Measurement Setup

Test Notes

- 1) The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The worst case emissions are reported with the EUT positioning, modulations, RB sizes and offsets, and channel bandwidth configurations shown in the tables below.
- 2) This unit was tested with its standard battery.

Frequency [MHz]	Channel Bandwidth [MHz]	Mod.	Battery	RB Size/Offset	Substitute Level [dBm]	Ant. Gain [dBi]	Ant. Pol. [H/V]	ERP [dBm]	ERP Limit [dBm]	Margin [dB]
706.50	5	QPSK	Standard	1 / 0	16.32	1.05	V	17.37	34.77	-17.40
710.00	5	QPSK	Standard	1 / 0	16.73	1.12	V	17.85	34.77	-16.92
713.50	5	QPSK	Standard	1 / 0	16.18	1.19	V	17.37	34.77	-17.40
706.50	5	16-QAM	Standard	1 / 0	15.48	1.05	V	16.53	34.77	-18.24
710.00	5	16-QAM	Standard	1 / 0	15.86	1.12	V	16.98	34.77	-17.79
713.50	5	16-QAM	Standard	1 / 0	15.15	1.19	V	16.34	34.77	-18.43
709.00	10	QPSK	Standard	1 / 0	15.82	1.10	V	16.92	34.77	-17.85
710.00	10	QPSK	Standard	1 / 0	15.91	1.12	V	17.03	34.77	-17.74
711.00	10	QPSK	Standard	1 / 0	16.02	1.14	V	17.16	34.77	-17.61
709.00	10	16-QAM	Standard	1 / 0	15.21	1.10	V	16.31	34.77	-18.46
710.00	10	16-QAM	Standard	1 / 0	15.16	1.12	V	16.28	34.77	-18.49
711.00	10	16-QAM	Standard	1 / 0	15.17	1.14	V	16.31	34.77	-18.46

Table 6-2. ERP Data (Band 17)

FCC ID: ZNFH634	 PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)					Reviewed by: Quality Manager
Test Report S/N: 0Y1504200766.ZNF	Test Dates: 4/20 - 5/4/2015	EUT Type: Portable Handset					Page 88 of 109

Frequency [MHz]	Channel Bandwidth [MHz]	Mod.	Battery	RB Size/Offset	Substitute Level [dBm]	Ant. Gain [dBd]	Ant. Pol. [H/V]	ERP [dBm]	ERP Limit [dBm]	Margin [dB]
824.70	1.4	QPSK	Standard	1 / 0	17.73	2.98	V	20.71	38.45	-17.74
836.50	1.4	QPSK	Standard	1 / 0	18.26	3.04	V	21.30	38.45	-17.15
848.30	1.4	QPSK	Standard	1 / 0	16.01	3.10	V	19.11	38.45	-19.34
824.70	1.4	16-QAM	Standard	1 / 0	16.57	2.98	V	19.55	38.45	-18.90
836.50	1.4	16-QAM	Standard	1 / 0	17.59	3.04	V	20.63	38.45	-17.82
848.30	1.4	16-QAM	Standard	1 / 0	15.26	3.10	V	18.36	38.45	-20.09
825.50	3	QPSK	Standard	1 / 0	17.30	2.98	V	20.28	38.45	-18.17
836.50	3	QPSK	Standard	1 / 0	17.97	3.04	V	21.01	38.45	-17.44
847.50	3	QPSK	Standard	1 / 0	17.38	3.10	V	20.48	38.45	-17.97
825.50	3	16-QAM	Standard	1 / 0	17.21	2.98	V	20.19	38.45	-18.26
836.50	3	16-QAM	Standard	1 / 0	16.82	3.04	V	19.86	38.45	-18.59
847.50	3	16-QAM	Standard	1 / 0	16.42	3.10	V	19.52	38.45	-18.93
826.50	5	QPSK	Standard	1 / 0	16.95	2.99	V	19.94	38.45	-18.51
836.50	5	QPSK	Standard	1 / 0	16.94	3.04	V	19.98	38.45	-18.47
846.50	5	QPSK	Standard	1 / 0	15.45	3.09	V	18.54	38.45	-19.91
826.50	5	16-QAM	Standard	1 / 0	16.45	2.99	V	19.44	38.45	-19.01
836.50	5	16-QAM	Standard	1 / 0	15.89	3.04	V	18.93	38.45	-19.52
846.50	5	16-QAM	Standard	1 / 0	14.39	3.09	V	17.48	38.45	-20.97
829.00	10	QPSK	Standard	1 / 0	17.12	3.00	V	20.12	38.45	-18.33
836.50	10	QPSK	Standard	1 / 0	17.34	3.04	V	20.38	38.45	-18.07
844.00	10	QPSK	Standard	1 / 0	16.55	3.08	V	19.63	38.45	-18.82
829.00	10	16-QAM	Standard	1 / 0	16.47	3.00	V	19.47	38.45	-18.98
836.50	10	16-QAM	Standard	1 / 0	16.48	3.04	V	19.52	38.45	-18.93
844.00	10	16-QAM	Standard	1 / 0	15.68	3.08	V	18.76	38.45	-19.69

Table 6-3. ERP Data (Band 5)

FCC ID: ZNFH634		FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)						Reviewed by: Quality Manager
Test Report S/N: 0Y1504200766.ZNF	Test Dates: 4/20 - 5/4/2015	EUT Type: Portable Handset					Page 89 of 109	

Frequency [MHz]	Channel Bandwidth [MHz]	Mod.	Battery	RB Size/Offset	Substitute Level [dBm]	Ant. Gain [dBi]	Ant. Pol. [H/V]	EIRP [dBm]	EIRP Limit [dBm]	Margin [dB]
1710.70	1.4	QPSK	Standard	3 / 2	10.07	9.28	V	19.35	30.00	-10.65
1732.50	1.4	QPSK	Standard	3 / 2	11.02	9.00	V	20.02	30.00	-9.98
1754.30	1.4	QPSK	Standard	3 / 2	9.10	8.72	V	17.82	30.00	-12.18
1710.70	1.4	16-QAM	Standard	3 / 2	8.97	9.28	V	18.25	30.00	-11.75
1732.50	1.4	16-QAM	Standard	3 / 2	10.47	9.00	V	19.47	30.00	-10.53
1754.30	1.4	16-QAM	Standard	3 / 2	8.30	8.72	V	17.02	30.00	-12.98
1711.50	3	QPSK	Standard	1 / 14	8.06	9.27	V	17.33	30.00	-12.67
1732.50	3	QPSK	Standard	1 / 14	10.45	9.00	V	19.45	30.00	-10.55
1753.50	3	QPSK	Standard	1 / 14	8.61	8.73	V	17.34	30.00	-12.66
1711.50	3	16-QAM	Standard	1 / 14	7.25	9.27	V	16.52	30.00	-13.48
1732.50	3	16-QAM	Standard	1 / 14	9.28	9.00	V	18.28	30.00	-11.72
1753.50	3	16-QAM	Standard	1 / 14	10.82	8.73	V	19.55	30.00	-10.45
1712.50	5	QPSK	Standard	1 / 24	9.39	9.26	V	18.65	30.00	-11.35
1732.50	5	QPSK	Standard	1 / 24	11.08	9.00	V	20.08	30.00	-9.92
1752.50	5	QPSK	Standard	1 / 24	9.05	8.74	V	17.79	30.00	-12.21
1712.50	5	16-QAM	Standard	1 / 24	8.55	9.26	V	17.81	30.00	-12.19
1732.50	5	16-QAM	Standard	1 / 24	9.96	9.00	V	18.96	30.00	-11.04
1752.50	5	16-QAM	Standard	1 / 24	8.32	8.74	V	17.06	30.00	-12.94
1715.00	10	QPSK	Standard	1 / 0	9.16	9.22	V	18.38	30.00	-11.62
1732.50	10	QPSK	Standard	1 / 0	10.30	9.00	V	19.30	30.00	-10.70
1750.00	10	QPSK	Standard	1 / 0	9.69	8.77	V	18.46	30.00	-11.54
1715.00	10	16-QAM	Standard	1 / 0	7.98	9.22	V	17.20	30.00	-12.80
1732.50	10	16-QAM	Standard	1 / 0	9.43	9.00	V	18.43	30.00	-11.57
1750.00	10	16-QAM	Standard	1 / 0	8.65	8.77	V	17.42	30.00	-12.58
1717.50	15	QPSK	Standard	1 / 74	9.55	9.19	V	18.74	30.00	-11.26
1732.50	15	QPSK	Standard	1 / 74	9.73	9.00	V	18.73	30.00	-11.27
1747.50	15	QPSK	Standard	1 / 74	8.57	8.80	V	17.37	30.00	-12.63
1717.50	15	16-QAM	Standard	1 / 74	8.59	9.19	V	17.78	30.00	-12.22
1732.50	15	16-QAM	Standard	1 / 74	8.75	9.00	V	17.75	30.00	-12.25
1747.50	15	16-QAM	Standard	1 / 74	7.74	8.80	V	16.54	30.00	-13.46
1720.00	20	QPSK	Standard	1 / 0	9.24	9.16	V	18.40	30.00	-11.60
1732.50	20	QPSK	Standard	1 / 0	10.91	9.00	V	19.91	30.00	-10.09
1745.00	20	QPSK	Standard	1 / 0	10.98	8.83	V	19.81	30.00	-10.19
1720.00	20	16-QAM	Standard	1 / 0	8.39	9.16	V	17.55	30.00	-12.45
1732.50	20	16-QAM	Standard	1 / 0	9.73	9.00	V	18.73	30.00	-11.27
1745.00	20	16-QAM	Standard	1 / 0	10.23	8.83	V	19.06	30.00	-10.94

Table 6-4. EIRP Data (Band 4)

FCC ID: ZNFH634	FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)							Reviewed by: 
Test Report S/N: 0Y1504200766.ZNF	Test Dates: 4/20 - 5/4/2015	EUT Type: Portable Handset						Page 90 of 109
© 2015 PCTEST Engineering Laboratory, Inc.					V 2.5	03/20/2015		

Frequency [MHz]	Channel Bandwidth [MHz]	Mod.	Battery	RB Size/Offset	Substitute Level [dBm]	Ant. Gain [dBi]	Ant. Pol. [H/V]	EIRP [dBm]	EIRP Limit [dBm]	Margin [dB]
1850.70	1.4	QPSK	Standard	1 / 0	12.51	8.34	V	20.85	33.01	-12.16
1880.00	1.4	QPSK	Standard	1 / 0	13.90	8.46	V	22.36	33.01	-10.65
1909.30	1.4	QPSK	Standard	1 / 0	13.57	8.64	V	22.21	33.01	-10.80
1850.70	1.4	16-QAM	Standard	1 / 0	11.81	8.34	V	20.15	33.01	-12.86
1880.00	1.4	16-QAM	Standard	1 / 0	13.04	8.46	V	21.50	33.01	-11.51
1909.30	1.4	16-QAM	Standard	1 / 0	12.60	8.64	V	21.24	33.01	-11.77
1851.50	3	QPSK	Standard	1 / 0	14.46	8.35	V	22.81	33.01	-10.20
1880.00	3	QPSK	Standard	1 / 0	14.49	8.46	V	22.95	33.01	-10.06
1908.50	3	QPSK	Standard	1 / 0	14.54	8.63	V	23.17	33.01	-9.84
1851.50	3	16-QAM	Standard	1 / 0	13.56	8.35	V	21.91	33.01	-11.10
1880.00	3	16-QAM	Standard	1 / 0	13.77	8.46	V	22.23	33.01	-10.78
1908.50	3	16-QAM	Standard	1 / 0	13.62	8.63	V	22.25	33.01	-10.76
1852.50	5	QPSK	Standard	1 / 0	15.37	8.35	V	23.72	33.01	-9.29
1880.00	5	QPSK	Standard	1 / 0	14.74	8.46	V	23.20	33.01	-9.81
1907.50	5	QPSK	Standard	1 / 0	14.43	8.62	V	23.05	33.01	-9.96
1852.50	5	16-QAM	Standard	1 / 0	14.48	8.35	V	22.83	33.01	-10.18
1880.00	5	16-QAM	Standard	1 / 0	13.98	8.46	V	22.44	33.01	-10.57
1907.50	5	16-QAM	Standard	1 / 0	13.42	8.62	V	22.04	33.01	-10.97
1855.00	10	QPSK	Standard	1 / 0	12.87	8.36	V	21.23	33.01	-11.78
1880.00	10	QPSK	Standard	1 / 0	14.75	8.46	V	23.21	33.01	-9.80
1905.00	10	QPSK	Standard	1 / 0	13.80	8.59	V	22.39	33.01	-10.62
1855.00	10	16-QAM	Standard	1 / 0	11.92	8.36	V	20.28	33.01	-12.73
1880.00	10	16-QAM	Standard	1 / 0	13.82	8.46	V	22.28	33.01	-10.73
1905.00	10	16-QAM	Standard	1 / 0	12.54	8.59	V	21.13	33.01	-11.88
1857.50	15	QPSK	Standard	1 / 74	13.62	8.37	V	21.99	33.01	-11.02
1880.00	15	QPSK	Standard	1 / 74	14.11	8.46	V	22.57	33.01	-10.44
1902.50	15	QPSK	Standard	1 / 74	13.90	8.56	V	22.46	33.01	-10.55
1857.50	15	16-QAM	Standard	1 / 74	12.43	8.37	V	20.80	33.01	-12.21
1880.00	15	16-QAM	Standard	1 / 74	13.26	8.46	V	21.72	33.01	-11.29
1902.50	15	16-QAM	Standard	1 / 74	13.14	8.56	V	21.70	33.01	-11.31
1860.00	20	QPSK	Standard	1 / 99	15.73	8.38	V	24.11	33.01	-8.90
1880.00	20	QPSK	Standard	1 / 99	14.17	8.46	V	22.63	33.01	-10.38
1900.00	20	QPSK	Standard	1 / 99	14.73	8.53	V	23.26	33.01	-9.75
1860.00	20	16-QAM	Standard	1 / 99	14.53	8.38	V	22.91	33.01	-10.10
1880.00	20	16-QAM	Standard	1 / 99	13.67	8.46	V	22.13	33.01	-10.88
1900.00	20	16-QAM	Standard	1 / 99	14.05	8.53	V	22.58	33.01	-10.43

Table 6-5. EIRP Data (Band 2)

FCC ID: ZNFH634	 PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)								Reviewed by: Quality Manager
Test Report S/N: 0Y1504200766.ZNF	Test Dates: 4/20 - 5/4/2015	EUT Type: Portable Handset								Page 91 of 109

6.7 Radiated Spurious Emissions Measurements

§2.1053 §22.917(a) §24.238(a) §27.53(g) §27.53(h)

Test Overview

Radiated spurious emissions measurements are performed using the substitution method described in ANSI/TIA-603-C-2004 with the EUT transmitting into an integral antenna. Measurements on signals operating below 1GHz are performed using vertically and horizontally polarized tuned dipole antennas. Measurements on signals operating above 1GHz are performed using vertically and horizontally polarized broadband horn antennas. All measurements are performed as peak measurements while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies.

Test Procedures Used

KDB 971168 v02r02 – Section 5.8

ANSI/TIA-603-C-2004 – Section 2.2.12

Test Settings

1. RBW = 100kHz for emissions below 1GHz and 1MHz for emissions above 1GHz
2. VBW $\geq 3 \times$ RBW
3. Span = 1.5 times the OBW
4. No. of sweep points $\geq 2 \times$ span / RBW
5. Detector = Peak
6. Trace mode = max hold
7. The trace was allowed to stabilize

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




Figure 6-6. Test Instrument & Measurement Setup

FCC ID: ZNFH634		FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1504200766.ZNF	Test Dates: 4/20 - 5/4/2015	EUT Type: Portable Handset		Page 92 of 109

Test Notes

- 1) The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The worst case emissions are reported with the EUT positioning, modulations, RB sizes and offsets, and channel bandwidth configurations shown in the tables below.
- 2) This unit was tested with its standard battery.
- 3) The spectrum is measured from 9kHz to the 10th harmonic of the fundamental frequency of the transmitter. The worst-case emissions are reported.
- 4) Emissions below 18GHz were measured at a 3 meter test distance while emissions above 18GHz were measured at a 1 meter test distance with the application of a distance correction factor.

OPERATING FREQUENCY:	706.50	MHz
CHANNEL:	23755	
MEASURED OUTPUT POWER:	17.37	dBm = 0.055 W
MODULATION SIGNAL:	QPSK	
BANDWIDTH:	5.0 MHz	
DISTANCE:	3 meters	
LIMIT:	43 + 10 log ₁₀ (W) = 30.37 dBc	

Frequency [MHz]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBd]	Spurious Emission Level [dBm]	Ant. Pol. [H/V]	[dBc]
1413.00	-50.72	2.56	-48.15	H	65.5
2119.50	-52.25	3.01	-49.24	H	66.6
2826.00	-55.62	4.74	-50.88	H	68.2

Table 6-6. Radiated Spurious Data (Band 17 – Low Channel)

FCC ID: ZNFH634		FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1504200766.ZNF	Test Dates: 4/20 - 5/4/2015	EUT Type: Portable Handset		Page 93 of 109

OPERATING FREQUENCY: 710.00 MHz
 CHANNEL: 23790
 MEASURED OUTPUT POWER: 17.85 dBm = 0.061 W
 MODULATION SIGNAL: QPSK
 BANDWIDTH: 5.0 MHz
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10} (W) =$ 30.85 dBc

Frequency [MHz]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBD]	Spurious Emission Level [dBm]	Ant. Pol. [H/V]	[dBc]
1420.00	-47.09	2.64	-44.45	H	62.3
2130.00	-51.90	3.04	-48.86	H	66.7
2840.00	-56.25	4.73	-51.52	H	69.4

Table 6-7. Radiated Spurious Data (Band 17 – Mid Channel)

OPERATING FREQUENCY: 713.50 MHz
 CHANNEL: 23825
 MEASURED OUTPUT POWER: 17.37 dBm = 0.055 W
 MODULATION SIGNAL: QPSK
 BANDWIDTH: 5.0 MHz
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10} (W) =$ 30.37 dBc

Frequency [MHz]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBD]	Spurious Emission Level [dBm]	Ant. Pol. [H/V]	[dBc]
1427.00	-46.76	2.72	-44.04	H	61.4
2140.50	-51.99	3.07	-48.92	H	66.3
2854.00	-56.21	4.73	-51.48	H	68.9

Table 6-8. Radiated Spurious Data (Band 17 – High Channel)

FCC ID: ZNFH634		FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)			Reviewed by: Quality Manager
Test Report S/N: 0Y1504200766.ZNF	Test Dates: 4/20 - 5/4/2015	EUT Type: Portable Handset		Page 94 of 109	

OPERATING FREQUENCY: 824.70 MHz
 CHANNEL: 20407
 MEASURED OUTPUT POWER: 20.71 dBm = 0.118 W
 MODULATION SIGNAL: QPSK
 BANDWIDTH: 1.4 MHz
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10} (W) =$ 33.71 dBc

Frequency [MHz]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBd]	Spurious Emission Level [dBm]	Ant. Pol. [H/V]	[dBc]
1649.40	-34.14	3.61	-30.53	H	51.2
2474.10	-54.42	3.57	-50.84	H	71.6

Table 6-9. Radiated Spurious Data (Band 5 – Low Channel)

OPERATING FREQUENCY: 836.50 MHz
 CHANNEL: 20525
 MEASURED OUTPUT POWER: 21.30 dBm = 0.135 W
 MODULATION SIGNAL: QPSK
 BANDWIDTH: 1.4 MHz
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10} (W) =$ 34.30 dBc

Frequency [MHz]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBd]	Spurious Emission Level [dBm]	Ant. Pol. [H/V]	[dBc]
1673.00	-29.24	3.53	-25.71	H	47.0
2509.50	-55.73	3.57	-52.16	H	73.5

Table 6-10. Radiated Spurious Data (Band 5 – Mid Channel)

FCC ID: ZNFH634		FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)			Reviewed by: Quality Manager
Test Report S/N: 0Y1504200766.ZNF	Test Dates: 4/20 - 5/4/2015	EUT Type: Portable Handset		Page 95 of 109	

OPERATING FREQUENCY: 848.30 MHz
 CHANNEL: 20643
 MEASURED OUTPUT POWER: 19.11 dBm = 0.082 W
 MODULATION SIGNAL: QPSK
 BANDWIDTH: 1.4 MHz
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10} (W) =$ 32.11 dBc

Frequency [MHz]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBd]	Spurious Emission Level [dBm]	Ant. Pol. [H/V]	[dBc]
1696.60	-33.25	3.44	-29.81	H	48.9
2544.90	-55.15	3.64	-51.51	H	70.6

Table 6-11. Radiated Spurious Data (Band 5 – High Channel)

OPERATING FREQUENCY: 1712.50 MHz
 CHANNEL: 19975
 MEASURED OUTPUT POWER: 18.65 dBm = 0.073 W
 MODULATION SIGNAL: QPSK
 BANDWIDTH: 5.0 MHz
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10} (W) =$ 31.65 dBc

Frequency [MHz]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Ant. Pol. [H/V]	[dBc]
3425.00	-49.37	8.15	-41.22	H	59.9
5137.50	-46.72	10.26	-36.45	H	55.1
6850.00	-45.98	11.39	-34.59	H	53.2
8562.50	-49.29	13.02	-36.27	H	54.9
10275.00	-51.39	13.27	-38.12	H	56.8
11987.50	-51.19	13.14	-38.05	H	56.7

Table 6-12. Radiated Spurious Data (Band 4 – Low Channel)

FCC ID: ZNFH634		FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)			Reviewed by: Quality Manager
Test Report S/N: 0Y1504200766.ZNF	Test Dates: 4/20 - 5/4/2015	EUT Type: Portable Handset			Page 96 of 109



OPERATING FREQUENCY: 1732.50 MHz
CHANNEL: 20175
MEASURED OUTPUT POWER: 20.08 dBm = 0.102 W
MODULATION SIGNAL: QPSK
BANDWIDTH: 5.0 MHz
DISTANCE: 3 meters
LIMIT: $43 + 10 \log_{10} (W) = 33.08$ dBc

Frequency [MHz]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Ant. Pol. [H/V]	[dBc]
3465.00	-52.48	8.29	-44.19	H	64.3
5197.50	-49.34	10.35	-39.00	H	59.1
6930.00	-44.59	11.49	-33.10	H	53.2
8662.50	-49.96	13.02	-36.94	H	57.0
10395.00	-49.49	13.16	-36.33	H	56.4
12127.50	-51.16	13.10	-38.06	H	58.1

Table 6-13. Radiated Spurious Data (Band 4 – Mid Channel)

OPERATING FREQUENCY: 1752.50 MHz
CHANNEL: 20375
MEASURED OUTPUT POWER: 17.79 dBm = 0.060 W
MODULATION SIGNAL: QPSK
BANDWIDTH: 5.0 MHz
DISTANCE: 3 meters
LIMIT: $43 + 10 \log_{10} (W) = 30.79$ dBc

Frequency [MHz]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Ant. Pol. [H/V]	[dBc]
3505.00	-49.04	8.40	-40.64	H	58.4
5257.50	-49.62	10.36	-39.26	H	57.1
7010.00	-42.87	11.56	-31.30	H	49.1
8762.50	-44.18	13.02	-31.16	H	48.9
10515.00	-46.38	13.01	-33.37	H	51.2
12267.50	-50.91	13.16	-37.75	H	55.5

Table 6-14. Radiated Spurious Data (Band 4 – High Channel)

FCC ID: ZNFH634		FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)			Reviewed by: Quality Manager
Test Report S/N: 0Y1504200766.ZNF	Test Dates: 4/20 - 5/4/2015	EUT Type: Portable Handset		Page 97 of 109	

OPERATING FREQUENCY: 1860.00 MHz
 CHANNEL: 18700
 MEASURED OUTPUT POWER: 24.11 dBm = 0.258 W
 MODULATION SIGNAL: QPSK
 BANDWIDTH: 20.0 MHz
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10} (W) =$ 37.11 dBc

Frequency [MHz]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Ant. Pol. [H/V]	[dBc]
3720.00	-55.24	8.40	-46.84	H	70.9
5580.00	-54.21	10.59	-43.62	H	67.7
7440.00	-47.80	12.06	-35.75	H	59.9
9300.00	-62.59	13.22	-49.37	H	73.5
11160.00	-58.48	13.26	-45.22	H	69.3
13020.00	-62.82	13.45	-49.36	H	73.5

Table 6-15. Radiated Spurious Data (Band 2 – Low Channel)

OPERATING FREQUENCY: 1880.00 MHz
 CHANNEL: 18900
 MEASURED OUTPUT POWER: 22.63 dBm = 0.183 W
 MODULATION SIGNAL: QPSK
 BANDWIDTH: 20.0 MHz
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10} (W) =$ 35.63 dBc

Frequency [MHz]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Ant. Pol. [H/V]	[dBc]
3760.00	-51.69	8.38	-43.31	H	65.9
5640.00	-50.91	10.70	-40.21	H	62.8
7520.00	-53.34	12.10	-41.24	H	63.9
9400.00	-62.35	13.19	-49.16	H	71.8
11280.00	-63.61	13.31	-50.30	H	72.9

Table 6-16. Radiated Spurious Data (Band 2 – Mid Channel)

FCC ID: ZNFH634		FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)			Reviewed by: Quality Manager
Test Report S/N: 0Y1504200766.ZNF	Test Dates: 4/20 - 5/4/2015	EUT Type: Portable Handset		Page 98 of 109	



OPERATING FREQUENCY: 1900.00 MHz
CHANNEL: 19100
MEASURED OUTPUT POWER: 23.26 dBm = 0.212 W
MODULATION SIGNAL: QPSK
BANDWIDTH: 20.0 MHz
DISTANCE: 3 meters
LIMIT: $43 + 10 \log_{10} (W) =$ 36.26 dBc

Frequency [MHz]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Ant. Pol. [H/V]	[dBc]
3800.00	-49.34	8.39	-40.95	H	64.2
5700.00	-51.54	10.75	-40.79	H	64.1
7600.00	-47.47	12.20	-35.27	H	58.5
9500.00	-57.04	13.19	-43.85	H	67.1
11400.00	-55.23	13.32	-41.91	H	65.2
13300.00	-53.05	13.57	-39.48	H	62.7
15200.00	-63.39	13.93	-49.46	H	72.7

Table 6-17. Radiated Spurious Data (Band 2 – High Channel)

FCC ID: ZNFH634		FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)			Reviewed by: Quality Manager
Test Report S/N: 0Y1504200766.ZNF	Test Dates: 4/20 - 5/4/2015	EUT Type: Portable Handset		Page 99 of 109	

6.8 Frequency Stability / Temperature Variation

§2.1055 §22.355 §24.235 §27.54

Test Overview and Limit

Frequency stability testing is performed in accordance with the guidelines of ANSI/TIA-603-C-2004. The frequency stability of the transmitter is measured by:

- a.) **Temperature:** The temperature is varied from -30°C to +50°C in 10°C increments using an environmental chamber.
- b.) **Primary Supply Voltage:** The primary supply voltage is varied from 85% to 115% of the nominal value for non hand-carried battery and AC powered equipment. For hand-carried, battery-powered equipment, primary supply voltage is reduced to the battery operating end point which shall be specified by the manufacturer.

For Part 22, the frequency stability of the transmitter shall be maintained within $\pm 0.00025\%$ (± 2.5 ppm) of the center frequency. For Part 24 and Part 27, the frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block.

Test Procedure Used

ANSI/TIA-603-C-2004

Test Settings

1. The carrier frequency of the transmitter is measured at room temperature (20°C to provide a reference).
2. The equipment is turned on in a “standby” condition for fifteen minutes before applying power to the transmitter. Measurement of the carrier frequency of the transmitter is made within one minute after applying power to the transmitter.
3. Frequency measurements are made at 10°C intervals ranging from -30°C to +50°C. A period of at least one half-hour is provided to allow stabilization of the equipment at each temperature level.

Test Setup

The EUT was connected via an RF cable to a spectrum analyzer with the EUT placed inside an environmental chamber.

Test Notes

None

FCC ID: ZNFH634		FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1504200766.ZNF	Test Dates: 4/20 - 5/4/2015	EUT Type: Portable Handset		Page 100 of 109

Band 17 Frequency Stability Measurements

\$2.1055 \$27.54

OPERATING FREQUENCY: 710,000,000 Hz

CHANNEL: 23090

REFERENCE VOLTAGE: 3.85 VDC

VOLTAGE (%)	POWER (VDC)	TEMP (°C)	FREQUENCY (Hz)	Freq. Dev. (Hz)	Deviation (%)
100 %	3.85	+ 20 (Ref)	710,000,434	434	0.0000611
100 %		- 30	709,999,562	-438	-0.0000617
100 %		- 20	710,000,439	439	0.0000618
100 %		- 10	710,000,071	71	0.0000100
100 %		0	709,999,535	-465	-0.0000655
100 %		+ 10	710,000,158	158	0.0000223
100 %		+ 20	710,000,305	305	0.0000430
100 %		+ 30	710,000,136	136	0.0000192
100 %		+ 40	710,000,349	349	0.0000492
100 %		+ 50	710,000,318	318	0.0000448
BATT. ENDPOINT	3.45	+ 20	710,000,449	449	0.0000632

Table 6-18. Frequency Stability Data (Band 17)

Note:

Based on the results of the frequency stability test at the center channel the frequency deviation results measured are very small. As such it is determined that the channels at the band edge would remain in-band when the maximum measured frequency deviation noted during the frequency stability tests is applied. Therefore the device is determined to remain operating in band over the temperature and voltage range as tested.

FCC ID: ZNFH634		FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)			Reviewed by: Quality Manager
Test Report S/N: 0Y1504200766.ZNF	Test Dates: 4/20 - 5/4/2015	EUT Type: Portable Handset		Page 101 of 109	

Band 17 Frequency Stability Measurements

[\\$2.1055](#) [\\$27.54](#)




Figure 6-7. Frequency Stability Graph (Band 17)

FCC ID: ZNFH634		FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)			Reviewed by: Quality Manager
Test Report S/N: 0Y1504200766.ZNF	Test Dates: 4/20 - 5/4/2015	EUT Type: Portable Handset			Page 102 of 109

Band 5 Frequency Stability Measurements

§2.1055 \$22.355

OPERATING FREQUENCY: 836,500,000 Hz
 CHANNEL: 20525
 REFERENCE VOLTAGE: 3.85 VDC
 DEVIATION LIMIT: ± 0.00025 % or 2.5 ppm

VOLTAGE (%)	POWER (VDC)	TEMP (°C)	FREQUENCY (Hz)	Freq. Dev. (Hz)	Deviation (%)
100 %	3.85	+ 20 (Ref)	836,499,933	-67	-0.0000080
100 %		- 30	836,500,212	212	0.0000253
100 %		- 20	836,500,012	12	0.0000014
100 %		- 10	836,500,293	293	0.0000350
100 %		0	836,499,554	-446	-0.0000533
100 %		+ 10	836,500,293	293	0.0000350
100 %		+ 20	836,499,769	-231	-0.0000276
100 %		+ 30	836,499,581	-419	-0.0000501
100 %		+ 40	836,499,625	-375	-0.0000448
100 %		+ 50	836,500,023	23	0.0000027
BATT. ENDPOINT	3.45	+ 20	836,500,148	148	0.0000177

Table 6-19. Frequency Stability Data (Band 5)

FCC ID: ZNFH634		FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)			Reviewed by: Quality Manager
Test Report S/N: 0Y1504200766.ZNF	Test Dates: 4/20 - 5/4/2015	EUT Type: Portable Handset		Page 103 of 109	

Band 5 Frequency Stability Measurements

[\\$2.1055](#) [\\$22.355](#)




Figure 6-8. Frequency Stability Graph (Band 5)

FCC ID: ZNFH634		FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)			Reviewed by: Quality Manager
Test Report S/N: 0Y1504200766.ZNF	Test Dates: 4/20 - 5/4/2015	EUT Type: Portable Handset			Page 104 of 109

Band 4 Frequency Stability Measurements

[\\$2.1055](#) [\\$27.54](#)

OPERATING FREQUENCY: 1,732,500,000 Hz
 CHANNEL: 20175
 REFERENCE VOLTAGE: 3.85 VDC

VOLTAGE (%)	POWER (VDC)	TEMP (°C)	FREQUENCY (Hz)	Freq. Dev. (Hz)	Deviation (%)
100 %	3.85	+ 20 (Ref)	1,732,500,317	317	0.0000183
100 %		- 30	1,732,500,371	371	0.0000214
100 %		- 20	1,732,499,988	-12	-0.0000007
100 %		- 10	1,732,500,293	293	0.0000169
100 %		0	1,732,500,437	437	0.0000252
100 %		+ 10	1,732,499,739	-261	-0.0000151
100 %		+ 20	1,732,500,179	179	0.0000103
100 %		+ 30	1,732,499,546	-454	-0.0000262
100 %		+ 40	1,732,499,890	-110	-0.0000063
100 %		+ 50	1,732,499,683	-317	-0.0000183
BATT. ENDPOINT	3.45	+ 20	1,732,500,210	210	0.0000121

Table 6-20. Frequency Stability Data (Band 4)

Note:

Based on the results of the frequency stability test at the center channel the frequency deviation results measured are very small. As such it is determined that the channels at the band edge would remain in-band when the maximum measured frequency deviation noted during the frequency stability tests is applied. Therefore the device is determined to remain operating in band over the temperature and voltage range as tested.

FCC ID: ZNFH634		FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)			Reviewed by: Quality Manager
Test Report S/N: 0Y1504200766.ZNF	Test Dates: 4/20 - 5/4/2015	EUT Type: Portable Handset		Page 105 of 109	

Band 4 Frequency Stability Measurements

[\\$2.1055](#) [\\$27.54](#)




Figure 6-9. Frequency Stability Graph (Band 4)

FCC ID: ZNFH634		FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1504200766.ZNF	Test Dates: 4/20 - 5/4/2015	EUT Type: Portable Handset		Page 106 of 109

Band 2 Frequency Stability Measurements

[\\$2.1055](#) [\\$24.235](#)

OPERATING FREQUENCY: 1,880,000,000 Hz

CHANNEL: 18900

REFERENCE VOLTAGE: 3.85 VDC

VOLTAGE (%)	POWER (VDC)	TEMP (°C)	FREQUENCY (Hz)	Freq. Dev. (Hz)	Deviation (%)
100 %	3.85	+ 20 (Ref)	1,880,000,257	257	0.0000137
100 %		- 30	1,879,999,581	-419	-0.0000223
100 %		- 20	1,879,999,995	-5	-0.0000003
100 %		- 10	1,879,999,805	-195	-0.0000104
100 %		0	1,879,999,851	-149	-0.0000079
100 %		+ 10	1,880,000,244	244	0.0000130
100 %		+ 20	1,879,999,873	-127	-0.0000068
100 %		+ 30	1,879,999,914	-86	-0.0000046
100 %		+ 40	1,879,999,812	-188	-0.0000100
100 %		+ 50	1,879,999,858	-142	-0.0000076
BATT. ENDPOINT	3.45	+ 20	1,879,999,906	-94	-0.0000050

Table 6-21. Frequency Stability Data (Band 2)

Note:

Based on the results of the frequency stability test at the center channel the frequency deviation results measured are very small. As such it is determined that the channels at the band edge would remain in-band when the maximum measured frequency deviation noted during the frequency stability tests is applied. Therefore the device is determined to remain operating in band over the temperature and voltage range as tested.

FCC ID: ZNFH634		FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)			Reviewed by: Quality Manager
Test Report S/N: 0Y1504200766.ZNF	Test Dates: 4/20 - 5/4/2015	EUT Type: Portable Handset		Page 107 of 109	

Band 2 Frequency Stability Measurements

§2.1055 \$24.235




Figure 6-10. Frequency Stability Graph (Band 2)

FCC ID: ZNFH634		FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)			Reviewed by: Quality Manager
Test Report S/N: 0Y1504200766.ZNF	Test Dates: 4/20 - 5/4/2015	EUT Type: Portable Handset			Page 108 of 109

7.0 CONCLUSION

The data collected relate only to the item(s) tested and show that the **LG Portable Handset** **FCC ID: ZNFH634** complies with all the requirements of Parts 22, 24, & 27 of the FCC rules for LTE operation only.

FCC ID: ZNFH634	 PCTEST [®] ENGINEERING LABORATORY, INC.	FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	
Test Report S/N: 0Y1504200766.ZNF	Test Dates: 4/20 - 5/4/2015	EUT Type: Portable Handset	Reviewed by:  LG Quality Manager Page 109 of 109