

File Number: **DRAFT-SAT-LOA-20260106-00007**

Call Sign:

S1. Satellite Information

a. Space Station or Satellite Network Name	b. Orbit Type	c. Estimated Operational Lifetime of Space Station(s) From Date of Launch (yrs)	d. Will the space station(s) operate on a Common Carrier basis?	e. Application Description
MEP-1	Geostationary (GSO)	8	No	Space Logistics, LLC applies for authority to operate the telemetry and commanding systems of the MEP-1 spacecraft.

S2. Operating Frequency Bands

a. Type of Service	b. If a. is Other, provide a service description	c. Satellite Frequency Band (MHz)	d. Satellite Frequency (Lower Band Edge) (MHz)	e. Satellite Frequency (Upper Band Edge) (MHz)	f. Direction of Transmission	g. Non Conforming Indicator
OTHER: Other Satellite Service	TT&C for satellite servicing missions	Other	11450	12200	Space-to-Earth (Transmit)	Yes
OTHER: Other Satellite Service	TT&C for satellite servicing missions	Other	13750	14500	Earth-to-Space (Receive)	Yes

S3. GSO Orbital Information

a. Orbital Longitude (°)	b. Hemisphere of Orbital Longitude (E/W)	c. East/West Station-Keeping Range: Toward East (°)	d. East/West Station-Keeping Range: Toward West (°)	e. North/South Station-Keeping Range: Toward North (°)	f. North/South Station-Keeping Range: Toward South (°)	g. Maximum Orbital Eccentricity	h. Antenna Axis Attitude Accuracy: Roll (°)	i. Antenna Axis Attitude Accuracy: Pitch (°)	j. Antenna Axis Attitude Accuracy: Yaw (°)
141	West	0.05	0.05	0.05	0.05		0.06	0.06	0.1

S4. Earth-to-Space (Receive) Beams

a. Beam ID:	BUKB	n. Beam Peak Flux Density at Command Threshold (dBW/m ²):	
b. Beam Frequency (Lower Band Edge) (MHz):	13750	o. Peak Isotropic Antenna Gain (dBi):	13.3
c. Beam Frequency (Upper Band Edge) (MHz):	14500	p. Isotropic Antenna Gain at 3 dB Beamwidth (dBi):	
d. Polarization:	LHCP	q. Antenna Pointing Error (°):	0.05
e. Can the space station vary the channel bandwidth with on-board processing?:	No	r. Antenna Rotational Error (°):	0.06
f. Is this a command beam? (Check box if Yes):	No	s. Will a GIMS container file containing all antenna contour data be provided?:	
g. Is the beam shapeable? (Check box if Yes):	No	t. Under what rules will the associated antenna contours be submitted?:	
h. Is the beam steerable? (Check box if Yes):	Yes	u. Provide a list of each orbital plane in which this antenna beam is used.:	
i. Is the beam fed into transponders? (Check box if Yes):	No	v. Are all space stations in the NGSO constellation identical?:	
j. Maximum G/T (dB/K):	-14.1	w. What information will be provided with the predicted antenna gain contours?:	
k. Minimum G/T (dB/K):	-14.1		

l. Maximum Saturation Flux Density (dBW/m²):m. Minimum Saturation Flux Density (dBW/m²):**x. Receive Channels**

(i) Channel ID	(ii) Channel Bandwidth (MHz)	(iii) Center Frequency (MHz)	(iv) Channel Frequency (Lower Band Edge) (MHz)	(v) Channel Frequency (Upper Band Edge) (MHz)	(vi) Channel Type	(vii) Point of Communication
CUBK	1	14125	14124.5	14125.5	TT&C	

S5. Space-to-Earth (Transmit) Beams

a. Beam ID:	BDKB	n. Beam Peak Flux Density at Command Threshold (dBW/m ²):	
b. Beam Frequency (Lower Band Edge) (MHz):	11450	o. Peak Isotropic Antenna Gain (dBi):	13.2
c. Beam Frequency (Upper Band Edge) (MHz):	12200	p. Isotropic Antenna Gain at 3 dB Beamwidth (dBi):	
d. Polarization:	RHCP	q. Antenna Pointing Error (°):	0.05
e. Can the space station vary the channel bandwidth with on-board processing?:	No	r. Antenna Rotational Error (°):	0.06
f. Is this a command beam? (Check box if Yes):	No	s. Will a GIMS container file containing all antenna contour data be provided?:	
g. Is the beam shapeable? (Check box if Yes):	No	t. Under what rules will the associated antenna contours be submitted?:	
h. Is the beam steerable? (Check box if Yes):	Yes	u. Provide a list of each orbital plane in which this antenna beam is used.:	
i. Is the beam fed into transponders? (Check box if Yes):	No	v. Are all space stations in the NGSO constellation identical?:	
j. Maximum Transmit EIRP Density (dBW/Ref BW):	-39.6	w. What information will be provided with the predicted antenna gain contours?:	
k. Maximum Transmit EIRP (dBW):	13.4		

x. Transmit Channels

(i) Channel ID	(ii) Channel Bandwidth (MHz)	(iii) Center Frequency (MHz)	(iv) Channel Frequency (Lower Band Edge) (MHz)	(v) Channel Frequency (Upper Band Edge) (MHz)	(vi) Channel Type	(vii) Point of Communication
CHKB	0.2	11850	11849.9	11850.1	TT&C	
CMKB	0.4	11850	11849.8	11850.2	TT&C	
CLKB	0.4	11850	11849.8	11850.2	TT&C	

y. Max. Power-Flux Densities

			Angles of Arrival PFD						Geographic Region PFD				
(i) Beam Sub-Frequency (Lower Band Edge) (MHz)	(ii) Beam Sub-Frequency (Upper Band Edge) (MHz)	(iii) Reference Bandwidth (BW)	(iv) 0-2° (dBW/m ² /BW)	(v) 2-5° (dBW/m ² /BW)	(vi) 5-15° (dBW/m ² /BW)	(vii) 15-20° (dBW/m ² /BW)	(viii) 20-25° (dBW/m ² /BW)	(ix) 25-90° (dBW/m ² /BW)	(x) Southeastern Region (dBW/m ² /BW)	(xi) Northeastern Region (dBW/m ² /BW)	(xii) Western Region (dBW/m ² /BW)	(xiii) Other Region (dBW/m ² /BW)	(xiv) Energy Dispersal Bandwidth (kHz)
11450	12200	4 kHz	-166.9	-166.8	-166.6	-166.5	-166.4	-165.6					

S6. Space-to-Space (Receive) Beams**S7. Space-to-Space (Transmit) Beams****S8. Attachments**