

NOISE BUDGET REFERENCE CALCULATION

Beam	Uplink	Downlink
	SSA	EUR

Carrier parameters

	D1	D2	D3	D4	D5	D6	D7
Data Rate (Mbps)	0.064	0.384	1.544	2.048	9.216	45	69.64
FEC	0.682	0.682	0.875	0.682	0.75	0.75	0.795
Modulation	QPSK	QPSK	QPSK	QPSK	QPSK	QPSK	QPSK
C/(N+I) - Total Required (dB)	7.4	7.4	10.8	7.4	9.9	5.6	8.7

Uplink parameters

[illegible]

(C/I)_{Up-ASI} (dB)	32.2	24.2	20.7	26.7	26.7	32.2	36.0
(C/N)_{Uplink Thermal} (dB)	27.5	19.6	16.1	22.1	22.1	27.5	31.4
C/(N_{thermal}+N_{ASI}+N_{intrasystem}) (dB)	24.7	18.0	14.7	20.3	20.3	24.7	27.0

Downlink parameters

	D1	D2	D3	D4	D5	D6	D7
Downlink Frequency (MHz)	11600	11600	11600	11600	11600	11600	11600
Beam peak EIRP density (dBW/Hz)	-23	-23	-23	-23	-23	-23	-23
Downlink EIRP/Carrier (dBW)	24.48	32.29	37.25	39.55	45.67	52.56	54.22
Edge of coverage EUR (dB)	6.0	6.0	6.0	6.0	6.0	6.0	6.0
Downlink EIRP/Carrier at EOC (dBW)	18.48	26.29	31.25	33.55	39.67	46.56	48.22
Rx E/S Antenna Diameter (Metres)	0.90	1.80	2.40	1.20	2.40	0.90	1.80
Rx Antenna Efficiency	0.65	0.65	0.65	0.65	0.65	0.65	0.65
Rx Antenna Gain (dB)	38.9	44.9	47.4	41.4	47.4	38.9	44.9
Rx System Noise temp (K)	110.0	110.0	110.0	110.0	110.0	110.0	110.0
Rx E/S G/T (dB/K)	18.5	24.5	27.0	21.0	27.0	18.5	24.5
Antenna mispointing error (dB)	0.5	0.5	0.5	0.5	0.5	0.5	0.5
Atmospheric loss (dB)	0.3	0.3	0.3	0.3	0.3	0.3	0.3
Downlink Path loss (dB)	206.1	206.1	206.1	206.1	206.1	206.1	206.1
Downlink Rain Attenuation (dB)	0.0	0.0	0.0	0.0	0.0	0.0	0.0
(C/I)_{Dn Intra-system} (dB)	30.0	30.0	30.0	30.0	30.0	30.0	30.0
(C/I)_{Down-ASI} (dB)	16.9	22.9	25.4	19.4	25.4	16.9	22.9
(C/N)_{Downlink Thermal} (dB)	11.1	17.2	19.7	13.6	19.7	11.2	17.2
C/(N_{thermal}+N_{ASI}+N_{intrasystem}) (dB)	10.1	16.0	18.3	12.5	18.3	10.1	16.0

End-to-End

	D1	D2	D3	D4	D5	D6	D7
(C/N+I) - Total Actual (dB)	9.9	13.9	13.1	11.9	16.2	9.9	15.7
(C/N+I) - Total Required(dB)	7.4	7.4	10.8	7.4	9.9	5.6	8.7
Margin (dB)	2.5	6.5	2.3	4.5	6.3	4.3	7.0