

HISPASAT-LINK BUDGET
DIGITAL SERVICES

REF. LINK
TRANSPONDER N°
SATELLITE

AMAZONAS-3
Clear Sky

Rain
up

Rain
down

GENERAL DATA

Transponder bandwidth(MHz)	54		
carrier type	outbound		
Modulation	8-PSK		
Information rate (Kb/s)	2048	OVERHEAD	15/16
FEC	2/3	Reed Solomon	67/73
bandwidth occupied (KHz)	1428.10		
BER	1.00E-07		
Eb/No (dB)	6.7	Nº portadoras	
Nº of carriers	32.00	32.41	30.40
IBO total (dB)	3.00		
OBO total (dB)	2.321		
C/I intermodulation	18.063		
Occupation factor	1.32		
availability (%)	99.80		
satellite longitude	-61		

UPLINK

E/T Tx Name	new York
E/T Tx (degrees E) Longitude	-74.00
E/T Tx (degrees N) latitude	40.75
E/T Tx (m) Altitude	100.00
Uplink Frequency (GHz)	5.89
EIRP E/T Tx.(dBW)	63.20

E/T Tx example

HPA (W)	43.80	
HPA-antena (dB) loss	0.20	ES off axis psd (dBW/Hz)
Ant. gain (dB)	46.99	-45.33
Ant. Diameter (m)	4.49	

Polarization discrim (dB)	35.00	
Accuracy polarization(°)	0.10	
% unavailability		0.08000
Rain atten.		0.46
Atmosp. Atten. loss (dB)	0.20	
aiming error loss (dB)	0.30	
sky loss (dB)	199.38	
D.F.P. (dBW/m2)	-106.83	-107.29
saturation D.F.P.in the BEAM CENTER (dBW/m2)	-89.00	
Back-off Input (dB)	17.83	18.29
Geogr. advantage (dB)	-7.00	
G/T satellite in the BEAM CENTER (dB/K)	-1.00	
C/N up (dB)	22.37	21.91
C/I cochannel up(dB)	24.89	24.43
C/(N+I) without other interf. satellites up) (dB)	17.35	16.88
psd Interference from satellite 2°(dBW/Hz)	-38.70	
C/I with other interf. Satellites 2° up (dB)	18.88	18.42
c/(N+I) with other interf. Satellites up (dB)	15.03	14.57
Xpolar Interference excess (dB)	3.0	

Clear sky

Rain
up

rain
down

DOWNLINK

E/T Rx Name	MIAMI		
E/T Rx (degrees E) Longitude	-80.18		
E/T Rx (degrees N) Latitude	25.77		
E/T Rx (Km) Altitude	100.00		
Down Frequency (GHz)	3.66		SAT deirp (dBW/Hz)
EIRP satellite in the beam center (dBW)	41.00		-37.70
Back-off output (dB)	17.15	17.61	
Geogr. advantage (dB)	-5.00		
% unavailability			0.12000
Rain Atten.			0.15
Atmosp. Atten. loss (dB)	0.20		
aiming error loss (dB)	0.30		
sky loss (dB)	195.06		
G/T E/T Rx. (dB/K)	24.50		23.80
E/T Rx Example			
Ant. Gain(dB)	43.28		
antenna-receptor loss(dB)	0.20		
Tina (°K)	40.00		
Ta (°K)	20.00		
Tsyst. (°K)	72.15		
Ant. Diameter (m)	4.55		

Polarization discrim.(dB)	35.00		
C/N down (dB)	14.84	14.38	13.99
C/I cochannel down(dB)	25.57	25.57	25.57
C/I channel adjacent (dB)	24.70	24.70	24.70
C/(N+I) without other interf. satellites down) (dB)	12.86	12.45	12.30
deirp Interference from satellite 2°(dBW/Hz)	-34.50		
C/I with other interf. Satellites 2° down (dB)	13.61	13.61	13.46
c/(N+I) with other interf. Satellites up (dB)	10.21	9.98	9.83
Xpolar Interference excess (dB)	2.3		

GLOBAL RESULTS

C/(N+I) without other interf. satellites TOTAL) (dB)	11.54	11.12	11.12
C/(N+I) with other interf. satellites Total (dB)	8.97	8.69	8.69
Excess margin (dB)	0.50	0.50	0.50
Eb/No available (interf nominal)(dB)	6.91	6.62	6.62
Eb/No request (dB)	6.70	6.70	6.70
Margin (nominal)(dB)	0.21	-0.08	-0.08