

HISPASAT-LINK BUDGET
DIGITAL SERVICES

REF. LINK
TRANSPONDER N°
SATELLITE

AMAZONAS-3
Clear Sky

Rain
up

Rain
down

GENERAL DATA

Transponder bandwidth(MHz)	54		
carrier type	outbound		
Modulation	QPSK		
Information rate (Kb/s)	8448	OVERHEAD	1
FEC	3/4	Reed Solomon	1
bandwidth occupied (KHz)	6758.40		
BER	1.00E-07		
Eb/No (dB)	8	Nº portadoras	
Nº of carriers	6.00	6.85	5.05
IBO total (dB)	3.00		
OBO total (dB)	2.321		
C/I intermodulation	18.063		
Occupation factor	1.32		
availability (%)	99.80		
satellite longitude	-61		

UPLINK

E/T Tx Name	new York
E/T Tx (degrees E) Longitude	-74.00
E/T Tx (degrees N) latitude	40.75
E/T Tx (m) Altitude	100.00
Uplink Frequency (GHz)	5.89
EIRP E/T Tx.(dBW)	71.00

E/T Tx example

HPA (W)	263.00	
HPA-antena (dB) loss	0.20	ES off axis psd (dBW/Hz)
Ant. gain (dB)	47.00	-44.30
Ant. Diameter (m)	4.50	

Polarization discrim (dB)	35.00	
Accuracy polarization(º)	0.10	
% unavailability		0.08000
Rain atten.		0.46
Atmosp. Atten. loss (dB)	0.20	
aiming error loss (dB)	0.30	
sky loss (dB)	199.38	
D.F.P. (dBW/m2)	-99.03	-99.49
saturation D.F.P.in the BEAM CENTER (dBW/m2)	-89.00	
Back-off Input (dB)	10.03	10.49
Geogr. advantage (dB)	-7.00	
G/T satellite in the BEAM CENTER (dB/K)	-1.00	
C/N up (dB)	23.42	22.96
C/I cochannel up(dB)	24.89	24.43
C/(N+I) without other interf. satellites up) (dB)	18.19	17.73
psd Interference from satellite 2º(dBW/Hz)	-38.70	
C/I with other interf. Satellites 2º up (dB)	19.93	19.46
c/(N+I) with other interf. Satellites up (dB)	15.96	15.50
Xpolar Interference excess (dB)	3.0	

Clear sky

Rain
up

rain
down

DOWNLINK

E/T Rx Name	MIAMI		
E/T Rx (degrees E) Longitude	-80.18		
E/T Rx (degrees N) Latitude	25.77		
E/T Rx (Km) Altitude	100.00		
Down Frequency (GHz)	3.66		SAT deirp (dBW/Hz)
EIRP satellite in the beam center (dBW)	41.00		-36.65
Back-off output (dB)	9.35	9.81	
Geogr. advantage (dB)	-5.00		
% unavailability			0.12000
Rain Atten.			0.15
Atmosp. Atten. loss (dB)	0.20		
aiming error loss (dB)	0.30		
sky loss (dB)	195.06		
G/T E/T Rx. (dB/K)	24.50		23.80
E/T Rx Example			
Ant. Gain(dB)	43.28		
antenna-receptor loss(dB)	0.20		
Tlna (ºK)	40.00		
Ta (ºK)	20.00		
Tsyst. (ºK)	72.15		
Ant. Diameter (m)	4.55		

Polarization discrim.(dB)	35.00		
C/N down (dB)	15.89	15.43	15.04
C/I cochannel down(dB)	25.57	25.57	25.57
C/I channel adjacent (dB)	24.70	24.70	24.70
C/(N+I) without other interf. satellites down) (dB)	13.77	13.37	13.23
deirp Interference from satellite 2º(dBW/Hz)	-34.50		
C/I with other interf. Satellites 2º down (dB)	14.66	14.66	14.51
c/(N+I) with other interf. Satellites up (dB)	11.18	10.96	10.81
Xpolar Interference excess (dB)	2.3		

GLOBAL RESULTS

C/(N+I) without other interf. satellites TOTAL) (dB)	12.43	12.02	12.03
C/(N+I) with other interf. satellites Total (dB)	9.94	9.65	9.65
Excess margin (dB)	0.50	0.50	0.50
Eb/No available (interf nominal)(dB)	8.47	8.18	8.18
Eb/No request (dB)	8.00	8.00	8.00
Margin (nominal)(dB)	0.47	0.18	0.18